

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

SEP 10 1980

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

O.C.D.
ARTESIA OFFICE Fee

Indicate Type of Lease
State Oil & Gas Lease No.
L-122

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Penasco IW Shallow
3. Address of Operator 207 S. 4th, Artesia, NM 88210	9. Well No. 6
4. Location of Well UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>31</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Penasco Draw SA Yeso Assoc
15. Elevation (Show whether DF, RT, GR, etc.) 3621.8 GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Perforate & treat</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2661 TD 3100' - WIH w/steel strip gun and perforated 2661-2746' w/11 .50" holes as follows:
2261, 63, 65, 67, 69, 71, 73, 77, 78, 2741, 46'. Sand frac'd down 4-1/2" casing
w/30,000 gal gelled 2% KCL water w/50,000# sand (40,000# 20/40 and 10,000# 100 mesh)
and 4 ball sealers. Average pressure 1750 psi @ 33 BPM. Flowed back 2 hours.
WBIH w/steel strip gun and perforated 2543-2589' w/10 .50" holes as follows: 2543, 45,
46, 48, 50, 82-1/2, 84, 86, 87, 89'. Sand frac'd w/30,000 gal gelled 2% KCL water w/
50,000# sand (40,000# 20/40 and 10,000# 100 mesh). Average pressure 1950 psi @31.25 BPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert K. Stahl TITLE Engineer DATE 9/9/80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE SEP 12 1980

CONDITIONS OF APPROVAL, IF ANY: