

SA 2 SURVEY REPORT

APPROVED	
DATE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATE	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION  
 P. O. BOX 2086  
 SANTA FE, NEW MEXICO 87501

RECEIVED

Form O-303  
 Revised 10-1-78

NOV 17 1982

O. C. D.  
 ARTESIA, OFFICE

No. Indicate Type of Lease  
 State  Free   
 State Oil & Gas Lease No.  
 E-7811

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPROPRIATE FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO THE SAME RESERVOIR.)

1. Kind of Well:  OIL WELL,  GAS WELL,  OTHER

7. Well Agreement Name

2. Name of Operator: Holly Energy Inc.

8. Name of Lease Name

3. Location of Well: P.O. Box 726 Artesia, New Mexico 88210

Sand Tank Shallow State  
 9. Well No. 1

4. Location of Well: Unit Letter D 990 FEET FROM THE North LINE AND 330 FEET FROM

und. Grayburg-San Andres  
 Loco Hills-Queen

5. Location of Well: West LINE, SECTION 2 TOWNSHIP 18-S RANGE 30-E N.M.P.M.

6. Location of Well: 3598 GR

10. County: Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

REPAIRS/REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
REPAIR/ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL UP ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Spud &amp; set surface casing</u> <input checked="" type="checkbox"/>

11. Executive Paragraph of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well @ 9:00 a.m. 11-13-82  
 Drill 11" hole to 512' and run 501' of 8-5/8 24# sec casing and set @ 512'.  
 Cement with 90 sacks pacesetter Class C, 6# salt, 5# gilsonite, 1/4# celoseal and 120 sacks Class C 2% calcium chloride.  
 Circulate 40 sacks to pit.  
 Plug down 5:30 a.m. 11-14-82  
 After waiting 18 hours, drill out with 7-7/8 bit. Tested 1000# for 30 minutes OK

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert Loyd TITLE Superintendent DATE 11-16-82

APPROVED BY Leslie A. Clements TITLE Supervisor District II DATE NOV 19 1982

CONDITIONS OF APPROVAL, IF ANY:

