

C/S 7

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Premier Production Co. ✓

3. ADDRESS OF OPERATOR

324 W. Main, Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL 330' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☒

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

APR 28 1983

Oil & Gas

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-29-83 Rig up & perf as follows: 1st stage: 3489', 90, 91, 92, 93, 94, 95, 96, 97, 98, 10-42" holes; 2nd stage: 3398', 99, 3400, 01, 02, 03, 04, 05, 06, 07, 10shots & 3254', 55, 56, 57, 58, 59, 6 shots. Acidize perfs 3489-98' w/750gals 20% NEFE; swabbed load+ (all water). 3/30 acidize perfs 3398-3407' w/1000gals 20% NEFE acid, swabbed load+ (all water). Acidize perfs 3254-59' w/500gals 20% NEFE, swabbed load+(all water) 3/31 rig up & perf as follows 3134', 35, 36, 40, 41, 57, 58, 59, 60, 61 & 62; 11 holes; 3056', 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 12 holes; 2951', 52, 53, 54, 55, 56, 57, 58, 59, 60, 10 holes. 4/1 Rig up & acidize perfs 3134-62' w/800gals 15% NE; swab load+; trace of oil, 99% water. 4/1 acidize perfs 3056-68' w/1000gal 15% NE; swabbed dry, recovered 30-40% oil. Frac w/40,000gals 2% KCL, 36,000# 20-40, 11,700# 10-20 sand. Put on pump to test.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

ROSWELL, NEW MEXICO