

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires July 31, 1997

clsf

MAY 1998
RECEIVED
OCD - ARTESIA

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. LC 029420B
6. If Indian, Allottee or Tribe Name _____
7. If Unit or CA/Agreement Name and/or No. _____

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well
 Oil Well Gas Well Other NSL-3856
2. Name of Operator OXY USA INC. 16696
3a. Address P.O. BOX 50250 3b. Phone No. (include area code)
MIDLAND, TX 79710-0250 915-685-5717
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2180 FSL 1980 FEL NWSE (J) Sec 33 T17S R31E

8. Well Name and No. Dow B 33 Federal #1
9. API Well No. 30-015-2706B
10. Field and Pool, or Exploratory Area Undesignated (Atoka)
11. County or Parish, State
EDDY NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- | | | | | |
|--|---|--|--|---|
| <input checked="" type="checkbox"/> Notice of Intent | <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Fracture Treat | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Final Abandonment Notice | <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input type="checkbox"/> Other _____ |
| | <input type="checkbox"/> Change Plans | <input checked="" type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | |
| | <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

See other side

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed): DAVID STEWART Title: REGULATORY ANALYST
Signature: *[Signature]* Date: 5/7/98

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by _____ Title _____ Date _____

Conditions of approval, if any, are attached. Approval of this notice does not warrant or Office certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

OXY USA INC.
DOW B 33 FEDERAL #1
SEC 33 T17S R31E
EDDY COUNTY, NM

TD - 11391' PBTD - 11306' PERFS - 11240-11301'

CASING: 11-3/4" 42# @ 653', 14-3/4", cmt w/ 590sx (circ)
8-5/8" 32# @ 5000', 11", cmt W/ 1770sx (circ)
5-1/2" 17# @ 10362', 7-7/8", cmt w/ 2300sx TOC-4000'
2-7/8" 10.4# @ 9495-11391', 4-3/4" W/ 90sx EST TOC-9495'

1. MIRU PU, NDWH, NUBOP. M&P 9.5# MUD LADEN FLUID, CEMENT SQUEEZE ATOKA PERFS 11301-11240' W/ 25sx CL C CMT SPOT TO 11040', POOH, WOC. RIH & TAG CMT PLUG, M&P 9.5# MUD LADEN FLUID, POOH TO 10697'.
2. M&P 10sx CL C CMT PLUG FROM 10947-10697', M&P 9.5# MUD LADEN FLUID, POOH TO 9663'.
3. M&P 10sx CL C CMT PLUG FROM TO 9963-9663', M&P 9.5# MUD LADEN FLUID, POOH TO 9345'.
4. M&P 20sx CL C CMT PLUG FROM TO 9645-9345', POOH, WOC. RIH & TAG CMT PLUG, M&P 9.5# MUD LADEN FLUID, POOH TO 8682'.
5. M&P 25sx CL C CMT PLUG FROM TO 8882-8682', M&P 9.5# MUD LADEN FLUID, POOH TO 7185'.
6. M&P 25sx CL C CMT PLUG FROM TO 7385-7185', M&P 9.5# MUD LADEN FLUID, POOH TO 4900'.
7. M&P 25sx CL C CMT PLUG FROM TO 5100-4900', M&P 9.5# MUD LADEN FLUID, POOH TO 3613'.
8. M&P 25sx CL C CMT PLUG FROM TO 3801-3613', M&P 9.5# MUD LADEN FLUID, POOH TO 1850'.
9. M&P 25sx CL C CMT PLUG FROM TO 2050-1850', M&P 9.5# MUD LADEN FLUID, POOH TO 553'.
10. M&P 25sx CL C CMT PLUG FROM TO 753-553', M&P 9.5# MUD LADEN FLUID, POOH.
11. M&P 15sx CL C CMT SURFACE PLUG. NDBOP, CUT-OFF CSG 3' BELOW GROUND LEVEL, RDPU, INSTALL DRY-HOLE MARKER, CLEAN LOC & BACKFILL W/O PIT.