

County Eddy Depth 2400' Pool Wildeat*

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Nix & Curtis Well No. 1 Lease Ohio-Faris

330 Feet from S. Line 330 Feet from E. Line, Sec. 4 Twp. 19S Rge. 26E

Land Patented Contractor Shelro Drlg. Co.

T. A
T. X
B. X
T. Del Li
T. Del Sd
T. Y
T. SR
T. Q
T. PR
T. GB
T. SA 1086
T. Glo
T. Blby
T. CF

Elevation 3339' GR Spudded 5-31-56 Completed 7-2-57

T. Tu Total Depth 3078' 2 1/2" P. B. 2-50
T. Full Top Pay 13-12 District 7
T. DR I.P. 25 BOPD
T. Wich A. Base on 80 Hrs.
T. Abo Choke: Inch
T. WC Tubing @ Ft.
T. Hu Press: Tbg. 40 Csg. 100
T. Per-Pe GOR Gravity 52.1
T. Penn Effective Perfs.:
T. Strawn
T. Miss 321 1/2" 400-75
T. WF 100 1/2" 400-75
T. Dev Acid. Frac & Shooting Record:

CSG. & CEMENTING RECORD

Size	Feet	Sax Cement
13 3/8	225	set #9
8 3/4	263	500 ✓
5 1/2	2451	400 ✓

T. Sil From To
T. Fuss From To
T. Mon From To
T. Simp From To
T. McK
T. Ell
T. G.W.
T. Gr SHOWS
T. S/
T. S/
T. S/
T. S/
T. S/
T. S/

6-6-56	TD 863' li. Prep to run 8 5/8" Csg.	
	Lost circu. @ 220' & 805'	
	TK 1030 (comp. 400 ft) - circ. @ 215' circ	
	C# 740-990 run 20' circ	C# 6-1724-55 run 20' circ
	W/ Red oil in 2 1/2" 154-59	2" 1/2" 154-59 run 20' circ
	C# 1740-1742 started wiring 2 1/2" 154	C# 1740-1742 started wiring 2 1/2" 154

TD 2478 Solo woc

TD 2478 Solo PR 2470 sub load

Perf 22h 1744-64 frac 16,000 + 19,000 =

TD 2478 Solo in

TD 2478 Solo in 2470th Perf to frac

Perf 40h 1784-74

TD 2478 Solo to 2430 sub load

frac 16,000 + 24,000 = Perf 1784-74

TD 2478 Solo PR 2430 Perf to treat

set CP² 1620 Perf 24h 1451-60 24h 1466-72

TD 2478 Solo PR 1010 woc on eq.

frac 10,000 + 10,000 = Perf 1456-72 sub load

did not rec and CP² 1110 Perf 40h 1052-72

16h 1072-72 frac 12,000 + 12,000 = Perf 1052-86

sub load + x sub with 2090 LD + 8390 with

sq. Perf 1052-86 w/ 50 gal

✓

Sept 5 TD 2478 Solo PR 1110 to 2470 + 10,000

filled out to 1100 + Perf 50 gal XW PH

resq. Perf 1056-86 w/ 50 gal

TD 2478 Solo PR 1690 sub load

Perf 32h 1402-10, 24h 1376-82

frac 8,000 + 8,000 = Perf 1402-10

frac 6,000 + 6,000 = Perf 1376-82

TD 2478 Solo PR 1690 sub load

did not rec and 1376² - 1402-10

s. 1402-10 - different CP to 2450 +

flow 25 BD 24' on 18" CP - from Perf 1456-72

+ 1784-74