

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

MM-066154

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL GAS WELL OTHER **Drilling**

2. NAME OF OPERATOR

G. W. Strake

3. ADDRESS OF OPERATOR

511 Midland Tower, Midland, Texas #79704

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

**1650' FWL and 990' FWL of Sec. 31, SW/4 of NW/4,
T19S, R1E, N2PM**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3397' GR

7. UNIT AGREEMENT NAME

Hackberry Deep Unit

8. FARM OR LEASE NAME

Adams-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T19S, R1E

12. COUNTY OR PARISH

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF: (Temporary)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**3/23/65 Plugged well as follows:
Total depth: 11,550' KDB
Circulated 10.0g drilling mud through drill pipe below, between and above plugs which were set at the following intervals:
35 sack plug from 11,450'-11,350'
30 sack plug from 11,200'-11,050'
35 sack plug from 10,200'-10,100'
35 sack plug from 8,480'-8,380'
35 sack plug from 6,850'-6,750'
35 sack plug from 5,330'-5,230'
55 sack plug from 4,200'-4,050' (base of intermediate casing)**

Temporarily plugged in accordance with telephone approval from Mr. Jim Knauf.

RECEIVED
MARCH 25 1965

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Gen. Supt.

DATE **March 24, 1965**

(This space for Federal or State office use)

APPROVED BY

APPROVED
APR 6 1965
[Signature]
RUDOLPH C. SAIER, JR.
ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED

APR 8 1965

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-665229
987-951

