

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
ANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION  
3-NMCCC - Artesia  
1-File  
2-Mesa Petroleum Company

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6096
7. Unit Agreement Name
8. Farm or Lease Name STATE K - 6096 B
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated (Morrow)
12. County EDDY

**RECEIVED**  
OCT 30 1975

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator GETTY OIL COMPANY ✓
3. Address of Operator P.O. Box 249, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER G, 1050 FEET FROM THE North LINE AND 1980 FEET FROM East 32 TOWNSHIP 19S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3500' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cactus Drilling Company spudded @ 8 PM MST 10-23-75. Drilled 17-1/2" hole to 463'. Set 13-3/8" 48# H-40 8 P Casing @ 460'. Cemented with 200 sacks HOWCO Lite with 2% CaCl<sub>2</sub>; 1/4# Flocele and 5# Gilsomite per sack and 200 sacks Class "C" with 2% CaCl<sub>2</sub>. Circulated estimated 75 sacks cement. W.O.C. 18 hours. Tagged top of cement on outside of 13-3/8" at 31'. Filled with pea-gravel. Tested casing to 1000# for 30 minutes, no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY: C.L. Wade: C. L. Wade	AREA SUPERINTENDENT	DATE 10-29-75
SIGNED	TITLE	DATE
APPROVED BY: W. A. A. [Signature]	TITLE: SUPERVISOR, DISTRICT II	DATE: OCT 31 1975

CONDITIONS OF APPROVAL, IF ANY: