

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate\*  
(Other instructions on re-  
verse side)Copy to SF  
Form approved.  
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 1530'

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "HF"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 10-19S-27E

Unit A NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

MAR 24 1977

O.C.C.  
ARTESIA OFFICE1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State laws.  
See also space 17 below.)  
At surface

660' FNL &amp; 660' FEL of Section 10-19S-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3475' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

Set Prod. Csg, Plug Back

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 3083'; PBTD 1896'. Plugged back 2050-1950' w/35 sacks of Class C cement. Laid down drill pipe and drill collars and ran 37 joints of 5½" 14# J-55 (1896') of casing set at 1896'. 1-Guide shoe and float collar at 1856'. 5 centralizers at 1855, 1680, 1600, 1450, 1400. Cemented w/115 sacks of Class C cement. Cement circulated. PD 2:15 AM 3-9-77. WOC and tested to 1000#. OK.

Perforated 1629-36' w/14 .45" holes and 1646-53' w/14.45" holes (Total 28 holes). Acidized w/500 gallon of HF 3-HCL 13.5 acid and ball sealers. Sand frac'd w/47000 gallons of treated water, 95000# sand, 20000# 100 mesh and 75000# 20-40 sand.

RECEIVED

MAR 21 1977

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christie Tomlinson

TITLE Geol. Secty

DATE 3-19-77

(This space for Federal or State office use)

APPROVED BY

Lee J. Lora

TITLE ACTING DISTRICT ENGINEER

DATE MAR 23 1977

CONDITIONS OF APPROVAL, IF ANY: