

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

FEB 14 1979

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		
7. Unit Agreement Name		
8. Farm or Lease Name Ross IZ Com		
9. Well No. 11		
10. Field and Pool, or Wildcat Und N. Cemetary Atoka		
12. County Eddy		

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-
2. Name of Operator Yates Petroleum Corporation ✓
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 28 TOWNSHIP 19S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3502' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER Plug back to Atoka <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Loaded hole, reset original packer at 9158' (Perf 9166-78), set standing valve in Pkr at 9158' Perf. Morrow at 9144-50 w/12 .50" holes, trtd perfs w/1000g 7½" MSA & nitrogen at 2.4 bpm and 5200#. Flwd back load and swbd dry. 14 hr SITP 100#. Set blanking plug in pkr at 9110' (TA Morrow) (perfs 9144-9178'). Load hole & pull tbg from on/off tool, perf. Atoka formation at 8930-35 w/10 .50" holes & 8952-56' w/8 .50" holes. RIH w/RBP & pkr on 2-3/8" tubing, set RBP at 8960', spotted acid and set pkr at 8900', trtd perfs 8930-56 w/1500g 15% DS-30 acid and ball sealers, 5.1 bpm at 4100 psi. Swbd back load and well flowed 10 psi on 1/2" choke = 150 MCFPD. Loaded hole, unseated pkr, latched on to RBP and reset RBP at 8900'. Pulled tbg & pkr, perf Atoka Fm at 8860-66' w/12 .50" holes. RIH w/tbg & pkr, spotted acid, set pkr at 8835', treated perfs 8860-66' w/2000g 15% DS30 acid and Nitrogen, 3 bpm at 4200 psi. Cleaned well. Loaded hole and pulled RBP, tbg & pkr rerun tbg & pkr, set pkr at 8835' and swabbed well in, flowed 300# on 1/4" choke ARO 430 MCFPD.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Eddie M. Hays</u>	TITLE <u>Engineer</u>	DATE <u>2-13-79</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>FEB 16 1979</u>

CONDITIONS OF APPROVAL, IF ANY: