

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIRECTORATE
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

APR 05 '88

5a. Indicate Type of Lease	State ☒ Fee ☐
5. State Oil & Gas Lease No.	LG 0463

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Unit Agreement Name GARDNER DRAW UNIT
2. Name of Operator TOTAL MINATOME CORPORATION	8. Farm or Lease Name GARDNER DRAW UT.
3. Address of Operator 500 DALLAS ST., SUITE 400, HOUSTON, TX 77002	9. Well No. 2
4. Location of Well UNIT LETTER B, 1980 FEET FROM THE EAST LINE AND 800 FEET FROM THE NORTH LINE, SECTION 19, TOWNSHIP 19S, RANGE 21E, NMPM.	10. GARDNER DRAW MORROW
11. Elevation (Show whether DF, RT, GR, etc.) 4405 GR	12. County EDDY

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☒	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

CURRENT PERFORATIONS ARE AT 6956-66' AND 7020-24'. LOAD HOLE WITH 9.5 PPG MUD TO KILL WELL. POOH W/GUIBERSON UNI-PACKER VI AND 2 3/8" TBG. RBIH W/CIBP AND SET AT 6900'. SPOT 12 SACKS CLASS "H" CEMENT W/ADDITIVES ON CIBP. LOAD HOLE WITH 9.5 PPG MUD TO SURFACE.

ATTEMPT TO SALVAGE 4 1/2" PRODUCTION CSG. CUT 4 1/2" PRODUCTION CASING @6500' AND POOH. SPOT 35 SACKS CLASS "H" CEMENT AT 6550'. TAG TOP OF CEMENT. SPOT 25 SACKS CLASS "H" CEMENT AT THE FOLLOWING DEPTHS: 5460', 4160' AND 3250'. SPOT 35 SACKS CLASS "H" CEMENT AT 1800'. TAG TOP OF CEMENT. SPOT 25 SACKS CLASS "H" CEMENT AT 400'.

SPOT 5 SACKS CLASS "H" CEMENT AT 10' TO SURFACE. MARK WELL WITH A 4" DIAMETER STEEL MARKER SET IN CONCRETE EXTENDING TO 4' ABOVE MEAN GROUND LEVEL. THE MARKER SHALL READ GARDNER DRAW UNIT, WELL NO. 2, SECTION 19, T19S, R21E, EDDY COUNTY, NEW MEXICO.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Pamela Grantham TITLE REGULATORY ADMINISTRATOR DATE 3/31/88

APPROVED Mike Williams TITLE OIL AND GAS INSPECTOR DATE APR 07 1988

CONDITIONS OF APPROVAL, IF ANY:

Plugging