

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JAN 30 1979

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG-2352

7. Unit Agreement Name
-

8. Form of Lease Name
State "24"

9. Well No.
1

10. Field and Pool, or Wildcat
Undesignated (Morrow)

12. County
Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR OPERATIONS TO BE DONE ON THE WELLS OR WELLS BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR REPORT ON WELLS (FORM C-103) FOR SUCH OPERATIONS.)

1. Kind of Well
Oil Well Gas Well OTHER

2. Name of Operator
Southland Royalty Company ✓

3. Address of Operator
1100 Wall Towers West Midland, TX 79701

4. Location of Well
UNIT LETTER L 1980 FEET FROM THE south LINE AND 660 FEET FROM
THE west LINE, SECTION 24 TOWNSHIP 19-S RANGE 29-E NMPM.

15. Elevation (Show whether DF, RT, CR, etc.)
3322.5 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud by Hondo Drlg. Co. Rig # 5 @ 4:30 PM, 1-5-79.
Drill 15" hole to 332'. (Lost returns @ 65'.)
Ran 11 3/4" 42# H-40 ST&C csg; set @ 332'. 1/4" @ 325'.
Cmt w/300 sxs Class C w/2% C.C. Plug down @ 3:45 AM, 1-6-79.
Cmt did not circ. Dump 7 yds redi-mix concrete behind 11 3/4" csg.
Install 11 3/4" x 12" Ser. 900 (3000#) csg head, BOP. WOC 18 hrs.
Test csg & BOP for 30" @ 1000#; held OK.
Drill ahead 11" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Harney Carr TITLE District Engineer DATE 1-16-79

APPROVED BY W. A. Gessett TITLE SUPERVISOR, DISTRICT II DATE JAN 30 1979

CONDITIONS OF APPROVAL, IF ANY: