

file

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 So. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1650' FSL &amp; 1650' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐☐☒☒☐☐☐☐☐☐

RECEIVED

OCT 8 1980

O. C. D.

ARTESIA OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
SEP 20 1980  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 3100'; PBTD 3003' WIH w/Steel Strip gun on wireline and perforated 2701-2770' w/10 .50" holes as follows: 2701, 11, 20, 24, 31, 33, 40, 42, 68 & 70'. Spotted acid and sand frac'd perfs 2701-2770' w/30000 gallons gelled 1% KCL water. 50000# sand (10000# 100 mesh and 40000# 20-40 sand). Flowed well back and recovered load. WIH w/Steel Strip gun on wireline and perforated 2486-2564' w/12 .50" holes as follows: 2486, 88, 90, 2537, 39, 41, 44, 47, 50, 53, 56 & 64'. Set RBP at 2617'. Spotted acid on perfs 2486-2564' and sand frac'd perfs w/30000 gallons gelled 1% KCL water, 50000# sand (10000# 100 mesh and 40000# 20-40 sand).

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Albert R. Hall*

TITLE

Engineer

DATE

Sept. 29, 1980

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD

*P. Chester*

APPROVAL IS ANY:

OCT 2 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE

DATE

\*See Instructions on Reverse Side