

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Exxon Corporation

3. ADDRESS OF OPERATOR

P. O. Box 1600, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FEL & 1980' FNL of Section

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Set Casing

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM-25336

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Crooked Canyon Federal "B" Fed.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T20S, R21E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico


14. API NO.

30-015-32186

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4425 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-28-80 Ran 9 jts 13 3/8", K-55, 54.5# csg set @ 357' w/460 sx Cl C, 17 1/2" hole. Cmt. did not circulate to surface. TOC @ 160'. Ran 1" tbg down backside, cmt w/250 sx Cl C w/3% Cacl. Circulated.

1-3-81 Ran 41 jts 8 5/8", K-55 STC, 24# csg set @ 1620' w/400 sx Thixolite, 600 sx Pacesetterlite, tail w/200 sx Cl C w/2% CC. Cmt did not circulate to surface. TOC @ 700'. 12 1/4" hole. Ran 1" tbg down backside. Cmt w/350 sx Thix-Ad. Circulated. Test csg to 1500# for 30 min. Held OK.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mason Truiping TITLE Proration Specialist DATE 1-8-81

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
PETER W. CHESTER

JAN 12 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side