


DRILLING CONTROL **CONDITION III-3000 PSI WP**

H₂S TRIM REQUIRED
 YES _____ NO _____



DRILLING CONTROL

MATERIAL LIST - CONDITION III

- A Texaco Wellhead
- B 3000# W.P. Dual ram type preventer, hydraulic operated with 1" steel, 3000# W.P. control lines (where sub-structure height is adequate, 2-3000# W.P. single ram preventers may be utilized with 3000# W.P. drilling spool with 2" minimum flanged outlet for kill line and 3" minimum flanged outlet for choke line. The drilling spool is to be installed below the single ram type preventers.)
- C 3000# W.P. Annular Preventer with 1" steel, 3000# W.P. control lines
- D Bell Nipple with flowline and fill-up outlets (kill line may also be used for fill-up line.)
- 1,3,4, 7,8 2" minimum 3000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve
- 2 2" minimum 3000# W.P. back pressure valve
- 5,6,9 3" minimum 3000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve
- 12 3" minimum Schedule 80, Grade B, seamless line pipe
- 13 2" minimum x 3" minimum 3000# W.P. flanged cross
- 10,11 2" minimum 3000# W.P. adjustable choke bodies
- 14 Cameron Mud Gauge or equivalent (location optional in Choke line.)

SCALE	DATE	REV NO	DWG NO
DRAWN BY			
CHECKED BY			
APPROVED BY			



TEXACO, INC.
 MIDLAND DIVISION
 MIDLAND, TEXAS



EXHIBIT D