

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAV - 8 '90

WELL API NO. 30-015-26226
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Clifford ADD
8. Well No. 1
9. Pool name or Wildcat North Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3631' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION ✓
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line Section 35 Township 19S Range 24E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Perforate & Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-18-90. Drill out DV tool and clean out to float collar. Spot 500 gals 20% NEFE acid and perforate 7804-21' w/8 .44" holes: 7804, 05, 06, 11, 14, 15, 16, 21. Treat perfs w/1500 gals 20% NEFE. Perforate 7917-29' w/7 .42" holes: 7917, 19, 23, 25, 28, 29. Acidize perfs w/2000 gals 20% NEFe acid.
4-28-90. Perforate 7660-7777' w/19 .50" holes: 7660, 61, 62, 7711, 13, 15, 17, 21, 23, 24, 42, 44, 48, 50, 64, 66, 67, 75, and 7777'. Acidized perfs 7660-7777' w/1600 gals 20% NEFE acid.
5-1-90. Blanket perforate 7660-68' (2 SPF-18 holes); 7690-7824' (2 SPF-270 holes). Acidize perforations 7660-7824' (296 holes) via tubing and annulus w/26000 gals 20% NEFE acid and 2 drops of block, 750# 1st drop and 500# 2nd drop.
RBP reset at 7850'. Ran sub pump and put well on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 5-7-90
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT I TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

MAV 16 1990