

BUREAU LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT -" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3. LEASE DESIGNATION AND SERIAL NO. NM-24160
2. NAME OF OPERATOR Siete Oil and Gas Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 2523 Roswell, NM 88202-2523		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2310' FSL & 1750' FEL, NW $\frac{1}{4}$ SE $\frac{1}{4}$, Unit Letter		8. FARM OR LEASE NAME Osage Federal
14. PERMIT NO 30-015-26283		9. WELL NO. 16
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3320' GR		10. FIELD AND POOL OR WILDCAT Parkway Bone Spring
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34: T19S, R29E
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		12. COUNTY OR PARISH Eddy
		13. STATE NM

RECEIVED

APR 30 '90

O.C.D.

ARTESIA, OFFICE

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud, 20" & 13 3/8" csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

(Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2/10/90 Ziadril Rig #6 spudded 26" hole @ 8:00 AM, TD 26" hole to 358' @ 4:45 PM RU & ran 11 jts (364') 94# H-40 ST&C 20" csg, set @ 358' w/150 sxs 35/65 POZA, 6% D-20, 15# D-42, 3% CaCl, tail-in w/250 sxs HEII, 3% CaCl, 1/4# D-29, PD @ 11:15 PM, did not circ.

2/11/90 Began 1" operations, set 1st plug @ 260' w/50 sxs CC, 4% CaCl, 2nd plug @ 230' w/100 sxs 35/65 POZA, 3% CaCl, 3rd plug @ 201' w/75 sxs CC, 4% CaCl, 4th plug @ 146' w/50 sxs CC, 4% CaCl, 5th plug @ 96' w/100 sxs 35/65 POZA, 3% CaCl, circ 5 sxs to pits.

2/12/90 TD 17 1/2" hole to 1150' @ 2:00 PM, TOH, RU & ran 25 jts (1131.26') 48# WC-40 ST&C 13 3/8" csg & 1 jt (31.2') 54.5# WC-40 ST&C csg, set @ 1150' w/550 sxs 35/65 POZA, 6% D-20, 10# salt, 3% CaCl, 1/4# D-29, tail-in w/250 sxs 25/75 POZA, 1% D-20, 3% CaCl, 1/4# D-29, PD @ 7:45 PM, circ 70 sxs to pits.

ACCEPTED FOR RECORD

APR 26 1990

CARLSBAD, NEW MEXICO

I hereby certify that the foregoing is true and correct

SIGNED

Cathy Butley-Sally

TITLE Drlg. & Prod. Tech.

DATE 4/9/90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.