Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

MAR - 2 1992

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

		NM 81708
Do not use this form for proposals to dr	AND REPORTS ON WELLS O. C. D. ill or to deepen or reentry to a different reservoir R PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well		
X Oil Gas Well Other		8. Well Name and No. Palo Verde AJV Fed. Com #1
2. Name of Operator  YATES PETROLEUM CORPORATION (505) 748-1471		9. API Well No.
YATES PETROLEUM CORPORATION ✓ (505) /48-14/1  3. Address and Telephone No.		30-015-26907
105 South 4th St., Artesia, NM 88210		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		South Dagger Draw U/Penn
Unit M, 760' FSL & 660' FWL, Sec. 24-T20S-R24E, NMPM		11. County or Parish, State
		Eddy, NM
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
<b>—</b>	Casing Repair	Water Shut-Off Conversion to Injection
Final Abandonment Notice	Altering Casing Other	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state a	Il pertinent details, and give pertinent dates, including estimated date of star cal depths for all markers and zones pertinent to this work.)*	
give subsurface locations and measured and true vert	92. Set 40' of 20" conductor. Notice	fied BLM. Carlsbad. NM.
of coud Resumed drilling 14-	3/4" hole 7:30 AM 2-22-92. Ran 25 jo	oints 9-5/8" 36# J-55
STAC casing set 1093'. Guide	shoe set 1093', insert float set 1049	9'. Cemented W/150 sx "H"
with 10#/sx Cal-Seal, 1/2#/sx	Flocele, $10\#/\text{sx}$ Gilsonite + 2% CaCl2	(yield 1.22, wt 15.5) +
700 sx Lite "C" with $1/2\#/sx$ F	locele, 10#/sx Gilsonite + 3% CaCl2	(yield 1.99, wt 12.4).
Tailed in $w/200 \text{ sx } "C" + 2\% \text{ Ca}$	C12 + 1/4#/sx Flocele (yield 1.32, w	t, 14.8). PD 11:45 PM
2-23-92. Bumped plug to 500 p	si, float held OK. Cement did not c ermission from BLM, Carlsbad, NM, to	redi-mix to surface.
Redi-mix with 1-1/2 yards. WO	C	
Drilled out 6:45 PM 2-24-92.	WOC 19 hours. NU and tested to $3000$	psi for 10 minutes, OK.
Reduced hole to 8-3/4", resume		
14. I hereby certify that the foregoing is trie and correct		0.05.00
Signed ( antia ) ovallet	Title Production Supervisor	Date
(This space for Federal or State office use)		_
Approved by	Title	Date
		77 L 1 188-1