

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

DEC 8 1 1992

O. C. D.
ARTS & CRAFTS

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Conoco Inc.

3. Address and Telephone No.
10 Desta Drive STE 100W, Midland, TX 79705

(915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FWL, SEC. 30, T-19S. R-25E, UNIT LTR 'F'

5. Lease Designation and Serial No.

NM 0559175

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

DAGGER DRAW NO. 13

9. API Well No.

30-015-27179

10. Field and Pool, or Exploratory Area

NORTH DAGGER DRAW UPR PENI
11. Country or Parish, State

EDDY CO., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other SPUD & SURFACE CSG

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-17-92 SPUD 14 3/4" HOLE DRILL TO DEPTH OF 1090'.
RIH W/ 25 JTS 9 A5/8" 40# K-55 LT&C CSG SET @ 1090'.
SHOE DEPTS @ 1090', COLLAR DEPTH @ 1047'.
CEMENT LEAD SLURRY 900 SX CLASS H/L W/ 3% CACL + 5#/SX GILSONITE + 1/2#/SX CELLOTATE.
TAIL SLURRY 200 SX CLASS C W/ 2% CACL. CMT RETURNS OF 134 BBLs. BUMP PLUG @ 1:45 AM ON
11-19. CONTINUE DRILLING 8 3/4" HOLE.



14. I hereby certify that the foregoing is true and correct

Signed David R. Glass

Title SR REGULATORY SPEC

Date 11-20-92

(This space for Federal or State office use)

Approved by David R. Glass

Title _____

Date _____

Conditions of approval, if any