

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

AUG 29 1994

WELL API NO.
30-015-27640

Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.
OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South Fourth Street - Artesia, NM 88210

4. Well Location
Unit Letter D : 810 Feet From The North Line and 660 Feet From The West Line
Section 28 Township 19S Range 25E NMPM Eddy County

7. Lease Name or Unit Agreement Name
Lorene ANN

8. Well No.
1

9. Pool name or Wildcat
North Dagger Draw Upper Penn

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3503' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Surface casing & cement</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1092'. Reached TD at 8:00 PM 8-21-94. Ran 25 joints of 9-5/8" 36# J-55 LT&C (1127.55') of casing set at 1092'. Texas Pattern notched guide shoe set at 1092'. Insert float set at 1045.67'. Cemented with 200 sacks "H", 12% Thixad, 10#/sack gilsonite and 1/2#/sack celloseal (yield 1.56, weight 14.6) and 900 sacks Pacesetter Lite, 10#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.4). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 7:30 PM 8-23-94. Bumped plug to 950 psi, OK. Circulated 71 sacks. WOC. Drilled out at 6:30 PM 8-24-94. WOC 23 hours. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 8-26-94
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

OCT 10 1994

APPROVED BY _____ TITLE _____ DATE _____