

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

10.6 24-84

FIELD REPORT FOR CEMENTING OF WELLS

Operator <b>MONSANTO</b>		Lease <b>BURTON FLAT DEEP</b>		Well # <b>23</b>	
Location of Well	Unit <b>H</b>	Section <b>2</b>	Township <b>21 S</b>	Range <b>27 E</b>	County <b>EDDY</b>
Drilling Contractor	<b>NA</b>		Type of Equipment <b>ROTARY</b>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8"	48.0	NEW	500	CIRC
* 11	8 5/8"	24.0	"	2500	CIRC
7 7/8	5 1/2"	15.5	"	5700	750 <del>SA</del>

Casing Data:

Surface 65 joints of 8 7/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by B. W. Wanner date 2-4-84

Cementing Program

Size of hole 11 Size of Casing 8 7/8 Sacks cement required 200

Type of Shoe used Guide Float collar used Float Btm 3 jts welded yes

TD of hole 2604 Set 2608 Feet of 8 7/8 Inch 24 # Grade J-55

New-used csg. @ 2608 with 200 sacks neat cement around shoe

+ 450 sax Class C additives 2% Calcium Chloride

Plug down @ 5700 (AM) (PM) Date 2-6-84

Cement circulated yes No. of Sacks 55

Cemented by Hewes Witnessed by B. W. Wanner

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Loss zone @ 1310 ft

Last Drilling Break 2447 ft