

OIL CONSERVATION DIVISION

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

SANTA FE, NEW MEXICO 87501

**RECEIVED BY**  
**FEB 28 1985**  
**O. C. D.**  
**ARTESIA OFFICE**

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Mobil Producing TX & N.M., Inc.

Address of Operator

Nine Greenway Plaza, Suite 2700, Houston, TX 77046

Location of Well

UNIT LETTER 0 3300 FEET FROM THE South LINE AND 1980 FEET FROM  
THE East LINE, SECTION 1 TOWNSHIP 21-S RANGE 27-E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Burton Flat

9. Well No.

2

10. Field and Pool, or Wildcat

E.Avalon-Bone Springs

15. Elevation (Show whether DF, RT, GR, etc.)

3178' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

CORRECTED REPORT

5½" Casing Recap

Drilled 7-7/8" hole to total depth of 5745'.  
Ran 5½", 15.5#, K-55 LT&C Casing to 5708' w/12 centralizers.  
Cemented casing w/525 sx Class "C" Pace Setter Lite, followed  
w/500 sx Class "C" Neat.  
Displaced cement w/136 bbl. fresh water. Had full returns.  
Bumped plug and cement job completed at 8:15 P.M., 12-28-84.  
Held 1600 psi on plug for 45 minutes with no pressure loss.  
RIH w/4-3/4" bit and tagged top of cement inside 5-1/2" casing at  
5598'. Drilled out cement to 5700 PBTD on 1-17-85.  
Pressured up on 5-1/2" casing to 1000 psi and held for 15 minutes  
with no pressure loss.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. C. McConnell  
W. C. McConnell Phone 915 688-1770

TITLE Environmental Specialist DATE 2-26-85

APPROVED BY \_\_\_\_\_

Original Signed By

Ledie A. Clements

Supervisor District II

DATE FEB 28 1985

CONDITIONS OF APPROVAL, IF ANY: