

Submit to Appropriate District Office  
 State Lease - 6 copies  
 Fee Lease - 5 copies  
 DISTRICT I  
 P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
 P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
 1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico  
 Energy, Minerals and Natural Resources Department

Form C-105  
 Revised 1-1-89

OIL CONSERVATION DIVISION  
 P.O. Box 2088  
 Santa Fe, New Mexico 87504-2088

JUN 26 1992

WELL API NO. 30-015-26906
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. L-5036

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> DRY <input type="checkbox"/> OTHER _____	7. Lease Name or Unit Agreement Name  Glider AKG State
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> FLUG BACK <input type="checkbox"/> DIFF RESVR <input type="checkbox"/> OTHER _____	
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471	8. Well No. 1
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat <i>Burnham East Strawn</i> Undes. Strawn

4. Well Location Unit Letter <u>F</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>West</u> Line  Section <u>17</u> Township <u>21S</u> Range <u>27E</u> NMPM <u>Eddy</u> County				
10. Date Spudded 3-25-92	11. Date T.D. Reached 5-7-92	12. Date Compl. (Ready to Prod.) 6-6-92	13. Elevations (DF & RKB, RT, GR, etc.) 3404' GR	14. Elev. Casinghead
15. Total Depth 11650'	16. Plug Back T.D. 10777'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools 0-11650'	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 10223-10342' Strawn			20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run CNL/LDT; DLL			22. Was Well Cored No	

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"		40'	26"	Redi Mix	<i>Post TD-2</i>
13-3/8"	54.5#	602'	17 1/2"	630 sx	<i>7-10-92</i>
9-5/8"	36#	2542'	12 1/2"	915 sx	<i>comp + BK</i>
5 1/2"	17#	11650'	8-3/4"	1225 sx	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	10161'	10161'

26. Perforation record (interval, size, and number) 10223-10342' w/38 - .42" Holes	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	10223-10342'	w/32000g. 15% HCL acid.

PRODUCTION

28. Date First Production 6-6-92	Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing	Well Status (Prod. or Shut-in) SI					
Date of Test 6-6-92	Hours Tested 24	Choke Size 1/2"	Prod'n For Test Period	Oil - Bbl.	Gas - MCF 1428	Water - Bbl.	Gas - Oil Ratio
Flow Tubing Press. 215 psi	Casing Pressure Pkr	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF 1428	Water - Bbl.	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Vented - Will be sold	Test Witnessed By Jim Krogman
---	----------------------------------

30. List Attachments  
 Deviation Survey, DST's, Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature *Juanita Goodlett* Printed Name Juanita Goodlett Title Production Supv. Date 6-28-92

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____	T. Strawn _____ 10110
B. Salt _____	T. Atoka _____ 10452
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____	T. Montoya _____
T. San Andres _____	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinebry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____ 2629
T. Drinkard _____	T. Bone Springs _____ 5000
T. Abo _____	T. Capitan Reef-1189 _____
T. Wolfcamp _____ 8796	T. Morrow Clastic-11130 _____
T. Penn _____	T. Lower Morrow -11375 _____
T. Cisco (Bough C) _____	T. _____

### Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

### OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....  
 No. 2, from.....to..... No. 4, from.....to.....

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....  
 No. 2, from.....to.....feet.....  
 No. 3, from.....to.....feet.....

### LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface	8920	8960	40	LS, Sh, SS
40	450	410	Redbeds, Anhy	8960	11180	2220	LS, Sh
450	730	280	Anhy	11180	11650	470	SS, Sh, LS
730	1160	430	Dolo, SS, Sh, Anhy				
1160	1250	90	Dolo				
1250	2542	1292	No Returns				
2542	3130	588	LS, SS				
3130	3660	530	SS, Sh				
3660	4870	1210	SS, Sh				
4870	5010	140	SS, Sh, Dolo				
5010	5960	950	LS, Sh				
5960	6400	440	Sh				
6400	6560	160	SS, Sh, LS				
6560	6780	220	LS				
6780	7100	320	LS, Sh				
7100	7260	160	SS, Sltstone, Sh, LS				
7260	7570	310	LS, Sh				
7570	7980	410	LS				
7980	8460	480	LS, Sh				
8460	8800	340	SS, Sh				
8800	8920	120	LS, Sh				