

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Fasken Oil and Ranch, Ltd. /

3. Address and Telephone No.

303 W. Wall, Suite 1800, Midland, TX 79701 (915) 687-1777

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

3287' FNL, 1780' FEL Section 1, T21S, R26E

5. Lease Designation and Serial No.

NM 911

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

18202

8. Well Name and No.

El Paso Federal No. 15

9. API Well No.

30-015-32385

10. Field and Pool, or Exploratory Area
Foster Draw-Delaware

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 4640' drilling a 7 7/8" hole on 9/16/02. Dry hole. Note: All cement plugs were Class C cement (s.w. 14.8 ppg, yield 1.34 cubic feet/sack). Plug 1: 50 sacks set at 4630'. Plug 2: 75 sx with 2% CaCl₂ set at 2390'. WOC 3 hours and tagged at 2195'. Plug 3: 35 sacks set at 534'. Plug 4: 20 sacks set at 50' to surface. Plugging operations witnessed by Mr. Duncan Whitlock with BLM. Cut off casing and welded 1/4" plate with 1" ball valve on casing stub. Rig released 9/18/02.

ACCEPTED FOR RECORD

OCT 21 2002

ALEXIS C. SWICORDA
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed

Title Regulatory Affairs Coordinator

Date 10/17/2002

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side