

EDDY
HUSKY OIL CO. OF
DELAWARE

Wildcat
2 Forehand
Sec 15, T23S, R27E

NM
Page #3

10-11-76

Continued

DST (Delaware) 5322-60', open 1 hr 5 mins, rec
503' DF + 120' VSO&GCM, 1 hr ISIP 213#, FP 114-
164#, 2 hr FSIP 534#, HP 2804-2804#, BHT 110 deg
Perf (Delaware) @ 5337', 5340', 5342', 5346',
5350', 5375', 5379', 5384', 5387', 5477', 5503',
5525' w/2 SPI
Acid (5477-5525') 500 gals
Swbd $\frac{1}{2}$ BF w/tr oil (5477-5525')
Acid (5337-87') 900 gals
Swbd 1 BF w/tr oil (5337-87')
Perf (Delaware) @ 4081', 4085', 4605', 4608' w/2
SPI
Acid (4605-08') 600 gals

11-2-22 NM

10-11-76

Continued

Swbd dry (4605-08')
Acid (4081-85') 500 gals
Swbd 1 $\frac{1}{2}$ BW (4081-85')
BP @ 3965'
Perf (Delaware) @ 3737', 3739', 3743', 3746',
3749', 3751' w/2 SPI
Acid (3737-51') 1092 gals
Swbd 143 BO & oil emulsion + 10% wtr (3737-51')
Frac (3737-51') 9000 gals kerosene + 13,000# sd
TD 5610'; PBD 3965'; Complete
Delaware Discovery, No Suggested Field Name
LOG TOPS: Salt 1186', Base Salt 1873', Delaware
Sand 2094', Bone Spring 5532'
LOGS RUN: DILL, CNL, FDC, MLAT, HDT
COMPLETION ISSUED

11-8-76

11-13-76

11-2-22 NM

IC 30-015-70164-76