Form 9-331 (May 1963)

DEPARTMENT OF THE INTERIOR (Other Instructions on re-

GEOLOGICAL SURVEY

Form approved.

	Budget	Buren	iu A	0. 42	101424
5. LEASE	DESIGN.	ATION	VND	SERIA	M. NO.
ALAA	. 11	رسم ر	11	,	
NM	י עט י	(37	16	L	
6. IF IND	HAN. ALİ	OTTER	OR	TRIBE	NAME

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.) 1. 7. UNIT AGREEMENT NAME DRY HOLE OLD INDIAN DRAW UNIT OTHER 2. NAME OF OPERATOR JAN 24 1977 AMOCO PRODUCTION COMPANY OLD INDIAN DRAW UNIT ADDRESS OF OPERATOR U.S. GEOLOGICAL SURVEY P.O. DRAWER A, LEVELLAND, TEXAS 79336 LOCATION OF WELL (Report location clearly and in accordance with any state leaffer the Lagrange of the location of the location clearly and in accordance with any state leaffer the lagrange of the location INDIAN DRAW DELAWARE
11. SEC., T., R., M., UR BLK. AND
SURVEY OR AREA 660' FAL X 1973' FWL, SEC. 19 (UNIT C NE/4 NW/4) 19-22-28 NMPM 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 00-015-21960

3074.2

EDDY

Copy to S.t.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	CE O	F INTENTION TO:	RECEIVATEDENT REPORT OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING	WATER SHUT-OFF REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE	 FREE TREATMENTS	1
SHOOT OR ACIDIZE		ABANDON*	 SHOOTING OR ACIDIZING ABANDONMENT*	I
REPAIR WELL	L	CHANGE PLANS	 (Other)	J
(Other)			Note: Report results of multiple completion on Well	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-6-77 COMMENCED PXA PROCEDURE BY LOADING HOLE WITH MUD SPOT 100 ft. (45 SX) CLASS "H" NEAT CEMENT PLUG RUN TUBING AND AT THE TOP OF THE INDIAN DRAW DELAWARE SAND INTERVAL 3230' to 3330. SPOT 100 ft. (45 sx) CLASS "H" NEAT CEMENT PLUG AT THE TOP OF THE DELAWARE SAND INTERVAL 2340' to 2440'. SPOT 100 ft. (65 SX) CLASS "H" NEAT CEMENT PLUG IN AND OUT SPOT 40 ft. (10 SK) PLUG OF THE 8 5/8" CASING 350' - 450'. ON CAP. ERECT PLUG AND ABONDONMENT MARKER. CACTUS RIG 11:00 PM 1-6-77. CLEAN UP LOCATION AND RESTORE GROWN TO CONTOUR.

WILL ADVISE WHEN FINAL INSPECTION CAN BE

18. I hereby certify that the foregoing is true and correct	102 1 71 7 10 10 10 10 10 10 10 10 10 10 10 10 10	
SIGNED Kay W. Cox	TITLE Administrative Assistant	DATE 1-13-77
(This space for Federal or State office use)	TITLE ACTING DISTRICT ENGINEER	FEB 7 - 1978
CONDITIONS OF APPROVAL, IF ANY:	•	

DIV.

· Susp.

BASS

*See Instructions on Reverse Side