

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

AUG 21 1978

O. C. C.
ARTESIA, OFFICE

Supervisors O&G
C-102 and C-103
Effective 1-1-65
30-015-22475

4. Indicate type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Firm or Lease Name Little Squaw
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat - Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator J. C. Barnes Oil Company ✓
3. Address of Operator P. O. Box 505 Midland, TX 79702
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>N</u> LINE AND <u>1980</u> FEET FROM THE <u>W</u> LINE, SECTION <u>27</u> TOWNSHIP <u>22 S</u> RANGE <u>28 E</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3074' G.R..

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 3/4" hole @ 12,735.00'

Ran 5 1/2" casing (17 & 20#) to 12,745.00' on July 20, 1978.

Top - 1400' 20# N-80
3700' 17# N-80
1000' 17# L-80
2746' 17# N-80
Bottom - 3954' 20# N-80

Cement used: 800 sx Type H w/3/4 of 1% CFR-2
1/4# FS, 4/10 of 1% Hal. 22, 5# KCL
650 sx Trin. Lite WT

TOC outside casing by temp survey - 6000'

Test casing - 4000# - OK
WOC 7-20-78 to 8-7-78

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Field Supt. DATE August 14, 1978

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE AUG 25 1978

CONDITIONS OF APPROVAL, IF ANY: