

Submit 3 Copies to Appropriate District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dst
Op +

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

JAN 18 1994

WELL API NO.
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name B.K.E.
8. Well No. 1
9. Pool name or Wildcat Undesignated Delaware
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3053' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL GAS WELL OTHER SWD

2. Name of Operator
Rowland Trucking Inc.

3. Address of Operator
P.O. Box 340, Hobbs, NM 88241

4. Well Location
Unit Letter H : 2310 Feet From The North Line and 860 Feet From The East Line
Section 13 Township 23S Range 27E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: Convert to S.W.D. <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

ORDER #SWD-495

- Spotted 25 sxs cement from 5546-5683'.
- Perforated Cherry Canyon 4014-42', 4072-128', and 4172-220' with 1 JSPF (total 135 holes).
- Acidized perms with 6700 gals. 15% HCL.
- Ran step-rate test.
- Sand frac perms with 32000 gals gel and 92000 lbs. 16-30 sand.
- Ran 7" Baker Model AD-1 plastic coated packer and 2 7/8" plastic coated tubing.
- Loaded hole with treated packer fluid and set packer at 3954'.
- Tested casing to 500 psi for 15 min. (witnessed by NMOCD - chart attached).
- Prepare to install surface facilities.

Part ID-3
3-4-94
conv to SWD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Marc Wise TITLE Agent DATE 1/14/94
TYPE OR PRINT NAME Marc Wise TELEPHONE NO 392-6950

(This space for State Use)
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE JAN 27 1994

CONDITIONS OF APPROVAL IF ANY