

C/S 7

NM OIL CONS. COMMISSION
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
New Mexico 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other APR 18 1983

2. NAME OF OPERATOR
Pogo Producing Company ✓ O. C. D.

3. ADDRESS OF OPERATOR
ARTESIA, OFFICE
P.O. Box 10340 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 890' FEL
AT TOP PROD. INTERVAL: 660' FSL & 890' FEL
AT TOTAL DEPTH: 660' FSL & 890' FEL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Run and cement 5 1/2" csg.

5. LEASE
NM 15433

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
NEL

9. WELL NO.
3

10. FIELD OR WILDCAT NAME
Loving Cherry Canyon

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 9, T-23-S, R-28-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3044.8 GR 3058.8 KDB

RECEIVED
(NOTE: Report results of multiple completion or zone change on Form 9-330.)
APR 12 1983
MINERALS
ROSWELL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/9/83 TD 4395' - TD 7 7/8" hole at 4395'. Run open-hole logs.
4/10/83 TD 4395' - Ran 98 jts (4010.62') 5 1/2" 14# J-55 Rg-3 ST&C csg, Shoe 1.2' and float collar 1.72' (total string 4013.54'). Shoe set at 4010' and float collar set at 3966'. Cemented with 940 sx Lite w/1/4# celloseal per sx followed by 300 sx neat. Circ 90 sx cmt. CIP at 7:50 pm CST 4/9/83. Witnessed by Mr. Cortez of BLM. ND BOP and NU well head. Rig released 12 am CST 4/9/83. Prep to complete well.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James R. Henry TITLE Division Engineer DATE 4/11/83

ACCEPTED FOR RECORD (Use this space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE _____ DATE _____
CONDITIONS OF APPROVAL APR 15 1983

ROSWELL, NEW MEXICO