

NM OFFICE OF THE UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
CARTERSBURG, NEW MEXICO

SUBMIT IN TRI
(Other instruction on re-

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

| | | |
|---|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. NM 40655 |
| 2. NAME OF OPERATOR Kaneb Energy Company | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR 400 Wilco Building Midland, Texas 79701-4466 | | 7. UNIT AGREEMENT NAME |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL & 330' FWL | | 8. FARM OR LEASE NAME Federal 24 |
| 14. PERMIT NO. API #30-015-25408 | | 9. WELL NO. 2 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3482' GL 3493' DF | | 10. FIELD AND POOL, OR WILDCAT Wildcat |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sand Dunes (Cherry Canyon) |
| | | 12. COUNTY OR PARISH Eddy |
| | | 13. STATE New Mexico |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

11-6-85: RU Apollo Wireline and ran GR/CBL/CCL log from 6140' to 4770'. TOC @ 5120'. Perf Cherry Canyon at 6065' - 6075' w/ 2 JSPF (22 holes). RU Monument Rig #34. TIH w/ Model R pkr, SN and 173 jts. 2-3/8" tbg. Set pkr at 5510'.

11-7-85: Pumped 10% acetic acid away on spot. Broke down @ 2000#. Pumped 5 BF @ 4.2 BPM @ 2450#. Open bypass. Spot 15% NE-HCl in tbg. Close bypass. Acidized perfs 6065' - 6075' w/ 1500 gals 15% NE-HCl w/ iron control, clay stab, 35 7/8" ball sealers. Surged balls, completed acid job @ 2300# @ 4 BPM. Made swab runs, recovered 33 BLW, LTR 49 BLW.

RECEIVED BY

DEC 19 1985

O. C. D.

ARTESIA, OFFICE

DEC 18 1985

CARTERSBURG, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Ass't Div. Production Mgr.

DATE Dec. 12, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side