

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

JUN 22 '90

WELL API NO.
30-015-26368

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
RB Operating Company

3. Address of Operator
2412 N. Grandview, Suite 201, Odessa, Tx. 79761

4. Well Location
Unit Letter H : 2140 Feet From The North Line and 400 Feet From The East Line
Section 23 Township 23S Range 28E NMPM Eddy County Eddy

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
2992.4 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/9/90 Spud 12-1/4" hole, drill to 579', set 8-5/8" 24# J-55 casing and cement w/350 sxs Class "C" w/2% CaCl & 1/4# Celloflake, WOC 18 hrs., tested to 1500#.

6/17/90 Drilled 7-7/8" hole to 6350', ran DLL-MLL-GR & DNL-GR-CAL cut 26 sidewall cores, set 5-1/2" 15.5# J-55 casing @ 6350' w/DV tool @ 3534'. cemented 1st stage w/400 sxs 50/50 Poz "C" + 2% D20, .2% D112, .5% D65, 10#/sx D42, 2% SI & 185 sxs Class "C" + 4% D60, .2% D65, .1% D133; 2nd stage w/1110 sxs 35/65 Poz "C" + 6% D20, 10% D44 and 100 sxs Class "C" + 2% SI.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Terrell Hansen TITLE Prod. Engineer DATE 6/24/90

TYPE OR PRINT NAME Terrell Hansen TELEPHONE NO. (915) 362-6302

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE JUN 26 1990

CONDITIONS OF APPROVAL, IF ANY: