

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE\*  
(Other instructions on re-  
verse side)

Form approved,  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC - 068282 - B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanson Federal

9. WELL NO.

# 15

10. FIELD AND POOL, OR WILDCAT

Delaware-Mason North

11. SEC., T., R., M., OR BLK. AND  
SUBVEY OR AREA

Sec 25, T 26-S, R 31-E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Hanson Oil Corporation

3. ADDRESS OF OPERATOR  
P. O. Box 1515, Roswell, New Mexico 88201

RECEIVED

NOV 10 1976

O. C. C.  
ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FNL & 2600' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3268 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud well & casing job

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-27-76 Moving in, rigging up rotary, spud well

9-28-76 T.D. 473', Set csg. @ 458', cmted w/175 sx class C cmt. w/2% cal. chlor., Plug Down @ 9:45 a.m. 9-29-76, Circ. 25 sx. to pit, USGS notified but not present. W.O.C. 18 hrs., Test csg. to 800 PSI for 30 min., Held O.K.

10-16-76 T.D. 4295', set 4 1/2" csg. @ 4283' (1019' N-80, 11.60# & 3264' of J-55 9.5#), cmted w/125 sx. class C cement w/5 lb. salt per sx. & 2% gel. USGS notified but not present, W.O.C. 18 hrs., Test to 1000 PSI for 30 min., held O.K.

RECEIVED

NOV 08 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Ray Miller*

TITLE V.P. Production

DATE 11-4-76

(This space for Federal or State office use)

APPROVED BY

*Joe J. Lara*

TITLE ACTING DISTRICT ENGINEER

DATE NOV 9 1976

CONDITIONS OF APPROVAL, IF ANY: