

Instructions

General: This form is designed for submitting proposals to perform certain well operations, as indicated, on all types of lands and leases for appropriate action by either a Federal or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable State or Federal regulations concerning subsequent work proposals or reports on the well.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on this reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal or State agency offices.

Items 15 and 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective production zone.

Item 22: Consult applicable Federal or State regulations, or appropriate officials, concerning approval of the proposal before operations are started.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-711-396
839-171

202 Instructions On Reverse Side

DEPARTMENT OF THE INTERIOR CEMENT PROGRAM (Also see Exhibit "F")

13-3/8" Casing - 155 sx HOWCO-LITE containing 5#/SL

gilsonite + 1/4#/SL Flocele + 200 sx
Class "C" containing 2% CaCl₂ and 1/4#/SL
flocele.

9-5/8" Casing - 925 sx Halliburton "Light" cement with 2%
CaCl₂, 5# gilsonite per sack and 1/4# flo-
cele per sack.

7-5/8" Casing - 125 sacks Class "H" cement (5# KCL/SL and 0.6%
CFR-2 per sack.

4-1/2" Casing - 270 sacks Class "H" cement with 0.75% CFR-2
per sack and 5# KCL per sack.

DATE OF HOLES	NO. OF CEMENT	WEIGHT PER FOOT	REMARKS
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	
12-15	3-25	38	

112 Program: See Exhibit "G"

808 Program: Series 1800 808 - See Exhibit "H"

Gas not dedicated