

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR:
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FNL & 735' FEL, Sec. 8
AT TOP PROD. INTERVAL: (Unit H, SE/4, NE/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☒
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
11952
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal BH
9. WELL NO.
#1
10. FIELD OR WILDCAT NAME
Wildcat Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
8-26-23
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4468.2 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 8361' and logged well. Set a 297' plug from 7553'-7850'. Ran 998' of 17# K-55 5-1/2" casing and 6202' of 15-1/2# K-55 5-1/2" casing set at 7200'. Cemented with 650SX Lite cement (with .6% CFR2, 5# Gilsonite/SX, 1/4# Flocele/SX and 15# salt/SX) and with 300 SX Class H cement (with .6% Halad 22A and .4% CFR2). Plugged down at 11:25 p.m. 8-16-80. Ran temp. survey. Top of cement at approx. 2050'. Will test casing when service unit is moved in.

0+4-USGS, A 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou
Subsurface Safety Valve: Manu. and Type Set @ Ft.
18. I hereby certify that the foregoing is true and correct
SIGNED Bob Davis TITLE Admin. Analyst DATE 8-27-80

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY