NMOCD- Artesia

C/SP

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No.: NM-27459
6. If Indian, Allottee or Tribe Name:
7. If Unit or CA, Agreement Designation: NA
8. Well Name and No.: Monsanto Federal #1
9. API Well No.: 30-015-25276
10. Field and Pool, or Exploratory Area: Unnamed
11. County or Parish, State: Eddy NM

1. Type of Well: ☐ Oil Well ☐ Gas Well ☒ Other Abandon Well
2. Name of Operator: General Atlantic Resources, Inc.
3. Address and Telephone No.: 410 17th Street, Suite 1400, Denver,CO., 80202 / (303) 573-5100
4. Location of Well (Footage, Sec., T., R., M., or Survey Description): 660' FSL & 1980' FWL, SESW Section 22, T25S-R26E

12. **CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other Plugging	☐ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Post ID-2
1-6-95
PAA

11/7/94 Well plugging was witnessed by Mr. Don Early of the BLM.

The well was plugged as follows:

1) Set CIBP at 2020', cap with 35' class "C" neat cement plug on top of CIBP.
2) Set CIBP at 1830', Cap with 35' class "C" neat cement plug on top of CIBP.
3) Shot off 4.5" casing at 1102'.
4) Set 50 sx plug 100' at 1102'.
5) Set 50 sx plug from 1020' to 920', tagged stationary.
6) 25 sx plug set from 250' to 150', tagged ok.
7) Set 25' plug at surface.
8) Cut off wellhead 4.5', and welded marker.
9) Cleaned up site.

BUREAU OF LAND MANAGEMENT RECEIVED NOV 18 1994 DIST. 6 Carlsbad

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed [signature] Title Regulatory Coordinator Date 11/16/94

(This space for Federal or State office use)

Approved by (ORIG. SGD.) JOE G. LARA Title PETROLEUM ENGINEER Date 12/13/94
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side