		ي	CLS
rm 3160-5	UNIT	ED STATES	FORM APPROVED
une 1990)		OF THE INTERIOR	Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT			5. Lease Designation and Serial No.
		NM-80645	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals			6. If Indian, Allottee or Tribe Name
	SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well			
X Oil Gas Other			8. Well Name and No.
2 Name of Operator YATES PETROLEUM CORPORATION (505) 748–1471)			Lily ALY Federal #8
YATES PETROLEUM CORPORATION (505) 748–1471) 3 Address and Telephone No.			
105 South 4th St., Artesia, NM 88210			10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)			Ingle Wells Delaware
990' FSL & 9	90' FEL of Section	n 3-T24S-R31E (Unit P, SESE)	11. County or Parish, State
			Eddy Co., NM
2. CHECK A	APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
	TYPE OF SUBMISSION TYPE OF ACTION		
			Change of Plans
L_J Notice of	f Intent		New Construction
X Subsequent	ent Report	Plugging Back	Non Routine Fracturing
		Casing Repair	Water Shut-Off
Final Abandonment Notice		Altering Cusing	Conversion to Injection
		X Other Spud, resume drilli	
		surface casing & cement	Completion or Recompletion Report and Log form 3
give subsurface local Spudded a 26 pipe. Cemen	nons and incasured and inceiventica b" hole with rat h nted to surface.	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta d depths for all markers and zones pertinent to this work )*	t (Nate: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) inting any proposed work. If well is directionally drilled, et 40' of 20'' conductor
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta al depths for all markers and zones pertinent to this work )* tole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serv:	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log form ) intring any proposed work If well is directionally drilled. et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta al depths for all markers and zones pertinent to this work). To le machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ble at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 cas Pattern notched guide shoe set sacks 65-35 Poz C, 6% gel, 1/4#/sac Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out luced hote to 11". Resumed drillin	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log (urin ) inting any proposed work. If well is directionally drilled, et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface boar Spudded a 26 pipe. Cemen Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta d depths for all markers and zones pertinent to this work ). tole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 cas Pattern notched guide shoe set eacks 65-35 Poz C, 6% gel, 1/4#/sac Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log (unit) intring any proposed work. If well is directionally drilled, et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC
give subsurface boar Spudded a 26 pipe. Cemen Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta d depths for all markers and zones pertinent to this work ). tole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 cas Pattern notched guide shoe set eacks 65-35 Poz C, 6% gel, 1/4#/sac Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log form ) inting any proposed work. If well is directionally drilled, et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta d depths for all markers and zones pertinent to this work ). tole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 cas Pattern notched guide shoe set eacks 65-35 Poz C, 6% gel, 1/4#/sac Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out	t (Nute Report results of multiple completion on Well Completion of Recompletion Report and Log (orm) inting any proposed work. If well is directionally drilled, et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a 24 hours and	tions and incasured and true vertice b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s , weight 12.4). T 7:15 AM 1-6-96. H and tested to 500#	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta a depths for all markers and zones pertinent to this work )* to le machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 tas Pattern notched guide shoe set a stacks 65-35 Poz C, 6% gel, 1/4#/sacl Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out hered to 11". Hesumed drillin AM 2 Drilled out Drilled out AM 2 Drilled out Drilled Drilled Out Drilled Drilled Out Drilled Drilled Out Drilled Drilled Drillin Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drille	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log (urin ) inting any proposed work. If well is directionally drilled, et 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a 24 hours and	foregoing is the and porrect	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta d depths for all markers and zones pertinent to this work )* toole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3, tas Pattern notched guide shoe set eacks 65-35 Poz C, 6% gel, 1/4#/sac Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK.) Drilled out thread hole to 11". Hesumed drillin	t (Nute Report results of multiple completion on Well Completion of Recompletion Report and Log form ) intring any proposed work. If well is directionally drilled, eet 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a 24 hours and 14 Thereby certify that the Signed	toons and measured and true vertice, b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s weight 12.4). T 7:15 AM 1-6-96. H and tested to 500# d 15 minutes. Rec foregoing is true and correct the state of the second or Stole office use)	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta a depths for all markers and zones pertinent to this work )* to le machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 tas Pattern notched guide shoe set a stacks 65-35 Poz C, 6% gel, 1/4#/sacl Cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out hered to 11". Hesumed drillin AM 2 Drilled out Drilled out AM 2 Drilled out Drilled Drilled Out Drilled Drilled Out Drilled Drilled Out Drilled Drilled Drillin Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drilled Drilled Drilled Drillin Drilled Drilled Drille	t (Nute Report results of multiple completion on Well Completion of Recompletion Report and Log (orm.) intring any proposed work. If well is directionally drilled, eet 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g.
give subsurface local Spudded a 26 pipe. Cemer Resumed dril TD 671'. Re of casing se at 624'. Ce (yield 1.99, 14.8). PD 7 Nippled up a 24 hours and 14 Thereby certify that the Signed (This space for Federal	toons and measured and true vertice, b" hole with rat h hted to surface. Lling a 17-1/2" ho eached TD at 12:15 et at 671'. 1-Tex emented with 375 s weight 12.4). T 7:15 AM 1-6-96. H and tested to 500# d 15 minutes. Rec foregoing is true and correct the state of the second or Stole office use)	surface casing & cement pertinent details, and give pertinent dates, including estimated date of sta a depths for all markers and zones pertinent to this work )* tole machine at 11:30 AM 1-3-96. So NOTE: Notified BLM Answering Serve ole at 9:30 PM 1-5-96. AM 1-6-96. Ran 15 joints of 13-3 tas Pattern notched guide shoe set a stacks 65-35 Poz C, 6% gel, 1/4#/sacle cailed in with 200 sacks "C" and 2% Sumped plug to 400 psi, OK. Circul for 10 minutes, OK. Drilled out hered hole to 11". Hesumed drillin AM 2 Difference of the set of the	t (Nute Report results of multiple completion on Well Completion or Recompletion Report and Log (urin ) intring any proposed work. If well is directionally drilled, eet 40' of 20" conductor ice in Carlsbad of spud. /8" 48# 8rd H-40 ST&C (678.0 at 671'. Insert float set k celloseal and 2% CaCl2 CaCl2 (yield 1.34, weight ated 140 sacks to pit. WOC. at 8:30 AM 1-7-96. WOC g. Date Jan. 8, 1996

\*See Instruction on Reverse Side