

District I

PO Box 1980, Hobbs, NM 88241-1980

District II

PO Drawer DD, Artesia, NM 88211-0719

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

PO Box 2088
Santa Fe, NM 97504-2088

Form C-101

Revised February 10, 1994

Instructions on back

Submit to Appropriate District Office

State Lease - 6 Copies

Fee Lease - 5 Copies

APR 17 1997

AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK OR ADD A ZONE

1. Operator Name and Address Mallon Oil Company P.O. Box 3256 Carlsbad, NM 88220					2. OGRID Number 013925									
4. Property Code 20475					5. Property Name Mallon 16 State					3. API Number 30-015-29538				
6. Well No. 2					7. Surface Location									
UL or lot no. D	Section 16	Township 24S	Range 26E	Lot Idn. N/A	Feet From the 660	North/South Line North	Feet From the 660	East/West Line West	County Eddy					

8. Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn.	Feet From the	North/South Line	Feet From the	East/West Line	County
9. Proposed Pool 1 WC Black River - Delaware, West					10. Proposed Pool 2 May 20, 1997				

11. Work Type Code N	12. Well Type Code O	13. Cable/Rotary R	14. Lease Type Code S	15. Ground Level Elevation 3443'
16. Multiple N/A	17. Proposed Depth 5500'	18. Formation Delaware	19. Contractor Unknown	20. Spud Date

21. Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
12-1/4"	9-5/8"	36#	500'	150	Surface
8-3/4"	5-1/2"	15.5# - 17#	5500'	1085	300'

22. Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 12-1/4" hole to 500', run and set 500' of 9-5/8" x 36# K55 LTC casing. Cement with 150 sks Class C + 2.00% CaCl₂, yeild 1.34, ppg 14.80. Circulate cement to surface. WOC - 18 hours

2. Drill 8-3/4" hole from 500'-5500'. Run and set 5500' of 5-1/2" x 15.5#/17# K55 LTC casing. Lead cement: 225 sks 35:65 POZ (35% POZ, 65% Class C) + 6% gel + 5% salt + .25 lb/sk Celloseal yeild 2.04 ppg 12.5. Tail cement: 860 sks Super C Modified, 61 lb/sk C cement, 15 lb/sk POZ A, 11 lb/sk BA 90 bonding, .61 lb/sk FL-52, .44 lb/sk FL-25, yeild 1.44, ppg 13.6.

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief.		OIL CONSERVATION DIVISION	
Signature: <i>Duane C. Winkler</i>		Approved by: <i>Jim W. Burns</i> BGA	
Printed Name: Duane C. Winkler		Title: District Supervisor	
Title: Operations Manager		Approval Date: 4-17-97 / Expires 4-17-98	
Date: 04/08/97	Phone: (505)-885-4596	Conditions of Approval:	
		Attached: _____	

C14F
Bum
SL
OP