Form 2160-3 (July 1992)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

 A_{i}^{-}

SUBMIT IN TRIP (Other instructions on

reverse side)

FORM APPROVED

5. LEASE DESIGNATION AND SERIAL NO.

OMB NO. 1004-0136 Expires February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN LC-053259 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 1a. TYPE OF WORK X Drill Deepen 7. UNIT AGREEMENT NAME 1736-4 b. TYPE OF WELL Grayburg Jackson WFU X Gas Well Single Zone Multiple Zone Oil Well 8. FARM OR LEASE NAME, WELL NO. 2. NAME OF OPERATOR 14711 Tract MA No. 7 Shahara Oil, LLC 3. ADDRESS AND TELEPHONE NO. 9. API WELL NO. 30-015-3034 505-885-5433 207 W. McKay Phone: 10. FIELD AND POOL, OR WILDCAT Grayburg Jackson 7 Rivers-QN-GB-SA 505-885-4989 Carlsbad, NM 88220 Fax: 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*) 11. SEC., T., R., M., OR BLK. At surface 1305' FNL & 1305' FEL, Unit A AND SURVEY OR AREA Section 28, T17S, R30E At proposed prod. zone Same 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE * 13. STATE 12. COUNTY OR PARISH 1.5 miles southeast of Loco Hills, NM Eddy NM 15. DISTANCE FROM PROPOSED 16. NO. OF ACRES IN LEASE 17. NO. OF ACRES ASSIGNED TO THIS WELL LOCATION TO NEAREST 1305 1080 40 PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any) 19. PROPOSED DEPTH 20. ROTARY OR CABLE TOOLS 18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, 1000' 3500' OR APPLIED FOR, ON THIS LEASE, FT. Rotary PROPOSED CASING AND CEMENTING PROGRAM SIZE OF HOLE GRADE, SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 500' 300 sx - circulate WITNES 12 1/4" 8 5/8" 24# K-55 5 1/2" 17# J-55 3500 600 sx -7 7/8" 100' above 8 5/8" csg shoe ROSWELL CONTROLLED WATER BASIN Post ID-1 The operator proposes to drill to a depth sufficient to test the Queen and Grayburg for oil. Specific programs are outlined in the following attachements: APF+ LOC SURFACE USE AND OPERATING PLAN **EXHIBIT A - ROAD MAP EXHIBIT B - EXISTING WELL MAP** APPROVAL SUBJECT TO EXHIBIT C - LOCATION AND ACREAGE DEDICATION PLAT GENERAL REQUIREMENTS AND **EXHIBIT C-1 - TOPO MAP** SPECIAL STIPULATIONS **EXHIBIT D - DRILLING AND RIG LAYOUT** ATTACHE**D EXHIBIT E - 3M BOP EQUIPMENT** IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally data of subsurface locations and measured and true vertical depths. Give blowout preventer program, if any 55 IDav SIGNED (This space for Federal or State office use) APPROVAL DATE PERMIT NO Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon Acting Assistant Field Office Manager, CONDITIONS OF APPROVAL, IF ANY: Lands and Minerals for his for realizable in the H JUL 1 4 1990

DISTRICT I P.O. Box 1980, Hobbe, NM 88241-1980

DISTRICT IV

State of New Mexico

Energy, Minerals and Natural Resources Department

Form C-102
Revised February 10, 1994
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

DISTRICT II P.O. Drawer DD, Artesia, NM 88211-0719

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

P.O. BOX 2088, SANTA FE, N.M. 87504-2088

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code 28509 Grayburg Jackso	Pool Name n 7Rivers-QN- GB-SA
Property Code	Property Name Grayburg Jackson WFU Tract MA	Well Number 7
ogrid No. 143119	Operator Name SHAHARA OIL, LLC	Elevation 3632

Surface Location

ſ	UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
	Α	28	17 S	30 E		1305	NORTH	1305	EAST	EDDY

Bottom Hole Location If Different From Surface

Bottom Hole Bottatom M. Sarrot and 1132 Tarrot									
UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
									ļ 1
Dedicated Acre	r Infill Co	nsolidation	Code Or	der No.					

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

ON A NON STAND	ARD UNIT HAS BEEN ATTROVED BY THE	
	3631.4' 3629.3' 1305' 3624.5' 3626.3'	OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and betief. Signature Signature Title Date SURVEYOR CERTIFICATION
		I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison, and that the same is true and correct to the best of my belief. APRIL 29, 1998 Date Surveys DMCC Signature & Shafford Market Surveys DMCC Signature & Shafford Market Surveys DMCC Centilia No. RONNICH DSON 3239 Centilia No. RONNICH DSON 3239 12641 APOFESSION CODONALD 12185

Exhibit "E"

BOP Equipment

Shahara Oil, LLC
Grayburg Jackson WFU Tract MA No. 7

1305' FNL & 1305' FEL, Unit A Section 28, T17S, R30E Eddy County, New Mexico DRILLING CONTROL
CONDITION IN-B 3000 PSI WP

H2S TRIM REQUIRED Lease No. NM-060528 YES HO 15 A SLOGIE LINE OR FLOW LINE FILL LIME D HEAD 10 8 5 G 12 PIPE RAMS ==© A BLIND FLANGE W/RE-ENTRY VALYE

DRILLING CONTROL

MATERIAL LIST - CONDITION III - 3

Wellhead

3000f M.P. Dual ram type preventur, hydraulic operated with 1" steel, 3000f M.P. control lines (where substructure height is adequate, 2 - 3000f M.P. single ram preventure may be utilized with 3000f M.P. drilling spool with 1" minimum flanged outlet for kill line and 3" minimum flanged outlet for choke line. The drilling spool is to be installed below the single ram type preventers).

3000f M.P. Annular Preventer with 1" steel, 3000f M.P. control lines.

Rotating Mess with fill up outlet and extended Bloois

D Rotating Head with fill up outlet and extended alouse line.

1,3,4, 2" minimum 1000f W.P. flanged full opening steel gate 7,2, valve, or Helliburton Lo Torr Plug valve.

2 ainimum 10001 W.P. back pressure valve.

5,6,9 3" minimum 1000f W.P. flanged full opening steel gate valve, or Halliberton to Tord Plug valve.

12 30 minimum Schedule 10, Grade B, seemless line pipe.

13 2" minimum x 3" minimum 2000@ W.P. flanged cross.

10,11 2" minimum 10000 W.P. edjustmble cheke bedies.

14 Cameron Mud Cauge or equivalent (location optional in Cheke line).

15 2º minimum 1000f W.P. Clanged or threaded full opening steel gate valve, or Malliburton Le Toro Flug valve.

SCALE: PATE EST NO PAGE

BRICO DY

CONCRED DY

CONCRED DY