Reference No. 088210-32



June 2, 2017

Mr. Zane Kurtz Sr. Safety and Environmental Representative 5509 Champions Dr. Midland, TX 79706 VIA E-Mail: zane_kurtz@eogresources.com

Dear Mr. Kurtz:

Re: Assessment Summary Report Bridge State Unit #602H (API #30-025-43584) 1RP-4649 EOG Resources, Inc. Site Location: Unit O, Sec. 29, T 22-S, R 35-E (Lat 32.356087°, Long -103.388662°) Lea County, New Mexico

GHD Services, Inc. (GHD) is pleased to present this report for the above referenced site. Assessment activities were performed at the Bridge State Unit #602H (hereafter referred to as the "Site"), from March 17, 2017 through May 9, 2017 by GHD. The Site is located within Unit O, Section 29, Township 22 South, Range 35 East, in Lea County, New Mexico (Figure 1).

The Site is an active well drilling site located approximately 14 miles west-southwest of Eunice, New Mexico. According to EOG personnel, a release of approximately 75 barrels (bbls) of drilling fluid occurred. None of the drilling fluid was recovered. The release was discovered on March 16, 2017 and a C-141 Form was submitted to the New Mexico Oil Conservation Division (NMOCD) on March 21, 2017. A remediation permit (RP) number 1RP-4649 was assigned to the Site.

GHD obtained a list of the drilling mud constituents from AES Drilling Fluids, LLC that were used for the drilling of the well. GHD reviewed the safety data sheets (SDSs) for the listed materials and prepared a summary of potential contaminants of concern. Based on review of the list and associated safety data sheets for the materials, it appears that the primary contaminants of concern (COCs) are potassium chloride and diesel. Based on this, the soil samples were analyzed for full range total petroleum hydrocarbons (TPH), benzene, toluene, ethylbenzene, and xylene (BTEX) and chloride. A copy of the summary of SDSs and the SDSs are included as Appendix A.

Initial soil sampling of the release area was performed by GHD on March 17, 2017. Subsequent soil sampling was performed by GHD on March 28, 2017, April 24, 2017, and May 9, 2017 following excavation of impacted soil in the affected area. Approximately 480 cubic yards (yd3) of impacted soil was removed and disposed of at the Sundance Services - Parabo Facility in Eunice, New Mexico (Sundance).





1. Introduction

There are relatively few groundwater wells in the area of the Site with which to obtain a depth to groundwater. Based on information available from the United States Geological Survey (USGS) website, the closest USGS gauging site, located approximately 1.8 miles north-northeast of the Site (see Appendix B, Water Well Report for depth to water), indicates groundwater at a depth of approximately 78 feet below ground surface (bgs) in 1997.

No wellhead protection areas or surface water bodies were identified within 200 to 1000 ft. of the Site. Therefore, the preliminary total ranking score for the Site is 10 (see table below).

Based on this score, the applicable NMOCD Site-specific Recommended Remediation Action Limits (RRALs) are 10 milligrams per kilogram (mg/kg) for benzene, 50 mg/kg BTEX, 1,000 mg/kg for TPH, and 250 mg/kg for chlorides.

New Mexico Oil Conservation Division Site Assessment	
Ranking Criteria	Score
Depth to Ground Water (> 50-99 ft. bgs)	10
Wellhead Protection Area (> 1000 ft. from water source, > 200 ft. from domestic source)	0
Distance to Surface Body Water (200-1000 ft.)	0
Ranking Criteria Total Score	10*

1. NMOCD Guidelines for Remediation of Leaks, Spills and Releases, August 13, 1993

2. Assessment Activities

Site assessment activities were performed between March 17, 2017 and May 9, 2017 by GHD. The assessment included initial sampling, excavation of the top 6 inches of impacted soil, and re-excavation to 12 inches as needed. Confirmation sampling was performed following final excavation activities. SDR Enterprises, LLC (SDR) of Hobbs, New Mexico, performed the excavation of impacted soil. Hall Environmental Analysis Laboratory (Hall Environmental) of Albuquerque, New Mexico and Xenco Laboratories (Xenco) of Midland, Texas analyzed the soil samples. Laboratory analytical reports are included in Appendix C.

Initial soil sampling consisted of collecting four soil samples from approximately 6 inches below ground surface within the affected area. Because the COCs were calcium chloride and diesel, the samples were submitted to Hall Environmental for analysis of chloride by EPA Method 300, for BTEX by EPA Method 8021, and gasoline, diesel, and motor oil range TPH by EPA Method 8015. The analytical data obtained from the initial soil samples indicated all analyzed constituents were below the laboratory reporting limits. The initial soil sample results are summarized in Table 1.

From March 22 to March 29, 2017 SDR removed the top 6 inches of soil in the affected area. On March 28, 2017, GHD collected four additional soil samples from the excavated area. The samples were



submitted to Hall Environmental for analysis of chloride by EPA Method 300, BTEX by EPA Method 8021, and TPH by EPA Method 418.1.

Laboratory analytical results from these events indicated that chloride concentrations in two samples along the southern portion of the scraped area (S-088210-032817-CM-3 and S-088210-032817-CM-4) were above the RRAL for chloride. These samples contained chloride concentrations of 570 mg/kg and 900 mg/kg, respectively. Concentrations of BTEX and TPH constituents for all four samples submitted were below the RRALs (Table 1). Based on these results, additional soil removal was performed in the southern portion of the affected area.

SDR excavated additional soil in the release area on April 18 and 19, 2017. GHD collected six more samples on April 24, 2017 and submitted them to Xenco for chloride analysis by EPA Method 300. Chloride concentrations ranged from less than the laboratory reporting limit to 45.7 mg/kg.

On May 9, 2017, GHD collected two additional samples (SS-088210-05091-CM-1 and SS-088210-05091-CM-2) in the vicinity of previously collected samples S-088210-032817-CM-3 and S-088210-032817-CM-4 (Figure 2). The samples were submitted to Xenco for chloride analysis by EPA Method 300. Chloride concentrations from these samples were either below the laboratory reporting limit or below the RRAL.

A total of approximately 480 cubic yards of impacted soil were removed during the above-mentioned scraping events and transported to Sundance for landfill disposal. Waste manifests are still being collected and will be submitted with the closure request report.

3. Summary and Recommendations

Based on the assessment of the chloride concentrations, GHD recommends the following:

- Backfilling of the scraped area with clean fill material and wheel compacting to grade.
- Fertilizing and reseeding of the disturbed area with a BLM-approved seed mix.

Should you have any questions, or require additional information regarding this submittal, please feel free to contact Bernie Bockisch at (505) 884-0672 or Bernard.Bockisch@ghd.com.

Sincerely,

GHD

Alan Brandon Senior Project Manager

AB/lb/1

Fnaick

Bernard Bockisch New Mexico Operations Manager



SOURCE: USGS 7.5 MINUTE QUAD "SAN SIMON SINK AND EAST LAKE, NEW MEXICO"

LAT/LONG: 32.355115° NORTH, 103.389177° WEST COORDINATE: NAD83 DATUM, U.S. FOOT STATE PLANE ZONE - NEW MEXICO EAST

Figure 1

SITE LOCATION MAP BRIDGE STATE UNIT #602H LEA COUNTY, NEW MEXICO EOG Resources



088210-32(000)GN-DL001 MAY 5, 2017



088210-32(000)GN-DL001 MAY 12, 2017

Bridge State Unit #602H - Summary of Soil Analytical Data

Sample ID	Depth (inches)	Date	Benzene	Toluene	Ethylbenzene	Xylenes	втех	TPH (GRO)	TPH (DRO)	TPH (MRO)	TPH (418.1)	Total TPH	Chloride
S-031717-CN-S16"	6	03/17/2017	< 0.024	<0.049	<0.049	<0.097	<0.219	<4.9	<9.8	<49.0	NA	<63.7	<30
S-031717-CN-S26"	6	03/17/2017	<0.025	<0.050	<0.050	<0.10	<0.225	<5.0	<10.0	<50.0	NA	<65.0	<30
S-031717-CN-S36"	6	03/17/2017	<0.025	< 0.050	< 0.050	<0.10	<0.225	<5.0	<10.0	<50.0	NA	<65.0	<30
S-031717-CN-S46"	6	03/17/2017	<0.024	<0.048	<0.048	<0.096	<0.216	<4.8	<9.4	<47.0	NA	<61.2	<30
S-088210-032817-CM-1	6	03/28/2017	<0.025	<0.049	<0.049	<0.098	<0.221	NA	NA	NA	21.0	21.0	66
S-088210-032817-CM-2	6	03/28/2017	<0.024	<0.048	<0.048	<0.096	<0.216	NA	NA	NA	<19.0	<19.0	38
S-088210-032817-CM-3	6	03/28/2017	<0.024	<0.048	<0.048	<0.097	<0.217	NA	NA	NA	75.0	75.0	570
S-088210-032817-CM-4	6	03/28/2017	<0.024	<0.048	<0.048	<0.095	<0.215	NA	NA	NA	91.0	91.0	900
S-088210-32-42417-BB-1*	4	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	5.51
S-088210-32-42417-BB-2*	5	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	25.3
S-088210-32-42417-BB-3*	6	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	45.7
S-088210-32-42417-BB-4*	6	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	9.14
S-088210-32-42417-BB-5*	3	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	<4.98
S-088210-32-42417-BB-6*	3	04/24/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	<4.93
SS-088210-050917-CM-1*	12	05/09/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20.4
SS-088210-050917-CM-2*	12	05/09/2017	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	42.4
NMOCD RRALs (Total R	anking Score	= 10)	10		NA				Т	otal TPH: 1,00	0		250

Notes:

All samples are in milligrams per kilogram

* = Sample Analyzed by Xenco Laboratories. All Others Analyzed by Hall Environmental

NA = Not Analyzed

NMOCD = New Mexico Oil Conservation Division

RRALs = Recommended Remediation Action Limits

Highlighted = Exceeds NMOCD RRAL



GHD | 088210-32Kurtz-1-Assessment Summary Report

Appendix A Safety Data Sheets

Operator: EOG Drilling	Rig Name and Number: H&P 653	ge State Unit #602H	Report #36
Material Used	Linit	Quantity	Comments
ARS MUI	1 GALLON GALLON	260	Distillates Diethanulamine 0.25 - 0.75% (Petroleum) 10 - 50%
AES VERT	1 BBL BBL	2363	Dissilates Dectalibrarilite 0.23 - 0.75 % (Perdeatin) 10 - 30 % Diesel #2 50 - 90%. Barite 5 - 65%
AES VIS III	50 LB SACK	35	Clay
AFS VIS I S	50 LB SACK	3	ClaySilica
AES WA II	1 GALLON GALLON	260	Phospholipids 40 - 60%
ALO MAII	TOTLEON ONLEON	200	Giutaraidenyde 20 - <30%
00540	5 ON LON DAT		Didecyldimethylammonium chlorides 5 - <10%
B2512	5 GALLON PAIL	21	Benzyl - C12 - C16 - alkyldimethyl chlorides 5 - >10%
			Ethanol 3 - <5%
BARITE SACK 4.05 SG	100 LB SACK	280	
BLUE MAX	1 GALLON GALLON	245	Surfactant Blend
C 2145	1 GALLON GALLON	355	Ethylene Glycol 5 - 10%
			Methanol 5 - 10%
CALCIUM CHLORIDE	50 LB SACK	46	CAS 10043 - 52 - 4
DEFOAMER	5 GALLON PAIL	32	Ethyl - 1 - Hexanol CAS 104 - 76 - 7
DURATEC	30 LB SACK	17	Trade Secret
ENER PAC REGULAR	50 LB SACK	12	Polyanionic Cellulose
ENERPLUS	5 GALLON PAIL	41	Distillates (Petroleum) 20 - 45%
FIBER SEAL	40 LB SACK	60	Vegetable, Cotton, Cellulose Fibers
FLR	50 LB SACK	50	Proprietary Gilsonite Blend
GEL, REGULAR	100 LB SACK	140	Bentonite, Silica
LIME	50 LB SACK	105	Calcium Hydroxide
MULTI-FIBER F	25 LB SACK	130	Trade Secret, Cellulose Blend
MULTI-FIBER M	25 LB SACK	70	Trade Secret
OIL SORB	50 LB SACK	24	Bentonite, Silica
PERMASEAL	25 LB SACK	120	Trade Secret, Silica
SALT GEL	50 LB SACK	100	Silica
SAPP	50 LB SACK	82	Disodium Pyrophosphate 100%
			CAS 7758 - 16 - 9
SILVER SEAL	50 LB SACK	88	Graphite, Silica, Trade Secret
SOLTEX	50 LB SACK	130	Acid Midified Petroleum Residum
	4510.040%		Proprietary
SUPER SWEEP	15 LB SACK	3	Polypropylene Water Soluble Corrosion Inhibitor
			Ethylene Glycol 30 - 60%
WCI 1013	5 GALLON PAIL	24	Methanol 10 - 30%
101010	O OPILLOIT I VIL	24	Alkyl Pvidine Derivs, 5 - 10%
			Alkyltrimethylene Diamine Acetate 5 - 10%
XG VIS	25 LB SACK	8	Silica. Trade Secret



ABS MUL

SECTION 1. IDENTIFICATION

Product Identifier	ABS MUL
Other Means of Identification	Blended Emulsifier
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency July 01, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) - Category 4; Acute toxicity (Dermal) - Category 4; Skin corrosion/irritation - Category 3; Serious eye damage/eye irritation - Category 2B; Skin sensitization - Category 1B; Carcinogenicity - Category 2; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 2 GHS Label Elements



×	V
Signal Word:	
Warning	
Hazard Statem	ent(s):
H302	Harmful if swallowed.
H305	May be harmful if swallowed and enters airways.
H312	Harmful in contact with skin.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H320	Causes eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
Prevention:	
P264	Wash hands and skin thoroughly after handling.
P261	Avoid breathing vapours, mist, spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing.
Response:	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P305 + P351 +	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Other Hazards

Hazardous to the environment.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Mixture of Fatty acids, tall oil	61790-12-3	10-50	
Distillates (petroleum), hydrotreated light	64742-47-8	10-50	
Fatty Amine	61791-26-2	2-3	
Blend of chemically modified tall oil derivative	68154,94-9	2-3	
Diethanolamine	111-42-2	0.25-0.75	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Get medical advice/attention if irritation develops.

Skin Contact

Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Seek medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Seek medical advice/attention.

Ingestion

Immediately call a Poison Centre or doctor. Rinse mouth with water. Do not induce vomiting. If vomiting occurs, have victim lean forward to reduce the risk of aspiration.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Specific Hazards Arising from the Chemical

Product can ignite if strongly heated and exposed to open flames. Closed containers may rupture violently when heated releasing contents.

Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Use water spray to cool containers/tanks.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Dike spilled product to prevent runoff. Do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Place contaminated vermiculite, earth or sand into suitable, covered, labelled containers for disposal. Store recovered product in suitable containers for disposal according to local regulations.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Avoid contact with eyes, skin and clothing. Do not ingest product. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Avoid generating vapours or mists. Keep containers tightly closed when not in use or empty. Keep away from heat and open flames. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials (see Section 10: Stability and Reactivity). Keep containers tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	ACGIH® TLV®		OSHA PEL		WEEL™
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Mixture of Fatty acids, tall oil	5 mg/m3	10 mg/m3	5 mg/m3	Not established	Not established	Not established
Diethanolamine	1 mg/m3 Skin		Not established		Not established	
Distillates (petroleum), hydrotreated light	5 mg/m3	Not established	5 mg/m3	Not established	Not established	Not established
Fatty Amine	Not established		Not established		Not established	
Blend of chemically modified tall oil derivative	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

TLV values are for Oil Mist. There is no established TLV or OEL's for petroleum distillates.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Wear safety glasses and if contact is possible wear chemical safety goggles.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product. If a splashing hazard exists wear chemical protective clothing e.g. gloves that extend up arms, aprons, boots.

Respiratory Protection

If conditions exist above the OEL wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

···· · · · · · · · · · · · · · · · · ·	
Appearance	Dark amber liquid.
Odour	Faint
Odour Threshold	Not available
рН	Not available
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	> 230 °F (110 °C)
Evaporation Rate	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.97
Solubility	Insoluble in water
Partition Coefficient,	Not available
n-Octanol/Water (Log Kow)	
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Liquid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Strong Oxidizing Agents.

Hazardous Decomposition Products

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; skin absorption; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Mixture of Fatty acids, tall oil	Not available	> 10000 mg/kg	Not available
Diethanolamine	Not available	.62 mg/kg (rat)	7.64 mg/kg (rabbit)
Distillates (petroleum), hydrotreated light	Not available	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Fatty Amine	Not available	620 mg/kg (rat)	> 10,000 mg/kg (rat)
Blend of chemically modified tall oil derivative	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause eye irritation. Symptoms include pain, redness and tearing.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract. May cause depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Skin Absorption

Ingredients of this product can be absorbed through the skin.

Ingestion

May cause irritation of the mouth, throat and stomach. May cause depression of the central nervous system.

Aspiration Hazard

Liquid may be aspirated into the lungs during ingestion or vomiting resulting in lung injury.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged skin contact may aggravate existing skin conditions such as dermatitis.

Respiratory and/or Skin Sensitization

May cause skin sensitization through skin contact. Not known to be a respiratory sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Mixture of Fatty acids, tall oil	Not Listed	Not Listed	Not Listed	Not Listed
Diethanolamine	Group 2B	A3	Not Listed	Not Listed
Distillates (petroleum), hydrotreated light	Group 3	A3	Not Listed	Not Listed
Fatty Amine	Not Listed	Not Listed	Not Listed	Not Listed
Blend of chemically modified tall oil derivative	Not Listed	Not Listed	Not Listed	Not Listed

May cause cancer based on animal studies.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 2B = Possibly carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A3 = Animal carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health

Administration. Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers. **Toxicity**

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Mixture of Fatty acids, tall oil	Not available	Not available	Not available	Not available
Diethanolamine	55 mg/L (Daphnia magna (water flea); 48-hour; fresh water; static)	Not available	Not available	Not available
Distillates (petroleum), hydrotreated light	2.9 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour)	Not available	Not available	Not available
Fatty Amine	Not available	Not available	Not available	Not available
Blend of chemically modified tall oil derivative	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

Special Precautions Not applicable

for User

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Other Information	The shipping descriptions included are for non-bulk shipments only and may not apply to
-------------------	---

Product Identifier: ABS MUL

Date of Preparation: July 01, 2015

shipments in bulk packages (see appropriate regulatory definition).

This product contains one or more ingredients as a hazardous substance in Appendix A of 49 CFR 172.101. The product quantity, in one package, which triggers the RQ requirements under 49 CFR for each hazardous substance is shown.

Reportable quantities:

RQ substance: Diethanolamine RQ limit for substance: 100lb RQ limit for product: 13200lb

Shipping information for product over in containers larger than 13200lb would be UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHANOLAMINE), CLASS 9, PG III

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: May contain <0.75% Diethanolamine. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Acute Hazards Chronic Health Hazard. SARA Title III - Section 313: May contain <1.0% Glycol Ether May contain <0.75% Diethanolamine.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 2 Flammability - 1 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	July 01, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss,

damage, direct or consequential, arising out of their use.

ABS MUL July 01, 2015



Page 07 of 07



AES VERT MUD SYSTEM

SECTION 1. IDENTIFICATION

Product Identifier	AES VERT MUD SYSTEM
Other Means of Identification	Diesel Based Invert Emulsion Drilling Fluid
Recommended Use	Drilling Fluid.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency July 01, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquid - Category 4; Acute toxicity (Oral) - Category 5; Acute toxicity (Dermal) - Category 5; Acute toxicity (Inhalation) - Category 5; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2B; Carcinogenicity - Category 2; Specific target organ toxicity (repeated exposure) - Category 2; Aspiration hazard - Category 2

GHS Label Elements



Signal Word:	
Warning	
Hazard Stateme	ent(s):
H227	Combustible liquid.
H305	May be harmful if swallowed and enters airways.
H315	Causes skin irritation.
H320	Causes eye irritation.
H333	May be harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H351	Suspected of causing cancer.
Precautionary S	Statement(s):
Prevention:	
P210	Keep away from flames and hot surfaces. – No smoking.
P262	Do not get in eyes, on skin, or on clothing.
P260	Do not breathe mist, vapours, spray.
P264	Wash hands and skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor/
P302 + P352	IF ON SKIN: Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P304 + P312 IF INHALED: Call a POISON CENTRE/doctor if you feel unwell.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Fuels, diesel, No. 2	68476-34-6	50-90	
Barite	7727-43-7	5-65	
Calcium chloride	10043-52-4	2-15	
Silica, quartz	14808-60-7	0.5-6	
Paraffins (petroleum)	64771-72-8	0.5-6	
Quaternary ammonium compounds	68953-58-2	0.5-6	
Calcium hydroxide	1305-62-0	0.5-5	
Gilsonite	12002-43-6	0.5-5	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs get medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Immediately call a Poison Centre or doctor.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon Dioxide, Foam, Dry chemical. Water spray or fog, do not use a direct stream as this may spread the fire.

Specific Hazards Arising from the Chemical

Closed containers may rupture violently when heated releasing contents. Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Use water spray to cool containers/tanks.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Small spills or leaks: do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Large spills or leaks: eliminate all ignition sources. Dike spilled product to prevent runoff. Remove or recover liquid using pumps or vacuum equipment. Contain and soak up spill using noncombustible material such as vermiculite, earth or sand. Place contaminated vermiculite, earth or sand into suitable, covered, labelled containers for disposal. Clean up residual with absorbent material, place in appropriate containers and flush with water. Store recovered product or absorbent material in suitable containers for disposal according to local regulations.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not breathe in this product. Do not get in eyes, on skin or on clothing. Only use where there is adequate ventilation. Avoid generating vapours or mists. Keep away from excessive heat, oxidizing agents, and ignition sources. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Wear personal protective equipment to avoid direct contact with this chemical. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: well-ventilated, cool, dry. Separate from incompatible materials away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Calcium chloride	Not established		Not established		Not established	
Calcium hydroxide	5 mg/m3		5 mg/m3		Not established	
Barite	5.0 mg/m3 (I)		5.0 mg/m3 (R)		5.0 mg/m3 (R)	
Gilsonite	3 mg/m3 (R)	Not established	5 mg/m3 (R)	Not established	Not established	Not established
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established	
Paraffins (petroleum)	Not established		Not established		Not established	
Quaternary ammonium compounds	Not established		Not established		Not established	
Fuels, diesel, No. 2	100 mg/m3 Skin		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use chemical goggles or a face shield if product could be splashed.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions exist above the OEL wear a NIOSH approved respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Dark brown - grey liquid.
Odour	Not available
Odour Threshold	Not available
рН	Not available
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	> 170 °F (77 °C)
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	Not available
Solubility	Insoluble in water
Partition Coefficient,	Not available
n-Octanol/Water (Log Kow)	
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Liquid

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions of use. Chemical Stability Normally stable. Possibility of Hazardous Reactions None expected under normal conditions of storage and use. Conditions to Avoid Strong Oxidizing Agents.

Hazardous Decomposition Products

Carbon oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Calcium chloride	> 160 mg/m3 (4-hour exposure)	1000 mg/kg	> 5000 mg/kg
Calcium hydroxide	Not available	7300 mg/kg (mouse)	Not available
Barite	Not available	Not available	Not available
Gilsonite	Not available	Not available	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Paraffins (petroleum)	Not available	Not available	Not available
Quaternary ammonium compounds	Not available	Not available	Not available
Fuels, diesel, No. 2	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause mild skin irritation.

Serious Eye Damage/Irritation

May cause mild eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory tract. Prolonged or repeated exposure may cause. depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Ingestion

May cause irritation of the mouth, throat and stomach.

Aspiration Hazard

Liquid may be aspirated into the lungs during ingestion or vomiting resulting in lung injury.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged exposures to high vapour concentrations can cause headache, dizziness, nausea, blurred vision and depression of central nervous system. Prolonged skin contact may aggravate existing skin conditions such as dermatitis. May cause damage to kidneys. Prolonged skin contact may aggravate existing skin conditions such as dermatitis.

Respiratory and/or Skin Sensitization

Not known to be a skin sensitizer. Not known to be a respiratory sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Calcium chloride	Not Listed	Not Listed	Not Listed	Not Listed
Calcium hydroxide	Not Listed	Not Listed	Not Listed	Not Listed
Barite	Not Listed	Not Listed	Not Listed	Not Listed
Gilsonite	Not Listed	Not Listed	Not Listed	Not Listed

Product Identifier: AES VERT MUD SYSTEM

Date of Preparation:

Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Paraffins (petroleum)	Not Listed	Not Listed	Not Listed	Not Listed
Quaternary ammonium compounds	Not Listed	Not Listed	Not Listed	Not Listed
Fuels, diesel, No. 2	Group 3	A3	Not Listed	Not Listed

May cause cancer based on animal studies.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. A3 = Animal carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers. **Toxicity**

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Calcium chloride	8.35 mg/L (Lepomis macrochirus (bluegill); fresh water; static)	.573 mg/L (Daphnia magna (water flea); fresh water; static)	Not available	Not available
Calcium hydroxide	Not available	Not available	Not available	Not available
Barite	Not available	32 mg/L (Daphnia magna (water flea); 48-hour; fresh water; static)	Not available	Not available
Gilsonite	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available
Paraffins (petroleum)	Not available	Not available	Not available	Not available
Quaternary ammonium compounds	Not available	Not available	Not available	Not available
Fuels, diesel, No. 2	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

Other Information This material does not sustain combustion when tested by ASTM-4206 and therefore meets the 49 CFR 173.120(b)(3) exemption from DOT hazmat shipping requirements.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Fire Hazard Immediate Health Hazard Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 2 Flammability - 2 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	July 01, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

AES VERT MUD SYSTEM July 01, 2015



Page 07 of 07



AES VIS III

SECTION 1. IDENTIFICATION

Product Identifier	AES VIS III
Other Means of Identification	Organic Clay / Quaternary Ammonium Bentonite
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency March 30, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) - Category 4; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

GHS Label Elements



× .	
Signal Word:	
Danger	
Hazard Statem	ent(s):
H302	Harmful if swallowed.
Dust in eye may	y result in mechanical irritation.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H350	May cause cancer.
Precautionary S	Statement(s):
Prevention:	
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	
P301 + P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P330	Rinse mouth.
P304 + P340	
P308 + P313	IF exposed or concerned: Get medical advice/attention.
	nse cautiously with water for several minutes.
P337 + P313 Storage:	If eye irritation persists: Get medical advice/attention.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Treated Clay	CBI*	90-99	
Silica, quartz	14808-60-7	0.1-1.0	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if irritation develops.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation persists, get medical advice/attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

Does not burn.

In a fire, the following hazardous materials may be generated: oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Dust is subject to combustion when exposed to ignition sources in heated environments. When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Store recovered product in suitable containers that are: tightly-covered. Containerize for solid waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Only use

where there is adequate ventilation. Avoid creating excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE). Eliminate ignition sources in dusty conditions.

Conditions for Safe Storage

Store in an area that is: well-ventilated. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust. Eliminate nearby ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	OSHA	OSHA PEL		ACGIH® TLV®		WEEL™
Chemical Name	TWA	Ceiling	TWA	STEL [C]	8-hr TWA	Short-term TWA [C]
Silica, quartz	0.1 mg/m3		0.025 mg/m3 A2		Not established	
Treated Clay	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Bable i flyelear and enemiear	
Appearance	Tan powder.
Odour	Faint
рН	Not available
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.6
Solubility	Insoluble in water
Auto-ignition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive. Chemical Stability Stable under normal conditions. Possibility of Hazardous Reactions None expected under normal conditions of storage and use. Conditions to Avoid None known. Incompatible Materials None known. Hazardous Decomposition Products Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Treated Clay	Not available	Not available	Not available

Skin Corrosion/Irritation

Irritating to skin, prolonged contact can de fat the skin and cause dermatitis.

Serious Eye Damage/Irritation

May cause eye irritation. May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract. May aggravate asthma.

Skin Absorption

Not harmful.

Ingestion

May be harmful if ingested may cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product may contain trace amounts of crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. May cause chronic bronchitis (inflammation of the airways leading to the lungs).

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Treated Clay	Not Listed	Not Listed	Not Listed	Not Listed

This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available
Treated Clay	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

AES VIS III

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Immediate Health Hazard Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

Product Identifier:

Date of Preparation: March 30, 2015

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 1 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	March 30, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information

our NS n and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.





AES VIS LS

SECTION 1. IDENTIFICATION

Product Identifier	AES VIS LS
Other Means of Identification	Organic Clay / Quaternary Ammonium Bentonite
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency March 31, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) - Category 4; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

GHS Label Elements



\mathbf{v}
ent(s):
Harmful if swallowed.
ly result in mechanical irritation.
led.
Causes damage to organs through prolonged or repeated exposure.
May cause cancer.
Statement(s):
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.
Use only outdoors or in a well-ventilated area.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
Rinse mouth.
• P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Treated Clay	CBI*	90-99	
Silica, quartz	14808-60-7	1-10	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if irritation develops.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation persists, get medical advice/attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

Does not burn.

In a fire, the following hazardous materials may be generated: oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Dust is subject to combustion when exposed to ignition sources in heated environments. When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Store recovered product in suitable containers that are: tightly-covered. Containerize for solid waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Only use where there is adequate ventilation. Avoid creating excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE). Eliminate ignition sources in dusty conditions.

Conditions for Safe Storage

Store in an area that is: well-ventilated. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust. Eliminate nearby ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established	
Treated Clay	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Tan powder.
Odour	Faint
рН	Not available
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.7 - 1.8
Solubility	Insoluble in water
Product Identifier: AES VIS LS	3

Date of Preparation:March 31, 2015

SECTION 10. STABILITY AND REACTIVITY

Reactivity
Not reactive.
Chemical Stability
Stable under normal conditions.
Possibility of Hazardous Reactions
None expected under normal conditions of storage and use.
Conditions to Avoid
None known.
Incompatible Materials
None known.
Hazardous Decomposition Products
Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Treated Clay	Not available	Not available	Not available

Skin Corrosion/Irritation

Irritating to skin, prolonged contact can de fat the skin and cause dermatitis.

Serious Eye Damage/Irritation

May cause eye irritation. May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract. May aggravate asthma.

Skin Absorption

Not harmful.

Ingestion

May be harmful if ingested may cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product contains small amounts of crystalline silica (quartz). long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. May cause chronic bronchitis (inflammation of the airways leading to the lungs).

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Product Identifier:	AES VIS LS			
Date of Preparation:	March 31, 2015			Page 04 of 06

Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Treated Clay	Not Listed	Not Listed	Not Listed	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. Group 2A = Probably carcinogenic to humans. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available
Treated Clay	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Acute Hazards Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 1 Instability - 0 AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	March 31, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: AES VIS LS March 31, 2015



Page 06 of 06



AES WA II

SECTION 1. IDENTIFICATION

Product Identifier	AES WA II
Recommended Use	Wetting Agent.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	February 28, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Dermal) - Category 5; Serious eye damage/eye irritation - Category 2A; Carcinogenicity - Category 2; Aspiration hazard - Category 2

GHS Label Elements



Signal Word:	
Warning	
Hazard State	ment(s):
H305	May be harmful if swallowed and enters airways.
H313	May be harmful in contact with skin.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
Precautionary	v Statement(s):
Prevention:	
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	
P301 + P310	
P302 + P352	IF ON SKIN: Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P305 + P351	+ P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to d	o. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P401	Store
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
		1	
Blend of Mineral Oil	64742-53-6	40-60	
----------------------	------------	-------	--
Phospholipids	8030-76-0	40-60	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Get medical advice/attention if you feel unwell or are concerned.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs get medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Seek medical advice/attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Call a Poison Centre or doctor if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

Closed containers may rupture violently when heated releasing contents. Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Containers may rupture from gas generation in a fire situation. Use water spray only to cool fully closed containers. When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Provide adequate ventilation to the spill area. Pump spilled product into suitable containers. Clean up residual with absorbent material, place in appropriate containers and flush with water. Prevent contamination of waterways or sewers.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. See Section 8 for appropriate Personal Protective Equipment (PPE). Wash hands thoroughly after handling this material. Keep away from sources of ignition, No Smoking while working with this product.

Conditions for Safe Storage

Store in an area that is: well-ventilated, cool, dry, separate from incompatible materials (see Section 10: Stability and Reactivity). Away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Blend of Mineral Oil	5 mg/m3		Not established		Not established		
Phospholipids	Not established		Not established		Not established		

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields. Wear chemical safety goggles if the product could be splashed.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions exist above the OEL wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties			
Appearance	Dark amber liquid.		
Odour	Faint		
Odour Threshold	Not available		
рН	Not available		
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)		
Initial Boiling Point/Range	Not available		
Evaporation Rate	Not applicable		
Flammability (solid, gas)	Will not burn.		
Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)		
Vapour Pressure	Not available		
Vapour Density (air = 1)	Not available		
Relative Density (water = 1)	0.91		
Solubility	Insoluble in water		
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available		
Auto-ignition Temperature Other Information	Not applicable		

SECTION 10. STABILITY AND REACTIVITY

Reactivity
Not reactive.
Chemical Stability
Stable under normal conditions.
Possibility of Hazardous Reactions
None expected under normal conditions of storage and use.
Conditions to Avoid
Open flames, sparks, static discharge, heat and other ignition sources.
Incompatible Materials
Strong Oxidizing Agents.
Hazardous Decomposition Products
Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Blend of Mineral Oil	Not available	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Phospholipids	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause serious eye irritation or corneal injury.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory tract. Contains soy, may cause allergic reaction in certain individuals.

Skin Absorption

Not harmful.

Ingestion

May be harmful if ingested may cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

Aspiration Hazard

Liquid may be aspirated into the lungs during ingestion or vomiting resulting in lung injury.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged skin contact may aggravate existing skin conditions such as dermatitis.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Blend of Mineral Oil	Group 3	A4	Known carcinogen	Not Listed
Phospholipids	Not Listed	Not Listed	Not Listed	Not Listed
be National Taxicalogy Program rates Minoral ails as known to be human careinagans				

The National Toxicology Program rates Mineral oils as known to be human carcinogens.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A4 = Not classifiable as a human carcinogen. NTP = National Toxicology Program. Known carcinogen = Known human carcinogen. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers. **Toxicity**

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Blend of Mineral Oil	Not available	Not available	Not available	Not available
Phospholipids	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory. All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: No listed components. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 0	Instability - 0
SDS Prepared By	AES Drilling Fluids	
Phone No.	281-556-5628	
Date of Preparation	February 28, 2015	
Disclaimer	this form is furnished solely for the products to ensure the safety and	tions on MSDS are read and understood. The information on e purpose of enabling those who transport, handle or use our health of their employees and to comply with various laws

products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.



Page 06 of 06

B2512 SAFETY DATA SHEET



SECTION 1 – IDENTIFICATION

Product Identifier:

Manufacturer:

Aquaserv, Inc. 61 Keel Avenue Memphis, TN 38107

B2512

 24 Hour Emergency Phone:
 (901) 525-7701

 CHEMTREC:
 (800) 424-9300

Recommended use:

Microbiocide

SECTION 2 – HAZARDS IDENTIFICATION

Physical Hazards: Not classified.

Health Hazards

Acute Toxicity: Oral, Category 4 Skin Corrosion/Irritation: Category 1C Serious Eye Damage/Eye Irritation: Category 1 Respiratory Sensitization: Category 1

OSHA Defined Hazards: Not classified

Label Elements Pictograms:

~·

.



Signal Word:	Danger!
Hazard Statement(s):	Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Precautionary Statement(s):	Avoid breathing mist or vapor. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.
Response Statement(s):	IF SWALLOWED: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting.IF ON SKIN/HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower.IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 2 of 12

	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.
Storage/Disposal Statement:	Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.
Environmental Hazards:	Hazardous to the aquatic environment, acute hazard (Category 1) Hazardous to the aquatic environment, long-term hazard (Category 1)
Hazard(s) Not Otherwise Classified (HNOC):	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Supplemental Information:	4% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.13.5% of the mixture consists of component(s) of unknown acute inhalation toxicity. 4% of the mixture consists of component(s) of unknown acute dermal toxicity.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	% by Wt
Glutaraldehyde	111-30-8	20 - < 30
Didecyldimethylammonium Chloride	7173-51-5	5 - < 10
Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides	68424-85-1	5 - < 10
Ethanol	64-17-5	3 - < 5
Other components below reportable levels		50 - < 60

SECTION 4 – FIRST AID MEASURES

Description of First Aid Measures

Inhalation: Move person to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; do not use mouth-to-mouth. Use rescuer protection (pocket mask equipped with a one-way valve or other proper respiratory medical device). If experiencing respiratory symptoms call a poison control center or doctor for treatment advice.

Skin Contact: Take off immediately all contaminated clothing. Wash skin with soap and plenty of water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye Contact: Wash immediately and continuously with flowing water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use a mouth-to-

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 3 of 12

mouth method if victim ingested the substance. Use a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most Important Symptoms/Effects, Acute and Chronic: Burning pain and severe corrosive skin damage. Nausea, vomiting. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Difficulty in breathing.

Indication of Immediate Medical Attention and Special Treatment Needed: Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General Advice: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, carbon dioxide (CO2), or dry chemical.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Hazardous Combustion Products: Under fire conditions some components of this product may form gases hazardous to health.

Special Protective Equipment for Firefighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Firefighting Procedures: Move containers from fire area if you can do so without risk.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials.

General Fire Hazards: No unusual fire or explosion hazards noted.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Evacuate area of unnecessary personnel. Keep upwind of spill. Only trained and properly protected personnel must be involved in clean-up operations. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

Spill or Leak Procedures: This product is miscible in water.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 4 of 12

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

SECTION 7 - HANDLING AND STORAGE

Conditions for Safe Handling: Avoid breathing mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage: Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Ethanol (CAS# 64-17-5)	PEL	1900 mg/m ³ / 1000 ppm

U.S. ACGIH Threshold Limit Values

Components	Туре	Value
Ethanol (CAS# 64-17-5)	STEL	1000 ppm
Glutaraldehyde (CAS# 111-30-8)	Ceiling	0.05 ppm

U.S. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value
Ethanol (CAS# 64-17-5)	TWA	1900 mg/m³ / 1000 ppm
Glutaraldehyde (CAS# 111-30-8)	Ceiling	0.8 mg/m ³ / 0.2 ppm

Biological Limit Values: No biological exposure limits noted for the ingredient(s).

Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Eye wash facilities and emergency shower must be available when handling this product.

Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles) and a face shield.

Hand Protection: Wear appropriate chemical resistant gloves.

Skin Protection: Wear suitable chemical resistant clothing and shoes.

Respiratory Protection: Chemical respirator with organic vapor cartridge, full face shield, dust and mist filter.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 5 of 12

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Keep away from food and drink. Always observe good personal hygiene measure, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colorless to light yellow liquid
Odor	Fruity
Odor Threshold	Not available
pH	4.4 @ 25 °C
Melting Point	Not available
Boiling Point	> 210.74 °F (99.3 °C)
Flash Point	210.7 °F (99.3 °C)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Lower Explosion Limit	Not available
Upper Explosion Limit	Not available
Vapor Pressure	Not available
Relative Vapor Density	Not available
Relative Density	Not available
Water Solubility	Miscible
Partition Coefficient: n-Octanol/Water	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	9.23 cSt
Viscosity Temperature	69.8 °F (21 °C)
Explosive Properties	Not explosive
Oxidizing Properties	Not oxidizing
Specific Gravity	1.04 – 1.06 @ 20 °C
VOC (Weigh %)	4 % estimated

NOTE: The above represents typical values and should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents and amines.

Hazardous Decomposition Products: No hazardous decomposition products are known.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 6 of 12

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: May cause irritation to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Eye Exposure: Causes serious eye damage.

Skin Exposure: Causes severe skin burns.

Ingestion: Harmful if swallowed. Causes digestive tract burns.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Burning pain and severe corrosive skin damage. Nausea, vomiting, serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Difficulty in breathing.

Information on Toxicological Effects

Acute Toxicity

Acute Oral Toxicity: Harmful if swallowed. As product (B2512) LD50, rat, 550 mg/kg

Didecyldimethylammonium Chloride (CAS# 7173-51-5) LD50, 238 mg/kg Rat, 329 mg/kg

Glutaraldehyde (CAS# 111-30-8) LD50, rat, 316 mg/kg 200 mg/kg

Quaternary Ammonium Compounds, Benzyl-C12 - C16-alkyldimethyl, Chlorides (CAS# 68424-85-1) LD50, 430 mg/kg

Ethanol (CAS# 64-17-5) LD50, rat, 10470 mg/kg

Acute Dermal Toxicity

Didecyldimethylammonium Chloride (CAS# 7173-51-5) LD50, 3342 mg/kg Rat, > 1000 mg/kg

Glutaraldehyde (CAS# 111-30-8) LD50, rabbit, >2000 mg/kg

Quaternary Ammonium Compounds, Benzyl-C12 - C16-alkyldimethyl, Chlorides (CAS# 68424-85-1) LD50, 3560 mg/kg

Acute Inhalation Toxicity

Ethanol (CAS# 64-17-5) LC50, rat, 117 - 125 mg/l, 4 h

Glutaraldehyde (CAS# 111-30-8) LC50, rat, 0.52 mg/l, 4 hour

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 7 of 12

*Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation

Causes severe skin burns and eye damage.

Serious Eye Damage/Eye Irritation

Causes serious eye damage.

Sensitization

ACGIH Sensitization (Glutaraldehyde) - Sensitizer

Respiratory Sensitization – May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sensitization – This product is not expected to cause skin sensitization.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.

Specific Target Organ Systemic Toxicity (Single Exposure): Not classified.

Specific Target Organ Systemic Toxicity (Repeated Exposure): Not classified.

Aspiration Hazard: Not an aspiration hazard.

Chronic effects: Prolonged inhalation may be harmful.

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity

Aquatic Toxicity - Very toxic to aquatic life with long lasting effects. Didecyldimethylammonium Chloride (CAS# 7173-51-5) Algae, EC50, algae, 0.062mg/l, 72 h

Crustacea, LC50, daphnia, 0.057 mg/l, 48 h Crustacea, NOEC, daphnia, 0.021 mg/l, 21 d

Fish, LC50, danio rerio, 0.97 mg/l, 96 h

Acute Fish, LC50, bluegill (lepomis macrochirus), 0.032 mg/l, 96 h

Chronic Crustacea, NOEC, dapnia, 0.01 mg/l

Ethanol (CAS# 64-17-5) Acute

Algae, EC50, algae, 675 mg/l, 72 h

Crustacea, EC50, daphnia, 5012 mg/l, 48 h

Fish, LC50, fathead minnow (pimephales promelas), 14200 mg/l, 96 h

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 8 of 12

Chronic

Crustacea, NOEC, daphnia, 9.6 mg/l, 9 d

Glutaraldehyde (CAS# 111-30-8)

Acute Algae, EC50, algae, 0.92 mg/l, 72 h

Crustacea, EC50, daphnia, 29.73 mg/l, 48 h

Fish, LC50, bluegill (lepomis macrochirus), 13 mg/l, 96 h

Chronic Crustacea, NOEC, daphnia, 5 mg/l, 21 d

Fish, NOEC, fish, 3.2 mg/l, 97 d

Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides (CAS# 68424-85-1) Acute

Fish, LC50, bluegill (lepomis macrochirus), 0.515 mg/l

Chronic Crustacea, NOEL, daphnia, 0.0042 mg/l

*Estimates for product may be based on additional component data not shown.

Persistence and Degradability

This product is expected to be readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Procedure: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance. Dispose of in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose of waste from residues/unused products in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

AQUASERV, INC.

SAFETY DATA SHEET

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 9 of 12

SECTION 14 - TRANSPORT INFORMATION

DOT	
Proper Shipping Name:	Disinfectants, liquid, corrosive n.o.s. (Quaternary Ammonium
	Compound)
UN Number:	1903
Transport Hazard Classes	
Class:	8
Subsidiary risk:	-
Label(s):	8
Packing Group:	
Special Precautions for User:	Read safety instructions, SDS and emergency procedures
	before handling.
Special Provisions:	IB3, T4, TP1
Packaging Exceptions:	154
Packaging Non-Bulk:	203
Packaging Bulk:	241
ERG Number:	153
ΙΑΤΑ	
Proper Shipping Name:	Disinfectants, liquid, corrosive n.o.s. (Quaternary Ammonium
	Compound)
UN Number:	1903
Transport Hazard Classes	
Class:	8
Subsidiary risk:	-
Packing Group:	
Environmental Hazards:	No
ERG Code:	8L
Special Precautions for User:	Read safety instructions, SDS and emergency procedures before handling.
Other Information	5
Passenger and cargo aircraft	: Allowed
Cargo aircraft only:	Allowed
IMDG	
Proper Shipping Name:	Disinfectants, liquid, corrosive n.o.s. (Quaternary Ammonium
	Compound)
UN Number:	1903
Transport Hazard Classes	
Class:	8
Subsidiary risk:	-
Packing Group:	III
Environmental Hazards	
Marine pollutant:	No
EmS:	F-A, S-B
Special Precautions for User:	Read safety instructions, SDS and emergency procedures
	before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not established.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 10 of 12



SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4) Ethanol (CAS# 64-17-5) – Listed.

SARA 304 Emergency Release Notification - Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) - Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories

Immediate Hazard – Yes Delayed Hazard – No Fire Hazard – No Pressure Hazard – No Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance – Not listed.

SARA 311/312 Hazardous Chemical – No

SARA 313 (TRI Reporting) - Not regulated.

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List - Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – Not regulated.

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 11 of 12

Safe Drinking Water Act (SDWA) - Not regulated. FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS# 64-17-5) - Low Priority.

FIFRA Information – This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Listed below is the hazard information as required on the pesticide label.

Signal Word – DANGER KEEP OUT OF REACH OF CHILDREN

Hazard Statement - Corrosive. Causes irreversible eye damage and skin burns. Harmful if swallowed, absorbed through the skin or inhaled.

EPA Registration Number: 10324-185-72714

Country(s) or Region	Inventory Name	On Inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

International Inventories

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SDS: B2512 Revision Date 10/03/2016 Version No.: 03 Page 12 of 12

SECTION 16 – OTHER INFORMATION

Issue Date: Revision Date: Version: Revision Summary: Prepared By: Revision Information: May 27, 2015 October 3, 2016 03 None Product Stewardship Team This document has undergone significant changes and should be reviewed in its entirety.

This Safety Data Sheet was prepared to comply with the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Aquaserv provides no warranties; either expressed or implied and assumes no responsibility for the accuracy or completeness of the data contained herein. The data contained in this Safety Data Sheet reflects the latest information available to us on hazards, properties, and handling of this product under the recommended conditions of use. The information on this Safety Data Sheet relates only to the material as supplied and does not relate to combinations with other materials or processes.



Barite

SECTION 1. IDENTIFICATION

Product Identifier Other Means of Identification	Barite Barium Sulfate
Other Identification	Baryte
Recommended Use	Drilling Mud Additive.
Manufacturer /	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Supplier	Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
SDS No.	0218
Date of Preparation	February 26, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation - Category 3; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

GHS Label Elements



Signal Word: Danger Hazard Statement(s): EYE: Dust in eye may result in mechanical irritation. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure. Precautionary Statement(s): Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash thoroughly after handling. Do not eat, drink or smoke when using this product. P270 In case of inadequate ventilation, wear respiratory protection. Wear safety glasses or goggles where elevated dust concentrations are a concern. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/attention. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Product Identifier:	Barite	
SDS No.:	0218	Page 01 of 06
Date of Preparation:	February 26, 2015	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Barium sulfate	7727-43-7	84-98	
Silica, quartz	14808-60-7	1-5	
Calcium carbonate	471-34-1	1-5	
Clay	1332-58-7	0.1-6.0	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Get medical advice/attention if irritation develops.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Get medical advice/attention if you feel unwell or are concerned.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Get medical advice/attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Specific Hazards Arising from the Chemical

Does not burn.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

No specific procedures given.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Use water fog or spray curtain to reduce amount of dust in air. Store recovered product in suitable containers that are: tightly-covered. Dispose of according to local, state and federal regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not breathe in this product. Only use where there is adequate ventilation. Avoid skin and eye contact. Avoid creating

Product Identifier:	Barite
SDS No.:	0218
Date of Preparation:	February 26, 2015

excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE). Immediately remove contaminated clothing using the method that minimizes exposure.

Conditions for Safe Storage

Store in an area that is: well-ventilated. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	TLV®	OSHA	A PEL	AIHA®	WEEL™
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Clay	3.0 mg/m3		5.0 mg/m3		Not established	
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established	
Barium sulfate	5.0 mg/m3 (I)		5.0 mg/m3 (R)			
Calcium carbonate	5 mg/m3 (R)		5 mg/m3 (R)			

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. Short-term TWA = Time-Weighted Average with specified time limit. R = Respirable fraction. I = Inhalable fraction. Product may cause irritation similar to nuisance dust and meet the criteria of Particulates Not Otherwise Specified inhalable particles, or total particles.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields are recommended to prevent eye contact. Use goggles or face shield when there is risk of eye contact or visible dust produced.

Skin Protection

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	White - tan powder.
Odour	Odourless
рН	Not available
Melting Point/Freezing Point	2876 °F (1580 °C) (melting); Not available (freezing)
Initial Boiling Point/Range	2912 °F (1600 °C)
Flash Point	Not applicable
Evaporation Rate	Not applicable
Flammability (solid, gas)	Will not burn.

Product Identifier:	Barite
SDS No.:	0218
Date of Preparation:	February 26, 2015

Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)
Vapour Pressure	Not applicable
Vapour Density (air = 1)	Not applicable
Relative Density (water = 1)	4.2 - 4.5
Solubility	Insoluble in water
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Generation of dust. **Incompatible Materials** None.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Clay	Not available	> 5,000 mg/kg (rat)	> 5,000 mg/kg (rat)
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Barium sulfate	Not available	Not available	Not available
Calcium carbonate	Not available	6,450 mg/kg (rat)	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause eye irritation. May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

High dust levels may cause irritation of the respiratory tract, including sneezing and coughing.

Ingestion

May cause discomfort if swallowed.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product contains small amounts of crystalline silica (quartz). long term exposure to respirable crystalline silica dust

Product Identifier:	Barite	
SDS No.:	0218	Page 04 of 06
Date of Preparation:	February 26, 2015	

over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Clay	Not evaluated	A4	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Barium sulfate	Not Listed	Not Listed	Not Listed	Not Listed
Calcium carbonate	Not Listed	Not Listed	Not Listed	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. A4 = Not classifiable as a human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration. **Reproductive Toxicity**

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Clay	> 1,100 mg/L (Daphnia pulex (water flea); 48-hour)	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available
Barium sulfate	Not available	32 mg/L (Daphnia magna (water flea); 48-hour; fresh water; static)	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 0 Instability - 0 AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	February 26, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.



Page 06 of 06



Blue Max

SECTION 1. IDENTIFICATION

Product Identifier	Blue Max
Other Means of Identification	Surfactant
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency March 27, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) - Category 5; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 1; Carcinogenicity - Category 2; Specific target organ toxicity (repeated exposure) - Category 2

GHS Label Elements



\sim	
Signal Word:	
Danger	
Hazard Statem	ent(s):
H303	May be harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Precautionary \$	Statement(s):
Prevention:	
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe vapours, mist, spray.
P264	Wash hands and skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P270	Do not eat, drink or smoke when using this product.
Response:	
P330	Rinse mouth.
P301 + P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P305 + P351 +	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do	. Continue rinsing.
P315	Get immediate medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Product Identifier	r Blue Max

Other Hazards

Hazardous to the environment.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:	
ivin/(coro.	

Chemical Name	CAS No.	%	Other Identifiers
Proprietary Surfactant	CBI*	5-10	
Surfactant Blend	68603-42-9	18	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Call a Poison Centre or doctor.

Skin Contact

Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Remove contaminated clothing and launder before reuse. Seek medical advice/attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. Seek immediate medical attention.

Ingestion

Rinse mouth with water. Never give anything by mouth to an unconscious person. Seek medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water, Carbon Dioxide, Dry chemical, Foam.

Unsuitable Extinguishing Media

Do not use direct streams of large volumes of water as this may spread the fire.

Specific Hazards Arising from the Chemical

In the event of a fire this product can release hazardous combustion products such as carbon oxides. Sealed systems of product may over pressurize when heated and rupture or explode.

Oxides of carbon oxides of nitrogen.

Special Protective Equipment and Precautions for Fire-fighters

Use water spray to cool containers/tanks. Do not use a solid stream of foam into hot, burning pools: this may causing frothing and increase fire intensity.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate the hazard area. Keep out unnecessary and unprotected personnel. See Section 8 for appropriate personal protective equipment.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Dike spilled product to prevent runoff. Contain and soak up spill with absorbent that does not react with spilled product. Do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Store recovered product or absorbent material in suitable containers for disposal according to local regulations. Prevent contamination of waterways or sewers. Clean up residual contamination with water and place in appropriate containers for disposal.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not breathe in this product. Do not get in eyes, on skin or on clothing. Wear personal protective equipment to avoid direct contact with this chemical. Wash hands thoroughly after handling this product and before eating, using the washroom or leaving work area.

Conditions for Safe Storage

Keep containers tightly closed when not in use. Store in an area that is: well-ventilated, cool, dry. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials store in the original, labelled, shipping container.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Surfactant Blend	1 mg/m3 Skin A3		Not established		Not established		
Proprietary Surfactant	Not established		Not established		Not established		

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields. Wear chemical safety goggles and a face shield when handling product.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear chemical protective clothing e.g. gloves, aprons, boots.

Respiratory Protection

If conditions exist above the OEL wear a NIOSH approved respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Product Identifier:	Blue Max
SDS No.:	0270
Date of Preparation:	March 27, 2015

Basic Physical and Chemical Properties

Dasie i nysical and Olicinical	Toperdes
Appearance	Blue liquid.
Odour	Aromatic
рН	7
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	> 400 °F
Evaporation Rate	Not available
Flammability (solid, gas)	Will not burn.
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.02
Solubility	Soluble in water
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Liquid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Inorganic acids (e.g. hydrofluoric acid), bases. Hypochlorites nitric acid, sulfuric acid, oxidizing agents (e.g. peroxides), oxygen. Permanganates perchlorates, peroxides. Chromates.

Hazardous Decomposition Products

Oxides of carbon. Oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; skin absorption; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Surfactant Blend	Not available	Not available	> 2000 mg/kg (rabbit)
Proprietary Surfactant	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause mild skin irritation.

Serious Eye Damage/Irritation

Product Identifier:	Blue Max
SDS No.:	0270
Date of Preparation:	March 27, 2015

May cause eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Spray mists may cause respiratory tract irritation. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Skin Absorption

No information was located.

Ingestion

May cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

Aspiration Hazard

No information was located.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged skin contact may cause defatting of the skin resulting in irritation and conditions such as dermatitis.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Surfactant Blend	Group 2B	A3	Not Listed	Not Listed
Proprietary Surfactant	Not Listed	Not Listed	Not Listed	Not Listed

May cause cancer.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 2B = Possibly carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A4 = Not classifiable as a human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers. **Toxicity**

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Surfactant Blend	Not available	3.3 mg/L (Daphnia magna (water flea); static)	Not available	Not available
Proprietary Surfactant	Not available	Not available	Not available	Not available

Persistence and Degradability

Product Identifier:	Blue Max
SDS No.:	0270
Date of Preparation:	March 27, 2015

No information was located. Bioaccumulative Potential No information was located. Mobility in Soil Studies are not available. Other Adverse Effects There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

Other Information The shipping descriptions included are for non-bulk shipments only and may not apply to shipments in bulk packages (see appropriate regulatory definition).

This product contains one or more ingredients as a hazardous substance in Appendix A of 49 CFR 172.101. The product quantity, in one package, which triggers the RQ requirements under 49 CFR for each hazardous substance is shown.

Reportable quantities:

RQ substance: Diethanolamine RQ limit for substance: 100lb RQ limit for product: 8300lb

Shipping information for product over in containers larger than 8300lb would be UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHANOLAMINE), CLASS 9, PG III

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: May contain <1.1% Diethanolamine. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Acute Hazards Chronic Health Hazard. SARA Title III - Section 313: May contain 0.75% to 0.25% concentration of Glycol Ethers May contain <1.1% Diethanolamine.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By Phone No.	Health - 2 Flammability - 1 AES Drilling Fluids 281-556-5628	Instability - 0
Product Identifier:	Blue Max	
SDS No.:	0270	Page 06 of 07
Date of Preparation:	March 27, 2015	

Date of Preparation Disclaimer

March 27, 2015

Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.



Page 07 of 07



SAFETY DATA SHEET

C 2145 Air Unit Corrosion Inhibitor W/S

Section 1. Identification

GHS product identifier	:	C 2145 Air Unit Corrosion Inhibitor W/S
Other means of identification	:	Corrosion Inhibitor
Product use	:	Not available.
Product type	:	Liquid.
Manufacturer	:	Jacam Manufacturing 2013, L.L.C. P.O.Box 208, 1656 Ave. Q. Sterling, Kansas 67579
Validation date	:	5/14/2015.
For Chemical Emergency Spill, Leak Fire, Exposure or Accident:	:	Call CHEMTREC Day or Night Within USA and Canada 800-424-9300 CCN# 11754 Or +1 703-527-3887 (Collect calls accepted)
		Direct all other calls to: Jacam Chemicals 2013, L.L.C. 620-278-3355 Mon – Fri 8 a.m. to 5 p.m. (Closed on major holidays)
Supplier's details	:	Jacam Chemicals 2013, L.L.C. P.O. Box 96, 205 S. Broadway Sterling, Kansas 67579

Section 2. Hazards identification

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

GHS label elements

Date	of issi	e/Date of	^c revision
------	---------	-----------	-----------------------

1/16

Section 2. Hazards identification

Hazard pictograms	
Signal word	: Warning
Hazard statements	: H302 - Harmful if swallowed. H319 - Causes serious eye irritation.
Precautionary statement	<u>'S</u>
Prevention	 P280 - Wear eye or face protection: Recommended: chemical splash goggles P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling.
Response	 P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
Storage	: Not applicable.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.
Routes of entry	 Dermal contact. Eye contact. Inhalation. INGESTION: Although not a normal route of entry, ingestion is expected to be harmful. DO NOT TAKE INTERNALLY. FOR INDUSTRIAL USE ONLY.
Target organs	: May cause damage to the following organs: kidneys, liver, gastrointestinal tract, upper respiratory tract, skin, eyes. Contains material which may cause damage to the following organs: heart, central nervous system (CNS), eye, lens or cornea.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Corrosion Inhibitor
identification	

CAS number/other identifiers

CAS	number	
-----	--------	--

: Not applicable.

Ingredient name	%	CAS number
Ethylene Glycol	5 - 10	107-21-1
Methanol	5 - 10	67-56-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Date o	f issue/.	Date of	revision	
--------	-----------	---------	----------	--

3/16

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If irritation persists, obtain medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. If irritation or symptoms persists, obtain medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If irritation persists, obtain medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important sympto	ms/effects, acute	and delayed	
Potential acute health	effects		
Eye contact	: Causes s	serious eye irritation.	
Inhalation	: May be h	armful if inhaled.	
Skin contact	: May caus	se skin irritation.	
Ingestion		f swallowed. Irritating to mouth, throat and s s to physician, below.	stomach.
Over-exposure signs/s	<u>symptoms</u>		
Eye contact	: Adverse pain or in watering redness	symptoms may include the following: ritation	
Inhalation	nausea o Irritation dizziness	ss/fatigue e	
Skin contact	redness burning	symptoms may include the following: on possible	
Date of issue/Date of revision	5/14/2015.	People + Products 辛 Performance"	Version : 1

Ingestion

: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician		Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination of half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, use three to four ounces oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Hemodialysis effectively removes ethylene glycol and it's metabolites from the body. Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration nausea, vomiting, and in severe cases coma, convulsions and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnia, tachycardia, mild hyotension, cyanosis and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement and congestive heart failure. The final stage occurs 24-72 hours post-exposure and is characterized by renal failure ranging from a mild increase in blood urea nitorgen and creatinine followed by recovery to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Easting and a later of sea all a	
<u>Extinguishing media</u>	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Additional Vapor Statement	: Not available.
	Not available.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Date of issue/Date of revision	People + Products <> Performance"Version: 14/16

Section 6. Accidental release measures

receptions, protective equipment and emergency precedures
recautions, protective equipment and emergency procedures
 In the second sec
gency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
ental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
nd materials for containment and cleaning up
 Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
S

Section 7. Handling and storage

Precautions for safe handling		
Protective measures		Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

5/16

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Methanol CEIL: 50 ppm CEIL: 125 mg/m³ Methanol ACGIH TLV (United States, 4/2014). C: 100 mg/m³ Form: Aerosol ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 260 pg/m³ 8 hours. STEL: 320 ppm 15 minutes. STEL: 250 ppm 16 hours. TWA: 260 mg/m³ 16 minutes. STEL: 250 ppm 16 hours. TWA: 260 mg/m³ 16 minutes. STEL: 250 ppm 16 hours. STEL: 250 ppm	Ingredient name		Exposure limits
Methanol ACGIH TLQ (United States, 4/2014). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 328 mg/m³ 15 minutes. STEL: 328 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/19 Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 325 mg/m³ 16 minutes. STEL: 325 mg/m³ 16 minutes. STEL: 325 mg/m³ 16 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. STEL: 325 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 16 hours. STEL: 325 mg/m³ 16 hours. STEL: 325 mg/m³ 16 hours. STEL: 260 mg/m³ 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 mg/m³ 8 hours. Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated ci Wash contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts	Ethylene Glycol		CEIL: 125 mg/m ³ ACGIH TLV (United States, 4/2014).
Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 328 mg/m³ 8 hours. STEL: 328 mg/m³ 15 minutes. STEL: 320 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 16 hours. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. TWA: 200 mg/m³ 10 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 320 mg/m³ 10 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 325 mg/m³ 15 minutes. STEL:	Methanol		
TWA: 200 ppm 8 hours. TWA: 202 mg/m³ 8 hours. STEL: 250 pm 15 minutes. STEL: 228 mg/m³ 15 minutes. STEL: 228 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/19 Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 250 mg/m³ 8 hours. STEL: 250 mg/m³ 16 minutes. STEL: 250 pm 15 minutes. STEL: 250 pm 15 minutes. STEL: 250 ppm 10 hours. TWA: 200 ppm 10 hours. STEL: 250 ppm 10 hours. STEL: 250 ppm 10 hours. STEL: 250 ppm 11 minutes. STEL: 250 ppm 15 minutes. STEL: 250 ppm 15 minutes. STEL: 250 ppm 16 minutes. STEL: 200 mg/m³ 10 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. STEL: 200 ppm 8 hours. STEL: 200 ppm 8 hours. STEL: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fure scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated ci Wash contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be wor unless the assessment indicates a higher degre	Methanoi		
OSHA PEL 1989 (United States, 3/19 Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 200 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 250 ppm 15 minutes. STEL: 250 ppm 16 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. STEL: 325 mg/m³ 16 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be working p appropriate the assessment indicates a higher degree of protection: chemical splayers, gases or dusts. If contact is possible, the following protection should be working p appropriate the assessment indicates a higher degree of protection: chemical splayers, gases or dusts. If c			TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes.
Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 250 ppm 15 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. STEL: 250 ppm 15 minutes. STEL: 250 ppm 16 hours. TWA: 260 mg/m³ 15 minutes. STEL: 250 ppm 8 hours. TWA: 260 mg/m³ 8 hours. TWA: 260 mg/m³ 8 hours. Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated c Wash contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical splashes, gases or dusts. If contact is possible, the following protection should be working p appropriate the assessment indicates a higher degree of protection: chemical splash			
TWA: 200 ppm 8 hours. TWA: 200 mg/m³ 8 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 10 hours. STEL: 320 ppm 16 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours. TWA: 200 pg/m³ 8 hours.Appropriate engineering controls::Environmental exposure controls::Environmental exposure controls::Environmental exposure controls::Environmental exposure controls::Environmental exposure controls::Environmental exposure controls::Environmental exposure controls::Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing.Eye/face protection:Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, th			
TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 260 mg/m³ 10 hours. STEL: 325 mg/m³ 10 hours. STEL: 325 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 10 hours. STEL: 325 mg/m³ 1			
STEL: 325 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 16 minutes. STEL: 326 mg/m³ 16 minutes. STEL: 326 mg/m³ 16 minutes. Stell: 325 mg/m³ 16 minutes. Stell: 325 mg/m³ 16 minutes. Stell: 326 mg/m³ 16 minutes. Stell: 327 mg/m³ 16 minutes. Stell: 328 mg/m³ 16 minutes. Stell: 329 mg/m³ 16 minutes. Stell: 320 mg/m³ 16 minutes.			
NIOSH REL (United States, 10/2013) Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 200 ppm 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 16 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 200 ppm 8 hours.Appropriate engineering controls:Good general ventilation should be sufficient to control worker exposure to ai contaminants.Environmental exposure controls:Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures Hygiene measures:Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated ci Wash contaminated clothing before reusing.Eye/face protection:Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be working p unless the assessment indicates a higher degree of protection: chemical splay			STEL: 250 ppm 15 minutes.
Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 250 mg/m³ 15 minutes. STEL: 200 ppm 8 hours. TWA: 200 ppm 8 hours. Two Two Two Two <td< td=""><td></td><td></td><td></td></td<>			
TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours.Appropriate engineering controls:Environmental exposure controls:Environmental exposure controls:Environmental exposure controls:Environmental exposure controls:Environmental exposure controls:Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing.Eye/face protection:Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be word unless the assessment indicates a higher degree of protection: chemical splashes,			
TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 16 minutes. STEL: 325 mg/m³ 16 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 200 mg/m³ 8 hours.Appropriate engineering controls:Good general ventilation should be sufficient to control worker exposure to ai contaminants.Environmental exposure controls:Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures Hygiene measures:Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated ci Wash contaminated clothing before reusing.Eye/face protection:Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be word unless the assessment indicates a higher degree of protection: chemical splay			U
STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. Two Environmental exposure Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Hygie			
STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. Environmental exposure Environmental exposure Environmental exposure Environmental exposure Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing. Eye/face protection Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unle			
OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be work unless the assessment indicates a higher degree of protection: chemical splay			
Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to al contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. ndividual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical splay			
Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to ai contaminants. Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated clothing before reusing. Eye/face protection : Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical splate			
controlscontaminants.Environmental exposure controlsEmissions from ventilation or work process equipment should be checked to they comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures Hygiene measures:Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing.Eye/face protection:Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection: chemical splay			TWA: 260 mg/m³ 8 hours.
controlsthey comply with the requirements of environmental protection legislation. In cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measuresWash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing.Eye/face protectionSafety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical splate		-	I be sufficient to control worker exposure to airborne
 Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated clowash contaminated clothing before reusing. Eye/face protection Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical splate 	-	they comply with the requireme cases, fume scrubbers, filters o	nts of environmental protection legislation. In some r engineering modifications to the process
 before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cl Wash contaminated clothing before reusing. Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical spla 	Individual protection measu	res	
assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worr unless the assessment indicates a higher degree of protection: chemical spla	Hygiene measures	before eating, smoking and usin Appropriate techniques should	ng the lavatory and at the end of the working period. be used to remove potentially contaminated clothing
goggioe. Robonninanaea, enemiear epiden goggioe.	Eye/face protection	assessment indicates this is ne gases or dusts. If contact is po unless the assessment indicate	cessary to avoid exposure to liquid splashes, mists, ssible, the following protection should be worn, s a higher degree of protection: chemical splash
Skin protection	Skin protection		
Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Personal protective equipment (Pictograms)	

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Yellow. [Light]
Odor	: Pungent. [Strong]
Odor threshold	: Not available.
рН	: 6 to 7
Melting point	: Not available.
Boiling point	: 93.333°C (200°F)
Flash point	: Closed cup: 115.56°C (240°F) [Pensky-Martens.] [Product does not sustain combustion.]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 3.2% Upper: 15.3%
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.12 to 1.15
Density	: 9.61 to 99.35 (lbs/gal)
Solubility	: Easily soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Dete diese (Dete derminise	unais People + Products -> Performance"

Date of issue/Date of revision

5/14/2015.

Section 9. Physical and chemical properties

Viscosity

: Not available.

Section 10. Stability and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Conditions to avoid	: No specific data.			
Incompatible materials	: No specific data.			
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

Section 11. Toxicological information

Information on toxicologica	al effects				
Acute toxicity					
Product/ingredient name	Result	Species	5	Dose I	Exposure
Ethylene Glycol	LD50 Oral	Rat		4700 mg/kg	-
Methanol	LD50 Dermal	Rabbit		15800 mg/kg	-
	LD50 Oral	Rat		143 mg/kg	-
Irritation/Corrosion					
Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethylene Glycol	Eyes - Mild irritant	Rabbit	-	24 hours 500) -
				milligrams	
	Eyes - Mild irritant	Rabbit	-	1 hours 100	-
		D 1 1 1		milligrams	
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440) -
	Skin - Mild irritant	Rabbit		milligrams 555	
	Skin - Milu Intant	Rabbit	-	milligrams	-
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100) -
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	40 milligrams	s -
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				milligrams	
Sensitization					
Product/ingredient name	Route of Species exposure			Result	
Not available.					

Section 11. Toxicological information **Mutagenicity Product/ingredient name** Test **Experiment** Result Not available. **Carcinogenicity Product/ingredient name** Result **Species** Dose **Exposure** Not available. **Product/ingredient name** Not available. **Reproductive toxicity Product/ingredient name** Maternal **Fertility Development** Species Dose Exposure toxicity toxin Not available. **Teratogenicity Product/ingredient name** Result **Species** Dose **Exposure** Not available. Specific target organ toxicity (single exposure) Name Category **Route of Target organs** exposure Not available. Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard	
Name	Result
Not available.	

Information on the likely ToxKinetics - routes of exposure	:	Routes of entry anticipated: Dermal, Inhalation.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	May be harmful if inhaled.
Skin contact	:	May cause skin irritation.
Ingestion	:	Harmful if swallowed. Irritating to mouth, throat and stomach. See notes to physician, below.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

	reaness
Inhalation	: Exposure to high concentrations may cause: nausea or vomiting Irritation dizziness/vertigo drowsiness/fatigue headache unconsciousness
Skin contact	: Adverse symptoms may include the following: redness burning absorption possible
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	1	Not available.		
<u>Long term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	1	Not available.		
Potential chronic health effects				

Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	1401.8 mg/kg

Other information

: Adverse symptoms may include the following: nausea or vomiting dizziness/vertigo drowsiness/fatigue headache pulmonary edema Cyanosis kidney abnormalities liver abnormalities coma death

10/16

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethylene Glycol	Acute LC50 100000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 10000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
Conclusion/Summary	Not available		

Conclusion/Summary

Not available.

Persistence and degradability

Not available.

Product/ingredient name

Not available.

Product/ingredient name

Not available.

Bioaccumulative potential			
Product/ingredient name	LogPow	BCF	Potential
Ethylene Glycol Methanol	-1.36 -0.77	- <10	low low

Mobility in soil Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

Date of issue/Date of revision

5/14/2015.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List	-		
Ingredient	CAS #	Status	Reference number
Methanol (I); Methyl alcohol (I)	67-56-1	Listed	U154

Section 14. Transport information

Regulatory UN/NA Proper shipping name information Number Proper shipping name DOT Classification Image: Classification Image: Classification		Proper shipping name	Hazard PG* Class(es)
			PG* : Packing grou
	Not regulated.	-	

Additional information

Label

TDG Classification		
Not - regulated.	-	-

Additional information

. .

Label

IMDG Class

Not regulated.

Marine pollutant notes: : Not available.

Date of issue/Date of revision

Section 14. Transport information

-

Additional information

Label

_

IATA-DGR Class

Not regulated.

Additional information

Label

		All component	-		xemption: I oted.	Not determ	lined	
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Listed						
Clean Air Act Section 602 Class I Substances	:	Not listed						
Clean Air Act Section 602 Class II Substances	:	Not listed						
DEA List I Chemicals (Precursor Chemicals)	:	Not listed						
DEA List II Chemicals (Essential Chemicals)	:	Not listed						
ARA 302/304								
omposition/information or	<u>ing</u>	<u>redients</u>						
o products were found.								
RA 304 RQ :	No	t applicable.						
RA 311/312								
assification		nmediate (acute elayed (chronic)						
omposition/information or	<u>ing</u>	<u>redients</u>						
ame			%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
thylene Glycol			5 - 10	No.	No.	No.	Yes.	Yes.
lethanol			5 - 10	Yes.	No.	No.	Yes.	Yes.

_

_

Section 15. Regulatory information

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Ethylene Glycol	107-21-1	5 - 10
	Methanol	67-56-1	5 - 10
Supplier notification	Ethylene Glycol	107-21-1	5 - 10
	Methanol	67-56-1	5 - 10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	:	The following components are listed: ETHYLENE GLYCOL; METHANOL
New York	:	The following components are listed: Ethylene glycol; Methanol
New Jersey	:	The following components are listed: ETHYLENE GLYCOL; 1,2-ETHANEDIOL; METHYL ALCOHOL; METHANOL
Pennsylvania	:	The following components are listed: 1,2-ETHANEDIOL; METHANOL

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Methanol	No.	Yes.	No.	23000 µg/day (ingestion) 47000 µg/day (inhalation)

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

```
Canada
```

· · · · ·	Class D-1B: Material causing immediate and seriou Class D-2A: Material causing other toxic effects (Ve Class D-2B: Material causing other toxic effects (To	ery toxic).	
<u>Canadian lists</u>			
Canadian NPRI (Pollution Release)	: The following components are listed: Ethyle	ne glycol; Methanol	
CEPA Toxic substances	: None of the components are listed.		
Canada inventory-DSL / NDSL International lists National inventory	All components are listed or exempted.		
Date of issue/Date of revision5/14/20	15. People + Products → Performance [™]	Version : 1	14/16

C 2145 Air Unit Corrosion Inhibitor W/S

Section 15. Regulatory information

Australia	: All components are listed or exempted.	
Canada	: All components are listed or exempted.	
China	: All components are listed or exempted.	
Europe	: All components are listed or exempted.	
Japan	: All components are listed or exempted.	
Malaysia	: All components are listed or exempted.	
New Zealand	: All components are listed or exempted.	
Philippines	All components are listed or exempted.	
Republic of Korea	All components are listed or exempted.	
Taiwan	: All components are listed or exempted.	

Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Normal Package Size(s): Ball: 2" Ball 50/Cooler; 4" Ball 12/Cooler Dry Product: 50 Lbs/Box Liquid: 5 Gallon/55 Gallon/Bulk Pellets: 30 Lbs/Cooler; 24 Lbs/Pail Stix: 1 1/4": 50 Each/Cooler

<u>matory</u>	
Date of issue/Date of revision	: 5/14/2015.
Version	: 1
Date of previous issue	: No previous validation.
Previous Validation Date	: No previous validation.
Prepared by	: Jacam Regulatory Department
(M)SDS Requests:	: SDS@jacam.com

History

Page: 15/16

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations
References	: Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

This Safety Data Sheet ("SDS") is a mandatory disclosure pursuant to 29 CFR § 1910.1200 and related rules and regulations. Therefore, it is not intended, nor shall it serve to create, any rights, obligations, liabilities, and remedies, of any kind whatsoever, between Jacam Chemicals 2013, LLC and related entities ("Jacam") and any users of this SDS ("Users").

To the extent that a court of competent jurisdiction determines that this SDS creates any rights, obligations, liabilities, and remedies, of any kind whatsoever, notwithstanding the foregoing paragraph, Users accept the product AS IS and WITH ALL FAULTS. Further, Jacam DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Users' sole and exclusive remedies shall be (if any), in Jacam's sole and absolute discretion, either: (1) return of the product and repayment of the purchase price; or (2) repair/replacement of the product. In no event shall Jacam be liable for any damages of any kind whatsoever, including but not limited to, actual, compensatory, reliance, expectancy, foreseeable, future, statutory, incidental, consequential, and exemplary damages. Users assume any and all risks of any kind whatsoever that in any way relate to the product.

*** END OF SDS ***

Safety Data Sheet



Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name

• 94-97% Calcium Chloride Powder

SDS Number/Grade CC-02

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Relevant identified use(s)
- Concrete acceleration, Drilling fluid additive, Dust control

1.3 Details of the supplier of the safety data sheet

Manufacturer • Cal-Chlor Corporation 627 Jefferson Street Lafayette, LA 70501 United States www.Cal-Chlor.com mscelsa@cal-chlor.com 1-800-245-6743

1.4 Emergency telephone number

Manufacturer

• 800-424-9300 - CHEMTREC

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

• Acute Toxicity Oral 4 - H302 Eye Irritation 2 - H319

DSD/DPD

- Eye Irritation 2 H3 Harmful (Xn) Irritant (Xi)
- 2.2 Label Elements



R22, R36

Hazard statements •	H319 - Causes serious eye irritation	
Precautionary statements		
Prevention •	P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear eye/face protection , .	
Response •	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P301+P312 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell. P330 - Rinse mouth.	
Storage/Disposal •	P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.	
DSD/DPD		
Risk phrases _●	R22 - Harmful if swallowed. R36 - Irritating to eyes.	
Safety phrases .	S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
.3 Other Hazards		
CLP •	According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.	
DSD/DPD •	This product is considered dangerous according to the European Directive 67/548/EEC.	
Inited States (US) ccording to OSHA 29 CFR 1910	.1200 HCS	
) 1 Classification of the su	botonoo or mixturo	

2.1 Classification of the substance or mixture

OSHA HCS 2012

- Acute Toxicity Oral 4 H302 Eye Irritation 2 - H319
- 2.2 Label elements

OSHA HCS 2012

WARNING



 Hazard statements Harmful if swallowed - H302 Causes serious eye irritation - H319
 Precautionary statements
 Prevention Wash thoroughly after handling. - P264 Do not eat, drink or smoke when using this product. - P270 Wear eye/face protection , . - P280
 Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - P305+P351+P338 If eye irritation persists: Get medical advice/attention. - P337+P313 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell. - P301+P312 Rinse mouth. - P330
 Storage/Disposal Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

2.3 Other hazards OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture **WHMIS**

- Other Toxic Effects D2B
- 2.2 Label elements **WHMIS**



- Other Toxic Effects D2B
- 2.3 Other hazards WHMIS
- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Calcium chloride	CAS:10043-52-4 EC Number:233- 140-8 EU Index:017- 013-00-2	94% TO 97%	Ingestion/Oral-Rat LD50 • 1 g/kg	EU DSD/DPD: Annex VI, Table 3.2: Xi R36; Additional Self Classification: Xn R22 EU CLP: Annex VI, Table 3.1: Eye Irrit. 2, H319; Additional Self Classification: Acute Tox. 4, H302 OSHA HCS 2012: Eye Irrit. 2; Acute Tox. 4 (orl)	NDA
Potassium chloride	CAS:7447-40-7 EC Number:231- 211-8	2% TO 3%	Ingestion/Oral-Rat LD50 • 2600 mg/kg	EU DSD/DPD: Self Classified: Xi R36 EU CLP: Self Classified: Eye Irrit. 2, H319 OSHA HCS 2012: Eye Irrit. 2	NDA
Sodium chloride	CAS: 7647-14-5 EC Number: 231- 598-3	1% TO 2%	Ingestion/Oral-Rat LD50 • 3000 mg/kg	EU DSD/DPD: Self Classified: Xi R36 EU CLP: Self Classified: Eye Irrit. 2, H319 OSHA HCS 2012: Eye Irrit. 2	NDA

3.2 Mixtures

Material does not meet the criteria of a mixture.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation	• Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. If signs/symptoms continue, get medical attention.	
Skin	 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. 	
Eye	 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention. 	
Ingestion	• Do NOT induce vomiting. Rinse mouth. Give one cup (8 ounces or 240 mL) of water or milk if available. Do not give anything by mouth to an unconscious person. Get medical attention immediately.	
4.2 Most important symptoms and effects, both acute and delayed		
	 Refer to Section 11 - Toxicological Information. 	

4.3 Indication of any immediate medical attention and special treatment needed

```
Notes to Physician
```

• All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media •	In case of fire use media as appropriate for surrounding fire.
Unsuitable Extinguishing • Media	No data available.
5.2 Special hazards arising	g from the substance or mixture
Unusual Fire and Explosion	Material does not burn.

Hazardous Combustion Products

5.3 Advice for firefighters

• Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Do not walk through spilled material. Wear appropriate personal protective equipment.
 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Spilled material may cause a slipping hazard.

Emergency Procedures

Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

• Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures • Avoid generating dust. SMALL DRY SPILLS: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area. Flush residue with plenty of water.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

• Use only with adequate ventilation. Avoid contact with skin, eyes, and clothing. Do not taste or swallow. Heat developed during diluting or dissolving is very high. Use cool water when diluting or dissolving (temperature less than 80°F, 27°C). Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

• Keep container tightly closed. Store in a cool, dry place. Protect from moisture.

7.3 Specific end use(s)

• Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters Exposure Limits/Guidelines	 No applicable exposure limits available for product or components.
8.2 Exposure controls	
Engineering Measures/Controls	 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Personal Protective Equipme	ent
Respiratory	• For limited exposure use an N95 dust mask. For prolonged exposure use an air- purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.
Eye/Face	 Wear safety goggles.
Skin/Body	 Wear appropriate gloves.
Environmental Exposure Controls	 Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	White powder with no odor.
Color	White	Odor	Odorless
Odor Threshold	Not relevant		
General Properties	•		•
Boiling Point	Not relevant	Melting Point	772 C(1421.6 F) (approximately)
Decomposition Temperature	Not relevant	рН	Not relevant
Specific Gravity/Relative Density	Not relevant	Bulk Density	65 lb(s)/ft ³ (estimated)
Water Solubility	Soluble	Viscosity	Not relevant
Explosive Properties	Not relevant.	Oxidizing Properties:	Not relevant.

Volatility

Volatility				
Vapor Pressure	Negligible	Vapor Density	Not relevant	
Evaporation Rate	Not relevant			
Flammability				
Flash Point	Not relevant	UEL	Not relevant	
LEL	Not relevant	Autoignition	Not relevant	
Flammability (solid, gas)	Not relevant.			
Environmental				
Octanol/Water Partition coefficient	Not relevant			

9.2 Other Information

• No additional physical and chemical parameters noted.

10.1 Reactivity

• No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

• Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

• Hazardous polymerization not indicated.

10.4 Conditions to avoid

• Avoid moisture.

10.5 Incompatible materials

• Heat is generated when mixed with water. Spattering and boiling can occur. Avoid contact with sulfuric acid. Corrosive when wet. Flammable hydrogen may be generated from contact with metals such as zinc and sodium. Reaction of bromide impurity with oxidizing materials may generate trace levels of impurities such as bromate.

10.6 Hazardous decomposition products

• Does not decompose.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components				
Calcium chloride (94% TO 97%)	10043-52-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 1 g/kg		
	Impurities, Stabilizers, etc			
Potassium chloride (2% TO 3%)		Acute Toxicity: Ingestion/Oral-Rat LD50 • 2600 mg/kg; Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation		
Sodium chloride (1% TO 2%)		Acute Toxicity: Ingestion/Oral-Rat LD50 • 3000 mg/kg; Irritation: Eye-Rabbit • 10 mg • Moderate irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Mild irritation		

GHS Properties	Classification

I

Acute toxicity		EU/CLP • Acute Toxicity - Oral 4 OSHA HCS 2012 • Acute Toxicity - Oral 4		
Asspiration Hazard		EU/CLP • Data lacking		
Aspiration Hazard		OSHA HCS 2012 • Data lacking		
Carcinogenicity		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Germ Cell Mutagenicity		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Skin corrosion/Irritation		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Skin sensitization		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
STOT-RE		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
STOT-SE		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Toxicity for Reproduction		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Respiratory sensitization		EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Serious eye damage/Irritation		EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2		
Route(s) of entry/exposure	 Inhalation, SI 	kin, Eye, Ingestion		
Medical Conditions Aggravated by Exposure Potential Health Effects	 Disorders of t 	the lungs.		
Inhalation				
Acute (Immediate)	or impact ma	dust may cause irritation. Processes such as cutting, grinding, crushing, y result in generation of excessive amounts of airborne dusts in the uisance dust may affect the lungs but reactions are typically reversible.		
Chronic (Delayed)	 No data availa 			
Skin				
Acute (Immediate)	 Exposure to 	dust may cause mechanical irritation.		
Chronic (Delayed)	 No data availa 	able.		
Eye				
Acute (Immediate)	 Causes serio workplace ma 	us eye irritation. Excessive concentrations of nuisance dust in the ay reduce visibility and may cause unpleasant deposits in eyes.		
Chronic (Delayed)	 No data availa 	able.		
Ingestion				
Acute (Immediate)	 Harmful if swa may cause m 	allowed. Excessive concentrations of nuisance dust in the workplace nechanical irritation to mucous membranes.		
Chronic (Delayed)	 No data availa 			
Key to abbreviations LD = Lethal Dose MLD = Mild				

MOD = Moderate

Section 12 - Ecological Information

12.1 Toxicity

94-97% Calcium Chloride Powder					
Dosage	Species	Duration	Results	Exposure Conditions	Comments
8350 to 10650 mg/L	Fish: Bluegill	NDA	LC50	NDA	Data for Calcium Chloride
759 to 3005 mg/L	Crustacea: Daphnia magna	NDA	EC50	NDA	Data for Calcium Chloride
= 4236 mg/L	Fish: Rainbow Trout	96 Hour(s)	LC50	NDA	Data for Potassium Chloride
= 590 mg/L	Crustacea: Daphnia magna	24 Hour(s)	EC50	NDA	Data for Potassium Chloride
= 3470 mg/L	Water Flea: Ceriodaphnia Dubia	96 Hour(s)	LC50	NDA	Data for Potassium Chloride
= 10610 mg/L	Fish: Fathead minnow	NDA	LC50	NDA	Data for Sodium Chloride
= 4571 mg/L	Crustacea: Daphnia magna	NDA	LC50	NDA	Data for Sodium Chloride

12.2 Persistence and degradability

Biodegradation is not applicable.

12.3 Bioaccumulative potential

No bioconcentration is expected because of the relatively high water solubility.

12.4 Mobility in Soil

Potential for mobility in soil is very high (Koc between 0 and 50). Partitioning from water to n-octanol is not applicable.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

Material is practically non-toxic to aquatic organisms on an acute basis. (LC50/EC50/EL50/LL50 >100mg/L in the most sensitive species tested).

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not Regulated	NDA	NDA	NDA

IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA
14.6 Special pro user	ecautions	for • None specified.			
14.7 Transport according to Ar MARPOL 73/78 Code		 Data lacking. 			

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute

			Inventory			
Component	CAS	Australia AICS	Canada DSL	Canada NDSL	China	EU EINECS
Calcium chloride	10043-52-4	Yes	Yes	No	Yes	Yes
Potassium chloride	7447-40-7	Yes	Yes	No	Yes	Yes
Sodium chloride	7647-14-5	Yes	Yes	No	Yes	Yes
			lassantans (Oa	K)		
			Inventory (Co	n't.)		
Component	CAS	EU ELNICS	Japan ENCS	n't.) Korea KECL	New Zealand	TSCA
Component Calcium chloride	CAS 10043-52-4	EU ELNICS No		, ,	New Zealand Yes	TSCA Yes
•			Japan ENCS	Korea KECL		

Canada

Canada - WHMIS - Classifications of Substances		
Calcium chloride	10043-52-4	D2B
Potassium chloride	7447-40-7	Uncontrolled product according to WHMIS classification criteria (includi 23.8%)
Sodium chloride	7647-14-5	Uncontrolled product according to WHMIS classification criteria
Canada - WHMIS - Ingredient Disclosure List		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
vironment Canada - CEPA - Priority Substances List		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed

Germany

Germany - Water Classification (VwVwS) - Annex 1		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes		
Calcium chloride	10043-52-4	ID Number 220, hazard class - low hazard to waters
Potassium chloride	7447-40-7	ID Number 230, hazard class - low hazard to waters
Sodium chloride	7647-14-5	ID Number 270, hazard class - low hazard to waters
Germany - Water Classification (VwVwS) - Annex 3		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed

United States

bor U.S OSHA - Process Safety Management - Highly Hazardous	s Chemicals	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
U.S OSHA - Specifically Regulated Chemicals		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7447-40-7 7647-14-5	Not Listed
J.S CERCLA/SARA - Hazardous Substances and their Report	able Quantities	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S CERCLA/SARA - Radionuclides and Their Reportable Qua	ntities	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S CERCLA/SARA - Section 302 Extremely Hazardous Substa	nces EPCRA RQs	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S CERCLA/SARA - Section 302 Extremely Hazardous Substa	ances TPQs	
Calcium chloride	10043-52-4	Not Listed

Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
U.S TSCA (Toxic Substances Control Act) - Section 5 - New Chemicals Progr	am (NCP) Chemica	I Categories
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed

United States - California

ironment S California - Proposition 65 - Carcinogens List		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S California - Proposition 65 - Developmental Toxicity		
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S California - Proposition 65 - Maximum Allowable Dose L	_evels (MADL)	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S California - Proposition 65 - No Significant Risk Levels (I	NSRL)	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S California - Proposition 65 - Reproductive Toxicity - Fen	nale	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed
J.S California - Proposition 65 - Reproductive Toxicity - Mal	e	
Calcium chloride	10043-52-4	Not Listed
Potassium chloride	7447-40-7	Not Listed
Sodium chloride	7647-14-5	Not Listed

15.2 Chemical Safety Assessment

• No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date

Preparation Date

Disclaimer/Statement of Liability

- 04/March/2014
 - 04/March/2014

• The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. No warranty of merchantability or fitness for a particular purpose, or warranty or guaranty of any other kind, express or implied, is made regarding performance, safety, suitability, stability or otherwise. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Cal-Chlor assumes no liability whatsoever for the use of or reliance upon this information. No suggestions for the use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any federal, state, local or foreign laws. OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees.

Key to abbreviations

NDA = No data available



Safety Data Sheet dated 27/5/2015, version 1 Printing date:29/5/2015 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Trade name: AES Defoam A F093619 MSDS code: Chemical description: Alcohols and esters blend 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Industrial uses. 1.3. Details of the supplier of the safety data sheet Supplier: Lamberti USA Inc. - Highway 59 at County Road 212 - P.O. Box 1000, Hungerford, TX 77448-U.S.A. Tel. n° 281 342-5675 Fax n° 979 532-3749 Competent person responsible for the safety data sheet: hse@lamberti.com 1.4. Emergency telephone number CHEMTREC - Phone n. 800 424-9300 **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture Following GHS and EC regulation criteria 1272/2008 (CLP) Warning, Flam. Liq. 4, Combustible liquid.

- Warning, Acute Tox. 4, Harmful if inhaled.
- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2A, Causes serious eye irritation.

(1) Warning, STOT SE 3, May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects: No other hazards

2.2. Label elements

Symbols:



Warning Hazard statements:

H227 Combustible liquid.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.



P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use Water and Carbon dioxide (CO2) to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

None

Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

- 3.1 Substances
- N.A.
- 3.2 Mixtures

Hazardous substances/components within GHS Classification and the meaning of the EEC directive 67/548 and CLP regulation and related classification

>=30% - <50% 2-Ethyl-1-hexanol

Index number: Not Available, CAS: 104-76-7, EC: 203-234-3

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. Seek immediately medical advice.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed Not known.
- 4.3. Indication of any immediate medical attention and special treatment needed Treatment: Not known.

SECTION 5: Firefighting measures

- 5.1. Extinguishing media Suitable extinguishing media:
 - Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons: Not known.

- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases.
- 5.3. Advice for firefighters Use suitable breathing apparatus.

Safety data sheet AES Defoam A



Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety.
 See protective measures under point 7 and 8.
- 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- 6.3. Methods and material for containment and cleaning up
 - Suitable material for taking up: absorbing material, organic, sand Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Do not use empty container before they have been cleaned.

Before making transfer operations, assure that there are not any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
- Keep away from food, drink and feed. Instructions as regards storage premises: Adequate ventilation in working area. Packaging suggested: Plastic drums.
- 7.3. Specific end use(s) None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
- No occupational exposure limit available
- DNEL Exposure Limit Values
- N.D.

PNEC Exposure Limit Values

N.D.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles. (ref. EN 166, EN 140, EN175).

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. (ref. EN 340).

Protection for hands:

Chemical-resistant protective gloves (EN 374). When prolonged or frequently repeated contact may occur, a glove is recommended to prevent contact. Examples of preferred glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). As general indication we suggest as suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) and suitable



materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness). This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances-mixtures.

Respiratory protection:

Use adequate protective respiratory equipment. (ref. EN 136, EN 140, EN 141, EN 143, EN 149, EN 405).

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

non of thysical and onemical pi	and the second
9.1. Information on basic physical and	· ·
Appearance and colour:	Liquid
Odour:	Slight
Odour threshold:	N.D.
pH:	N.D.
Melting point / freezing point:	<-10C (< 12F)
Initial boiling point and boiling ra	
Solid/gas flammability:	N.D.
Upper/lower flammability or exp	losive limits: N.D.
Vapour density:	N.D.
Flash point:	>63C (>145F)
Evaporation rate:	N.D.
Vapour pressure:	N.D.
Relative density:	0.900 - 0.950
Solubility in water:	Insoluble
Solubility in oil:	N.D.
Partition coefficient (n-octanol/v	vater): N.D.
Auto-ignition temperature:	N.D.
Decomposition temperature:	N.D.
Viscosity:	N.D.
Explosive properties:	N.D.
Oxidizing properties:	N.D.
9.2. Other information	
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant pro	perties N.D.
Osha Flammability:	Combustible liquid
,	•

SECTION 10: Stability and reactivity

10.1. Reactivity
Stable under normal conditions
10.2. Chemical stability
Stable under normal conditions
10.3. Possibility of hazardous reactions
Stable under normal conditions
10.4. Conditions to avoid
Stable under normal conditions.
10.5. Incompatible materials
Strong acids
Strong oxidizers
10.6 Hazardous decomposition produc

10.6. Hazardous decomposition products Not known.



11.1. Information on toxicological effects

Toxicological information of the substance:

- a) acute toxicity:
 - Toxicity Oral Rat LD50> 2000 mg/kg. By analogy to product with similar composition.
- b) skin corrosion/irritation:
 - Irritation Skin : Causes skin irritation.
- c) serious eye damage/irritation:
 - Irritation Eye : Causes serious eye irritation.
- d) respiratory or skin sensitisation:
 - Irritation Inhalation: May cause respiratory irritation.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.D.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- i) aspiration hazard.
- Carcinogenic IARC:

Not Carcinogenic IARC/NTP/OSHA

SECTION 12: Ecological information

- 12.1. Toxicity
 - Ecological information of the substance: a) Aquatic acute toxicity:
 - Data not available.
- 12.2. Persistence and degradability Ecological information of the substance: Biodegradability: Data not available.
- 12.3. Bioaccumulative potential Ecological information of the substance: Bioaccumulation: Data not available.
- 12.4. Mobility in soil Ecological information of the substance: Mobility in soil: Data not available.
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects None Use according to criteria of good industrial practice, avoiding product dispersion in the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

If possible recover the product, otherwise dispose of in authorized landfill or incineration in accordance with local regulation.

SECTION 14: Transport information

- 14.1. UN number
 - N.A.
- 14.2. UN proper shipping name Proper Shipping Name:
- 14.3. Transport hazard class(es) US DOT (non-bulk): US DOT (bulk):

N.A.

Not Regulated NA1993, Combustible liquid, n.o.s., (2-Ethyl-1-hexanol), PG-III

Safety data sheet AES Defoam A



Road (ADR): Air (ICAO/IATA): Sea (IMO/IMDG): Not Regulated Not Regulated Not Regulated

14.4. Packing group ADR-Packing Group: IATA-Packing group:

N.A. N.A.

N.A.

- IMDG-Packing group: 14.5. Environmental hazards N.A.
- 14.6. Special precautions for user N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH).

For non-EU Countries, the Material Safety Data Sheet it is prepared following the main principles of Globally Harmonized System of Classification and Labelling of Chemicals (GHS) which are adopted worldwide.

Refer to other local regulations that may be relevant (i.e. : sanitary control, waste treatment etc.)

15.2. Chemical safety assessm No	ent				
Regulatory information USA:					
HMIS INFORMATION	HAZARD INDE	X: 4 = S	SEVERE		
HEALTH 1		3 = S	SERIOUS		
FLAMMABILITY 2		2 = N	IODERATE		
REACTIVITY 1		1 = S	LIGHT		
PERSONAL PROT. C		0 = N	IINIMAL		
C* Safety glasses, gloves, cher	nical apron				
n Name	CAS	TSCA	CERCLA	Sara302	Sara313
0 2-Ethyl-1-hexanol	104-76-7	Yes	No	No	No
1 Non Hazardous components	s -	Yes	No	No	No

SARA Title III Section 311/312: Immediate (acute) health effects.

State Regulations:

Canadian Regulations: All the ingredients as such or as chemical group are registered in DSL. Canadian WHMIS Classification: D-2B (Toxic material) B-3 (Combustible liquid) California Proposition 65: Not cited (all components).

SECTION 16: Other information

N.A. = Not Applicable

N.D. = No Data available

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

TOXNET - Databases on toxicology, hazardous chemicals, environmental health, and toxic releases;

NIOSH - Registry of toxic effects of chemical substances (1983) - Occupational Health Guidelines for Chemical Hazards (1995) - Pocket Guide to Chemical Hazards (on line) European Chemical Bureau - ESIS: European chemical Substances Information System; CESIO - Classification and labelling of anionic, nonionic surfactants (January 2000).



M.Sittig-Handbook of toxic and Hazardous Chemicals and Carcinogens- III Ed. E.R. Plunkett - Handbook of Industrial Toxicology - III Ed. 1991. Samson Chem. Pub.-Chemical Safety Sheet working safely with hazardous chemical. SAX'S Dangerous Properties of Industrial Materials. VIII (1993) ACGIH "2013 TLVs and BEIs". ILV "1998/24/EC Directive and subsequent addition".

The product must be stored, handled and used according to criteria of good industrial practice and to regulations in force. This leaflet is offered for your consideration and guidance only. This leaflet complements the Technical Data Sheet but does not replace it. The information herein contained is given to the best of our knowledge at the time of issue.

Due to the several ways in which the product may be used and the possible interaction with variables not depending on or unknown to the supplier, we also cannot accept any liability whatsoever for any loss or damage however arising from the handling and use of our products.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP: DNEL:	Classification, Labeling, Packaging. Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: GHS:	Ordinance on Hazardous Substances, Germany. Globally Harmonized System of Classification and Labeling of
010.	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI: KSt:	International Nomenclature of Cosmetic Ingredients. Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
REACH:	Registration Evaluation and Authorization of Chemicals.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
SVHC:	Candidate List of Substances of Very High Concerns.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
ASTM:	American Society of Testing and Materials.
CBI:	Confidential Business Information
CFR:	Code of Federal Regulations
DOT:	Department of Transportation
EPA: EU:	Environmental Protection Agency European Union
FIFRA:	Federal Insecticide, Fungicide and Rodenticide Act
HCS:	Hazard Communication Standard
IARC:	International Agency for Research on Cancer
IUPAC:	International Union of Pure and Applied Chemistry
mg/kg:	Milligram per kilogram

Safety data sheet AES Defoam A



MSDS:	Material Safety Data Sheet
NAFTA:	North American Free Trade Agreement
OSHA:	Occupational Safety and Health Administration
OECD:	The Organization for Economic Cooperation and Development
QSARs:	Quantitative Structure-Activity Relationships
TSCA:	Toxic Substances Control Act
UN:	United Nations
WHMIS:	Workplace Hazardous Materials Information System



Duratec

SECTION 1. IDENTIFICATION

Product Identifier	Duratec
Other Means of Identification	Drilling fluid additive
Recommended Use	Fluid Loss Control.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No. Date of Preparation	CHEMTREC, 1-800-424-9300, 24-hour Emergency February 27, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2B; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 2

GHS Label Elements



V	
Signal Word:	
Warning	
Hazard Stateme	ent(s):
H320	Causes eye irritation.
H315	Causes skin irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H350	May cause cancer.
Precautionary S	Statement(s):
Prevention:	
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
Response:	
P305 + P351 +	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do.	Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
Storage:	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

POTENTIAL HEALTH EFFECTS: EYE: Dust in eye may result in mechanical irritation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains no hazardous ingredients. Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Diatomaceous earth, uncalcined	61790-53-2	11-14	
Silica, quartz	14808-60-7	<1	
Trade Secret	CBI*	Confidential	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation persists, get medical advice/attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Keep respiratory tract clear. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Dry chemical, Carbon Dioxide, Foam. Not combustible. Use extinguishing agent suitable for surrounding fire.

Specific Hazards Arising from the Chemical

This product presents no unusual hazards in a fire situation.

The nature of decomposition products is not known and will be influenced by other products/materials involved in the fire.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Containerize for solid waste disposal. Dispose of according to local, state and federal regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

See Section 8 for appropriate Personal Protective Equipment (PPE). Avoid creating excessive dust while handling the product. Ensure adequate ventilation.

Conditions for Safe Storage

STORAGE: Keep in closed containers in cool, dry, well ventilated area.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Diatomaceous earth, uncalcined	0.025 mg/m3 A2		0.1 mg/m3		Not established		
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established		
Trade Secret	Not established		Not established		Not established		

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Wear gloves and apron if exposure is expected. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

White - tan powder.
Faint
Not applicable
Not available (melting); Not applicable (freezing)
Not applicable
Not available
Not applicable
Not available
Not available (upper); Not available (lower)
Not applicable
Not applicable

Relative Density (water = 1)	1.03
Solubility	Insoluble in water
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Strong oxidizers. **Incompatible Materials** None known. **Hazardous Decomposition Products** Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Diatomaceous earth, uncalcined	Not available	Not available	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Trade Secret	Not available	Not available	Not available

LC50: No information was located.

LD50 (oral): No information was located.

LD50 (dermal): No information was located.

Skin Corrosion/Irritation

May cause mild skin irritation.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May result in mechanical irritation of the respiratory tract from high dust concentrations. May aggravate asthma. **Ingestion**

May cause discomfort if swallowed.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Diatomaceous earth, uncalcined	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Trade Secret	Not Listed	Not designated	Not Listed	Not Listed

This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Diatomaceous earth, uncalcined	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Immediate Health Hazard Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 0 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	February 27, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.




ENERPAC R

SECTION 1. IDENTIFICATION

Product Identifier	ENERPAC R
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	May 15, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Dermal) - Category 5 OSHA Defined Hazards: Combustible dust

GHS Label Elements

Signal Word:	
Warning	
Hazard Stateme	ent(s):
May form comb	ustible dust concentrations in air
H313	May be harmful in contact with skin.
Precautionary S Prevention:	Statement(s):
P264 Response:	Wash hands and skin thoroughly after handling.
P312	Call a POISON CENTRE/doctor if you feel unwell.
Other Hazards	

EYE: Dust in eye may result in mechanical irritation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance:

Chemical Name	CAS No.	%	Other Identifiers
Polyanionic Cellulose (PAC)	9004-32-4	100	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap. Remove contaminated clothing and launder before reuse. Get medical advice/attention if you feel unwell or are concerned.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Call a Poison Centre or doctor if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Dry chemical. Alcohol-resistant foams.

Specific Hazards Arising from the Chemical

Product can ignite if strongly heated and exposed to open flames. At very high dust concentrations, product may form combustible dust concentrations or explosive dust-air mixtures.

Thermal decomposition of this product may lead to the release of irritating gases and vapours. oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

Dust explosion hazard. Use water spray or fog to prevent dust formation and minimize risk of explosion. When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the product enters drains, soil, ditches, sewers, waterways and/or groundwater inform EH&S and appropriate authorities.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Place solid waste in a sealed container for disposal in accordance with local environmental and public health regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Only use where there is adequate ventilation. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Remove and wash contaminated clothing before re-use. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Polyanionic Cellulose (PAC)	Not established	3 mg/m3 (R)	5 mg/m3 (R)	Not established	Not established	Not established

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Product may cause irritation similar to nuisance dust and meet the criteria of Particulates Not Otherwise Specified inhalable particles, or total particles.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Light yellow powder.
Odour	Not available
Odour Threshold	Not available
рН	6.5 - 8.5
Melting Point/Freezing Point	525 °F (274 °C) (melting); 525 °F (274 °C) (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	Not available
Solubility	Not available in water
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Open flames, sparks, static discharge, heat and other ignition sources. **Incompatible Materials** Strong Oxidizing Agents. Carbon oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Polyanionic Cellulose (PAC)	> 5800 mg/m3 (rat) (4-hour exposure)	27000 mg/kg (rat)	> 2000 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation. May be harmful if inhaled.

Skin Absorption

No information was located.

Ingestion

May cause irritation of the digestive tract.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Polyanionic Cellulose (PAC)	Not Listed	Not Listed	Not Listed	Not Listed

No information was located.

Key to Abbreviations

IARC = International Agency for Research on Cancer. ACGIH® = American Conference of Governmental Industrial Hygienists. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Product Identifier:	ENERPAC R
Date of Preparation:	May 15, 2015

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Polyanionic Cellulose (PAC)	100-1000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour)	87.26 mg/L (Daphnia magna (water flea); 48-hour)	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: None SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 1 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	May 15, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: ENERPAC R May 15, 2015



Page 06 of 06





Ener Pac Regular

SECTION 1. IDENTIFICATION

Product Identifier	Ener Pac Regular
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	May 15, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Label Ele	ments
Hazard Statem	ent(s):
H402	Harmful to aquatic life.
Precautionary S	Statement(s):
P273	Avoid release to the environment.
P501	Dispose of contents/container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance:			
Chemical Name	CAS No.	%	Other Identifiers
Polyanionic Cellulose (PAC)	9004-32-4	100	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap. Remove contaminated clothing and launder before reuse. Get medical advice/attention if you feel unwell or are concerned.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Call a Poison Centre or doctor if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Dry chemical. Alcohol-resistant foams.

Specific Hazards Arising from the Chemical

Product can ignite if strongly heated and exposed to open flames.

Thermal decomposition of this product may lead to the release of irritating gases and vapours. oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the product enters drains, soil, ditches, sewers, waterways and/or groundwater inform EH&S and appropriate authorities.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Place solid waste in a sealed container for disposal in accordance with local environmental and public health regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Only use where there is adequate ventilation. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Remove and wash contaminated clothing before re-use. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	TLV®	OSHA	A PEL	AIHA®	WEEL™
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Polyanionic Cellulose (PAC)	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. Skin Protection

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical	•
Appearance	Light yellow powder.
Odour	Not available
Odour Threshold	Not available
рН	6.5 - 8.5
Melting Point/Freezing Point	525 °F (274 °C) (melting); 525 °F (274 °C) (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	Not available
Solubility	Not available in water
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions of use. Chemical Stability Stable under normal conditions. Possibility of Hazardous Reactions None expected under normal conditions of storage and use. Conditions to Avoid Open flames, sparks, static discharge, heat and other ignition sources. Incompatible Materials Strong Oxidizing Agents. Hazardous Decomposition Products Carbon oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Polyanionic Cellulose (PAC)	> 5800 mg/m3 (rat) (4-hour exposure)	27000 mg/kg (rat)	> 2000 mg/kg (rabbit)

Skin Corrosion/Irritation

Product Identifier:	Ener Pac Regular
Date of Preparation:	May 15, 2015

May cause skin irritation.

Serious Eye Damage/Irritation

May cause eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation. May be harmful if inhaled.

Skin Absorption

No information was located.

Ingestion

May cause irritation of the digestive tract.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Polyanionic Cellulose (PAC)	Not Listed	Not Listed	Not Listed	Not Listed

No information was located.

Key to Abbreviations

IARC = International Agency for Research on Cancer. ACGIH® = American Conference of Governmental Industrial Hygienists. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration. Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Polyanionic Cellulose (PAC)	100-1000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour)	87.26 mg/L (Daphnia magna (water flea); 48-hour)		Not available

Persistence and Degradability No information was located. Bioaccumulative Potential

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b) All ingredients are on the TSCA Inventory or exempt from the TSCA. Additional USA Regulatory Lists CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: None

SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 1 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	May 15, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.





Fiber Seal

SECTION 1. IDENTIFICATION

Product Identifier	Fiber Seal
Other Means of Identification	Fiber Seal
Supplier	Bri-Chem Supply Corp, 5151 Bannock Street Unit 5, Denver, CO, 80216, 303-722-1681, www.brichemsupplycorp.com
Emergency Phone No.	ChemTrec, (800) 424-9300, 24/7
SDS No.	0823

SECTION 2. HAZARDS IDENTIFICATION

GHS Label Elements

Non-hazardous ingredients. Potential respiratory hazard only to persons with severe obstructive lung disease when exposed to high levels of dust, not fiber as supplied.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Blend of vegetable, cotton, and cellulose-based polymer fibers	None	100	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell or are concerned.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Call a Poison Centre or doctor if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

Can irritate the nose and throat.

If in eyes:

May cause slight irritation as a "foreign object". Tearing, blinking and mild temporary pain may occur as particles are rinsed from the eye by tears.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

Can ignite if strongly heated.

This product presents no unusual hazards in a fire situation.

Special Protective Equipment and Precautions for Fire-fighters

A full-body encapsulating chemical protective suit with positive pressure SCBA may be necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

No special precautions are necessary.

Methods and Materials for Containment and Cleaning Up

No special clean-up methods are necessary.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid generating dusts. Do not grind to a fine fiber.

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling.

Conditions for Safe Storage

Store in an area that is: dry, well-ventilated, out of direct sunlight and away from heat and ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

(Cotton Dust) OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. 1 mg/m3

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. 0.2 mg/m3

(Cellulose Dust)

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. 15 mg/m3

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. 10 mg/m3.

Appropriate Engineering Controls

Use a local exhaust ventilation and enclosure, if necessary, to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles.

Product Identifier:	Fiber Seal
SDS No.:	0823
Date of Preparation:	October 05, 2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Earthy
Not available
Not available
Not available
Insoluble in water; Not available (in other liquids)
Not available
Not available (kinematic)
Solid
Not available
Not available

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability Normally stable. Possibility of Hazardous Reactions Hazardous polymerization will not occur. Conditions to Avoid None known. Incompatible Materials None known. Hazardous Decomposition Products None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Inhalation LC50: Testing not conducted. Oral LD50: Testing not conducted. Dermal LD50: Testing not conducted. **Skin Corrosion/Irritation** Not a skin irritant.

Not irritating.

Serious Eye Damage/Irritation

Human experience shows mild irritation. May cause slight irritation as a "foreign object". Tearing, blinking and mild temporary pain may occur as particles are rinsed from the eye by tears.

STOT (Specific Target Organ Toxicity) - Single Exposure Inhalation

Product Identifier:	Fiber Seal
SDS No.:	0823
Date of Preparation:	October 05, 2015

As with any product where dust can be produced, persons with existing severe obstructive lung disease should avoid inhalation of any fine particulate or dust produced. Can irritate the nose and throat.

Ingestion

Not a likely route of exposure. No adverse effects expected.

Carcinogenicity

IARC: Group 3 – Not classifiable as to its carcinogenicity to humans.

NTP: Not specifically listed.

OSHA: Not specifically listed.

No information was located for: Serious Eye Damage/Irritation, STOT (Specific Target Organ Toxicity) - Repeated Exposure, Respiratory and/or Skin Sensitization, Development of Offspring, Sexual Function and Fertility, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

Ecological testing has not been conducted on this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Recycle and reuse product, if possible. Contact local environmental authorities for approved disposal or recycling methods in your jurisdiction.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG Regulations.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	NA1365	Cotton	9	

Special Precautions Not applicable

for User

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Not regulated.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 0	
SDS Prepared By	Bri-Chem Supply Corp	
Date of Preparation	October 05, 2015	
Disclaimer	This Health and Safety information is correct to the best of our knowledge and date of its publication, but we cannot accept liability for any loss, injury or dam result from its use. We shall ensure, so far as is reasonably practicable, that a Data Sheet is sent to all customers to whom we have directly supplied this su point out that it is the responsibility of any intermediate supplier to ensure that passed to the ultimate user. The information given in the Data Sheet is design guidance for safe handling, storage, and the use of the substance. It is not a s does it guarantee any specific properties. All chemicals should be handled on personnel, within a controlled environment. Should further information be requ obtained through the sales office whose address is at the top of this data sheet	hage which may any revision of this bstance, but must is such revision is hed only as specification nor ly by competent uired, this can be
Product Identifier:	Fiber Seal	
SDS No.:	0823 Pa	age 04 of 05
Date of Preparation:	October 05, 2015	

Product Identifier: Fiber Seal SDS No.: Date of Preparation:

0823 October 05, 2015



Page 05 of 05



FLR

SECTION 1. IDENTIFICATION

Product IdentifierFLROther Means of
IdentificationGilsonite blendRecommended UseDrilling Fluid Additive.Manufacturer/Supplier
IdentifierAES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Information, 281-556-5628Emergency Phone No.AES Drilling Fluids, LLC, 1-888-556-4533Date of PreparationApril 21, 2016

SECTION 2. HAZARD IDENTIFICATION

Classification

Combustible dust - Category 1; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

Label Elements



Signal Word: Danger

Hazard Stat	tement(s):
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
Precautiona	iry Statement(s):
Preventio	n:
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P264	Wash hands and skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eve protection/face protection

Response:

P314 Get medical advice or attention if you feel unwell.

Storage: P405

Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:					
Chemical Name	CAS No.	%	Other Identifiers		
Proprietary Gilsonite blend	CBI*	97 - 99			
Silica, quartz	14808-60-7	0.1 - 3.0			

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Move to fresh air. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap. If irritation persists, get medical advice/attention.

Eye Contact

Flush eyes with large quantities of water for 15 minutes. Obtain medical assistance if irritation persists.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon Dioxide, Foam, Dry chemical, Water.

Specific Hazards Arising from the Product

At very high dust concentrations, product may form combustible dust concentrations or explosive dust-air mixtures. Oxides of carbon. Oxides of nitrogen.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Methods and Materials for Containment and Cleaning Up

Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Containerize

for solid waste disposal. Clean up residual contamination with water and place in appropriate containers for disposal. Dispose of according to local, state and federal regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Avoid skin and eye contact. Only use where there is adequate ventilation. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. See Section 8 for appropriate Personal Protective Equipment (PPE). Avoid generating dusts. Dust may form an explosive mixture with air at high concentrations. Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs.

Conditions for Safe Storage

Store in an area that is: cool, well-ventilated. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	ACGIH® TLV®		TLV® OSHA PEL		AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Proprietary Gilsonite blend	3 mg/m3 (R)	Not established	5 mg/m3 (R)	Not established	Not established	Not established	
Silica, quartz	0.025 mg/m3 A2	Not established	0.1 mg/m3	Not established	Not established	Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. R = Respirable fraction. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL® = Workplace Environmental Exposure Limit. Control parameter values for respirable dust.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Use goggles or face shield when there is risk of eye contact or visible dust produced.

Skin Protection

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions exist above the OEL if conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

5	•
Appearance	Dark powder.
рН	Not available
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available

Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapor Pressure	Not available
Vapor Density (air = 1)	Not available
Relative Density (water = 1)	1.1 - 1.6
Solubility	Slightly soluble in water
Auto-ignition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Strong Oxidizing Agents. Sparks. Heat. Open flames. **Incompatible Materials** Strong Oxidizing Agents. **Hazardous Decomposition Products** Oxides of carbon. Oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Proprietary Gilsonite blend	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available

Skin Corrosion/Irritation

May aggravate dermatitis.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

High dust levels may cause irritation of the respiratory tract.

Skin Absorption

No information was located.

Ingestion

May cause. irritation of the gastrointestinal tract.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged exposure to high dust concentrations may cause difficulty breathing. Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Proprietary Gilsonite blend	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans. Data gathered from studies suggest that gilsonite is not carcinogenic and has a low order of toxicity. Though evidently not a carcinogen in its normal state, the complex hydrocarbon structure of gilsonite may be altered by extremely high temperatures, possibly producing carcinogenic substances. Inhalation of vapor or mists produced in high-temperature processes using this product should be avoided. Skin should be covered when these vapors or mists are present.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers.

Ecotoxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Proprietary Gilsonite blend	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

Studies are not available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Chronic Health Hazard. SARA Title III - Section 313: None.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 1 Instability - 0
SDS Prepared By	HSE Department
Phone No.	403-269-2800
Date of Preparation	April 21, 2016
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information

this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

FLR April 21, 2016





GEL

SECTION 1. IDENTIFICATION

Product IdentifierGELOther Means of
IdentificationViscosifierRecommended UseDrilling Fluid Additive.Manufacturer/Supplier
IdentifierAES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Information, 281-556-5628Emergency Phone No.AES Drilling Fluids, LLC, 1-888-556-4533Date of PreparationAugust 17, 2015

SECTION 2. HAZARD IDENTIFICATION

Classification Not classified under any hazard class. Label Elements Not applicable

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
BENTONITE	1302-78-9	100	
Christalline silica; cristobalite	14464-46-1	<1	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Get medical advice or attention if you feel unwell or are concerned.

Eye Contact

Rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Specific Hazards Arising from the Product

This product presents no unusual hazards in a fire situation. Does not burn. Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Ensure adequate ventilation in area. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Remove or isolate incompatible materials as well as other hazardous materials.

Environmental Precautions

It is good practice to prevent releases into the environment.

Methods and Materials for Containment and Cleaning Up

Avoid generating dust. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Store recovered product or absorbent material in suitable containers for disposal according to local regulations.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Avoid contact with eyes, skin and clothing. Avoid creating excessive dust while handling the product. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area.

Conditions for Safe Storage

Store in an area that is: dry, cool, well-ventilated. Separate from incompatible materials keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

ACGIH® TLV®		Alberta		SASK		
Chemical Name	TWA	STEL [C]	OEL	STEL	OEL	STEL
BENTONITE	3 mg/m3 (R)	Not established	3 mg/m3 (R)	Not established	3 mg/m3	6 mg/m3
Christalline silica; cristobalite	0.025 mg/m3 A2	Not established	0.025 mg/m3	Not established	0.05 mg/m3	Not established

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. STEL = Short-term Exposure Limit. C = Ceiling limit. OEL = Occupational Exposure Limit r = Respirable fraction. Product may cause irritation similar to nuisance dust and meet the criteria of Particulates Not Otherwise Specified, respirable particles.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields are recommended to prevent eye contact. Use goggles or face shield when there is

Product Identifier: GEL

Date of Preparation: August 17, 2015

risk of eye contact or visible dust produced.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties			
Appearance	fine powder.		
Odour	Odourless		
Odour Threshold	Not available		
рН	8.5 - 11.0		
Melting Point/Freezing Point	> 842 °F (450 °C) (melting); Not available (freezing)		
Initial Boiling Point/Range	Not available		
Flash Point	Not available		
Evaporation Rate	Not available		
Flammability (solid, gas)	Will not burn.		
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)		
Vapour Pressure	0 kPa at 25 ⁰C		
Vapour Density (air = 1)	Not available		
Relative Density (water = 1)	2.6		
Solubility	< 0.9 mg/L in water		
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available		
Auto-ignition Temperature	Not available		
Decomposition Temperature	> 932 °F (500 °C)		
Viscosity	Not available (kinematic); Not available (dynamic)		
Other Information			
Physical State	Solid		

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Exposure to moisture may affect product quality. **Incompatible Materials** None known.

Hazardous Decomposition Products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion. dust may result in irritation of skin, eye or respiratory system. **Acute Toxicity**

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
BENTONITE	> 5.27 mg/L (rat) (4-hour exposure)	> 2000 mg/kg (rat)	Not available
Christalline silica; cristobalite	Not available	500 mg/kg (rat)	Not available

Skin Corrosion/Irritation

Not a skin irritant.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

High dust levels may cause irritation of the respiratory tract.

Skin Absorption

No information was located.

Ingestion

No effects anticipated.

Aspiration Hazard

No information was located.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product may contain trace amounts of crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not a skin sensitizer. May cause respiratory irritation, not classified.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
BENTONITE	Not Listed	Not designated	Not Listed	Not Listed
Christalline silica; cristobalite	Group 1	A2	Known carcinogen	Not Listed

This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Ecotoxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EL SULL FUSTACOA	ErC50 Aquatic Plants	ErC50 Algae
BENTONITE	19000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	> 100 mg/L (Daphnia magna (water flea); 48-hour)	Not available	Not available
Christalline silica; cristobalite	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released into the environment, this product can move slowly through the soil.

Other Adverse Effects

No known significant effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of unused product in accordance with local environmental and public health regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL or are not required to be listed.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

Additional USA Regulatory Lists

Product does not contain any chemicals subject to the reporting requirement of CERCLA.

SARA Title III - Section 302: No listed components.

SARA Title III - Section 311/312: No listed components.

SARA Title III - Section 313: No listed components.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 0 Flammability - 0 HSE Department	Instability - 0
Product Identifier:	GEL	
Date of Preparation:	August 17, 2015	Page 05 of 06

Phone No. Date of Preparation Disclaimer 403-269-2800

August 17, 2015

Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

GEL August 17, 2015



Page 06 of 06



Lime

SECTION 1. IDENTIFICATION

Product IdentifierLimeRecommended UseDrilling Fluid Additive.Manufacturer/SupplierAES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Information, 281-556-5628Emergency Phone No.AES Drilling Fluids, LLC, 1-888-556-4533Date of PreparationAugust 20, 2015

SECTION 2. HAZARD IDENTIFICATION

Classified according to the US Hazard Communication Standard (HCS 2012).

Classification

Skin irritation - Category 2; Serious eye damage - Category 1; Specific target organ toxicity (single exposure) - Category 3

Label Elements



SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Calcium hydroxide	1305-62-0	>85	
Silica, quartz	14808-60-7	<0.1	

Notes

Concentrations are expressed in % weight/weight.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. If breathing has stopped, trained personnel should begin rescue breathing. Give artificial respiration only with the aid of a pocket mask equipped with a one way valve or other proper respiratory medical device. Immediately call a Poison Centre or doctor.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Seek medical advice/attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes, while holding the eyelid(s) open. Immediately call a Poison Centre or doctor.

Ingestion

Do not induce vomiting without medical advice. Get medical advice or attention if you feel unwell or are concerned. Never give anything by mouth to an unconscious person.

First-aid Comments

Due to irritant properties, swallowing may result in burns/ulceration of the mouth, stomach and lower GI tract.

Most Important Symptoms and Effects, Acute and Delayed

Irritation of skin, eyes, gastrointestinal tract or respiratory tract.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical. Use flooding quantities of water or other suitable extinguishing agent.

Specific Hazards Arising from the Product

Bulk powder calcium oxide may heat spontaneously when damp. Humidity or contact with water may generate sufficient heat to ignite flammable and combustible materials.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus. Firefighters should wear appropriate breathing apparatus and protective clothing. When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Do not use water on bulk spills. Lime reacts violently with water. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Avoid dust formation. Do not clean up materials with compressed air. Evacuate

the area immediately. Evacuate downwind locations.

Environmental Precautions

Minimize dust during clean up. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Avoid generating dust. Prevent contamination of waterways or sewers. Clean up residual contamination with water and place in appropriate containers for disposal. Wash equipment with either a mild vinegar solution, or detergent and water.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Keep containers tightly closed when not in use or empty. Protect containers from physical damage. Avoid contact with eyes, skin and clothing.

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated, separate from incompatible materials (see Section 10: Stability and Reactivity). Keep away from moisture long term storage in aluminum containers is not recommended, as calcium oxide may corrode aluminum over long periods of time.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	ACGIH® TLV® A		perta	SASK	
Chemical Name	TWA	STEL [C]	OEL	STEL	OEL	STEL
Calcium hydroxide	5 mg/m3		5 mg/m3		5 mg/m3	10 mg/m3
Silica, quartz	0.025 mg/m3 A2	Not established	0.025 mg/m3	Not established	0.05 mg/m3	Not established

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OEL = Occupational Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. An eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible. It is not recommended to wear contact lenses while working with product.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product. Wear chemical protective clothing e.g. gloves, aprons, boots.

Respiratory Protection

If conditions exist above the OEL if conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	White - grey fine powder.
Odour	Odourless
Odour Threshold	Not available

рН	12.45 (saturated solution)
Melting Point/Freezing Point	1076 °F (580 °C) (melting); Not available (freezing)
Initial Boiling Point/Range	5162 °F (2850 °C)
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	2.2 - 2.4
Solubility	0.070 - 0.185 g/100 mL (Slightly soluble) in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid
Bulk Density	720 - 1200 kg/m3 (45 - 75 lb/ft3)

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Reacts with water to form calcium hydroxide. The heat generated when mixed with water or moist air is sufficient enough to ignite surrounding materials such as paper, wood or cloth.

Chemical Stability

Unstable under certain conditions - see Conditions to Avoid.

Possibility of Hazardous Reactions

Humidity or contact with water may generate sufficient heat to ignite flammable and combustible materials.

Conditions to Avoid

Water, moisture or humidity.

Incompatible Materials

Strong acids. Water. Avoid contact with: boron trifluoride, chlorine trifluoride, ethanol, fluorine. Powdered metals aluminum, acid anhydrides (e.g. acetic anhydride), hydrogen fluoride, phosphorus pentoxide.

Hazardous Decomposition Products

Reacts with water to form calcium hydroxide and generates heat.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Calcium hydroxide	Not available	7300 mg/kg (mouse)	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available

Skin Corrosion/Irritation

Corrosive. May cause severe skin irritation. Contact can cause pain, redness, burns, and blistering. Permanent scarring can result.

Serious Eye Damage/Irritation

Contact causes severe burns with redness, swelling, pain and blurred vision. Permanent damage including blindness can result.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Material is irritating to mucous membranes and upper respiratory tract. May cause coughing, sneezing, inflammation of respiratory tract, ulceration and perforation of nasal septum, bronchitis, possible pneumonia.

Skin Absorption

No information was located.

Ingestion

Product is harmful if ingested. May cause burning and edema of the digestive tract. Symptoms may include abundant salivation, difficulties in swallowing and breathing, vomiting blood, drop in blood pressure which would be an indication of the esophagus or stomach.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Prolonged skin contact may cause defatting of the skin resulting in irritation and conditions such as dermatitis. Prolonged or repeated skin contact may cause skin corrosion.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Calcium hydroxide	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

- **Development of Offspring**
- No information was located.
- **Sexual Function and Fertility**
- No information was located.
- Effects on or via Lactation
- No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers.

Ecotoxicity

Expected to be toxic to aquatic organisms. Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Calcium hydroxide	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released into the environment, this product can move slowly through the soil. Contamination of groundwater could occur.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. If this product as supplied, and unmixed, becomes a waste, it will not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL or are not required to be listed.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Immediate Health Hazard SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 3 Flammability - 0 Instability - 0		
SDS Prepared By	HSE Department		
Phone No.	403-269-2800		
Date of Preparation	August 20, 2015		
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.		

Product Identifier: Date of Preparation:

August 20, 2015

Lime

Created using



Page 06 of 06



MULTI FIBER FINE

SECTION 1. IDENTIFICATION

Product Identifier	MULTI FIBER FINE
Other Means of Identification	Cellulose, fiber blend
Recommended Use	Fluid Loss Control.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	April 09, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

OSHA Defined Hazards: Combustible dust

GHS Label Elements

Signal Word: Warning Hazard Statement(s): Dust in eye may result in mechanical irritation. May form combustible dust concentrations in air Prevention: Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/eye protection/face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. P337 + P313 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308 + P313 IF exposed or concerned: Get medical advice/attention. Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains no hazardous ingredients. Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Trade Secret	CBI*	Trade Secret	
Cellulose Blend	9004-34-6	Trade Secret	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap.

Eye Contact

Flush eyes with large quantities of water for 15 minutes. Obtain medical assistance if irritation persists.

Ingestion

Rinse mouth with water. If large amounts are ingested, give water to drink and get medical advice. Do not induce vomiting without medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

At very high dust concentrations, product may form combustible dust concentrations or explosive dust-air mixtures. Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet. Keep out unnecessary and unprotected personnel.

Environmental Precautions

Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Avoid generating dust. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Containerize for solid waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in dust. Avoid contact with eyes, skin and clothing. Do not ingest product. See Section 8 for appropriate Personal Protective Equipment (PPE). Keep away from sources of ignition, No Smoking while working with this product. Avoid creating excessive dust while handling the product. Dust may form an explosive mixture with air at high concentrations.

Conditions for Safe Storage

Store in an area that is: ventilated. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials (see Section 10: Stability and Reactivity). Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Control Parameters

	ACGIH®	TLV®	OSHA PEL AIHA® W		WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Trade Secret	10 mg/m3 (R)	Not established	5 mg/m3 (R)	Not established	Not established	Not established
Cellulose Blend	10 mg/m3		5 mg/m3 (R)		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. R = Respirable fraction. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Control parameter values for respirable dust.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields. Use goggles or face shield when there is risk of eye contact or visible dust produced.

Skin Protection

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Grey powder.
Odour	Odourless
рН	6.0 (5% solution)
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.8 - 0.9
Solubility	Insoluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature Other Information	Not available
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Generation of dust.

Incompatible Materials

None known.

Hazardous Decomposition Products

Carbon Monoxide and Carbon Dioxide may form on combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Trade Secret	> 5800 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Cellulose Blend	> 5800 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)

Skin Corrosion/Irritation

Not a skin irritant.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract.

Ingestion

No effects anticipated.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No known significant effects.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Cellulose Blend	Not Listed	Not Listed	Not Listed	Not Listed

Not known to cause cancer.

Key to Abbreviations

IARC = International Agency for Research on Cancer. ACGIH® = American Conference of Governmental Industrial Hygienists. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Trade Secret	Not available	Not available	Not available	Not available
Cellulose Blend	Not available	Not available		Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: None SARA Title III - Section 313: None.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 1 AES Drilling Fluids	Instability - 0
Phone No.	281-556-5628	
Date of Preparation	April 09, 2015	
Disclaimer		ions on MSDS are read and understood. The information on purpose of enabling those who transport, handle or use our
Product Identifier:	MULTI FIBER FINE	
Date of Preparation:	April 09, 2015	Page 05 of 06

products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: MULTI FIBER FINE April 09, 2015



Page 06 of 06



MULTI FIBER MEDIUM

SECTION 1. IDENTIFICATION

Product Identifier	MULTI FIBER MEDIUM
Other Means of Identification	Cellulose, fiber blend
Recommended Use	Fluid Loss Control.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	April 10, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

OSHA Defined Hazards: Combustible dust

GHS Label Elements

Signal Word: Warning Hazard Statement(s): Dust in eye may result in mechanical irritation. May form combustible dust concentrations in air Prevention: Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/eye protection/face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308 + P313 IF exposed or concerned: Get medical advice/attention. Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:					
Chemical Name	CAS No.	%	Other Identifiers		
Cellulose Blend	9004-34-6	60 - 80			
Trade Secret	CBI*	Trade Secret			
Trade Secret	CBI*	Trade Secret			

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap.

Eye Contact

Flush eyes with large quantities of water for 15 minutes. Obtain medical assistance if irritation persists.

Ingestion

Rinse mouth with water. If large amounts are ingested, give water to drink and get medical advice. Do not induce vomiting without medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

At very high dust concentrations, product may form combustible dust concentrations or explosive dust-air mixtures. Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet. Keep out unnecessary and unprotected personnel.

Environmental Precautions

Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Avoid generating dust. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Containerize for solid waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in dust. Avoid contact with eyes, skin and clothing. Do not ingest product. See Section 8 for appropriate Personal Protective Equipment (PPE). Keep away from sources of ignition, No Smoking while working with this product. Avoid creating excessive dust while handling the product. Dust may form an explosive mixture with air at high concentrations.

Conditions for Safe Storage

Store in an area that is: ventilated. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH®	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Cellulose Blend	10 mg/m3 (R)	Not established	5 mg/m3 (R)	Not established	Not established	Not established	
Trade Secret	0.025 mg/m3 A2		0.1 mg/m3		Not established		
Trade Secret	Not established		Not established		Not established		

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. R = Respirable fraction. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields. Use goggles or face shield when there is risk of eye contact or visible dust produced.

Skin Protection

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical I	Properties
Appearance	Light brown powder.
Odour	Odourless
Odour Threshold	Not available
рН	6.0 (5% solution)
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.8 - 0.9
Solubility	Insoluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Normally stable. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Generation of dust. **Incompatible Materials** None known. **Hazardous Decomposition Products** Carbon Monoxide and Carbon Dioxide may form on combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Cellulose Blend	> 5800 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Trade Secret	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available

Skin Corrosion/Irritation

Not a skin irritant.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract.

Ingestion

No effects anticipated.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No known significant effects.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

IARC	ACGIH®	NTP	OSHA
Not Listed	Not Listed	Not Listed	Not Listed
Not Listed	Not Listed	Not Listed	Not Listed
Not Listed	Not Listed	Not Listed	Not Listed
	Not Listed Not Listed	Not Listed Not Listed Not Listed Not Listed	Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed

This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer

(IARC) has listed as Group 1 - Carcinogenic to humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. ACGIH® = American Conference of Governmental Industrial Hygienists. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Cellulose Blend	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1 Flammability - 1 Instability - 0
SDS Prepared By	AES Drilling Fluids
Phone No.	281-556-5628
Date of Preparation	April 10, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: MULTI FIBER MEDIUM April 10, 2015



Page 06 of 06



OIL SORB

SECTION 1. IDENTIFICATION

Product Identifier Other Means of Identification	OIL SORB Absorbent Clay
Recommended Use	Absorbent.
Manufacturer /	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Supplier	Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	May 15, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) - Category 5; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

GHS Label Elements



~	
Signal Word:	
Danger	
Hazard Stateme	ent(s):
Dust in eye may	result in mechanical irritation.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H350	May cause cancer.
Precautionary S	Statement(s):
Prevention:	
P260	Do not breathe dust.
P264	Wash hands and skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	
P305 + P351 +	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do.	Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P401	Store
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Fuller's earth	8031-18-3	45-50	
BENTONITE	1302-78-9	45-50	
Silica, quartz	14808-60-7	<0.1	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms (e.g. coughing, shortness of breath, wheezing), call a Poison Centre or doctor.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation develops, seek medical attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Get medical advice/attention if you feel unwell or are concerned.

First-aid Comments

Inhalation of product may aggravate existing respiratory illness.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

Does not burn.

Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Store recovered product in suitable containers for disposal according to local regulations. Avoid generating dust.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not breathe in this product. Avoid skin and eye contact. Ensure adequate ventilation. Avoid generating dusts. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and

before going on breaks outside of the work area. Wear personal protective equipment to avoid direct contact with this chemical. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Fuller's earth	Not established	Not established	Not established	Not established	Not established	Not established	
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established		
BENTONITE	Not established	Not established	Not established	Not established	Not established	Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit. Short-term TWA = Time-Weighted Average with specified time limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions exist above the OEL if conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance		Tan - white.
Odour		Odourless
рН		~ 7
Melting Point/Freezing	Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Ran	nge	Not available
Flash Point		Not available
Evaporation Rate		Not available
Flammability (solid, gas	5)	Will not burn.
Upper/Lower Flammabi Explosive Limit	lity or	Not available (upper); Not available (lower)
Vapour Pressure		Not available
Vapour Density (air = 1))	Not available
Relative Density (water	= 1)	1.5
Solubility		Insoluble in water
Product Identifier:	OIL SORB	

Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

When mixed with highly oxidizable liquids, heat build up may occur. Allow time to cool before packaging or storing in sealable containers.

Incompatible Materials

Strong acids. Inorganic acids (e.g. hydrofluoric acid), unsaturated hydrocarbons (e.g. turpentine), vegetable oils. Unsaturated organic compounds.

Hazardous Decomposition Products

Carbon oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Fuller's earth	Not available	Not available	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available
BENTONITE	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May be harmful if inhaled.

Skin Absorption

No information was located.

Ingestion

Low ingestion hazard in normal use. If large amounts are swallowed may cause. irritation of the gastrointestinal tract.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Product Identifier:	OIL SORB
Date of Preparation:	May 15, 2015

This product may contain trace amounts of crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Fuller's earth	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
BENTONITE	Not Listed	Not designated	Not Listed	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

SECTION 12. ECOLOGICAL INFORMATION

No known significant effects or critical hazards.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available
BENTONITE	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Acute Hazards Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating	lealth - 1 Flammability - 0 Instability - 0	
SDS Prepared By	ES Drilling Fluids	
Phone No.	81-556-5628	
Date of Preparation	1ay 15, 2015	
Disclaimer	to not handle or use until precautions on MSDS are read and understood. The information is form is furnished solely for the purpose of enabling those who transport, handle or us roducts to ensure the safety and health of their employees and to comply with various la nd regulations (federal, state and local). We believe the statements, technical information recommendations contained herein are reliable but, they are given without warranty of uarantee of any kind, express or implied and we assume no responsibility for any loss, amage, direct or consequential, arising out of their use.	e our Iws on





PERMASEAL

SECTION 1. IDENTIFICATION

Product IdentifierPERMASEALOther Means of
IdentificationFiber BlendRecommended UseDrilling Fluid Additive.Manufacturer/Supplier
IdentifierAES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &
Information, 281-556-5628Emergency Phone No.AES Drilling Fluids, LLC, 1-888-556-4533Date of PreparationApril 21, 2016

SECTION 2. HAZARD IDENTIFICATION

Classification Combustible dust - Category 1; Carcinogenicity - Category 1A Label Elements



Signal Word: Danger

Hazard Statement(s): May form combustible dust concentrations in air. H350 May cause cancer.

Precautionary S Prevention:	Statement(s):
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P280	Wear protective gloves, protective clothing, eye protection.
Response:	
D000 . D040	IF sum as a discussion and the stand discussion and the stimular

P308 + P313	IF exposed or concerned: Get medical advice or attention.
Storage:	
P405	Store locked up.
Disposal:	
P501 regulations.	Dispose of contents and container in accordance with local, regional, national and international

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains no hazardous ingredients.

Chemical Name	CAS No.	%	Other Identifiers
Trade Secret	CBI*	30 - 60	
Trade Secret	CBI*	Proprietary	
Silica, quartz	14808-60-7	<1	
Proprietary Fiber Blend	CBI*	Proprietary	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if irritation develops.

Skin Contact

Rinse with lukewarm, gently flowing water for 5 minutes. If irritation develops, seek medical attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Specific Hazards Arising from the Product

Does not burn.

Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Containerize for solid waste disposal. Clean up residual contamination with water and place in appropriate containers for disposal. Dispose of according to local, state and federal regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in dust. Avoid skin and eye contact. Wash hands thoroughly after handling this material. Only use where there is adequate ventilation. See Section 8 for appropriate Personal Protective Equipment (PPE). Avoid creating excessive dust while handling the product. Dust may form an explosive mixture with air at high concentrations.

Conditions for Safe Storage

STORAGE: Keep in closed containers in cool, dry, well ventilated area. Separate from incompatible materials (see Section 10: Stability and Reactivity). Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	D TLV®	OSH	A PEL	AIHA®	WEEL®
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Trade Secret	2 mg/m3 (R)		3 mg/m3 (R)		Not established	
Silica, quartz	0.025 mg/m3 A2	Not established	0.1 mg/m3	Not established	Not established	Not established
Trade Secret	Not established		Not established		Not established	
Proprietary Fiber Blend	Not established	Not established	Not established	Not established	Not established	Not established

ACGIH = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. R = Respirable fraction. F = Respirable fibers. STEL = Short-term Exposure Limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL® = Workplace Environmental Exposure Limit. Short-term TWA = Time-Weighted Average with specified time limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties			
Appearance	Dark powder.		
Odor	Odorless		
рН	Not available		
Melting Point/Freezing Point	Not available (melting); Not available (freezing)		
Initial Boiling Point/Range	Not available		
Flash Point	Not available		
Evaporation Rate	Not available		
Flammability (solid, gas)	Not available		
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)		

Vapor Pressure	Not available
Vapor Density (air = 1)	Not available
Relative Density (water = 1)	0.4 - 0.8
Solubility	Not available in water
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Normally stable. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** None known. **Incompatible Materials** Strong Oxidizing Agents. **Hazardous Decomposition Products** Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Trade Secret	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available
Proprietary Fiber Blend	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Material is irritating to mucous membranes and upper respiratory tract.

Skin Absorption

No information was located.

Ingestion

No effects anticipated.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced

Product Identifier:	PERMASEAL
Date of Preparation:	April 21, 2016

pulmonary function.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Proprietary Fiber Blend	Not Listed	Not Listed	Not Listed	Not Listed

May cause cancer. This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. Group 2B = Possibly carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. A3 = Animal carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers.

Ecotoxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Trade Secret	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Proprietary Fiber Blend	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

Product does not contain any chemicals subject to the reporting requirement of CERCLA.

SARA Title III - Section 302: No listed components.

SARA Title III - Section 311/312: Chronic Health Hazard.

SARA Title III - Section 313: None.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 1 Instability - 0 HSE Department
Phone No.	403-269-2800
Date of Preparation	April 21, 2016
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.





SALT GEL

SECTION 1. IDENTIFICATION

Product Identifier	SALT GEL
Other Means of Identification	Drilling fluid additive
Recommended Use	Viscosifier.
Manufacturer/Supplier Identifier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	AES Drilling Fluids, LLC, 1-888-556-4533
Date of Preparation	October 23, 2015

SECTION 2. HAZARD IDENTIFICATION

Classified according to the US Hazard Communication Standard (HCS 2012).

Classification

Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1 Label Elements



×	
Signal Word:	
Danger	
Hazard Stateme	ent(s):
H350	May cause cancer.
H372	Causes damage to organs (lungs) through prolonged or repeated exposure if inhaled.
Precautionary S	Statement(s):
Prevention:	
P260	Do not breathe dust.
P264	Wash hands and skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	
P305 + P351 +	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do.	Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
Storage:	
P405	Store locked up.
Disposal:	
P501	Dispose of contents and container in accordance with local, regional, national and international
regulations.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Fuller's earth	8031-18-3	90 - 100	
Silica, quartz	14808-60-7	0 - 10	

Notes

Concentrations are expressed in % weight/weight.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms (e.g. coughing, shortness of breath, wheezing), call a Poison Centre or doctor.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation develops, seek medical attention.

Eye Contact

Rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Unsuitable Extinguishing Media

Do not use direct streams of large volumes of water as this may spread the fire.

Specific Hazards Arising from the Product

Does not burn.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Store recovered product in suitable containers for disposal according to local regulations. Avoid generating dust.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not breathe in this product. Avoid skin and eye contact. Ensure adequate ventilation. Avoid generating dusts. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Wear personal protective equipment to avoid direct contact with this chemical. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust. Separate from incompatible materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	H® TLV® OSHA		A PEL	AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Fuller's earth	Not established	Not established	Not established	Not established	Not established	Not established
Silica, quartz	0.025 mg/m3 A2	Not established	0.1 mg/m3	Not established	Not established	Not established

ACGIH® = American Conference of Governmental Industrial Hygienists. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL® = Workplace Environmental Exposure Limit. Short-term TWA = Time-Weighted Average with specified time limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. An eyewash and safety shower should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use goggles or face shield when there is risk of eye contact or visible dust produced. **Skin Protection**

Wear appropriate gloves while handling product. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

Wear a NIOSH approved air-purifying respirator with N100, R100, or P100 filter(s).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Yellow - grey powder.
Not available
Not available
7.0 - 10.5
Not available (melting); Not available (freezing)
Not available
Not available
Not available
Will not burn.
Not available (upper); Not available (lower)
Not available

Vapour Density (air = 1)	Not available
Relative Density (water = 1)	2.4
Solubility	Insoluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Normally stable. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Generation of dust. Incompatible materials. **Incompatible Materials** Inorganic acids (e.g. hydrofluoric acid). **Hazardous Decomposition Products** None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Fuller's earth	Not available	Not available	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available

Skin Corrosion/Irritation

Direct skin contact may cause slight or mild, transient irritation.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Skin Absorption

No information was located.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product may contain trace amounts of crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Fuller's earth	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

- No information was located.
- Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

SECTION 12. ECOLOGICAL INFORMATION

No known significant effects or critical hazards.

Ecotoxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground or into any body of water. Dispose of unused product in accordance with local environmental and public health regulations. Empty containers retain product residue. Follow label warnings even if container appears to be empty. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of or recycle empty containers through an approved waste management facility. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 0 Instability - 0 HSE Department
Phone No.	403-269-2800
Date of Preparation	October 23, 2015
Disclaimer	Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: SALT GEL October 23, 2015



Page 06 of 06



SAPP

SECTION 1. IDENTIFICATION

Product Identifier	SAPP
Other Means of Identification	Drilling fluid additive
Recommended Use	Drilling Fluid Additive.
Manufacturer/Supplier Identifier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	AES Drilling Fluids, LLC, 1-888-556-4533
Date of Preparation	October 27, 2015

SECTION 2. HAZARD IDENTIFICATION

Classification

Skin irritation - Category 2; Eye irritation - Category 2A; Specific target organ toxicity (single exposure) - Category 3 Label Elements



ent(s):
Causes skin and eye irritation.
May cause respiratory irritation.
Statement(s):
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, eye protection.
IF ON SKIN: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
Continue rinsing.
Call a POISON CENTRE or doctor if you feel unwell.
If skin irritation occurs: Get medical advice or attention.
If eye irritation persists: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents and container in accordance with local, regional, national and international

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
DISODIUM PYROPHOSPHATE	7758-16-9	100	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes. If skin irritation occurs, get medical advice or attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Immediately call a Poison Centre or doctor.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Corrosive phosphorous oxides.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

Methods and Materials for Containment and Cleaning Up

Dike spilled product to prevent runoff. Vacuum or sweep product up, try to minimize dust build-up. Clean up residual with absorbent material, place in appropriate containers and flush with water. Store recovered product or absorbent material in suitable containers for disposal according to local regulations. Dispose of according to local, state and federal regulations.

Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Keep containers tightly closed when not in use or empty. Do not breathe in this product. Do not get in eyes, on skin or on clothing. Only use where there is adequate ventilation. Avoid generating vapours or mists. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Wear personal protective equipment to avoid direct contact with this chemical. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: well-ventilated, cool, dry. Separate from incompatible materials away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH® TLV®		OSHA PEL		AIHA® WEEL®	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
DISODIUM PYROPHOSPHATE	3 mg/m3	Not established	5 mg/m3	Not established	Not established	Not established

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL® = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. A suitable eyewash station should be within acceptable distance to the work area. Provide safety shower in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles. Use chemical goggles or a face shield if product could be splashed.

Skin Protection

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

Wear a NIOSH approved particulate respiratory equipped with an N95, R95, or P95 filter.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

•	•
Appearance	White crystalline powder.
Odour	Odourless
Odour Threshold	Not available
рН	3.8 - 4.5
Melting Point/Freezing Point	1652 °C (3006 °F) (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Will not burn.

Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.61
Solubility	Soluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity
No reactivity test data was located.
Chemical Stability
Stable under normal conditions.
Possibility of Hazardous Reactions
Product will not undergo hazardous polymerization.
Conditions to Avoid
Generation of dust.
Incompatible Materials
Strong bases. Strong Oxidizing Agents.
Hazardous Decomposition Products

Oxides of phosphorus.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
DISODIUM PYROPHOSPHATE	Not available	2650 mg/kg (mouse)	> 300 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause serious eye irritation or corneal injury.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory tract.

Skin Absorption

No information was located.

Aspiration Hazard

No information was located.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
DISODIUM PYROPHOSPHATE	Not Listed	Not Listed	Not Listed	Not Listed

Not listed.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. A3 = Animal carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
DISODIUM PYROPHOSPHATE	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of unused product in accordance with local environmental and public health regulations. Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous.

SECTION 14. TRANSPORT INFORMATION

Product Identifier:SAPPDate of Preparation:October 27, 2015

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL or are not required to be listed Listed on the DSL.

CEPA - National Pollutant Release Inventory (NPRI)

Not Listed.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 313: No chemicals are reportable under Section 313. SARA Title III - Section 311/312: Immediate Health Hazard.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1	Flammability - 0	Instability - 0
SDS Prepared By	HSE Departr	nent	
Phone No.	403-269-280	0	
Date of Preparation	October 27, 2	2015	
Disclaimer	this form is fu products to e	urnished solely for the ensure the safety and h	ons on MSDS are read and understood. The information on purpose of enabling those who transport, handle or use our lealth of their employees and to comply with various laws

products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.



Page 06 of 06



SILVERSEAL

SECTION 1. IDENTIFICATION

Product Identifier	SILVERSEAL
Other Means of Identification	Blended Powder
Recommended Use	Drilling Fluid Additive.
Manufacturer/Supplier Identifier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	AES Drilling Fluids, LLC, 1-888-556-4533
Date of Preparation	April 21, 2016

SECTION 2. HAZARD IDENTIFICATION

Classification

Combustible dust - Category 1; Acute toxicity (Oral) - Category 4; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

Label Elements



Signal Word:	
Danger	
Hazard Stateme	ent(s):
May form comb	ustible dust concentrations in air.
H302	Harmful if swallowed.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary Statement(s):

Prevention:

1 1010110011	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response:

110000011001	
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P330	Rinse mouth.
P308 + P313	IF exposed or concerned: Get medical advice or attention.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Graphite (natural)	7782-42-5	<16	
Silica, quartz	14808-60-7	<1	
Trade Secret	CBI*	Confidential	
Trade Secret	CBI*	Confidential	
Trade Secret	CBI*	Confidential	
Trade Secret	CBI*	Confidential	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if irritation develops.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap. If irritation persists, get medical advice/attention.

Eye Contact

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Do not induce vomiting without medical advice. Seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Product

At very high dust concentrations, product may form combustible dust concentrations or explosive dust-air mixtures. Oxides of carbon.

Special Protective Equipment and Precautions for Fire-fighters

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment

Product Identifier:	SILVERSEAL
Date of Preparation:	April 21, 2016
recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Store recovered product in suitable containers that are: tightly-covered. Containerize for solid waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Only use where there is adequate ventilation. Avoid creating excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Store in an area that is: well-ventilated. Away from open flames, excessive heat or sources of ignition. Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	D TLV®	OSH	A PEL	AIHA®	WEEL®
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Silica, quartz	0.025 mg/m3 A2	Not established	0.1 mg/m3	Not established	Not established	Not established
Graphite (natural)	2 mg/m3 (R)		3 mg/m3 (R)		Not established	
Trade Secret	5 mg/m3 (R)		5 mg/m3 (R)		Not established	
Trade Secret	2 mg/m3 (R) A4	Not established	2 mg/m3 (R)		Not established	
Trade Secret	0.025 mg/m3 A2		0.1 mg/m3		Not established	
Trade Secret	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL® = Workplace Environmental Exposure Limit. R = Respirable fraction.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Use goggles or face shield when there is risk of eye contact or visible dust produced.

Skin Protection

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties
Grey powder.
Not available
Not available
Not applicable (melting); Not applicable (freezing)
Not available
Not applicable
Not applicable
Not available
Not applicable (upper); Not applicable (lower)
Not available
Not available
1.5 - 2.0
Insoluble in water
Not available
Not available
Not available
Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability** Stable under normal conditions. **Possibility of Hazardous Reactions** None expected under normal conditions of storage and use. **Conditions to Avoid** Generation of dust. **Incompatible Materials** Strong Oxidizing Agents. **Hazardous Decomposition Products** Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Silica, quartz	Not available	Not available	Not available
Graphite (natural)	Not available	Not available	Not available
Trade Secret	Not available	6450 mg/kg (rat)	Not available

Product Identifier: Date of Preparation:

Trade Secret	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available

Skin Corrosion/Irritation

May cause skin irritation.

Serious Eye Damage/Irritation

May cause eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the mucous membranes and upper respiratory tract.

Skin Absorption

Not harmful.

Ingestion

May be harmful if ingested. May cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product contains crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Chronic inhalation exposure to natural graphite is associated with the development of pneumoconiosis, a disease of the lungs.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Graphite (natural)	Not Listed	Not Listed	Not Listed	Not Listed
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Trade Secret	Group 3	A4	Not Listed	Not Listed
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. A4 = Not classifiable as a human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

SECTION 12. ECOLOGICAL INFORMATION

Product Identifier:	SILVERSEAL
Date of Preparation:	April 21, 2016

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers. **Ecotoxicity**

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available
Graphite (natural)	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA. SARA Title III - Section 302: No listed components. SARA Title III - Section 311/312: Immediate Health Hazard Chronic Health Hazard. SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By	Health - 1 Flammability - 1 HSE Department	Instability - 0
Phone No.	403-269-2800	
Date of Preparation	April 21, 2016	
Disclaimer	this form is furnished solely for the products to ensure the safety and I and regulations (federal, state and	ons on MSDS are read and understood. The information on purpose of enabling those who transport, handle or use our nealth of their employees and to comply with various laws local). We believe the statements, technical information erein are reliable but, they are given without warranty or
Product Identifier:	SILVERSEAL	
Date of Preparation:	April 21, 2016	Page 06 of 07

guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

Product Identifier: Date of Preparation: SILVERSEAL April 21, 2016



Page 07 of 07

SAFETY DATA SHEET



Soltex® Additive

Version 3.0

Revision Date 2015-11-25

SECTION 1: Identification	of the su	bstance/mixture and of the company/undertaking	
Product information			
Product Name Material	:	Soltex® Additive 1079530, 1016807	
Use	:	Drilling Mud Additive	
Company	:	Chevron Phillips Chemical Company LP Drilling Specialties Company LLC 10001 Six Pines Drive The Woodlands, TX 77380	
Emergency telephone	:		
Canada) Asia: +800 CHEMCA EUROPE: BIG +32.1	ernational 124.9300 ALL (+800 14.58454		
Responsible Departmer E-mail address Website		Product Safety and Toxicology Group SDS@CPChem.com www.CPChem.com	
SECTION 2: Hazards identi	fication		
Classification of the substance or mixture This product has been classified in accordance with the hazard communication standard 29 CFR 910.1200; the SDS and labels contain all the information as required by the standard.			
Emergency Overview			
Danger			
-	cal state		
	OSHA Hazards : Combustible dust, Carcinogen		
MSDS Number:1000000134	10	1/13	

SAFETY DATA SHEET

Version 3.0

Revision Date 2015-11-25

_

Classification	
	: Combustible dust Carcinogenicity, Category 1A
	Carcinogenicity, Category TA
Labeling	
Symbol(s)	
Signal Word	: Danger
Hazard Statements	: May form combustible dust concentrations in air. H350: May cause cancer.
Precautionary Statements	: Prevention: P261 Avoid breathing dust.
	P281 Use personal protective equipment as required.
Potential Health Effects	
Physical Hazards	: Mechanical processing may form combustible dust
	concentrations in air and thermal processing at elevated temperatures may generate simple hydrocarbons and carbon oxides.
Carcinogenicity:	
IARC	Group 1: Carcinogenic to humans
	Crystalline Silica 14808-60-7
NTP	Known to be human carcinogen
	Crystalline Silica 14808-60-7
ACGIH	Crystalline Silica 14808-60-7 Suspected human carcinogen
ACGIH	-
ACGIH	Suspected human carcinogen
ACGIH CTION 3: Composition/infor	Suspected human carcinogen Crystalline Silica 14808-60-7
	Suspected human carcinogen Crystalline Silica 14808-60-7
CTION 3: Composition/infor	Suspected human carcinogen Crystalline Silica 14808-60-7 rmation on ingredients
CTION 3: Composition/infor Synonyms Molecular formula	Suspected human carcinogen Crystalline Silica 14808-60-7 mation on ingredients : Drilling Mud Additive : Mixture
CTION 3: Composition/infor Synonyms Molecular formula	Suspected human carcinogen Crystalline Silica 14808-60-7 mation on ingredients : Drilling Mud Additive : Mixture CAS-No. Weight %
CTION 3: Composition/infor Synonyms Molecular formula	Suspected human carcinogen Crystalline Silica 14808-60-7 mation on ingredients : Drilling Mud Additive : Mixture CAS-No. Weight %
CTION 3: Composition/infor Synonyms Molecular formula Component Acid modified petroleum res Crystalline Silica	Suspected human carcinogen Crystalline Silica 14808-60-7 rmation on ingredients : Drilling Mud Additive : Mixture Mixture Siduum Proprietary 14808-60-7 0.1 - 1
CTION 3: Composition/infor Synonyms Molecular formula Component Acid modified petroleum res	Suspected human carcinogen Crystalline Silica 14808-60-7 rmation on ingredients : Drilling Mud Additive : Mixture Mixture Siduum Proprietary 14808-60-7 0.1 - 1
CTION 3: Composition/infor Synonyms Molecular formula Component Acid modified petroleum res Crystalline Silica	Suspected human carcinogen Crystalline Silica 14808-60-7 mation on ingredients : Drilling Mud Additive : Mixture <u>CAS-No. Weight %</u> siduum Proprietary 60 - 70 14808-60-7 0.1 - 1 s
CTION 3: Composition/infor Synonyms Molecular formula Component Acid modified petroleum res Crystalline Silica	Suspected human carcinogen Crystalline Silica 14808-60-7 rmation on ingredients : Drilling Mud Additive : Mixture Mixture Siduum Proprietary 14808-60-7 0.1 - 1

sion 3.0	Revision Date 2015-
	sheet to the doctor in attendance.
lf inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
TION 5: Firefighting measu	es
Flash point	: Not applicable
Autoignition temperature	: Not applicable
Unsuitable extinguishing media	: High volume water jet.
Specific hazards during fire fighting	: Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. or floors and ledges.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire and explosion protection	: Avoid dust formation. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Provide appropriate exhaust ventilation at places where dust is formed.
Hazardous decomposition products	: Carbon oxides. Sulfur oxides.
TION 6: Accidental release	measures
5 1 <i>3</i>	
Personal precautions	: Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Pick up and arrange disposal without creating dust. Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.

		SAFETY DATA SHEET
Soltex® Additive		
Version 3.0		Revision Date 2015-11-2
Additional advice	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
SECTION 7: Handling and stor	age	
Handling		
Advice on safe handling	:	Avoid formation of respirable particles. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient.
Advice on protection against fire and explosion	:	Avoid dust formation. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Provide appropriate exhaust ventilation at places where dust is formed.
Storage		
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
SECTION 8: Exposure controls	s/per	sonal protection
Ingredients with workplac	e co	ntrol parameters

Ingredients		Basis	Value	Control parameters	Note
Crystalline Si	lica	ACGIH	TWA	0.025 mg/m3	A2, Respirable fraction
		OSHA Z-3	TWA	30mg/m3 / %SiO2+2	total dust
		OSHA Z-3	TWA	250mppcf / %SiO2+5	a, b, respirable
		OSHA Z-3	TWA	10mg/m3 / %SiO2+2	e, respirable
		OSHA Z-1-A	TWA	0.1 mg/m3	Respirable fraction
		OSHA Z-3	TWA	0.1 mg/m3	Respirable fraction
		OSHA Z-1-A	TWA	0.1 mg/m3	respirable dust fraction
		ACGIH	TWA	0.025 mg/m3	A2, Respirable fraction
-	 a Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. A2 Suspected human carcinogen b The percentage of crystalline silica in the formula is the amount determined from airborne samples, except in those instances in which other methods have been shown to be applicable. e Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics: Aerodynamic diameter (unit density sphere): 2; Percent passing selector: 90 Aerodynamic diameter (unit density sphere): 2; Percent passing selector: 50 Aerodynamic diameter (unit density sphere): 5, C; Percent passing selector: 50 Aerodynamic diameter (unit density sphere): 5, C; Percent passing selector: 10; Percent passing selector: 0 The measurements under this note refer to the use of an AEC (now NRC) instrument. The respirable fraction of coal dust is determined with an MRE; the figure corresponding to that of 2.4 mg/m3 in the table for coal dust is 4.5 mg/m3. 				
	The respirable fraction of				
lazardous cor	The respirable fraction of	coal dust is determine	d with an MRE; the fig		

SAFETY DATA SHEET

Soltex® Additive

Version 3.0

Revision Date 2015-11-25

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Crystalline Silica	14808-60-7	Immediately Dangerous to Life or Health Concentration Value 50 mg/m ³	1995-03-01
		Immediately Dangerous to Life or Health Concentration Value 50 mg/m ³	1995-03-01

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	:	Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Dusts and Mists / P100. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	:	Eye wash bottle with pure water. Safety glasses.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Protective suit. Safety shoes.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
SECTION 9: Physical and cher	nica	l properties
Information on basic phys	sical	and chemical properties

Appearance

Form

: Powder

MSDS Number:100000013416

5/13

SAFETY DATA SHEET

Version 3.0		Revision Date 2015-11-25
Physical state Color Odor Odor Threshold	: Solid : Black : No odor : Not applicable	
Safety data		
Flash point	: Not applicable	
Lower explosion limit	: No data available	
Upper explosion limit	: No data available	
Oxidizing properties	: No	
Autoignition temperature	: Not applicable	
Molecular formula	: Mixture	
Molecular weight	: No data available	
рН	: 7 - 10	
Pour point	: Not applicable	
Boiling point/boiling range	: Not applicable	
Vapor pressure	: Not applicable	
Relative density	: Not applicable	
Density	: 1.54 g/cm3	
Water solubility	: Partly soluble	
Partition coefficient: n-	: No data available	
octanol/water Viscosity, kinematic	: Not applicable	
Relative vapor density	: Not applicable	
Evaporation rate	: Not applicable	
SECTION 10: Stability and reactiv	ity	
Chemical stability	: This material is considered stable under anticipated storage and handling condi and pressure.	

Possibility of hazardous reactions

Conditions to avoid : Generation of Dusts.

MSDS Number:100000013416

6/13

oltex® Additive	
ersion 3.0	Revision Date 2015-11
Hazardous decomposition products	: Carbon oxides Sulfur oxides
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological info	rmation
Acute oral toxicity	
Acid modified petroleum residuum	: LD50: > 5,000 mg/kg
Acute inhalation toxicity	
residuum	Exposure time: 4 h Species: Rat Sex: male and female Test atmosphere: dust/mist Method: OECD Test Guideline 403 Rats exposed to a 5.3 mg/L dust aerosol for 4-hr resulted in effects generally expected with high concentrations of dust aerosols made of relatively dense particles. Higher lung weight and atelectasis persisted after the 14-day recovery period. There were no reports of lethality or any significant clinical observations. There was however an acute inflammatory response with evidence of recovery after 14- days. The presence of particulate matter with indication of partial clearance from the lung after the 14-day recovery period was noted. These effects would not be expected during normal operating conditions when using this substance.
Acute dermal toxicity Acid modified petroleum residuum	: No data available
Skin irritation	
Acid modified petroleum residuum	: No skin irritation
Eye irritation Acid modified petroleum residuum	: No eye irritation
Sensitization	
Acid modified petroleum residuum	: Did not cause sensitization on laboratory animals.
Repeated dose toxicity	
Acid modified petroleum residuum	: Species: Rat, Male and female Sex: Male and female Application Route: Oral
SDS Number:100000013416	7/13

oltex® Additive	SAFETY DATA SHE
ersion 3.0	Revision Date 2015-11-
	Dose: 0, 250, 500, 1000 mg/kg Exposure time: 43 - 54 D Number of exposures: daily NOEL: 1,000 mg/kg Method: OECD Guideline 422
Reproductive toxicity	
Acid modified petroleum residuum	: Species: Rat Sex: male and female Application Route: oral gavage Dose: 0, 250, 500, 1000 mg/kg Exposure time: 43-54 D Number of exposures: daily Method: OECD Guideline 422 NOAEL Parent: 1,000 mg/kg NOAEL F1: 1,000 mg/kg
Developmental Toxicity	
Acid modified petroleum residuum	: Species: Rat Application Route: oral gavage Dose: 0, 250, 500, 1000 mg/kg Number of exposures: daily Test period: 54 D NOAEL Teratogenicity: 1,000 mg/kg NOAEL Maternal: 1,000 mg/kg
CMR effects	
Acid modified petroleum residuum	 Carcinogenicity: Not available Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: Animal testing did not show any effects on fertility.
Crystalline Silica	Carcinogenicity: Human carcinogen.
Soltex® Additive Further information	: Chronic Health Hazard.
ECTION 12: Ecological inform	ation
Toxicity to fish	
Acid modified petroleum residuum	 LC50: > 240 mg/l Exposure time: 96 h Species: Scophthalmus maximus (Flatfish, Flounder) semi-static test Method: OECD Test Guideline 203
Toxicity to daphnia and oth	ner aquatic invertebrates
Acid modified petroleum	: LC50: 380 mg/l
SDS Number:100000013416	8/13

oltex® Additive	
rsion 3.0	Revision Date 2015-11-
residuum	Exposure time: 48 h Species: Acartia tonsa (Marine Copepod) static test Method: ISO TC147/SC5/WG2
Toxicity to algae	
Acid modified petroleum residuum	: EC50: 240 mg/l Exposure time: 72 h Species: Skeletonema costatum (Marine Algae) static test Method: ISO 10253
Elimination information (persi	istence and degradability)
Biodegradability	: This material is not expected to be readily biodegradable.
Ecotoxicology Assessment	t
Results of PBT assessment Acid modified petroleum residuum	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: This material is not expected to be harmful to aquatic organisms.
CTION 13: Disposal consider	rations
The information in this SDS p	pertains only to the product as shipped.
Use material for its intended may meet the criteria of a has other State and local regulate regulated components may b	pertains only to the product as shipped. purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste
Use material for its intended may meet the criteria of a har other State and local regulation regulated components may be classified as a hazardous wa	purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is
Use material for its intended may meet the criteria of a has other State and local regulate regulated components may b classified as a hazardous wa disposal facility.	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Use material for its intended may meet the criteria of a har other State and local regulation regulated components may b classified as a hazardous war disposal facility. Product	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
Use material for its intended may meet the criteria of a har other State and local regulation regulated components may be classified as a hazardous wat disposal facility. Product Contaminated packaging CTION 14: Transport information The shipping descriptions	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
Use material for its intended may meet the criteria of a har other State and local regulation regulated components may be classified as a hazardous wan disposal facility. Product Contaminated packaging CTION 14: Transport informa The shipping descriptions as shipments in non-bulk pack	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
Use material for its intended may meet the criteria of a har other State and local regulation regulated components may be classified as a hazardous wan disposal facility. Product Contaminated packaging CTION 14: Transport informat The shipping descriptions as shipments in non-bulk pack Consult the appropriate dome Goods Regulations for addition etc.) Therefore, the information	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. ttion shown here are for bulk shipments only, and may not apply to kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or name ion shown here, may not always agree with the bill of lading shipping
Use material for its intended may meet the criteria of a har other State and local regulative regulated components may be classified as a hazardous way disposal facility. Product Contaminated packaging CTION 14: Transport information The shipping descriptions as shipments in non-bulk pack Consult the appropriate dome Goods Regulations for addition etc.) Therefore, the information description for the material. If bill of lading.	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. tion tion shown here are for bulk shipments only, and may not apply to kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or name ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the state of the
Use material for its intended may meet the criteria of a har other State and local regulative regulated components may be classified as a hazardous way disposal facility. Product Contaminated packaging CTION 14: Transport information The shipping descriptions of shipments in non-bulk pact Consult the appropriate dome Goods Regulations for addition etc.) Therefore, the information description for the material. If bill of lading.	 purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. tion shown here are for bulk shipments only, and may not apply to kages (see regulatory definition).

SAFETY DATA SHEET

Version 3.0

Revision Date 2015-11-25

TRANSPORTATION BY THIS AGENCY.

	NAL MARITIME DANGEROUS GOODS) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	R TRANSPORT ASSOCIATION) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	NGEROUS GOODS BY ROAD (EUROPE)) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	CERNING THE INTERNATIONAL TRANSPORT OF
DANGEROUS GOODS (EU NOT REGULATED AS A TRANSPORTATION BY	HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
	MENT CONCERNING THE INTERNATIONAL CARRIAGE
	BY INLAND WATERWAYS) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
Transport in bulk according to	Annex II of MARPOL 73/78 and the IBC Code
SECTION 15: Regulatory inform	nation
SECTION 15: Regulatory inform National legislation	nation
	nation : Chronic Health Hazard Fire Hazard
National legislation	: Chronic Health Hazard
National legislation SARA 311/312 Hazards CERCLA Reportable	 Chronic Health Hazard Fire Hazard This material does not contain any components with a CERCLA
National legislation SARA 311/312 Hazards CERCLA Reportable Quantity SARA 302 Reportable	 Chronic Health Hazard Fire Hazard This material does not contain any components with a CERCLA RQ. This material does not contain any components with a SARA
National legislation SARA 311/312 Hazards CERCLA Reportable Quantity SARA 302 Reportable Quantity SARA 302 Threshold	 Chronic Health Hazard Fire Hazard This material does not contain any components with a CERCLA RQ. This material does not contain any components with a SARA 302 RQ. No chemicals in this material are subject to the reporting

tex® Additive	
sion 3.0	Revision Date 2015-11
SARA 313 Ingredients	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	
Potential Class II	duct neither contains, nor was manufactured with a Class I or ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR pt. A, App.A + B).
This product does not contain a Act Section 12 (40 CFR 61).	any hazardous air pollutants (HAP), as defined by the U.S. Clean A
This product does not contain a Accidental Release Prevention	any chemicals listed under the U.S. Clean Air Act Section 112(r) for a (40 CFR 68.130, Subpart F).
This product does not contain a Intermediate or Final VOC's (4	any chemicals listed under the U.S. Clean Air Act Section 111 SOC 0 CFR 60.489).
US State Regulations	
Pennsylvania Right To Know	: Crystalline Silica - 14808-60-7
Pennsylvania Right To Know New Jersey Right To Know	: Crystalline Silica - 14808-60-7 : Crystalline Silica - 14808-60-7
Pennsylvania Right To Know New Jersey Right To Know	
Pennsylvania Right To Know New Jersey Right To Know California Prop. 65	 Crystalline Silica - 14808-60-7 WARNING! This product contains a chemical known in the State of California to cause cancer. On the inventory, or in compliance with the inventory

Version 3.0

SAFETY DATA SHEET

Revision Date 2015-11-25

Occupational Safety & Health

Permissible Exposure Limit

Short-term Exposure Limit

Presumed Not Toxic

No Observed Effect Concentration

Philippines Inventory of Commercial Chemical Substances

Resource Conservation Recovery

Level

Act

Administration

SECTION 16: Other information

NFPA Class	Fire Haz		
		, Hazara. U	
Further info	ormation		
Legacy SDS	Number : 59370		
information a guidance for not to be con specific mat	and belief at the date of its pur safe handling, use, processi nsidered a warranty or quality	blication. The inform ng, storage, transpo specification. The in be valid for such ma	to the best of our knowledge, nation given is designed only as a rtation, disposal and release and is nformation relates only to the aterial used in combination with any
	Key or legend to abbreviation		ed in the safety data sheet
ACGIH	American Conference of Government Industrial Hygi	LD50 enists	Lethal Dose 50%
AICS	Australia, Inventory of Cher Substances	nical LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substan List	ces NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect

NOEC

OSHA

PICCS

PRNT

RCRA

STEL

PEL

	IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
				Reauthorization Act.
	IARC	International Agency for Research	TLV	Threshold Limit Value
		on Cancer		
	IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average
MSDS	S Number:1000	00013416	12/13	
			,	

Scenario Tool

Values

Effective Concentration 50%

EOSCA Generic Exposure

European Oilfield Specialty

European Inventory of Existing

Globally Harmonized System

Greater Than or Equal To

Germany Maximum Concentration

Chemicals Association

Chemical Substances

EC50

EGEST

EOSCA

EINECS

MAK

GHS

>=

SAFETY DATA SHEET

Version 3.0

Revision Date 2015-11-25

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

MSDS Number:100000013416



Version 4 Revision Date 1/27/16

1. Product and Company Identification

Name of Product:

Super-Sweep Recommended use: Hole Cleaning Agent

Producer:

Forta Corporation 100 Forta Drive Grove City, PA 16127 1-800-245-0306

Emergency Number:

1-800-245-0306

724-458-5221

2. Hazard(s) Identification:

Hazard Classification:

Not Classified

Label Elements:

Hazard Symbol:	No Symbol
Signal Word:	No Signal Word
Hazard Statement:	NONE
Precautionary	NONE
Statement:	

HMIS (United States)			
Health	1		
Flammability	0		
Reactivity	0		
PPE			

3. Composition/Information on Ingredients



Version 4 Revision Date 1/27/16

Name	CAS#	% by Weight
Polypropylene	9003-07-0	> 60.0

4. First Aid Measures

Inhalation:

Leave area to breathe fresh air.

Skin Contact:

No known applicable information.

Eye Contact:

Flush with water for 15 minutes. If irritation persists, get medical attention.

Ingestion:

Not applicable under normal conditions of use.

5. Fire Fighting Measures

Flash Point: 600°F, 316°C Flash Point Method: NONE Autoignition Temperature: NONE Burning Rate: NONE Fire and Explosion Hazard: None Firefighting Equipment: Use dry chemicals, CO², foam. Hazardous Products of Combustion:

Carbon monoxide and other organics when burning.

6. Accidental Release Measures

Small Spill or Leak: NONE Large Spill or Leak: NONE



Version 4 Revision Date 1/27/16

7. Handling and Storage

Handling Precautions: NONE Storage Requirements: No specific storage is required, use any dry container.

8. Exposure Controls/Personal Protection

Engineering Measures:

Not required under normal conditions of use.

Protective Equipment

Respirators-Wear NIOSH/MSHA approved dust respirator when the fiber concentration exceeds the exposure limits indicated on the MSDS. Wear a type C full face supplied air respirator when the fiber concentration exceeds 50 fibers/cc.

Protective Gloves- Impervious gloves.

Eye Protection- Glasses or Goggles

Protective Clothing-NONE

Exposure Guidelines/Other

Chemical	CAS Number	Regulation	Limit	Form
Name				
Polyproptlyene	9003-07-0	ACGIH TWA	3mg/m ³	Respirable particles
		ACGIH TWA	10mg/m ³	Inhalable particles
		OSHA PEL	15mg/m ³	Total dust
		OSHA PEL	5mg/m ³	Respirable fraction
		OSHA TWA	15mg/m ³	Total dust
		OSHA TWA	5mg/m ³	Respirable fraction

9. Physical and Chemical Properties

Appearance: White Fiber Physical State: Solid Boiling Point:

Version 4 Revision Date 1/27/16

NONE Odor: Odorless Freezing/Melting Point: NONE pH: NONE Solubility: NONE Specific Gravity: 1.3

10. Stability and Reactivity

Stability: This product is stable Conditions to avoid: None Materials to avoid (Incompatibility): Strong acids. Oxidizing agents.

11. Toxicological Information

Toxicity to Animals:

This product has not been tested for animal effects. This product is not expected to be toxic to animals.

Toxicity to Humans:

This product has not been tested for human effects. This product is not expected to be toxic to humans.

12. Ecological Information

Ecotoxicity: Not expected to be ecotoxic. BOD5 and COD: NONE Biodegradable / OECD:





Version 4 Revision Date 1/27/16

NONE Mobility: NONE Toxicity of the Products of Biodegradation: NONE Special Remarks on the Products of Biodegradation: NONE

13. Disposal Considerations

Not classified as hazardous waste. Dispose of in accordance with Federal, State and local regulations.

14. Transport Information

	Restrictions:
	NONE
	DOT Requirements:
	Not a DOT controlled material. (USA)
	ADR Requirements:
	Not an ADR controlled material. (Europe)
	IMDG Requirements:
	Not an IMDG controlled material.
	IATA requirements:
	Not an IATA controlled material.
	Marine Pollutant:
	Not a marine pollutant.
_	

15. Regulatory Information

U.S. Federal Regulations

Chemical (SARA 302	SARA 304	SARA 313	CERCLA Rq	CAA 112(r	RCRA
& CAS	(EHS) Rq	(EHS) Rq	de minimis)	Code
Number)					TQ	
NONE						

All quantities in pounds

State Regulations



Version 4 Revision Date 1/27/16

Chemical (& CAS	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK RI RTK	
Number)						
9003-07-0				х		
9003-07-0					х	

International Regulations Water Hazard Class (WGK) NWG DSL (Canada): None EINECS: None WHMIS: Not classified as hazardous. HTS/Schedule B 5503.40.0000 16. Other Information Prepared by: Forta Corporation. **Telephone:** 1-800-245-0306 Website:

www. Super-Sweep.com



Version 4 Revision Date 1/27/16

The information and recommendations contained in this Material Safety Data sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.



SAFETY DATA SHEET

WCI 1013 Water Soluble Corrosion Inhibitor

Section 1. Identification

GHS product identifier	;	WCI 1013 Water Soluble Corrosion Inhibitor
Other means of identification	:	Water Soluble Corrosion Inhibitor
Product use	:	Not available.
Product type	:	Liquid.
Manufacturer	:	Jacam Manufacturing 2013, L.L.C. P.O.Box 208, 1656 Ave. Q. Sterling, Kansas 67579
Validation date	:	5/28/2015.
For Chemical Emergency Spill, Leak Fire, Exposure or Accident:	:	Call CHEMTREC Day or Night Within USA and Canada 800-424-9300 CCN# 11754 Or +1 703-527-3887 (Collect calls accepted)
		Direct all other calls to: Jacam Chemicals 2013, L.L.C. 620-278-3355 Mon – Fri 8 a.m. to 5 p.m. (Closed on major holidays)
Supplier's details	:	Jacam Chemicals 2013, L.L.C. P.O. Box 96, 205 S. Broadway Sterling, Kansas 67579

Section 2. Hazards identification

Classification of the substance or mixture	: AMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 48.4%

2/17

Section 2. Hazards identification

GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 F227 - Combustible liquid. H302 - Harmful if swallowed. H319 - Causes serious eye irritation. H315 - Causes skin irritation.
Precautionary statements	
Prevention	 280 - Wear protective gloves: > 8 hours (breakthrough time): nitrile rubber. Wear eye or face protection: Recommended: face shield , splash goggles , Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts P210 - Keep away from flames and hot surfaces No smoking. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling.
Response	 P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. P302 + P352 + P362-2 + P363 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
Storage	 P403 - Store in a well-ventilated place. P235 - Keep cool. Store in accordance with all local, regional, national and international regulations.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.
Routes of entry	: Dermal contact. Eye contact. Inhalation.
	INGESTION: Although not a normal route of entry, ingestion is expected to be harmful. DO NOT TAKE INTERNALLY. FOR INDUSTRIAL USE ONLY.
Target organs	: Contains material which may cause damage to the following organs: kidneys, liver, heart, gastrointestinal tract, upper respiratory tract, immune system, skin, central nervous system (CNS), eye, lens or cornea.

Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Other means of identification	:	Water Soluble Corrosion Inhibitor

CAS number/other identifiers

CAS number	: Not app	licable.	
Date of issue/Date of revision	5/28/2015.	People + Products < Performance"	Version : 1.01

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Ethylene Glycol	30 - 60	107-21-1
Methanol	10 - 30	67-56-1
Alkyl Pyridine Derivs.	5 - 10	68391-11-7
Alkyltrimethylene Diamine Acetate	5 - 10	61791-63-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures			
Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If irritation persists, obtain medical attention.	
Inhalation	-	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	-	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 15 minutes. If irritation persists, obtain medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If irritation persists, obtain medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	

Most important symptoms/effects, acute and delayed				
Potential acute health	<u>effects</u>			
Eye contact	: Causes serious eye irritation.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: Causes skin irritation.			
Ingestion	: Harmful if swallowed. Irritating to mouth, throat and stomach.			
Over-exposure signs/s	symptoms			

Section 4. First aid measures

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: rritation redness	
Ingestion	No specific data.	
Indication of immediate me	attention and special treatment needed, if necessary	
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	Э
Specific treatments	No specific treatment.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. may be dangerous to the person providing aid to give mouth-to-mouth resuscit	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Additional Vapor Statement	: Not available.
	Not available.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide
	carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-
	combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent
	material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non- sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage,	Store in accordance with local regulations. Store in a segregated and approved
including any	area. Store in original container protected from direct sunlight in a dry, cool and
incompatibilities	well-ventilated area, away from incompatible materials (see Section 10) and food
	and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep
	container tightly closed and sealed until ready for use. Containers that have been
	opened must be carefully resealed and kept upright to prevent leakage. Do not
	store in unlabeled containers. Use appropriate containment to avoid environmental
	contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Ethylene Glycol	ACGIH TLV (United States, 4/2014).
	C: 100 mg/m ³ Form: Aerosol
	OSHA PEL 1989 (United States, 3/1989).
	CEIL: 50 ppm
	CEIL: 125 mg/m ³
Methanol	ACGIH TLV (United States, 4/2014).
	Absorbed through skin.
	TWA: 200 ppm 8 hours.
	TWA: 262 mg/m ³ 8 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 328 mg/m ³ 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	Absorbed through skin.
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m ³ 8 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 325 mg/m ³ 15 minutes.
	NIOSH REL (United States, 10/2013).
	Absorbed through skin.
	TWA: 200 ppm 10 hours.
	TWA: 260 mg/m ³ 10 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 325 mg/m ³ 15 minutes.
	OSHA PEL (United States, 2/2013).
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m ³ 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: face shield , splash goggles , Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Personal protective equipment (Pictograms)	

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid. [Clear.]
Color	: Amber. Brown. [Dark]
Odor	: Unpleasant.
Odor threshold	: Not available.
рН	: 4 to 5
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: 💋osed cup: 63.889°C (147°F) [Pensky-Martens.]
Evaporation rate	: Not available.

Section 9. Physical and chemical properties

1		
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	1	Not available.
Vapor pressure	1	Not available.
Vapor density	1	Not available.
Relative density	1	1.02 to 1.06
Density	:	8.51 to 8.85 (lbs/gal)
Solubility	;	Easily soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Viscosity	:	Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects							
Acute toxicity							
Product/ingredient name	Result	Species	Dose	Exposure			
Pyridine, alkyl derivs.	LD50 Oral	Rat	2.5 g/kg	-			
Ethylene Glycol	LD50 Oral	Rat	4700 mg/kg	-			
Methanol	LD50 Dermal	Rabbit	15800 mg/kg	-			

Section 11. Toxicological information

Irritation/Corrosion					
Product/ingredient name	Result		Species	Score	Exposure Observation
Ethylene Glycol	Eyes - Mild	irritant	Rabbit	-	24 hours 500 - milligrams
	Eyes - Mild	irritant	Rabbit	-	1 hours 100 -
	Eyes - Mode	erate irritant	Rabbit	_	milligrams 6 hours 1440 -
	Skin - Mild i		Rabbit		milligrams 555 -
				-	milligrams
Methanol	Eyes - Mode	erate irritant	Rabbit	-	24 hours 100 - milligrams
	Eyes - Mode Skin - Mode		Rabbit Rabbit	-	40 milligrams - 24 hours 20 -
	SKIII - MOUE		Raddil	-	milligrams
Sensitization					
Product/ingredient name	Route of exposure	Specie	?S	Resul	t
Not available.					
Mutagenicity					
Product/ingredient name	Test		Experiment		Result
Not available.					
Carcinogenicity					
Product/ingredient name	Result		Species	Dose	Exposure
Not available.					
Product/ingredient name					
Not available.					
Reproductive toxicity					
Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose Exposure
Not available.					
Teratogenicity					
Product/ingredient name	Result		Species	Dos	se Exposure
Not available.					
Specific target organ toxici	ty (single exp	osure)			
Name			Category	Route expos	• •
Not available.				expos	
Specific target organ toxici	ty (repeated e	exposure)			
Not available.					

Section 11. Toxicological information

Aspiration hazard Name

Result

Not available.

ToxKinetics - routes of exposure	Ī	
Potential acute health effects	<u>;</u>	
Eye contact	1	Causes serious eye irritation.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes skin irritation.
Ingestion	:	Harmful if swallowed. Irritating to mouth, throat and stomach.
Symptoms related to the phy	<u>sic</u>	cal, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	1	No specific data.

Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.

Information on the likely : Routes of entry anticipated: Dermal, Inhalation.

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate : Not available. effects Potential delayed effects : Not available.

Long term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	1	Not available.			
Potential chronic health effects					

Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Date of issue/Date of revision 5/28/2015.	People + Products 辛
---	---------------------

Performance"

Section 11. Toxicological information

Acute toxicity estimates

Route

Øral

ATE value

651.2 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Alkyltrimethylene Diamine	Acute LC50 1300 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Ethylene Glycol	Acute LC50 100000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 10000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
Conclusion/Summary	Not available.		

Persistence and degradability

Not available.

Product/ingredient name

Not available.

Product/ingredient name

Not available.

Bioaccumulative potential			
Product/ingredient name	LogPow	BCF	Potential
Ethylene Glycol Methanol	-1.36 -0.77	- <10	low low

<u>Mobility in soil</u>

Soil/water partition : Not available. coefficient (K_{oc})
Section 12. Ecological information

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
United States - RCRA Toxic	hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Methanol (I); Methyl alcohol (I)	67-56-1	Listed	U154

Section 14. Transport information

Regulatory information	UN/NA Number	Proper shipping name	Hazard PG* Class(es)
DOT Classificatio	on		PG* : Packing group
	NA1993	Combustible liquid, n.o.s. (Methanol) RQ (Ethylene Glycol, Methanol)	fombustible III liquid.

Additional information

Emergency Response Guide (ERG): 128

Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity.

Reportable quantity

13257.7 lbs / 6019 kg [1528.9 gal / 5787.5 L]

Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Label

Section 14. Transport information **VN3082** Environmentally Hazardous Substance, Liquid, N.O.S. (Ethylene 9 Ш Glycol) Additional information Remarks For Bulk Shipment ONLY. Not Regulated in less than (<119 gallons) bulk quantity. Label **IMDG Class VN3082** 9 **E**nvironmentally Hazardous Substance, Liquid, N.O.S. (Ethylene III Glycol) Marine pollutant notes: . Not available. **Additional information Remarks** For Bulk Shipment ONLY. Not Regulated in less than (<119 gallons) bulk quantity. Label **IATA-DGR Class VN3082** 9 **E**nvironmentally Hazardous Substance, Liquid, N.O.S. (Ethylene Ш Glycol)

Additional information

The environmentally hazardous substance mark may appear if required by other transportation regulations.

<u>Remarks</u>

Label

For Bulk Shipment ONLY. Not Regulated in less than (<119 gallons) bulk quantity.



Section 15. Regulatory information

1	-		-						
	U.S. Federal regulations	:	TSCA 8(a) PAI TSCA 8(a) CDI All components Clean Water A	R Exempt/P are listed c	artial ex r exemp	cemption : N ted.	ot determ	ined	
	Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Listed						
	Clean Air Act Section 602 Class I Substances	1	Not listed						
	Clean Air Act Section 602 Class II Substances	1	Not listed						
	DEA List I Chemicals (Precursor Chemicals)	1	Not listed						
	DEA List II Chemicals (Essential Chemicals)	1	Not listed						
	SARA 302/304								
1	Composition/information on	ing	<u>redients</u>						
	No products were found.								
5	SARA 304 RQ :	No	t applicable.						
_	SARA 311/312								
	Classification :		re hazard						
			mediate (acute)	health haza	ard				
I	Composition/information on	ing	redients	1		1		r	1
	Name			%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard

Ethylene Glycol	
Methanol	

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Ethylene Glycol	107-21-1	30 - 60
	Methanol	67-56-1	10 - 30
Supplier notification	Ethylene Glycol	107-21-1	30 - 60
	Methanol	67-56-1	10 - 30

30 - 60

10 - 30

No.

Yes.

No.

No.

No.

No.

Yes.

Yes.

No.

Yes.

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: ETHYLENE GLYCOL; METHANOL
New York	: The following components are listed: Ethylene glycol; Methanol
New Jersey	: The following components are listed: ETHYLENE GLYCOL; 1,2-ETHANEDIOL; METHYL ALCOHOL; METHANOL

Section 15. Regulatory information

2

Pennsylvania

The following components are listed: 1,2-ETHANEDIOL; METHANOL

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Methanol	No.	Yes.	No.	23000 μg/day (ingestion) 47000 μg/day (inhalation)

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed. Montreal Protocol (Annexes A, B, C, E) Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. **Rotterdam Convention on Prior Inform Consent (PIC)** Not listed. **UNECE Aarhus Protocol on POPs and Heavy Metals** Not listed. Canada WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). Class D-1B: Material causing immediate and serious toxic effects (Toxic). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic). **Canadian lists** : The following components are listed: Ethylene glycol; Methanol; Oxyalkylated **Canadian NPRI** Resins (Pollution Release) **CEPA Toxic substances** The following components are listed: Oxyalkylated Resins Canada inventory-DSL / NDSL All components are listed or exempted. **International lists National inventory** Australia : All components are listed or exempted. Canada : All components are listed or exempted. China : All components are listed or exempted. Europe : All components are listed or exempted. Japan : Not determined.

Malaysia Not determined. 5

New Zealand 2.1 All components are listed or exempted. **Philippines** 2 Not determined.

Republic of Korea 2 All components are listed or exempted. Taiwan 2 All components are listed or exempted.

Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>Normal Package Size(s):</u>	Dry Product: 50 Liquid: 5 Gallor	n/55 Gallon/Bulk /Cooler; 24 Lbs/Pail
<u>History</u>		
Date of issue/Date of re	vision	5/28/2015.
Versio	<u>n</u> :	: 1.01
Date of previous issue	:	5/28/2015.
Previous Validation Dat	e :	5/28/2015.
Prepared by	:	Jacam Regulatory Department
(M)SDS Requests:	:	SDS@jacam.com
Key to abbreviations	BCF = Bi GHS = G IATA = In IBC = Inte IMDG = I LogPow = MARPOL 1973 as r UN = Uni	cute Toxicity Estimate oconcentration Factor lobally Harmonized System of Classification and Labelling of Chemicals international Air Transport Association ermediate Bulk Container nternational Maritime Dangerous Goods = logarithm of the octanol/water partition coefficient . 73/78 = International Convention for the Prevention of Pollution From Ships, modified by the Protocol of 1978. ("Marpol" = marine pollution) ted Nations
References	: Not availa	able.

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

This Safety Data Sheet ("SDS") is a mandatory disclosure pursuant to 29 CFR § 1910.1200 and related rules and regulations. Therefore, it is not intended, nor shall it serve to create, any rights, obligations, liabilities, and remedies, of any kind whatsoever, between Jacam Chemicals 2013, LLC and related entities ("Jacam") and any users of this SDS ("Users").

To the extent that a court of competent jurisdiction determines that this SDS creates any rights, obligations, liabilities, and remedies, of any kind whatsoever, notwithstanding the foregoing paragraph, Users accept the product AS IS and WITH ALL FAULTS. Further, Jacam DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Users' sole and exclusive remedies shall be (if any), in Jacam's sole and absolute discretion, either: (1) return of the product and repayment of the purchase price; or (2) repair/replacement of the product. In no event shall Jacam be liable for any damages of any kind whatsoever, including but not limited to, actual, compensatory, reliance, expectancy, foreseeable, future, statutory, incidental, consequential, and exemplary damages. Users assume any and all risks of any kind whatsoever that in any way relate to the product.

*** END OF SDS ***





XG-VIS

SECTION 1. IDENTIFICATION

Product Identifier	XG-VIS
Recommended Use	Drilling Fluid Additive.
Manufacturer / Supplier	AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales & Information, 281-556-5628
Emergency Phone No.	CHEMTREC, 1-800-424-9300, 24-hour Emergency
Date of Preparation	February 25, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 2 GHS Label Elements



	Signal Word:						
	Danger						
Hazard Statement(s):							
	Dust in eye may result in mechanical irritation.						
	May cause irrita	tion of mucous membranes.					
	H373	May cause damage to organs through prolonged or repeated exposure.					
	H350	May cause cancer.					
	Precautionary S	tatement(s):					
	P202	Do not handle until all safety precautions have been read and understood.					
	P264	Wash hands and skin thoroughly after handling.					
	P271	Use only outdoors or in a well-ventilated area.					
	P280	Wear protective gloves/protective clothing/eye protection/face protection.					
Response:							
	P305 + P351 + I	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present					
	and easy to do.	Continue rinsing.					
	P337 + P313	If eye irritation persists: Get medical advice/attention.					
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.					
	P308 + P313	IF exposed or concerned: Get medical advice/attention.					
	Storage:						
	P403 + P233	Store in a well-ventilated place. Keep container tightly closed.					

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains no hazardous ingredients. Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Xanthan gum	11138-66-2	100	

Silica, quartz	14808-60-7	<1	
Trade Secret	CBI*	Trade Secret	

Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of contaminant or move to fresh air.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation persists, get medical advice/attention.

Eye Contact

Rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

Ingestion

First aid is generally not required.

First-aid Comments

Get medical advice/attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Carbon Dioxide, Foam, Dry chemical.

Specific Hazards Arising from the Chemical

Does not burn.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

No special precautions are necessary.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

No special precautions are necessary.

Methods and Materials for Containment and Cleaning Up

Vacuum or sweep product up, try to minimize dust build-up. Spill material may cause floors and contact surfaces to become slippery, flush slowly with water, collect and store in suitable containers. Store recovered product or absorbent material in suitable containers for disposal according to local regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Avoid creating excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE).

Conditions for Safe Storage

Keep containers tightly closed when not in use. Use good housekeeping to prevent accumulation of dust.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH®	ACGIH® TLV®			AIHA® WEEL™	
	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Trade Secret	0.025 mg/m3 A2		0.1 mg/m3		Not established	
Xanthan gum	15 mg/m3		10 mg/m3		Not established	
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL[™] = Workplace Environmental Exposure Limit.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

Individual Protection Measures

Eye/Face Protection

Safety glasses or goggles.

Skin Protection

Not required, if used as directed.

Respiratory Protection

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

···· , · · · · · · · · · · · · · · · ·	
Appearance	Light powder.
Odour	Faint
рН	7.0
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not applicable
Evaporation Rate	Not applicable
Flammability (solid, gas)	Will not burn.
Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)
Vapour Pressure	Not applicable
Relative Density (water = 1)	Not available
Solubility	Soluble in water
Auto-ignition Temperature	Not applicable
Other Information	
Physical State	Solid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive.

Chemical Stability Stable under normal conditions. Possibility of Hazardous Reactions None expected under normal conditions of storage and use. Conditions to Avoid Strong Oxidizing Agents. Incompatible Materials Strong Oxidizing Agents. Hazardous Decomposition Products Oxidea of eacher

Oxides of carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Trade Secret	Not available	Not available	Not available
Xanthan gum	Not available	> 1,000 mg/kg (mouse)	Not available
Silica, quartz	Not available	500 mg/kg (rat)	Not available

Skin Corrosion/Irritation

Not a skin irritant.

Serious Eye Damage/Irritation

May cause mechanical irritation to eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May result in mechanical irritation of the respiratory tract from high dust concentrations.

Skin Absorption

Not harmful.

Ingestion

Not harmful.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product may contain trace amounts of crystalline silica (quartz). Long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Xanthan gum	Not Listed	Not Listed	Not Listed	Not Listed
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed

This product may contain trace amounts of crystalline silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Key to Abbreviations

IARC = International Agency for Research on Cancer. ACGIH® = American Conference of Governmental Industrial Hygienists. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration. **Reproductive Toxicity**

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Environmental information was not located.

Toxicity

No information was located.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Trade Secret	Not available	Not available	Not available	Not available
Xanthan gum	Not available	Not available	Not available	Not available
Silica, quartz	Not available	Not available	Not available	Not available

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

SECTION 14. TRANSPORT INFORMATION

Not regulated under US DOT Regulations.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

Additional USA Regulatory Lists

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA.

SARA Title III - Section 302: No listed components.

SARA Title III - Section 311/312: Chronic Health Hazard.

SARA Title III - Section 313: No chemicals are reportable under Section 313.

SECTION 16. OTHER INFORMATION

NFPA Rating SDS Prepared By Phone No.	Health - 1Flammability - 0AES Drilling Fluids281-556-5628	Instability - 0
Product Identifier:	XG-VIS	
Date of Preparation:	February 25, 2015	Page 05 of 06

Date of Preparation Disclaimer

February 25, 2015

Do not handle or use until precautions on MSDS are read and understood. The information on this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, direct or consequential, arising out of their use.

XG-VIS February 25, 2015



Page 06 of 06

Appendix B USGS Well Information



USGS Home Contact USGS Search USGS

National Water Information System: Web Interface

USGS Water Resources

 Data Category:
 Geographic Area:

 Groundwater
 V
 United States
 GO

Click to hideNews Bulletins

Please see news on new formats

• Full News 🖾

Groundwater levels for the Nation

Search Results -- 1 sites found

Agency code = usgs site_no list =

• 322238103225201

Minimum number of levels = 1

Save file of selected sites to local disk for future upload

USGS 322238103225201 22S.35E.20.22442

Lea County, New Mexico Latitude 32°22'38", Longitude 103°22'52" NAD27 Land-surface elevation 3,539 feet above NAVD88 This well is completed in the Ogallala Formation (1210GLL) local aquifer.

Output formats

Table of data

Tab-separated data

<u>Graph of data</u>

Reselect period

Date	Time	? Water- level date- time accuracy	Water level, feet below land surface	Water level, feet above specific vertical datum	Referenced vertical datum	? Water- level accuracy	? Status	? Method of measurement	? Measuring agency	? Source of measurem
1965-11-02		D	77.57			2		U		
1968-06-10		D	75.64			2	S	U		
1970-12-04		D	77.17			2	S	ប		
1996-02-16		D	78.75			2		S		

Section	Code	Description
Water-level date-time accuracy	D	Date is accurate to the Day
Water-level accuracy	2	Water level accuracy to nearest hundredth of a foot
Status		The reported water-level measurement represents a static level
Status	S	Nearby site that taps the same aquifer was being pumped.
Method of measurement	S	Steel-tape measurement.
Method of measurement	U	Unknown
Measuring agency		Not determined
Source of measurement	U	Source is unknown.
Water-level approval status	А	Approved for publication Processing and review completed.

Questions about sites/data? Feedback on this web site

https://nwis.waterdata.usgs.gov/nwis/gwlevels?site_no=322238103225201&agency_cd=U... 4/27/2017

Automated retrievals Help Data Tips Explanation of terms Subscribe for system changes News

 Accessibility
 Plug-Ins
 FOIA
 Privacy
 Policies and Notices

 U.S. Department of the Interior | U.S. Geological Survey
 Title: Groundwater for USA: Water Levels
 URL: https://nwis.waterdata.usgs.gov/nwis/gwlevels?

Page Contact Information: <u>USGS Water Data Support Team</u> Page Last Modified: 2017-04-27 11:06:24 EDT 0.4 0.4 nadww01 USA.gov

Appendix C Analytical Reports



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: <u>www.hallenvironmental.com</u>

March 22, 2017

Bernie Bockish GHD 6121 Indian School Road, NE #200 Albuquerque, NM 87110 TEL: (505) 884-0672 FAX

OrderNo.: 1703999

RE: EOG Frac Rig

Dear Bernie Bockish:

Hall Environmental Analysis Laboratory received 4 sample(s) on 3/20/2017 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to <u>www.hallenvironmental.com</u> or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

andy

Andy Freeman Laboratory Manager 4901 Hawkins NE Albuquerque, NM 87109

Analytical Report
Lab Order 1703999

Date Reported: 3/22/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: EOG Frac Rig

Client Sample ID: S-031717-CN-S16" Collection Date: 3/17/2017 1:43:00 PM Received Date: 3/20/2017 12:04:00 PM

Lab ID: 1703999-001	Matrix:	SOIL	Received	Received Date: 3/20/2017 12:04:00 PM			
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch	
EPA METHOD 300.0: ANIONS					Analyst	MRA	
Chloride	ND	30	mg/Kg	20	3/21/2017 11:02:57 AN	30827	
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst	TOM	
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	3/21/2017 9:53:13 AM	30802	
Motor Oil Range Organics (MRO)	ND	49	mg/Kg	1	3/21/2017 9:53:13 AM	30802	
Surr: DNOP	102	70-130	%Rec	1	3/21/2017 9:53:13 AM	30802	
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	: NSB	
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	3/21/2017 9:03:00 AM	30800	
Surr: BFB	75.6	54-150	%Rec	1	3/21/2017 9:03:00 AM	30800	
EPA METHOD 8021B: VOLATILES					Analyst	: NSB	
Benzene	ND	0.024	mg/Kg	1	3/21/2017 9:03:00 AM	30800	
Toluene	ND	0.049	mg/Kg	1	3/21/2017 9:03:00 AM	30800	
Ethylbenzene	ND	0.049	mg/Kg	1	3/21/2017 9:03:00 AM	30800	
Xylenes, Total	ND	0.097	mg/Kg	1	3/21/2017 9:03:00 AM	30800	
Surr: 4-Bromofluorobenzene	83.1	66.6-132	%Rec	1	3/21/2017 9:03:00 AM	30800	

Oualifiers:	*	Value exceeds Maximum Contaminant Level.	
Quanners.		Value exceeds Maximum Containmant Level.	

- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 9
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Analytical Report Lab Order 1703999 Date Reported: 3/22/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

EOG Frac Rig

Project:

Client Sample ID: S-031717-CN-S26" Collection Date: 3/17/2017 2:05:00 PM Received Date: 3/20/2017 12:04:00 PM

Lab ID: 1703999-002	Matrix:	SOIL	Received	Received Date: 3/20/2017 12:04:00 PM			
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch	
EPA METHOD 300.0: ANIONS					Analyst	: MRA	
Chloride	ND	30	mg/Kg	20	3/21/2017 11:15:22 AN	30827	
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst	: ТОМ	
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	3/21/2017 10:15:16 AM	30802	
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	3/21/2017 10:15:16 AN	30802	
Surr: DNOP	112	70-130	%Rec	1	3/21/2017 10:15:16 AM	30802	
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	: NSB	
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	3/21/2017 9:29:24 AM	30800	
Surr: BFB	74.3	54-150	%Rec	1	3/21/2017 9:29:24 AM	30800	
EPA METHOD 8021B: VOLATILES					Analyst	: NSB	
Benzene	ND	0.025	mg/Kg	1	3/21/2017 9:29:24 AM	30800	
Toluene	ND	0.050	mg/Kg	1	3/21/2017 9:29:24 AM	30800	
Ethylbenzene	ND	0.050	mg/Kg	1	3/21/2017 9:29:24 AM	30800	
Xylenes, Total	ND	0.10	mg/Kg	1	3/21/2017 9:29:24 AM	30800	
Surr: 4-Bromofluorobenzene	80.6	66.6-132	%Rec	1	3/21/2017 9:29:24 AM	30800	

Qualifiers: *	Value exceeds Maximum Contaminant Level.
---------------	--

- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 2 of 9
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Analytical Report Lab Order 1703999 Date Reported: 3/22/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

EOG Frac Rig

Project:

Client Sample ID: S-031717-CN-S36" Collection Date: 3/17/2017 2:21:00 PM Received Date: 3/20/2017 12:04:00 PM

Lab ID: 1703999-003	Matrix:	SOIL	Received	Received Date: 3/20/2017 12:04:00 PM				
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch		
EPA METHOD 300.0: ANIONS					Analyst	MRA		
Chloride	ND	30	mg/Kg	20	3/21/2017 11:27:46 AM	30827		
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst	том		
Diesel Range Organics (DRO)	ND	9.3	mg/Kg	1	3/21/2017 10:37:14 AM	30802		
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	3/21/2017 10:37:14 AM	30802		
Surr: DNOP	113	70-130	%Rec	1	3/21/2017 10:37:14 AM	30802		
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	NSB		
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	3/21/2017 12:59:55 PM	30800		
Surr: BFB	75.2	54-150	%Rec	1	3/21/2017 12:59:55 PM	30800		
EPA METHOD 8021B: VOLATILES					Analyst	NSB		
Benzene	ND	0.024	mg/Kg	1	3/21/2017 12:59:55 PM	30800		
Toluene	ND	0.048	mg/Kg	1	3/21/2017 12:59:55 PM	30800		
Ethylbenzene	ND	0.048	mg/Kg	1	3/21/2017 12:59:55 PM	30800		
Xylenes, Total	ND	0.097	mg/Kg	1	3/21/2017 12:59:55 PM	30800		
Surr: 4-Bromofluorobenzene	82.5	66.6-132	%Rec	1	3/21/2017 12:59:55 PM	30800		

Qualifiers:	*	Value exceeds Maximum Contaminant Level.
	D	Sample Diluted Due to Matrix
	Н	Holding times for preparation or analysis exceeded

- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 3 of 9
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Analytical Report Lab Order 1703999 Date Reported: 3/22/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: EOG Frac Rig

Client Sample ID: S-031717-CN-S46" Collection Date: 3/17/2017 2:37:00 PM Received Date: 3/20/2017 12:04:00 PM

Lab ID: 1703999-004	Matrix:	SOIL	Received 1	Received Date: 3/20/2017 12:04:00 PM				
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch		
EPA METHOD 300.0: ANIONS					Analyst	MRA		
Chloride	ND	30	mg/Kg	20	3/21/2017 11:40:11 AM	30827		
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst	: том		
Diesel Range Organics (DRO)	ND	9.4	mg/Kg	1	3/21/2017 10:59:38 AM	30802		
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	3/21/2017 10:59:38 AM	30802		
Surr: DNOP	134	70-130	S %Rec	1	3/21/2017 10:59:38 AM	30802		
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	: NSB		
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	3/21/2017 1:26:14 PM	30800		
Surr: BFB	69.2	54-150	%Rec	1	3/21/2017 1:26:14 PM	30800		
EPA METHOD 8021B: VOLATILES					Analyst	: NSB		
Benzene	ND	0.024	mg/Kg	1	3/21/2017 1:26:14 PM	30800		
Toluene	ND	0.048	mg/Kg	1	3/21/2017 1:26:14 PM	30800		
Ethylbenzene	ND	0.048	mg/Kg	1	3/21/2017 1:26:14 PM	30800		
Xylenes, Total	ND	0.096	mg/Kg	1	3/21/2017 1:26:14 PM	30800		
Surr: 4-Bromofluorobenzene	77.4	66.6-132	%Rec	1	3/21/2017 1:26:14 PM	30800		

Qualifiers:	*	Value exceeds Maximum Contaminant Level.
Quanner 5.		value exceeds iviaxiniani Containinant Eevel.

- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 4 of 9
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

GHD

Page 5 of 9

Project: EOG F	Frac Rig					
Sample ID MB-30827	SampType: mblk TestCode: EPA Method 300.0: Anions					
Client ID: PBS	Batch ID: 30827	RunNo: 41545				
Prep Date: 3/21/2017	Analysis Date: 3/21/2017	SeqNo: 1302689	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Chloride	ND 1.5					
Sample ID LCS-30827	SampType: Ics	TestCode: EPA Method	300.0: Anions			
Client ID: LCSS	Batch ID: 30827	RunNo: 41545				
Prep Date: 3/21/2017	Analysis Date: 3/21/2017	SeqNo: 1302690	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Chloride	15 1.5 15.00	0 96.8 90	110			

Qualifiers:

Client:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Client:GHDProject:EOG Fr	rac Rig								
Sample ID LCS-30802	SampType: LC	s	Tes	tCode: EPA M	lethod 8	3015M/D: Die	sel Range	e Organics	
Client ID: LCSS	Batch ID: 30	802	R	RunNo: 41527	,				
Prep Date: 3/20/2017	Analysis Date: 3	/21/2017	S	SeqNo: 13023	856	Units: mg/Kg	9		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC Lov	wLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	49 10	50.00	0	98.9	63.8	116			
Surr: DNOP	5.2	5.000		104	70	130			
Sample ID MB-30802	SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics								
Client ID: PBS	Batch ID: 30	802	R	RunNo: 41527	,				
Prep Date: 3/20/2017	Analysis Date: 3	/21/2017	S	SeqNo: 13023	860	Units: mg/Kg	9		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC Low	wLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10								
Motor Oil Range Organics (MRO)	ND 50								
Surr: DNOP	11	10.00		105	70	130			
Sample ID MB-30783	SampType: MI	BLK	Tes	tCode: EPA M	lethod 8	3015M/D: Die	sel Range	e Organics	
Client ID: PBS	Batch ID: 30	783	R	RunNo: 41527	,				
Prep Date: 3/20/2017	Analysis Date: 3	/21/2017	S	SeqNo: 13025	594	Units: %Rec			
Analyte	Result PQL	SPK value	SPK Ref Val	%REC Lov	wLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	10	10.00		104	70	130			
Sample ID LCS-30783	SampType: LC	s	Tes	tCode: EPA M	lethod 8	3015M/D: Die	sel Range	e Organics	
Client ID: LCSS	Batch ID: 30	783	R	RunNo: 41527	,				
Prep Date: 3/20/2017	Analysis Date: 3	/21/2017	S	eqNo: 13026	630	Units: %Rec			
Analyte	Result PQL	SPK value	SPK Ref Val	%REC Lov	wLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	5.2	5.000		103	70	130			

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified
- Page 6 of 9

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Project:	GHD EOG Frac	c Rig									
Sample ID	MB-30800	SampTy	/pe: M I	BLK	Tes	tCode: E	PA Method	8015D: Gasc	line Rang	e	
Client ID:	PBS	Batch	ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303061	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Surr: BFB	e Organics (GRO)	ND 780	5.0	1000		78.3	54	150			
Sample ID	LCS-30800	SampTy	pe: LC	cs	Tes	tCode: E	PA Method	8015D: Gasc	line Rang	e	
Client ID:	LCSS	Batch	ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303062	Units: mg/k	ζg		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range	e Organics (GRO)	28	5.0	25.00	0	113	76.4	125			
Surr: BFB		900		1000		90.0	54	150			
Sample ID	1703999-002AMS	SampTy	/pe: M	S	Tes	tCode: E	PA Method	8015D: Gasc	line Rang	e	
Client ID:	S-031717-CN-S26'	Batch	ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303071	Units: mg/ #	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
,	e Organics (GRO)	28	4.7	23.28	0	120	61.3	150			
Surr: BFB		790		931.1		85.1	54	150			
Sample ID	1703999-002AMSE	D SampTy	/pe: M	SD	Tes	tCode: E	PA Method	8015D: Gasc	line Rang	e	
Client ID:	S-031717-CN-S26'	Batch	ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303072	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
,	e Organics (GRO)	29	4.8	24.20	0	118	61.3	150	2.38	20	
Surr: BFB		880		968.1		90.4	54	150	0	0	
Sample ID	MB-30782	SampTy	/pe: M I	BLK	Tes	tCode: E	PA Method	8015D: Gaso	line Rang	e	
Client ID:	PBS	Batch	ID: 30	782	F	RunNo: 4	1546		-		
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303073	Units: %Re	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		740		1000		73.8	54	150			
Sample ID	LCS-30782	SampTy	/pe: LC	cs	Tes	tCode: E	PA Method	8015D: Gasc	line Rang	e	
Client ID:		Batch	ID: 30	782	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis Da	ate: 3 /	/21/2017	S	SeqNo: 1	303076	Units: %Re	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Analyte											

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank

E Value above quantitation range

- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 7 of 9

Hall Er	nvironmenta	al Anal	ysis I	Laborat	ory, Inc.					WO#.	22-Mar-1
Client: Project:	GHD EOG Frac										
Sample ID	MB-30800	Samp	Гуре: МВ	BLK	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	PBS	Batc	h ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis [SeqNo: 1		Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.025								
Foluene		ND	0.050								
Ethylbenzene		ND	0.050								
(ylenes, Total		ND	0.10								
Surr: 4-Bron	nofluorobenzene	0.85		1.000		85.4	66.6	132			
Sample ID	LCS-30800	Samp	Гуре: LC	S	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	ID: LCSS Batch ID: 30800				F	RunNo: 41546					
Prep Date:	3/20/2017	Analysis [Date: 3/	21/2017	S	SeqNo: 1	303105	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.95	0.025	1.000	0	95.1	80	120			
oluene		0.97	0.050	1.000	0	96.8	80	120			
thylbenzene		0.97	0.050	1.000	0	96.8	80	120			
Kylenes, Total		3.0	0.10	3.000	0	99.3	80	120			
Surr: 4-Bron	nofluorobenzene	0.84		1.000		83.6	66.6	132			
Sample ID	1703999-001AMS	Samp	Гуре: М	6	Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID:	S-031717-CN-S16	" Batc	h ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis [Date: 3/	21/2017	S	SeqNo: 1	303106	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.0	0.024	0.9407	0	109	61.5	138			
oluene		1.1	0.047	0.9407	0.005631	111	71.4	127			
Ethylbenzene		1.1	0.047	0.9407	0	115	70.9	132			
(ylenes, Total		3.3	0.094	2.822	0	117	76.2	123			
Surr: 4-Bron	nofluorobenzene	0.82		0.9407		87.7	66.6	132			
Sample ID	1703999-001AMS	D Samp	Гуре: М	SD	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	S-031717-CN-S16	" Batc	h ID: 30	800	F	RunNo: 4	1546				
Prep Date:	3/20/2017	Analysis [Date: 3/	21/2017	S	SeqNo: 1	303107	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.0	0.024	0.9662	0	106	61.5	138	0.528	20	
oluene		1.1	0.048	0.9662	0.005631	109	71.4	127	0.499	20	
Ethylbenzene		1.1	0.048	0.9662	0	109	70.9	132	2.84	20	
Kylenes, Total		3.2	0.097	2.899	0	111	76.2	123	2.18	20	
Surr: 4-Bron	nofluorobenzene	0.77		0.9662		80.1	66.6	132	0	0	

Qualifiers:

* Value exceeds Maximum Contaminant Level.

QC SUMMARY REPORT

- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 8 of 9

WO#: **1703999**

Client: GHD Project: EOG Frac Rig

Project:	EOU	J Frac Rig	
Sample ID	MB-30782	SampType: MBLK	TestCode: EPA Method 8021B: Volatiles
Client ID:	PBS	Batch ID: 30782	RunNo: 41546

Prep Date: 3/20/2017	Analysis Date	3/21/2017	S	SeqNo: 1	303108	Units: %Rec	;		
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.82	1.000		81.5	66.6	132			
Sample ID LCS-30782	SampType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch ID	30782	F	RunNo: 4	1546				
Prep Date: 3/20/2017	Analysis Date	3/21/2017	S	SeqNo: 1	303109	Units: %Rec	;		
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.74	1.000		74.4	66.6	132			

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified
- Page 9 of 9

HALL ENVIRONMENTAL ANALYSIS LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: GHD	Work Order Numbe	er: 1703999		RcptNo:	1
Received by/date:	032017				<u> </u>
Logged By: Lindsay Mangin	3/20/2017 12:04:00 F	M	And y House		
Completed By: Lindsay Mangin	3/20/2017 12:40:15 F	M	June House		
Reviewed By:	03/20/17		0.00		
Chain of Custody			· · · · · · · · · · · · · · · · · · ·)
1. Custody seals intact on sample bottles	?	Yes 🗌	No 🗌	Not Present 🗹	
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		<u>Client</u>			
<u>Log In</u>					
4. Was an attempt made to cool the sam	ples?	Yes 🗹	No 🗌	NA 🗌	
5. Were all samples received at a temper	ature of >0° C to 6.0°C	Yes 🔽	No 🗌		
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌		
7. Sufficient sample volume for indicated	test(s)?	Yes 🖌	No 🗌		
8. Are samples (except VOA and ONG) p	roperly preserved?	Yes 🗹	No 🗆		
9. Was preservative added to bottles?		Yes	No 🗹	NA 🗆	
10.VOA vials have zero headspace?		Yes	No 🗌	No VOA Vials 🗹	
11. Were any sample containers received	broken?	Yes 🗆	No 🗹 🗌	# of preserved bottles checked	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custod	v)	Yes 🗹	Νο	for pH:	>12 unless noted)
13. Are matrices correctly identified on Cha	• ·	Yes 🗹	No 🗌	Adjusted?	·
14. Is it clear what analyses were requeste	d?	Yes 🗹	No 🗌		
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🔽	No 🗌 🏻	Checked by:	<u></u>
Special Handling (if applicable)					
16. Was client notified of all discrepancies	with this order?	Yes 🗌	No 🗌		-
Person Notified:	Date				
By Whom:	Via:	eMail 🗌	Phone 🗌 Fax	In Person	
Regarding: Client Instructions:					
17. Additional remarks:					
18. <u>Cooler Information</u> Cooler No Temp °C Condition	Seal Intact Seal No	Seal Date	Signed By		
1 3.4 Good	Not Present		0.9.100 Dy		
			<u></u>		

Page 1 of 1

	HALL ENVIRONMENTAL	ANALYSIS LABORATORY	mental.com	Endue, NMI 67 103	ouo-s4s-410/ Request		/ 910.	10		(AOV) 8081 Pesticid (AOV) 80888 (A-imse) 0758 X=75 X=75 X=75 X=75 X=75 X=75 X=75 X=75		~ ~ ~ ~	111	>>>			Tour of which	a crease	
	HALLEN		Www.hallenvironmental.com	Tel 606-246-2076 Eav	Analysis Analysis	(O) (A)	(SM AM / C	из ода (11) (13 (13) (13) (13) (13) (13) (13)	als ot 8 1 20 1 418 6 4 8 1 4 1 4 1 8 1 4 1 8 1 4 1 8 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1 7	BTEX + MTB BTEX + MTB BTPH (Method TPH (Method EDB (Method PAH's (8310 PAH's (8310 PAH's (9310 PAH's (9310) PAH's (9310 PAH's (9310) PAH's (93							Remarks: // // / / / / / /	HOW JUCK	
Turn-Around Time:	D Standard Rush 24 hov		EDG Fine R.g	Project #:	012830		Backisch		Temperature: 3.4	er Preservative HEAL No. 17708999	2402) Ju 1/14 -001	2 (402) Su 1/14 -002	2(402)Ju N/A -003	2 lyezist NA -CELT			Date Time	à	CORVED DVJ
n-of-Custody Record			Mailing Address 6/21 ladion School 20 NE #20		Phone #: 505 884 06 72	email or Fax#: Surnord. Bock. schood dad. www Project Manager.	e:			Matrix Sample Request ID	5 Secret 17-00-516" 21	5 5-031717-CN-526"	5 5-031717 -EN-536" 0	5-031717-04-546"			Reinquished by: Re	Churst ward	
Chai	Client: 6HD		Mailing Addre	Albuard	Phone #: 505	email or Fax#	QA/QC Package:	Accreditation	EDD (Type)	Date Time	3-17-17 1343	3-17-17 1405	3-12-17 1421	3-17-17 1437			Date: Time:	Date Time:	



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: <u>www.hallenvironmental.com</u>

April 05, 2017

Angela Bown GHD 6121 Indian School Road, NE #200 Albuquerque, NM 87110 TEL: (505) 884-0672 FAX

RE: Bridge State #604

OrderNo.: 1704034

Dear Angela Bown:

Hall Environmental Analysis Laboratory received 4 sample(s) on 4/3/2017 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to <u>www.hallenvironmental.com</u> or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

andy

Andy Freeman Laboratory Manager 4901 Hawkins NE Albuquerque, NM 87109

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: Bridge State #604

Client Sample ID: S-088210-032817-CM-1 Collection Date: 3/28/2017 5:00:00 PM

Lab ID: 1704034-001	Matrix:	SOIL	Received 1	Date: 4/3	8/2017 1:55:00 PM	
Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 418.1: TPH					Analys	t: MAB
Petroleum Hydrocarbons, TR	21	19	mg/Kg	1	4/5/2017	31061
EPA METHOD 300.0: ANIONS					Analys	t: MRA
Chloride	66	30	mg/Kg	20	4/4/2017 1:07:26 PM	31062
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.025	mg/Kg	1	4/4/2017 2:54:00 PM	31034
Toluene	ND	0.049	mg/Kg	1	4/4/2017 2:54:00 PM	31034
Ethylbenzene	ND	0.049	mg/Kg	1	4/4/2017 2:54:00 PM	31034
Xylenes, Total	ND	0.098	mg/Kg	1	4/4/2017 2:54:00 PM	31034
Surr: 4-Bromofluorobenzene	77.7	66.6-132	%Rec	1	4/4/2017 2:54:00 PM	31034

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Meth

- D Sample Diluted Due to Matrix
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- Е Value above quantitation range
- Analyte detected below quantitation limits Page 1 of 7 J
- Р Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified W

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: Bridge State #604

Client Sample ID: S-088210-032817-CM-2 Collection Date: 3/28/2017 5:05:00 PM

Lab ID: 1704034-002	Matrix:	SOIL	Received	Date: 4/3	/2017 1:55:00 PM	
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 418.1: TPH					Analys	st: MAB
Petroleum Hydrocarbons, TR	ND	19	mg/Kg	1	4/5/2017	31061
EPA METHOD 300.0: ANIONS					Analys	st: MRA
Chloride	38	30	mg/Kg	20	4/4/2017 1:19:50 PM	31062
EPA METHOD 8021B: VOLATILES					Analys	st: NSB
Benzene	ND	0.024	mg/Kg	1	4/4/2017 3:20:29 PM	31034
Toluene	ND	0.048	mg/Kg	1	4/4/2017 3:20:29 PM	31034
Ethylbenzene	ND	0.048	mg/Kg	1	4/4/2017 3:20:29 PM	31034
Xylenes, Total	ND	0.096	mg/Kg	1	4/4/2017 3:20:29 PM	31034
Surr: 4-Bromofluorobenzene	74.6	66.6-132	%Rec	1	4/4/2017 3:20:29 PM	31034

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.
	D	Sample Diluted Due to Matrix
	Н	Holding times for preparation or analysis exceeded
	ND	Not Detected at the Reporting Limit
	R	RPD outside accepted recovery limits
	S	% Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 2 of 7
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: Bridge State #604

Client Sample ID: S-088210-032817-CM-3 Collection Date: 3/28/2017 5:10:00 PM

Lab ID: 1704034-003	Matrix:	SOIL	Received	Date: 4/3	3/2017 1:55:00 PM	
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 418.1: TPH					Analys	t: MAB
Petroleum Hydrocarbons, TR	75	19	mg/Kg	1	4/5/2017	31061
EPA METHOD 300.0: ANIONS					Analys	t: MRA
Chloride	570	30	mg/Kg	20	4/4/2017 1:32:14 PM	31062
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.024	mg/Kg	1	4/4/2017 3:46:54 PM	31034
Toluene	ND	0.048	mg/Kg	1	4/4/2017 3:46:54 PM	31034
Ethylbenzene	ND	0.048	mg/Kg	1	4/4/2017 3:46:54 PM	31034
Xylenes, Total	ND	0.097	mg/Kg	1	4/4/2017 3:46:54 PM	31034
Surr: 4-Bromofluorobenzene	78.8	66.6-132	%Rec	1	4/4/2017 3:46:54 PM	31034

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyt
	D	Sample Diluted Due to Matrix	Е	Value
	Н	Holding times for preparation or analysis exceeded	J	Analyt
	ND	Not Detected at the Reporting Limit	Р	Sample
	R	RPD outside accepted recovery limits	RL	Report
	S	% Recovery outside of range due to dilution or matrix	W	Sampl

- yte detected in the associated Method Blank
- above quantitation range
- yte detected below quantitation limits Page 3 of 7
- ole pH Not In Range
- rting Detection Limit
- ble container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

CLIENT: GHD

Project: Bridge State #604

Client Sample ID: S-088210-032817-CM-4 Collection Date: 3/28/2017 5:15:00 PM

Lab ID: 1704034-004	Matrix:	SOIL	Received	Date: 4/3	3/2017 1:55:00 PM	
Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 418.1: TPH					Analys	t: MAB
Petroleum Hydrocarbons, TR	91	19	mg/Kg	1	4/5/2017	31061
EPA METHOD 300.0: ANIONS					Analys	t: MRA
Chloride	900	30	mg/Kg	20	4/4/2017 1:44:39 PM	31062
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.024	mg/Kg	1	4/4/2017 4:13:19 PM	31034
Toluene	ND	0.048	mg/Kg	1	4/4/2017 4:13:19 PM	31034
Ethylbenzene	ND	0.048	mg/Kg	1	4/4/2017 4:13:19 PM	31034
Xylenes, Total	ND	0.095	mg/Kg	1	4/4/2017 4:13:19 PM	31034
Surr: 4-Bromofluorobenzene	75.1	66.6-132	%Rec	1	4/4/2017 4:13:19 PM	31034

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Keter to the QC building report and sample form encounts for harded QC data and preservation morning

- * Value exceeds Maximum Contaminant Level.
 - D Sample Diluted Due to Matrix

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 4 of 7
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1704034 05-Apr-17

Page 5 of 7

Client: Project:	GHD Bridge S	State #604							
Sample ID	MB-31062	SampType: mb	lk	Tes	tCode: EPA Meth	od 300.0: Anior	าร		
Client ID:	PBS	Batch ID: 31	062	F	RunNo: 41868				
Prep Date:	4/4/2017	Analysis Date: 4/	4/2017	S	SeqNo: 1315672	Units: mg/l	٨g		
Analyte		Result PQL	SPK value	SPK Ref Val	%REC LowLir	nit HighLimit	%RPD	RPDLimit	Qual
Chloride		ND 1.5							
Sample ID	LCS-31062	SampType: Ics		Tes	tCode: EPA Meth	od 300.0: Anior	ıs		
Client ID:	LCSS	Batch ID: 31	062	F	RunNo: 41868				
Prep Date:	4/4/2017	Analysis Date: 4/	4/2017	S	SeqNo: 1315673	Units: mg/l	۶g		
Analyte		Result PQL	SPK value	SPK Ref Val	%REC LowLir	nit HighLimit	%RPD	RPDLimit	Qual
Chloride		15 1.5	15.00	0	96.9	90 110			

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Client:	GHD										
Project:	Bridge S	tate #604									
Sample ID	MB-31061	SampTyp	e: ME	BLK	Tes	tCode: El	PA Method	418.1: TPH			
Client ID:	PBS	Batch II	D: 310	061	R	aunNo: 4	1899				
Prep Date:	4/4/2017	Analysis Date	e: 4/	5/2017	S	SeqNo: 1	315985	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	rocarbons, TR	ND	20								
Sample ID	LCS-31061	SampTyp	e: LC	S	Tes	tCode: El	PA Method	418.1: TPH			
Client ID:	LCSS	Batch II	D: 310	061	R	RunNo: 4	1899				
Prep Date:	4/4/2017	Analysis Date	e: 4/	5/2017	S	SeqNo: 1	315986	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	rocarbons, TR	110	20	100.0	0	110	61.7	138			
Sample ID	LCSD-31061	SampTyp	e: LC	SD	Tes	tCode: El	PA Method	418.1: TPH			
Client ID:	LCSS02	Batch II	D: 310	061	R	RunNo: 4	1899				
Prep Date:	4/4/2017	Analysis Date	e: 4/	5/2017	S	SeqNo: 1	315987	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	rocarbons, TR	100	20	100.0	0	104	61.7	138	5.88	20	

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified
- Page 6 of 7

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

05-Apr-17

Client:	GHD										
Project:	Bridge St	ate #604									
Sample ID	RB	SampT	ype: MI	BLK	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID:	PBS	Batch	ID: B4	1869	F	RunNo: 4	1869				
Prep Date:		Analysis D	ate: 4/	/4/2017	5	SeqNo: 1	315328	Units: %Red	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Brom	ofluorobenzene	0.98		1.000		98.1	66.6	132			
Sample ID	100NG BTEX LCS	SampT	ype: LC	s	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID:	LCSS	Batch	ID: B4	1869	F	RunNo: 4	1869				
Prep Date:		Analysis D	ate: 4/	4/2017	S	SeqNo: 1	315329	Units: %Red	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Brom	ofluorobenzene	0.90		1.000		89.7	66.6	132			
Sample ID	MB-31034	SampT	ype: MI	BLK	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID:	PBS	Batch	ID: 31	034	F	RunNo: 4	1869				
Prep Date:	4/3/2017	Analysis D	ate: 4/	4/2017	S	SeqNo: 1	315332	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.025								
Toluene		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total Surr: 4-Brom	ofluorobenzene	ND 0.78	0.10	1.000		77.6	66.6	132			
Sample ID	LCS-31034	SampT	vpe: LC	s	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID:			ID: 31		F	RunNo: 4	1869				
Prep Date:	4/3/2017	Analysis D	ate: 4/	/4/2017	S	SeqNo: 1	315333	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.0	0.025	1.000	0	103	80	120			
Toluene		1.0	0.050	1.000	0	104	80	120			
Ethylbenzene		1.1	0.050	1.000	0	106	80	120			
Xylenes, Total		3.2	0.10	3.000	0	108	80	120			
Surr: 4-Brom	ofluorobenzene	0.79		1.000		79.0	66.6	132			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 7 of 7
HALL ENVIRONMENTAL ANALYSIS LABORATORY	Hall Environmental Alb TEL: 505-345-3975 Website: www.ha	4901 Hawkins uquerque, NM 87 FAX: 505-345-4	NE 109 Sam 107	Sample Log-In Check List		
Client Name: GHD	Work Order Number:	1704034		RcptNo: 1		
Received By: Andy Jansson	4/3/2017 1:55:00 PM		DNY Comm			
Completed By: Andy Jansson	4/3/2017 2:27:37 PM		Dory Contract			
Reviewed By:	103/17		,			
Chain of Custody	-///					
1. Custody seals intact on sample bottles?		Yes 🗌	No 🗌	Not Present 🗹		
2. Is Chain of Custody complete?		Yes 🖌	No 🗌	Not Present		
3. How was the sample delivered?		<u>Client</u>				
<u>Log In</u>						
4. Was an attempt made to cool the sample	es?	Yes 🗹	No 🗌			
5. Were all samples received at a temperat	ture of >0° C to 6.0°C	Yes 🗍 Approved b	No 🗹	NA 🗌		
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌			
7. Sufficient sample volume for indicated te	st(s)?	Yes 🔽	No 🗌			
8. Are samples (except VOA and ONG) pro	perly preserved?	Yes 🗹	No 🗌			
9. Was preservative added to bottles?		Yes 🗌	No 🗹	NA 🗌		
10.VOA vials have zero headspace?		Yes 🗌	No 🗌	No VOA Vials 🗹		
11. Were any sample containers received be	roken?	Yes 🗌	No 🔽	# of preserved		
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🔽	No 🗌	bottles checked for pH: (<2 or >12	2 unless noted	
13. Are matrices correctly identified on Chair		Yes 🗹	No 🗌	Adjusted?		
14. Is it clear what analyses were requested	?	Yes 🗹	No 🗌			
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🔽	No 🗍	Checked by:		
Special Handling (if applicable)						
16. Was client notified of all discrepancies w	ith this order?	Yes	No 🗌	NA 🗹		
Person Notified:	Date:					
By Whom:	Via: [eMail 🛛 P	hone 🗌 Fax	In Person		
Regarding:		*****		<u></u>		
Client Instructions:						
17. Additional remarks:						
18. <u>Cooler Information</u> │ Cooler No │ Temp ºC │ Condition │	Seal Intact Seal No	Seal Date	Signed By I			
	Not Present		Signed By			

_ _

_

	 .=	 _	_	_	
Page 1 of 1					

NM 87110 COC	HAD, NM cooler No:	ID Idons) Carrier: HdnA De Increations: Airbill No: Total # of Containers: 8.6% SPECIAL INSTRUCTIONS: Comments/ SPECIAL INSTRUCTIONS: Devolutions: D	40 HR THT cerved BY CERVED BY CERVED BY CERVED BY CERVED BY CERVED BY COMPANY
CHAIN OF CUSTODY REC Address: \$121 Judgon Sheo # 202 Phone: Phone: 505-869-06 72	Laboratory Name: FUI	Sample Sample	Date Time Requirements: Date Time Requirements: Date Time Requirements: Date Time 1 Date 1 1 Date 1 1 Date 1 1 Date 3 2 Stopy is a Legal Document - All FleLDS Must Black PINK - Shi
	Project Name: D 1. O. O 1. 1. 1. 1.	Project Location: The Mode Stort Hund Project Location: The MM A BOUN Minute Sampler(s): C MAHAUS DOUN Minute Sampler(s): C MAHAUS DATE TIME Sampler(s): C MAHAUS DATE TIME Sampler(s): C MAHAUS DATE TIME Sampler(s): C MAHAUS DATE TIME Containers (streact) sample ring) DATE TIME Containers (streact) sample ring) DATE TIME Containers (streact) sample ring) DATE TIME DATE DENTIFICATION Sampler(s): C MAHAUS DATE TIME Containers (streact) sample ring) DATE TIME DATE DENTIFICATION Sampler(s): C MAHAUS DATE TIME Containers (streact) sample ring) DATE TIME Containers (streact) and the Container on crecine) DATE TIME Sampler(s): C MAHAUS DATE TIME Sample	12 12 TAT Required in business days (use separate COCs for different TATs): 1 Day 2 Days 1 1 Day 2 Distribution: Method Method Method Method 1 1 Day 2 Distribution:

Analytical Report 551745

for GHD-Albuquerque, NM

Project Manager: Bernie Bockisch

Bridge State

088210-32

28-APR-17

Collected By: Client





1211 W. Florida Ave, Midland TX 79701

Xenco-Houston (EPA Lab code: TX00122): Texas (T104704215), Arizona (AZ0765), Florida (E871002), Louisiana (03054) Oklahoma (9218)

Xenco-Dallas (EPA Lab code: TX01468): Texas (T104704295) Xenco-Odessa (EPA Lab code: TX00158): Texas (T104704400) Xenco-San Antonio: Texas (T104704534) Xenco Phoenix (EPA Lab Code: AZ00901): Arizona(AZ0757) Xenco-Phoenix Mobile (EPA Lab code: AZ00901): Arizona (AZM757)





NP ACCREDUED

Project Manager: **Bernie Bockisch GHD-Albuquerque, NM** 6121 Indian School Rd. NE Suite 200

Albuquerque, NM 87110

Reference: XENCO Report No(s): **551745 Bridge State** Project Address:

Bernie Bockisch:

We are reporting to you the results of the analyses performed on the samples received under the project name referenced above and identified with the XENCO Report Number(s) 551745. All results being reported under this Report Number apply to the samples analyzed and properly identified with a Laboratory ID number. Subcontracted analyses are identified in this report with either the NELAC certification number of the subcontract lab in the analyst ID field, or the complete subcontracted report attached to this report.

Unless otherwise noted in a Case Narrative, all data reported in this Analytical Report are in compliance with NELAC standards. The uncertainty of measurement associated with the results of analysis reported is available upon request. Should insufficient sample be provided to the laboratory to meet the method and NELAC Matrix Duplicate and Matrix Spike requirements, then the data will be analyzed, evaluated and reported using all other available quality control measures.

The validity and integrity of this report will remain intact as long as it is accompanied by this letter and reproduced in full, unless written approval is granted by XENCO Laboratories. This report will be filed for at least 5 years in our archives after which time it will be destroyed without further notice, unless otherwise arranged with you. The samples received, and described as recorded in Report No. 551745 will be filed for 60 days, and after that time they will be properly disposed without further notice, unless otherwise arranged with you. We reserve the right to return to you any unused samples, extracts or solutions related to them if we consider so necessary (e.g., samples identified as hazardous waste, sample sizes exceeding analytical standard practices, controlled substances under regulated protocols, etc).

We thank you for selecting XENCO Laboratories to serve your analytical needs. If you have any questions concerning this report, please feel free to contact us at any time.

Respectfully,

Hurs Hoah

Kelsey Brooks Project Manager

Recipient of the Prestigious Small Business Administration Award of Excellence in 1994. Certified and approved by numerous States and Agencies. A Small Business and Minority Status Company that delivers SERVICE and QUALITY

Houston - Dallas - Midland - San Antonio - Phoenix - Oklahoma - Latin America



Sample Cross Reference 551745



GHD-Albuquerque, NM, Albuquerque, NM

Sample Id	Matrix	Date Collected	Sample Depth	Lab Sample Id
S-088210-32-42417-BB-1	S	04-24-17 15:20	- 4 In	551745-001
S-088210-32-42417-BB-2	S	04-24-17 15:24	- 5 In	551745-002
S-088210-32-42417-BB-3	S	04-24-17 15:33	- 6 In	551745-003
S-088210-32-42417-BB-4	S	04-24-17 15:37	- 6 In	551745-004
S-088210-32-42417-BB-5	S	04-24-17 15:43	- 3 In	551745-005
S-088210-32-42417-BB-6	S	04-24-17 15:50	- 3 In	551745-006



CASE NARRATIVE

Client Name: GHD-Albuquerque, NM Project Name: Bridge State

 Project ID:
 088210-32

 Work Order Number(s):
 551745

Report Date: 28-APR-17 Date Received: 04/26/2017

Sample receipt non conformances and comments:

Sample receipt non conformances and comments per sample:

None

Analytical non conformances and comments:

Batch: LBA-3015995 Inorganic Anions by EPA 300/300.1

Lab Sample ID 551820-001 was randomly selected for Matrix Spike/Matrix Spike Duplicate (MS/MSD). Chloride recovered above QC limits in the Matrix Spike and Matrix Spike Duplicate. Outlier/s are due to possible matrix interference. Samples in the analytical batch are: 551745-001, -002, -003, -004, -005, -006.

The Laboratory Control Sample for Chloride is within laboratory Control Limits, therefore the data was accepted.





GHD-Albuquerque, NM, Albuquerque, NM

BB-1	Matrix: Date Collec	Soil cted: 04.24.17 15.20				02
as by EPA 300/300.1	l Date Prep:	04.27.17 19.00		% Moisture:		
Cas Number	Result	RL	Units	Analysis Date	Flag	Dil
	·	Date Collectors by EPA 300/300.1 Date Prep: Cas Number Result	Date Collected: 04.24.17 15.20 Date Prep: 04.27.17 19.00 Cas Number Result RL	Date Collected: 04.24.17 15.20 Date Solution Date Prep: 04.27.17 19.00 Cas Number Result RL Units	Date Collected: 04.24.17 15.20 Sample Depth: 4 I ns by EPA 300/300.1 Prep Method: E30 % Moisture: Date Prep: 04.27.17 19.00 Basis: We Cas Number Result Result RL Units Analysis Date	Date Collected: 04.24.17 15.20 Sample Depth: 4 In ns by EPA 300/300.1 Prep Method: E300P Date Prep: 04.27.17 19.00 Basis: Wet Weight Cas Number RL Units Analysis Date Flag





GHD-Albuquerque, NM, Albuquerque, NM

Sample Id:S-088210-32-42417-BB-2Lab Sample Id:551745-002	Matrix: Date Collec	Soil ted: 04.24.17 15.24		Date Received:04 Sample Depth: 5		2
Analytical Method: Inorganic Anions by EPA 300/30 Tech: MGO Analyst: MGO Seq Number: 3015995	00.1 Date Prep:	04.27.17 19.00		Prep Method: E3 % Moisture: Basis: Wo	00P et Weight	
Parameter Cas Number Chloride 16887-00-6	Result	RL 4.97	Units mg/kg	Analysis Date 04.28.17 02.25	Flag	Dil





GHD-Albuquerque, NM, Albuquerque, NM

Sample Id: S-088210-32-42417-BB-3 Lab Sample Id: 551745-003	3	Matrix: Date Collec	Soil ted: 04.24.17 15.33		Date Received: Sample Depth:		2
Analytical Method: Inorganic Anions by Tech: MGO Analyst: MGO	EPA 300/300.1	Date Prep:	04.27.17 19.00		Prep Method: 1 % Moisture: Basis:	E300P Wet Weight	
Seq Number: 3015995 Parameter	Cas Number	Result	RL	Units	Analysis Dat	te Flag	Dil
Chloride 16	5887-00-6	45.7	4.92	mg/kg	04.28.17 02.3		1





GHD-Albuquerque, NM, Albuquerque, NM

Sample Id: Lab Sample Id	S-088210-32-42417- d: 551745-004	3B-4	Matrix: Date Colle	Soil cted: 04.24.17 15.37		Date Received:04. Sample Depth: 6		2
Analytical Me Tech:	ethod: Inorganic Anions MGO	by EPA 300/300.1				Prep Method: E3 % Moisture:	00P	
Analyst:	MGO		Date Prep:	04.27.17 19.00		Basis: We	et Weight	
Seq Number: Parameter	3015995	Cas Number	Result	RL	Units	Analysis Date	Flag	Dil
Chloride		16887-00-6	9.14	4.93	mg/kg	04.28.17 02.40	8	1





GHD-Albuquerque, NM, Albuquerque, NM

Sample Id: S Lab Sample Id: 5	- 088210-32-42417-B 51745-005	8-5	Matrix: Date Collec	Soil ted: 04.24.17 15.43		Date Received: Sample Depth:		02
Tech: M	d: Inorganic Anions b GO GO	by EPA 300/300.1	Date Prep:	04.27.17 19.00		Prep Method: % Moisture: Basis:	E300P Wet Weight	
Seq Number: 30)15995							
Parameter		Cas Number	Result	RL	Units	Analysis Da	te Flag	Dil
Chloride		16887-00-6	ND	4.98	mg/kg	04.28.17 02.4	48 U	1





GHD-Albuquerque, NM, Albuquerque, NM

Sample Id: Lab Sample Id	S-088210-32-42417-E d: 551745-006	BB-6	Matrix: Date Collec	Soil cted: 04.24.17 15.50		Date Received:04.2 Sample Depth: 3		2
Analytical Me Tech:	ethod: Inorganic Anions MGO	by EPA 300/300.1				Prep Method: E30 % Moisture:	00P	
Analyst: Seq Number:	MGO 3015995		Date Prep:	04.27.17 19.00		Basis: We	t Weight	
Parameter		Cas Number	Result	RL	Units	Analysis Date	Flag	Dil
Chloride		16887-00-6	ND	4.93	mg/kg	04.28.17 03.10	U	1



Flagging Criteria



- X In our quality control review of the data a QC deficiency was observed and flagged as noted. MS/MSD recoveries were found to be outside of the laboratory control limits due to possible matrix /chemical interference, or a concentration of target analyte high enough to affect the recovery of the spike concentration. This condition could also affect the relative percent difference in the MS/MSD.
- **B** A target analyte or common laboratory contaminant was identified in the method blank. Its presence indicates possible field or laboratory contamination.
- **D** The sample(s) were diluted due to targets detected over the highest point of the calibration curve, or due to matrix interference. Dilution factors are included in the final results. The result is from a diluted sample.
- E The data exceeds the upper calibration limit; therefore, the concentration is reported as estimated.
- **F** RPD exceeded lab control limits.
- J The target analyte was positively identified below the quantitation limit and above the detection limit.
- U Analyte was not detected.
- L The LCS data for this analytical batch was reported below the laboratory control limits for this analyte. The department supervisor and QA Director reviewed data. The samples were either reanalyzed or flagged as estimated concentrations.
- **H** The LCS data for this analytical batch was reported above the laboratory control limits. Supporting QC Data were reviewed by the Department Supervisor and QA Director. Data were determined to be valid for reporting.
- **K** Sample analyzed outside of recommended hold time.
- JN A combination of the "N" and the "J" qualifier. The analysis indicates that the analyte is "tentatively identified" and the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- ** Surrogate recovered outside laboratory control limit.
- **BRL** Below Reporting Limit.
- RL Reporting Limit

MDL Method Detection Limit	SDL Sample Detection Limit	LOD Limit of Detection
PQL Practical Quantitation Limit	MQL Method Quantitation Limit	LOQ Limit of Quantitation

- **DL** Method Detection Limit
- NC Non-Calculable
- + NELAC certification not offered for this compound.
- * (Next to analyte name or method description) = Outside XENCO's scope of NELAC accreditation

Recipient of the Prestigious Small Business Administration Award of Excellence in 1994.

Certified and approved by numerous States and Agencies.

A Small Business and Minority Status Company that delivers SERVICE and QUALITY

Houston - Dallas - San Antonio - Atlanta - Midland/Odessa - Tampa/Lakeland - Phoenix - Latin America

	Phone	Fax
4147 Greenbriar Dr, Stafford, TX 77477	(281) 240-4200	(281) 240-4280
9701 Harry Hines Blvd, Dallas, TX 75220	(214) 902 0300	(214) 351-9139
5332 Blackberry Drive, San Antonio TX 78238	(210) 509-3334	(210) 509-3335
1211 W Florida Ave, Midland, TX 79701	(432) 563-1800	(432) 563-1713
2525 W. Huntington Dr Suite 102, Tempe AZ 85282	(602) 437-0330	



QC Summary 551745

GHD-Albuquerque, NM Bridge State

Analytical Method:	Inorganic Anions b	y EPA 300	/300.1					Pr	ep Metho	od: E300)P	
Seq Number:	3015995			Matrix:	Solid				Date Pre	ep: 04.2	7.17	
MB Sample Id:	723751-1-BLK		LCS Sar	nple Id:	723751-1-	BKS		LCSI	O Sample	Id: 7237	751-1-BSD	
Parameter	MB Result	Spike Amount	LCS Result	LCS %Rec	LCSD Result	LCSD %Rec	Limits	%RPD	RPD Limit	Units	Analysis Date	Flag
Chloride	< 5.00	250	258	103	258	103	90-110	0	20	mg/kg	04.28.17 00:46	

Analytical Method:	Inorganic Anions b	y EPA 300	/300.1					Pr	ep Metho	od: E30	0P	
Seq Number:	3015995			Matrix:	Soil				Date Pre	ep: 04.2	7.17	
Parent Sample Id:	551745-005		MS Sar	nple Id:	551745-00)5 S		MSI	O Sample	Id: 5517	745-005 SD	
Parameter	Parent Result	Spike Amount	MS Result	MS %Rec	MSD Result	MSD %Rec	Limits	%RPD	RPD Limit	Units	Analysis Date	Flag

Analytical Method:	Inorganic Anions b	y EPA 300/	/300.1					Pr	ep Metho	od: E30	0P	
Seq Number:	3015995			Matrix:	Soil				Date Pre	ep: 04.2	7.17	
Parent Sample Id:	551820-001		MS Sar	nple Id:	551820-00	01 S		MSI	O Sample	Id: 5518	320-001 SD	
Parameter	Parent Result	Spike Amount	MS Result	MS %Rec	MSD Result	MSD %Rec	Limits	%RPD	RPD Limit	Units	Analysis Date	Flag
Chloride	58.6	245	390	135	383	132	90-110	2	20	mg/kg	04.28.17 01:09	Х

Notice: Signature of this document and relinquishment of these samples constitutes a valid purchase order from client company to Xenco Laboratories and its affiliates, subcontractors and assigns under Xenco's standard terms and conditions of service unless previously negotiated under a fully executed client contract.

www.xenco.com

Matrix: Air (A), Product (P), Solid (S), Water (W), Liquid (L) Committed to Excellence in Service and Quality

Cont. Size: 4oz (4), 8oz (8), 32oz (32), 40ml VOA (40), 1L (1), 500ml (5), Tedlar Bag (B), Various (V), Other Cont. Type: Glass Amb (A), Glass Clear (C), Plastic (P), Various (V)

1 1) BBC Set The WORL TH 4/196/17/10:35 2) 4)	(Initials and Sign) Date &				65-088240-32-47417-198-6 4/241/17 1550 3" 5 x 1 407 C NA	5 5-000210-32-42417-883-5 4/241/17 1543 3"5 x 1 402 c NA	45-088210-32-42417-88-4 4124117 1537 6"5 x 1 402 C NA	35-08030-32-43417-58-3 4/14/17 1533 6 " S x 1 407 C. NA	25-020210-32-43417-58-2 4134117 1524 5" 5" X 11 402 C NA	 ARGUALERAUE Phone Support Phone Support
 A). ZnAc&NaOH (Z). (Cool. <4C) (C). None (NA). See Label (L). Other (O) A). ZnAc&NaOH (Z). (Cool. <4C) (C). None (NA). See Label (L). Other (O) 	Date & Time	1 ~	CF:(0-6: 0.0107) (0-23: +0.1 0)	Temp: 1.2 IR ID:R-9 8						VOA: PP TCL DW Appdx-1 Appdx-2 CALL Other: Stypically 57 PAHs SIM 8310 8270 TX-1005 DRO GRO MA EPH MA VPH SVOCs: Full-List DW BN&AE TCLP PP Appdx-2 CALL Vorking Days for leve OC Pesticides PCBs Herbicides OP Pesticides Metals: RCRA-8 RCRA-4 Pb 13PP 23TAL Appdx 1 Appdx2 SPLP - TCLP (Metals VOCs SVOCs Pest. Herb. PCBs) EDB / DBCP

ANALYSIS REQUEST & CHAIN OF CUSTODY RECORD

Final 1.000



Client: GHD-Albuquerque, NM

XENCO Laboratories



Prelogin/Nonconformance Report- Sample Log-In

Acceptable Temperature Range: 0 - 6 degC Air and Metal samples Acceptable Range: Ambient Date/ Time Received: 04/26/2017 10:02:00 AM Temperature Measuring device used : r9 Work Order #: 551745 Comments Sample Receipt Checklist 1.2 #1 *Temperature of cooler(s)? #2 *Shipping container in good condition? Yes #3 *Samples received on ice? Yes #4 *Custody Seal present on shipping container/ cooler? Yes #5 *Custody Seals intact on shipping container/ cooler? Yes #6 Custody Seals intact on sample bottles? No #7 *Custody Seals Signed and dated? No #8 *Chain of Custody present? Yes #9 Sample instructions complete on Chain of Custody? Yes #10 Any missing/extra samples? No #11 Chain of Custody signed when relinguished/ received? Yes #12 Chain of Custody agrees with sample label(s)? Yes #13 Container label(s) legible and intact? Yes #14 Sample matrix/ properties agree with Chain of Custody? Yes #15 Samples in proper container/ bottle? Yes #16 Samples properly preserved? Yes #17 Sample container(s) intact? Yes #18 Sufficient sample amount for indicated test(s)? Yes #19 All samples received within hold time? Yes #20 Subcontract of sample(s)? No #21 VOC samples have zero headspace? N/A #22 <2 for all samples preserved with HNO3,HCL, H2SO4? Except for N/A samples for the analysis of HEM or HEM-SGT which are verified by the

analysts. #23 >10 for all samples preserved with NaAsO2+NaOH, ZnAc+NaOH? N/A

* Must be completed for after-hours delivery of samples prior to placing in the refrigerator

Analyst:

PH Device/Lot#:

Checklist completed by: Jessica WAMER Jessica Kramer Checklist reviewed by: Kelsey Brooks

Date: 04/26/2017

Date: 04/27/2017

Analytical Report 552757

for GHD-Albuquerque, NM

Project Manager: Christine Mathews

BRIDGE STATE

088210-32

12-MAY-17

Collected By: Client





1211 W. Florida Ave, Midland TX 79701

Xenco-Houston (EPA Lab code: TX00122): Texas (T104704215), Arizona (AZ0765), Florida (E871002), Louisiana (03054) Oklahoma (9218)

Xenco-Dallas (EPA Lab code: TX01468): Texas (T104704295) Xenco-Odessa (EPA Lab code: TX00158): Texas (T104704400) Xenco-San Antonio: Texas (T104704534) Xenco Phoenix (EPA Lab Code: AZ00901): Arizona(AZ0757) Xenco-Phoenix Mobile (EPA Lab code: AZ00901): Arizona (AZM757)



Table of Contents

Cover Page	1
Cover Letter	3
Sample ID Cross Reference	4
Case Narrative	5
Certificate of Analysis (Detailed Report)	6
Explanation of Qualifiers (Flags)	8
LCS / LCSD Recoveries	9
MS / MSD Recoveries	10
Chain of Custody	11
Sample Receipt Conformance Report	13





12-MAY-17

Project Manager: Christine Mathews GHD-Albuquerque, NM 6121 Indian School Rd. NE Suite 200

Albuquerque, NM 87110

Reference: XENCO Report No(s): **552757 BRIDGE STATE** Project Address: LEA COUNTY,NM

Christine Mathews:

We are reporting to you the results of the analyses performed on the samples received under the project name referenced above and identified with the XENCO Report Number(s) 552757. All results being reported under this Report Number apply to the samples analyzed and properly identified with a Laboratory ID number. Subcontracted analyses are identified in this report with either the NELAC certification number of the subcontract lab in the analyst ID field, or the complete subcontracted report attached to this report.

Unless otherwise noted in a Case Narrative, all data reported in this Analytical Report are in compliance with NELAC standards. The uncertainty of measurement associated with the results of analysis reported is available upon request. Should insufficient sample be provided to the laboratory to meet the method and NELAC Matrix Duplicate and Matrix Spike requirements, then the data will be analyzed, evaluated and reported using all other available quality control measures.

The validity and integrity of this report will remain intact as long as it is accompanied by this letter and reproduced in full, unless written approval is granted by XENCO Laboratories. This report will be filed for at least 5 years in our archives after which time it will be destroyed without further notice, unless otherwise arranged with you. The samples received, and described as recorded in Report No. 552757 will be filed for 60 days, and after that time they will be properly disposed without further notice, unless otherwise arranged with you. We reserve the right to return to you any unused samples, extracts or solutions related to them if we consider so necessary (e.g., samples identified as hazardous waste, sample sizes exceeding analytical standard practices, controlled substances under regulated protocols, etc).

We thank you for selecting XENCO Laboratories to serve your analytical needs. If you have any questions concerning this report, please feel free to contact us at any time.

Respectfully,

Hurs Hoah

Kelsey Brooks Project Manager

Recipient of the Prestigious Small Business Administration Award of Excellence in 1994. Certified and approved by numerous States and Agencies. A Small Business and Minority Status Company that delivers SERVICE and QUALITY

Houston - Dallas - Midland - San Antonio - Phoenix - Oklahoma - Latin America



Sample Cross Reference 552757



GHD-Albuquerque, NM, Albuquerque, NM

BRIDGE STATE

Sample Id	Matrix	Date Collected	Sample Depth	Lab Sample Id
SS-088210-050917-CM-1	S	05-09-17 11:47		552757-001
SS-088210-050917-CM-2	S	05-09-17 11:55		552757-002



CASE NARRATIVE

Client Name: GHD-Albuquerque, NM Project Name: BRIDGE STATE

 Project ID:
 088210-32

 Work Order Number(s):
 552757

 Report Date:
 12-MAY-17

 Date Received:
 05/10/2017

This laboratory is NELAC accredited under the Texas Laboratory Accreditation Program for all the methods, analytes, and matrices reported in this data package except as noted. The data have been reviewed and are technically compliant with the requirements of the methods used, except where noted by the laboratory.

Sample receipt non conformances and comments:

Sample receipt non conformances and comments per sample:

None



Certificate of Analytical Results 552757 GHD-Albuquerque, NM, Albuquerque, NM



BRIDGE STATE

Sample Id: SS-088210-050917-CM-1		Matrix:	Soil		Sample	e Depth:		
Lab Sample Id: 552757-001		Date Collecte	ed: 05.09.17	11.47	Date R	eceived: 05.10.	17 10.	25
Analytical Method: Inorganic Anions by EF	PA 300/300.1				Prep M	lethod: E300P	,	
Analyst: MGO		% Moist:			Tech:	MGO		
Seq Number: 3017050		Date Prep: 05	5.11.17 08.00)				
		Prep seq: 72	24436					
Parameter	CAS Number	Result	MQL	SDL	Units	Analysis Date	Flag	Dil Factor
Chloride	16887-00-6	20.4	5.00	0.858	mg/kg	05.11.17 13:53		1
Sample Id: SS-088210-050917-CM-2		Matrix:	Soil		Sample	e Depth:		
Lab Sample Id: 552757-002		Date Collecte	ed: 05.09.17	11.55	Date R	eceived: 05.10.	17 10.	25
Analytical Method: Inorganic Anions by EF	PA 300/300.1				Prep M	lethod: E300P	,	
Analyst: MGO		% Moist:			Tech:	MGO		
Seq Number: 3017050		Date Prep: 05	5.11.17 08.00	1				
		Prep seq: 72	24436					
Parameter	CAS Number	Result	MQL	SDL	Units	Analysis Date	Flag	Dil Factor
Chloride	16887-00-6	42.4	5.00	0.858	mg/kg	05.11.17 14:00		1



Certificate of Analytical Results 552757 GHD-Albuquerque, NM, Albuquerque, NM



BRIDGE STATE

Sample Id: 724436-1-BLK	Matrix:	Solid		Sample	e Depth:		
Lab Sample Id: 724436-1-BLK	Date Collecte	ed:		Date R	eceived:		
Analytical Method: Inorganic Anions by EPA 300/300.1				Prep M	lethod: E300P		
Analyst: MGO	% Moist:			Tech:	MGO		
Seq Number: 3017050	Date Prep: 05	5.11.17 08.00					
	Prep seq: 72	24436					
Parameter CAS Number	Result	MQL	SDL	Units	Analysis Date	Flag	Dil Factor
Chloride 16887-00-6	< 0.858	5.00	0.858	mg/kg	05.11.17 09:34	U	1



Flagging Criteria



- X In our quality control review of the data a QC deficiency was observed and flagged as noted. MS/MSD recoveries were found to be outside of the laboratory control limits due to possible matrix /chemical interference, or a concentration of target analyte high enough to affect the recovery of the spike concentration. This condition could also affect the relative percent difference in the MS/MSD.
- **B** A target analyte or common laboratory contaminant was identified in the method blank. Its presence indicates possible field or laboratory contamination.
- **D** The sample(s) were diluted due to targets detected over the highest point of the calibration curve, or due to matrix interference. Dilution factors are included in the final results. The result is from a diluted sample.
- E The data exceeds the upper calibration limit; therefore, the concentration is reported as estimated.
- **F** RPD exceeded lab control limits.
- J The target analyte was positively identified below the quantitation limit and above the detection limit.
- U Analyte was not detected.
- L The LCS data for this analytical batch was reported below the laboratory control limits for this analyte. The department supervisor and QA Director reviewed data. The samples were either reanalyzed or flagged as estimated concentrations.
- **H** The LCS data for this analytical batch was reported above the laboratory control limits. Supporting QC Data were reviewed by the Department Supervisor and QA Director. Data were determined to be valid for reporting.
- **K** Sample analyzed outside of recommended hold time.
- JN A combination of the "N" and the "J" qualifier. The analysis indicates that the analyte is "tentatively identified" and the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- ** Surrogate recovered outside laboratory control limit.
- **BRL** Below Reporting Limit.
- RL Reporting Limit

MDL Method Detection Limit	SDL Sample Detection Limit	LOD Limit of Detection
PQL Practical Quantitation Limit	MQL Method Quantitation Limit	LOQ Limit of Quantitation

- **DL** Method Detection Limit
- NC Non-Calculable
- + NELAC certification not offered for this compound.
- * (Next to analyte name or method description) = Outside XENCO's scope of NELAC accreditation

Recipient of the Prestigious Small Business Administration Award of Excellence in 1994.

Certified and approved by numerous States and Agencies.

A Small Business and Minority Status Company that delivers SERVICE and QUALITY

Houston - Dallas - San Antonio - Atlanta - Midland/Odessa - Tampa/Lakeland - Phoenix - Latin America

	Phone	гах
4147 Greenbriar Dr, Stafford, TX 77477	(281) 240-4200	(281) 240-4280
9701 Harry Hines Blvd , Dallas, TX 75220	(214) 902 0300	(214) 351-9139
5332 Blackberry Drive, San Antonio TX 78238	(210) 509-3334	(210) 509-3335
1211 W Florida Ave, Midland, TX 79701	(432) 563-1800	(432) 563-1713
2525 W. Huntington Dr Suite 102, Tempe AZ 85282	(602) 437-0330	



BS / BSD Recoveries



Project Name: BRIDGE STATE

Work Order #: 552757 Project ID: 088210-32											
Analyst: MGO	Analyst: MGO Date Prepared: 05/11/2017 Date Analyzed: 05/11/2017										
Lab Batch ID: 3017050 Sample: 724436-1-BKS Batch #: 1 1							Matrix: S	Solid			
Units: mg/kg		BLAN	K /BLANK S	SPIKE / I	BLANK	SPIKE DUPI	LICATE	RECOV	ERY STUI	ŊŶ	
Inorganic Anions by EPA 300/300.1	Blank Sample Result [A]	Spike Added	Blank Spike Result	Blank Spike %R	Spike Added	Blank Spike Duplicate	Blk. Spk Dup. %R	RPD %	Control Limits %R	Control Limits %RPD	Flag
Analytes		[B]	[C]	[D]	[E]	Result [F]	[G]				
Chloride	<0.858	250	267	107	250	270	108	1	90-110	20	

Relative Percent Difference RPD = $200^{*}|(C-F)/(C+F)|$ Blank Spike Recovery [D] = $100^{*}(C)/[B]$ Blank Spike Duplicate Recovery [G] = $100^{*}(F)/[E]$ All results are based on MDL and Validated for QC Purposes



Form 3 - MS / MSD Recoveries

Project Name: BRIDGE STATE



Work Order # :	552757						Project II): 088210	0-32			
Lab Batch ID:	3017050	QC- Sample ID:	552867	-001 S	Ba	tch #:	1 Matrix	k: Soil				
Date Analyzed:	05/11/2017	Date Prepared:	05/11/2	017	Ar	alyst: 1	MGO					
Reporting Units:	mg/kg		N	IATRIX SPIK	E / MAT	RIX SPI	IKE DUPLICA	TE REC	OVERY	STUDY		
Inorga	nic Anions by EPA 300/300.1	Parent Sample Result	Spike Added	Spiked Sample Result [C]	Spiked Sample %R	Spike Added	Duplicate Spiked Sample Result [F]	Spiked Dup. %R	RPD %	Control Limits %R	Control Limits %RPD	Flag
	Analytes	[A]	[B]	[C]	/0K [D]	[E]	Kesunt [F]	[G]	70	/0K	70KF D	
Chloride		8.54	247	260	102	247	269	105	3	90-110	20	
Lab Batch ID:	3017050	QC- Sample ID:	552868	-001 S	Ba	tch #:	1 Matrix	k: Soil				
Date Analyzed:	05/11/2017	Date Prepared:	05/11/2	017	Ar	alyst: 1	MGO					
Reporting Units:	mg/kg	MATRIX SPIKE / MATRIX SPIKE DUPLICATE RECOVERY STUDY										
Inorgai	Inorganic Anions by EPA 300/300.1		Spike Added	Spiked Sample Result [C]	Spiked Sample %R	Spike Added	Duplicate Spiked Sample Result [F]	Spiked Dup. %R	RPD %	Control Limits %R	Control Limits %RPD	Flag
	Analytes	Result [A]	[B]	[C]	/0K [D]	[E]	Kesult [F]	[G]	/0	/0K		
Chloride		7190	248	7040	0	248	7080	0	1	90-110	20	X

Matrix Spike Percent Recovery $[D] = 100^{\circ}(C-A)/B$ Relative Percent Difference RPD = $200^{\circ}|(C-F)/(C+F)|$ Matrix Spike Duplicate Percent Recovery [G] = 100*(F-A)/E

Distribution: WHITE – Fully Executed Copy (CRA)		Anna Manna	RELINQUISHED BY	TAT Required in business days (use separate COCs for different TATs): 1 Day 2 Days 3 Days 1 Week 2 Week Other:	12	11	10	U		7) ол	4	U ODGDU CA	1 SS-089210-050917-01-1	PRESERVATION - (S	The SAMPLE IDENTIFICATION (Containers for each sample may be combined on one line)	sampler(s): A Malleus	GHD Chemistry Contact	Project Location: LIC Awardy	Project Nov Phase/Task Code: 08020	GHD
			DHN	COCs for different : ☐ 2 Week ☐ Other:					+	+			1 that can	11/20/20	EE BACK OF COC	ine) (mm/dd//yy)		the	MAN	132	02757
THE CHAIN OF CUSTODY IS A LEGAL DOCUMENT – YELLOW – Receiving Laboratory Copy		Con 111 1C	2 DATE TIME											IIHTSO 6 X	PRESERVATION - (SEE BACK OF COC FOR ABBREVIATIONS)		of COC)	c) _ 30	SAMPLE TYPE	Laboratory Name: Lab Contact:	Nº O
- ALL FIELDS MUST BE COMPLETED ACCURATELY PINK – Shipper GOLDENROD – Sampling Crew	3.	2 Manauf	1. RECEIVED BY	Notes/Special Requirements: Temp J. 4°C															Anal YSIS REQUESTED (See Back of COC for Definitions)	1(0	USTODY REC
GOLDENROD – S		2 a	ر	-												Total Con	tainers/sam		(S)	Midland	ORD ABQ, MM
ampling Crew		lenco	COMPANY													MS/MSD I		Airbill No:	Carrier:	X	1.87110CC Fax:
GHD Form: COC-10B (20110804)		SC:01 11015	DATE TIME	-							Pag	ge 11 o	f 13)	COMMENTS/ SPECIAL INSTRUCTIONS	Total # of Containers:	000		Cooler No:	COC NO.: 55530





Client: GHD-Albuquerque, NM

XENCO Laboratories Prelogin/Nonconformance Report- Sample Log-In

Acceptable Temperature Range: 0 - 6 degC



Air and Metal samples Acceptable Range: Ambient Date/ Time Received: 05/10/2017 10:25:00 AM Temperature Measuring device used : R9 Work Order #: 552757 Comments Sample Receipt Checklist 2.4 #1 *Temperature of cooler(s)? #2 *Shipping container in good condition? Yes #3 *Samples received on ice? Yes #4 *Custody Seal present on shipping container/ cooler? Yes #5 *Custody Seals intact on shipping container/ cooler? Yes N/A #6 Custody Seals intact on sample bottles? #7 *Custody Seals Signed and dated? N/A #8 *Chain of Custody present? Yes #9 Sample instructions complete on Chain of Custody? Yes #10 Any missing/extra samples? No #11 Chain of Custody signed when relinguished/ received? Yes #12 Chain of Custody agrees with sample label(s)? Yes #13 Container label(s) legible and intact? Yes #14 Sample matrix/ properties agree with Chain of Custody? Yes #15 Samples in proper container/ bottle? Yes #16 Samples properly preserved? Yes #17 Sample container(s) intact? Yes #18 Sufficient sample amount for indicated test(s)? Yes #19 All samples received within hold time? Yes #20 Subcontract of sample(s)? N/A #21 VOC samples have zero headspace? N/A #22 <2 for all samples preserved with HNO3,HCL, H2SO4? Except for N/A samples for the analysis of HEM or HEM-SGT which are verified by the analysts. #23 >10 for all samples preserved with NaAsO2+NaOH, ZnAc+NaOH? N/A

* Must be completed for after-hours delivery of samples prior to placing in the refrigerator

Analyst:

PH Device/Lot#:

Checklist completed by: Marithza Anaya

Date: 05/10/2017

Checklist reviewed by: Mmg Moah

Date: 05/10/2017