

SOIL BORING / MONITOR WELL LOG

Project:	CONDOR 32 STATE REUSE PIT
Project Number:	—
Client:	EOG RESOURCES
Boring / Well Number:	B-1
Total Depth:	75
Surface Elevation:	N/A
Geologist:	—
Latitude:	—

Drilling Company: **WHITE DRILLING**

Driller: **DALLAS RADAR**

Drilling Method: **AIR ROTARY**



Bore Hole Diameter: **5"**

Screen: Diam. Length Slot Size

Casing: Diam. Length Type

Date Drilled: **07/02/2018**

Drill Rig: **FAILING 1500 AIR ROTARY RIG**

DEPTH IN FEET	SYMBOL	SAMPLE	MATERIAL DESCRIPTION	N-BLOWS PER FOOT	TEXAS CONE PENETROMETER		Qp (tsf)	DEPTH SCALE				
					1st 6"	2nd 6"						
5			TAN SAND									
		SS	- DRY - NO MOISTURE	12								
10			CALICHE									
		SS	- DRY - NO MOISTURE	50/2"								
5			- DRY - NO MOISTURE	6								
		SS	TAN SAND									
20			- DRY - NO MOISTURE	59								
		SS	TAN TIGHT PACKED SAND									
5			- DRY - NO MOISTURE	50/4"								
		SS	- DRY - NO MOISTURE	50/5"								
30			- DRY - NO MOISTURE	50/1"								
		SS	TAN SANDSTONE									
40			- DRY - NO MOISTURE	50/3"								
		SS	- DRY - NO MOISTURE									
CONTINUED ON NEXT SHEET												
NOTE NO GROUNDWATER WAS PRESENT DURING OR AT COMPLETION OF DRILLING ACTIVITIES.												

SOIL BORING / MONITOR WELL LOG

Project: **CONDOR 32 STATE REUSE PIT**

Drilling Company: **WHITE DRILLING**

Project Number: _____

Driller: **DALLAS RADAR**

Client: **EOG RESOURCES**

Drilling Method: **AIR ROTARY**

Boring / Well Number: **B-1 (CONT.)**

Bore Hole Diameter: **5"**

Total Depth: **75**

Screen:	Diam.	Length	Slot Size
---------	-------	--------	-----------

Surface Elevation: **N/A**







Casing: Diam. _____ Length _____ Type _____

Geologist: _____

Date Drilled: 07/02/2018

Latitude: _____

Drill Rig: **FAILING 1500 AIR ROTARY RIG**

DEPTH IN FEET	SYMBOL	SAMPLE	MATERIAL DESCRIPTION	N-BLOWS PER FOOT	TEXAS CONE PENETROMETER		Qp (tsf)	DEPTH SCALE
					1st 6"	2nd 6"		
5		SS	TAN SANDSTONE - DRY - NO MOISTURE	50/1"				
50		SS	- DRY - NO MOISTURE	50/5"				
5			RED SANDY CLAY					
5		SS	- DRY - NO MOISTURE	50/4"				
60		SS	- DRY - NO MOISTURE	50/1"				
5		SS	TAN SANDSTONE WITH THICK CLAY LAYERS - DRY - NO MOISTURE	50/ 1/2"				
70		SS	- DRY - NO MOISTURE	50/1"				
5		SS	- DRY - NO MOISTURE	50/ 1/2"				
TOTAL DEPTH OF BORING 75 FEET								
NOTE NO GROUNDWATER WAS PRESENT DURING OR AT COMPLETION OF DRILLING ACTIVITIES.								