

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

|  |
|--|
| WELL API NO.<br>30-025-34970   |
| Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| State Oil & Gas Lease No.<br>N/A   |
| Lease Name or Unit Agreement Name<br>Howser  |
| Well No.<br>1  |
| Pool name or Wildcat<br>House : Blinebry   |

|  |  |
|--|--|
| <b>SUNDRY NOTICES AND REPORTS ON WELLS</b><br>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)      |  |
| Type of Well:<br>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>   |  |
| Name of Operator<br>Trilogy Operating, Inc   |  |
| Address of Operator<br>P.O. Box 7606, Midland, Texas 79708   |  |
| Well Location<br>Unit Letter <u>J</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>East</u> Line<br>Section <u>1</u> Township <u>20S</u> Range <u>38E</u> NMPM <u>Lea</u> County |  |
| Elevation (Show whether DF, RKB, RT, GR, etc.)<br>3484 GR  |  |

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/5/04 - MIRU pulling unit, POH w/ tbg - RUWL and dump 35' of cement on top of CIBP @ 6300', Set CIBP @ 6000' and dump 35' of cement on top of CIBP @ 6000', RDMO WL, RIH w/ tbg to 5990' - circulate hole w/ 9.6 ppg drilling mud, pull tbg to 5664' and spot 50 sx cement plug, pull tbg to 4418' and spot 50 sx cement plug, pull tbg to 1623' and spot 50 sx cement plug w/ 3% Cacl2 - wait on cement approx 2 hrs, RIH and tag hard top of cement @ 628', POH w/ tbg to 415' spot 35 sx cement, POH w/ tbg - use cementers hose and put in hole 20' - cement to surface w/ 10.62 cement - RDMO cementers @ 10:00 PM

4/6/04 - Weld on dry hole marker w/ well location information, start location clean-up, last well on lease so roads will also be reclaimed

Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael G. Mooney TITLE Engineer DATE 04-13-2004  
TYPE OR PRINT NAME Michael G. Mooney TELEPHONE NO. 432/686-2027

(This space for State Use)

APPROVED BY Harry W. Wink OC FIELD REPRESENTATIVE II/STAFF MANAGER  
CONDITIONS OF APPROVAL, IF ANY  
DATE MAY 03 2004