Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M. Oil Cons. Division 1625 N. French Dr. Hobbs, NM 88240

FORM APPROVED OMB No. 1004-0135

Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					5. Lease Serial No. LC-068882A 6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side 1. Type of Well					7. If Unit or CA/Agreement, Name and/or No.			
X Oil Well Gas Well Other					8. Well Name and No.			
2. Name of Operator					Flood AFN Federal 1			
Yates Petroleum Corporation					9. API Well No.			
3a. Address	Bb. Phone No. (include	•			30-025-30944			
105 S. 4th Str., Artesia, NM 88210 4. Location of Well (Footage, Sec.,T.,R.,M., OR Survey Description)			505-748-1471			10. Field and Pool, or Exploratory Area Lusk Delaware, West		
4. Education of West (Footage, Sec., F., N., W., On Survey Description)						11. County or Parish, State		
330' FSL & 660' FWL Sec. 30-T19S-R32E					Lea, NM			
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RI					the control of the co			
TYPE OF SUBMISSION TYPE OF ACTION								
TITE OF SUDIVIDUOUN TIPE OF ACTION								
	Acidize	Deepen		Production (S	tart/Resume)	Water Shu	t-Off	
Notice of Intent	Alter Casing	Fracture Treat	Fracture Treat		Reclamation		rity	
	Casing Repair	New Construct	New Construction Recomple			X Other	Squeeze	
Subsequent Report	Change Plans	Plug and Aban	Plug and Abandon Temporaril		y Abandon			
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal					
following complete of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 4-14-04 to 4-30-04 Set RBP @ 5780' and spotted 20' sand on top. Set cement retainer @ 5700'. Squeezed perfs 5741-56' w/50 sx "H" @ 2400#. Set cement @ 2000#. Set cement retainer @ 4594' and squeezed perfs 4661-76' w/50 sx "H" @ 1950#. Set cement retainer @ 4368' and squeezed perfs 4424-38' w/80 sx "H" @ 2100#. Drilled out retainer @ 4368' and cement to 4420'. Drilled cement to retainer @ 4594'. Tested 4424-38' to 500#. Drilled retainer @ 4594' and cement to 4740'. Tested 4661-76' to 500#. Drilled retainer @ 5332', retainer @ 5890' and cement to 5720'. Drilled out cement on perfs/5741-56' and tested to 500#. Cleaned sand off RBP @ 5850'. Moved RBP to 7050'. Spotted drum of CaSo4 across perfs 7009-25'. Pulled packer to 6992'. Acidized 7009-25' w/500 gal 15% NEFE HCI. 2-7/8" x 5-1/2" TAC @ 6793', SN @ 7158', bull plug @ 7197' Producing from Delaware 6870-7166'								
Well is back on produc 14. I hereby certify that the foregoing is true					5 2	ANA -		
Name (Printed/Typed) Stormi Davis	o and correct	Title	Regulatory	Compliar	MAY 5 2	004 an		
Signature Storm	Janus		5/3/04	†'L	GARY GOUR TROLEUM EN	ILEY		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved by			Title					
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willbully to make to any department or agency of the United								

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction