Submit 3 Copies To Appropriate District Office State of New M	Mexico Form C-103
District I Energy, Minerals and Na	
1625 N. French Dr., Hobbs, NM 88240 District II	WELL API NO. 30 025 33417
1301 W. Grand Ave., Artesia, NM 88210 District III 1220 South St. Fu	5 Indicate Type of Longo
1000 Rio Brazos Rd., Aztec, NM 87410	STATE X FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No.
87505	B-2317
SUNDRY NOTICES AND REPORTS ON WEL	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101)	FOR GUOTI
PROPOSALS.)	State 35 Unit 8. Well Number
1. Type of Well: Oil Well X Gas Well Other	28
2. Name of Operator 9. OGRID Number	
McGowan Working Partners, Inc.	
3. Address of Operator	10. Pool name or Wildcat
P O Box 55809, Jackson MS 39296-5809	Vacuum Grayburg / San Anres
4. Well Location	
Unit Letter P: 1170 feet from the south line and 660 feet from the east line	
Section 35 Township 17S Range 34E NMPM County Lea	
Section 35 Township 17S Range 34E NMPM County Lea 11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
4008' GL	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. PLUG AND
PULL OR ALTER CASING MULTIPLE	CASING TEST AND
COMPLETION	CEMENT JOB
OTHER: coplare tubing and pump	OTHER: replaced tubing and pump X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
Pulled tubing, packer and pump; ran in hole with stainless steel stinger, 2-1/4" WBBL with seat nipple above it, anchor (40K), 95 jts 2-7/8" N-80, crossover, 35 jts 3-1/2" N-80; set anchor and pulled 21,000#; set slips.	
04/24/04 Ran in hole with 1-1/2" pump, 24' brass/Ni-Carb insert bottom hold down, 3 1-3/4" sinker bars, 1 7/8" rods, 43 7/8" rods, 42 1" rods, 2 8' subs, 1 2' sub, 26' 1-1/2" polish rod; rigged down.	
Set bottom of tubing at 4280.56'. Returned well to service.	
23 23 24 25 25 25 1 Returned well to service.	
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	E'es, allie
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Thoreby county unagene information above as true and complete to the best of my knowledge and belief.	
SIGNATURE	Regulatory Officer DATE May 5, 2004
Type or print name E-mail	address: Telephone No.
(This space for State use)	
APPPROVED BY TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE AV 1 3 2004	
Conditions of approval, if any:	