

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-29398
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Chevron USA Inc		6. State Oil & Gas Lease No.
3. Address of Operator 15 Smith Rd, Midland, TX, 79705		7. Lease Name or Unit Agreement Name: Eunice Monument South Unit
4. Well Location Unit Letter <u>G</u> : <u>1980</u> feet from the <u>North</u> line and <u>2080</u> feet from the <u>East</u> line Section <u>22</u> Township <u>21-S</u> Range <u>36-E</u> NMPM <u>Lea</u> County		8. Well No. 447
10. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. Pool name or Wildcat Eunice Monument, Grayburg, San Andres

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐


SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. ~~SEE RULE 103. For Multiple Completions.~~ Attach wellbore diagram of proposed completion or recompletion.

HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED.

1. Notify OCD 24 hrs prior to MI and RU.
2. RIH Tag 5 1/2" CIBP at 3920, spot 25sx, plug 3920-3700 (Grayburg) WOC Tag.
3. Displace hole w/MLF 9.5# Brine w/25# gel P/BBL.
4. Spot 35sx, plug 2900-2600 (8 5/8 Shoe, B-Salt) WOC Tag.
5. Perf 4 holes at 1600, sqz 75sx, plug 1600-1300 (T-Salt) WOC Tag.
6. Perf 4 holes at 410, sqz 60sx, plug 410-200 (11 3/4 Shoe) WOC Tag.
7. 10sx Surf, install dry hole marker.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G.R. Bledsoe TITLE HES Specialist DATE 5/5/2004

Type or print name G.R. Bledsoe

Telephone No. (432) 687-7153

(This space for State use)

APPROVED BY Chris Williams TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE MAY 18 2004

Conditions of approval, if any:

Submit C-144 when closing pit! CW

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRON USA INC.

LEASE NAME EMMIE MONUMENT SOUTH UNIT

WELL # 447

SECT 22 TWN 21-S RNG 36-E

FROM 1980 (NSL 2080) (EWL)

TD 4051 FORMATION @ TD Grayburg

PBTD FORMATION @ PBTD

11 3/4
@ 365
TOC SURF

8 5/8
@ 2850
TOC SURF

MLF
4/25/01
CIBP SET @ 3920

5 1/2
@ 4051
TOC 2000

TD 4051

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	11 3/4	365	SURF	CIRC.
INTMED 1	8 5/8	2850	SURF	CIRC.
INTMED 2				
PROD	5 1/2	4051	2000	T.S.

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	3943- 3983
INTMED 2	OPENHOLE	
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	GRAYBURG	25	3920
YATES	2	8 5/8 SHOE	35	2900
QUEEN	3	T-SALT	75	1600
GRAYBURG	4	11 3/4 SHOE	60	410
SAN ANDRES	5	SURF	10	10
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				