

Submit 3 Copies To Appropriate District
Tice
strict I
25 N. French Dr., Hobbs, NM 88240
strict II
01 W. Grand Ave., Artesia, NM 88210
strict III
00 Rio Brazos Rd., Aztec, NM 87410
strict IV
20 S. St. Francis Dr., Santa Fe, NM
505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-36191
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No. 30730
7. Lease Name or Unit Agreement Name: R.E. GRAHAM "7"
8. Well No. #8
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

Type of Well:
Oil Well ☒ Gas Well ☐ Other

Name of Operator
CIMAREX OPERATING COMPANY

Address of Operator
EAST 5TH STREET SUITE 1000, TULSA, OKLA 74103

Well Location

Unit Letter **M** : **660** feet from the **SOUTH** line and **400** feet from the **WEST** line

Section **7** Township **18S** Range **32E** NMPM County **LEA**

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3760 G.L.

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ☒
Approved as to plugging and abandonment.

CASING TEST AND under bond is retained until
CEMENT JOBS surface restoration is completed.

OTHER: ☐

2. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. **PER A WELL ON 4/12/13/03 AS FOLLOWS:**

ST 100' PLUG WITH 27 SX CLASS "C" CEMENT FROM 3750' - 3650' (T.D. @ 3750)
ST 100' PLUG WITH 50 SX CLASS "C" CEMENT FROM 2476' - 2376'
ST 100' PLUG WITH 34 SX CLASS "C" CEMENT FROM 1050' - 950'
ST 420' PLUG WITH 111 SX CLASS "C" CEMENT FROM 777' - 357' (CEMENT W/ 270 S)
HT 6 HRS TIE IN & TAG PLUG @ 357'
ST 60' PLUG WITH 17 SX CLASS "C" CEMENT FROM 60' TO SURFACE
T 14" CONDUCTOR & 8 5/8" CSG 4' BELOW G.L. & C AP. WELD dry hole
LE WITH WELL INFORMATION & COVER HOLE

EMENT by SCHLUMBERGER - SLURRY MIXED @ 14.8 ppg YIELD 1.33 FT³/SX

hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE **Ronnie Goddard**

TITLE **Drilling Supervisor**

DATE **4/15/03**

Type or print name **RONNIE GODDARD**

Telephone No **(405) 823-6798**

This space for State use)

APPROVED BY **Larry W. Wink**

TITLE **Approved Representative II/STAFF MANAGER**

Conditions of approval, if any:

Liability under bond is retained until
surface restoration is completed.

MAY 01 2003

← MARKER POLE WITH WELL INFORMATION

GRAHAM 7" WELL #6

SECTION 7-18S-32E

330 FSL 330 FEL

SEA COUNTY, NEW MEXICO

↑ 4' BELOW S.L.
↓ WITH 1/4" PLATE

60' 17SX CEMENT PLUG
FROM 60' TO SURFACE

14" CONDUCTOR
SET @ 40'

393' 102SX CEMENT
PLUG FROM 778'-385'

8 5/8 24" K55 ST&L
SET @ 728' CEMENT TO SURF.

100' 34SX CEMENT PLUG
FROM 1050' TO 950'

← 7 1/8" OPENHOLE

100' 50SX CEMENT PLUG
FROM 2622' TO 2522'

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

100' 27SX CEMENT PLUG
FROM 3780' TO 3680'

T.D. 3780'