

DISTRICT I

1625 N. French Dr., Hobbs NM 88240

DISTRICT II

1301 W. Grand Avenue, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87504-2088

Form C-103

Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-29741
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-5930
3. Address of Operator 105 South 4th Str., Artesia, NM 88210		7. Lease Name or Unit Agreement Name Kookaburra AZB State
4. Well Location Unit Letter B : 660 feet from the North line and 1980 feet from the East line Section 24 Township 12S Range 34E NMPM County Lea		8. Well No. 2
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4127.5' GR		9. Pool Name or Wildcat Wildcat Morrow & Wildcat Atoka

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Completion Operations ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

4-21-04 5-1-04 Perforated Morrow (6 JSPF) 12138-41' (18), 12148-50' (12) and 12164-70' (36) for total of 66 - .25" holes. Acidized w/1500 gal 7-1/2% Morrow acid. Frac w/30000 gal 40# Medallion 40Q foam w/20000# 20/40 Interprop. Perforated Atoka (6 JSPF) 11926-32' (36) and 11952-58' (36), for total of 72 - .25" holes. Spearhead 1500 gal 7-1/2% Morrow acid. Frac w/20500 gal 40# Medallion 40Q foam w/12450# 20/40 Interprop.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 5/10/04
Type or print name **Stormi Davis** Telephone No. **505-748-1471**
(This space for State use)
APPROVED BY [Signature] TITLE PETROLEUM ENGINEER DATE JUN 14 2004
Conditions of approval, if any: