

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
March 4, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-04431
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Eunice Monument South Unit
8. Well Number 168W
9. OGRID Number
10. Pool name or Wildcat Grayburg - San Andres

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☐ Other ☐ Injector

2. Name of Operator  
Chevron USA Inc

3. Address of Operator  
15 Smith Rd, Midland, TX 79705

4. Well Location  
Unit Letter O : 660 feet from the South line and 1980 feet from the East line  
Section 36 Township 20-S Range 36-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

**Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)**

Pit Location: UL O Sect 36 Twp 20S Rng 36E Pit type Steel Depth to Groundwater 170 Distance from nearest fresh water well Over 1000'  
Distance from nearest surface water \_\_\_\_\_ Below-grade Tank Location UL \_\_\_\_\_ Sect \_\_\_\_\_ Twp \_\_\_\_\_ Rng \_\_\_\_\_ ;  
660 feet from the South line and 1980 feet from the East line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI and RU.
2. Set 5 1/2" CIBP at 3675, spot 25sx, plug from 3675-3500 (Grayburg) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# gel P/BBL.
4. Spot 25sx, plug from 2700-2500 (Yates, B-Salt).
5. Perf 4 holes at 1200, sqz 45sx, plug rom 1200-1000 (7 5/8 Shoe, T-Salt) WOC Tag.
6. Perf 4 holes at 300, sqz 45 sx, plug from 300-150 (10 3/4 Shoe) WOC Tag.
7. 10sx Surf, install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE G.R. Bledsoe TITLE HES Specialist DATE 6/17/2004  
Type or print name G.R. Bledsoe E-mail address: gbledsoe@chevron.com Telephone No. 432-687-7153

(This space for State use)

APPROVED BY Harry W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JUN 22 2004  
Conditions of approval, if any:

# PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRON USA INC.

LEASE NAME EUNICE MONUMENT SOUTH UNIT

WELL # 168 W

SECT 36 TWN 20-S RNG 36-E  
FROM 660 N1S1 1980 EWL       
TD 3910 FORMATION @ TD Grayburg  
PBDT      FORMATION @ PBDT     

10 3/4  
@ 254  
TOC SURF

75/8  
@ 1086  
TOC 227

5 1/2  
@ 3736  
TOC 2076

TD 3910

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	10 3/4	254	SURF	CIRC.
INTMED 1	75/8	1086	227	CALC
INTMED 2				
PROD	5 1/2	3736	2076	CALC.

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2	OPENHOLE	3736 - 3910
PROD		

## \*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)		CIBP	25	3675
YATES		B-SALT	25	2700
QUEEN		75/8 S	45	1200
GRAYBURG		10 3/4 S	45	300
SAN ANDRES		SURF	10	10
CAPTAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

**New Mexico Office of the State Engineer**  
**Well Reports and Downloads**

Township: 20S Range: 36E Sections:

NAD27 X: Y: Zone: Search Radius:

County: LE Basin: Number: Suffix:

Owner Name: (First) (Last) Non-Domestic Domestic  
All

Well / Surface Data Report

Avg Depth to Water Report

Water Column Report

Clear Form

WATERS Menu

Help

**AVERAGE DEPTH OF WATER REPORT 06/16/2004**

Bsn	Tws	Rng	Sec	Zone	X	Y	Wells	(Depth Water in Feet)		
								Min	Max	Avg
L	20S	36E	01				1	40	40	40
L	20S	36E	02				2	92	92	92
L	20S	36E	09				2	38	38	38
L	20S	36E	14				5	20	53	45
L	20S	36E	18				2	34	34	34
L	20S	36E	26				2	170	170	170

Record Count: 14

