

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
March 4, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-04462
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Injector <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Chevron USA Inc		6. State Oil & Gas Lease No.
3. Address of Operator 15 Smith Rd, Midland, TX 79705		7. Lease Name or Unit Agreement Name Eunice Monument South Unit
4. Well Location Unit Letter <u>N</u> : <u>3508</u> feet from the <u>North</u> line and <u>410</u> feet from the <u>West</u> line Section <u>4</u> Township <u>21-S</u> Range <u>36-E</u> NMPM Lea County		8. Well Number 259
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number
		10. Pool name or Wildcat Grayburg - San Andres

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL N Sect 4 Twp 21S Rng 36E Pit type Steel Depth to Groundwater 200 Distance from nearest fresh water well Over 1000'
Distance from nearest surface water _____ Below-grade Tank Location UL _____ Sect _____ Twp _____ Rng _____ ;
3508 feet from the North line and 410 feet from the West line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI and RU.
2. Set 5 1/2" CIBP at 3650, spot 25sx, plug from 3650-3500 (Grayburg) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# gel P/BBL.
4. Spot 25sx, plug from 2700-2500 (Yates, B-Salt).
5. Spot 40sx, plug from 1700-1300 (7 5/8 Shoe, T-Salt) WOC Tag.
6. Spot 25sx, plug from 400-200 (10 3/4 Shoe) WOC Tag.
7. 10sx Surf, install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE G.R. Bledsoe TITLE HES Specialist DATE 6/17/2004
Type or print name G.R. Bledsoe E-mail address: gbledsoe@chemtexnm.com Telephone No. 432-687-7153

(This space for State use)

APPROVED BY Larry W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER
Conditions of approval, if any: _____ DATE JUN 22 2004

PLUGGING & ABANDONMENT WORKSHEET (3 STRING CSNG)

OPERATOR CHEVRON USA INC.
 LEASE NAME EUNICE MONUMENT SOUTH UNIT
 WELL # 259 W

SECT 4 TWN 21-S RNG 36-E
 FROM 3508 NSL 410 ENL
 TD 3900 FORMATION @ TD GRAYBURG
 PBTD FORMATION @ PBTD

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	10 3/4	329	SURF	Circ
INTMED 1	7 5/8	1614	SURF	Circ
INTMED 2				
PROD	5 1/2	3783	SURF	Circ

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	3701 - 3760
INTMED 2	OPENHOLE	
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)		CIBP	25	3650
YATES		B-SALT	25	2700
QUEEN		7 5/8 S	40	1700
GRAYBURG		10 3/4 S	25	400
SAN ANDRES		SURF	10	10
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

MLF

10 3/4

@ 329

TOC SURF

MLF

7 5/8

@ 1614

TOC SURF

MLF

5 1/2

@ 3783

TOC SURF

TD 3900

New Mexico Office of the State Engineer
Well Reports and Downloads

Township: 21S Range: 36E Sections: _____

NAD27 X: _____ Y: _____ Zone: _____ Search Radius: _____

County: LE Basin: _____ Number: _____ Suffix: _____

Owner Name: (First) _____ (Last) _____ Non-Domestic Domestic
All

Well / Surface Data Report

Avg Depth to Water Report

Water Column Report

Clear Form

WATERS Menu

Help

AVERAGE DEPTH OF WATER REPORT 06/16/2004

Bsn	Tws	Rng	Sec	Zone	X	Y	Wells	(Depth Water in Feet)		
								Min	Max	Avg
CP	21S	36E	10				1	200	200	200
CP	21S	36E	16				1	195	195	195
CP	21S	36E	18				1	106	106	106
CP	21S	36E	23				1	150	150	150
CP	21S	36E	25				1	148	148	148

Record Count: 5

