Single S		State of New Mexico	Form C-103
DIL CONSERVATION DIVISION DIAMENTAL DISTRICT OF CONSERVATION DIVISION DISTRICT. DISTRI		Energy, Minerals and Natural Resources	
1301 W. Grand Are, Aracis, NM 8210 1220 South St. Francis Dr. Santa Fc, NM 87505 Santa			
STATE STAT	1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION		
District of Not Use Tills Form For Proposed to To Defile On Property of Sunday For Not Not Not Person Not Not Person Not Not Person Not			
SUNDRY NOTICES AND REPORTS ON WELLS ON ONT LIST THIS FORM FOR PROPOSALS TO BEILL OR TO DEFERNOR PLIG BACK TO A DEFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS) 1. Type of Well: Oil Well	District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS OD NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DIFFERENT ESSERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCI PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DIFFERENT ESSERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCI PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DIFFERENT ESSERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCI PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DIFFERENT ESSERVOIR USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCI PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DOING FOR SUCI PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO A DOING FOR SUCI PROPOSALS THE PROPOSALS TO DRILL OR TO DEPENS OR PLUG BACK TO BE A DIFFERENT ESSERVOIR USE TO DRILL OR TO DEPENS OR PLUG BACK TO DRILL OR TO DEPENS OR PLUG BACK TO DRILL OR TO DEPENS OR TO DRILL OR DRILL OR TO DRILL OR			
DOING TUSE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DOING BERK STARE COMPENDED BY WEIL OIL WEIL			
Dolly BER State Com	l e e e e e e e e e e e e e e e e e e e	7. Lease Name or Unit Agreement Name	
1. Type of Well: Git Well:	DIFFERENT RESERVOIR. USE "APPLICA	Dolly BER State Com	
Oil Well	l '		
2. Name of Operator Yates Petroleum Corporation 3. Address of Operator 105 South Fourth Street, Artesia, NM 88210 4. Well Location Unit Letter M : 660 feet from the South line and 660 feet from the West line Section 34 Township 108 Range 34E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4.201 'GR 4. Township 108 Range 34E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4.201 'GR 4.201 'GR 4. Township 108 Range 34E NMPM Lea County 12. Check Application (For pi or below-grade Tank Accation UL Sect Twp Rng Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Below-grade Tank Location UL Sect Twp Rng : feet from the line and feet from the line 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUS AND ABANDON COMMENCE DRILLING OPNS PUBB CASING COMMENCE DRILLING OPNS PUBB CASING COMMENCE DRILLING OPNS PUBB CASING ABANDONMENT TEMPORARILY ABANDON CHANGE PLANS COMPLETION OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion or recompletion with the public of the p		Other	1
Yates Peroleum Corporation 0.25575			9 OGRID Number
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210 4. Well Location Unit Letter M : 660 feet from the South line and 660 feet from the Section 34 Township 10S Range 34E NMFM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4201 GR Plt or Below grade Tank Application (For nit or below-grade tank closures, a form C-144 must be attacked) Plt Location: U Sect Twp Rup_ Plt type Depth to Groundwater Distance from nearest surface water Below-grade Tank Location U Sect Twp Rup_; feet from the line and feet from the			,
Well Location			4. Pool name or Wildcat
Unit Letter M : 660 feet from the South line and 660 feet from the West line Section 34 Township 10S Range 34E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4201 GR Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached) Pit Location: UL. Sect Twp Rng Pit type Dept to Groundwater Distance from nearest fresh water well Distance from nearest surface water Below-grade Tank Location: UL. Sect Twp Rng ; feet from the Ine and feet from the Ine 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433". Set 13-3/8" 48# casing @ 433". Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250" @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250". Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400" (TS). Ran 1" to 422" and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 TITLE: Regulatory Compliance Technician DATE: 7-6-04		a, NM 88210	Sand Springs; Mississippian (Gas)
Section 34 Township 10S Range 34E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4201' GR Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-14d must be attached) Pit Location: UL_Sect_Twp_Rng_Pit type			
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4201' GR	Unit Letter M: 6	60 feet from the South line and	660 feet from theWest line
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4201' GR	Section 34	Township 10S Range 34F	NMPM Lea County
Sect Twp Rng Pit type Depth to Groundwater Distance from nearest fresh water well	Section		
Pit Location: U Sect Twp Rng Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Below-grade Tank Location UL Sect Twp Rng; feet from the line and		4201' GR	
Distance from nearest surface water Below-grade Tank Location UI. Sect Twp Rng ; feet from the line and feet from the line 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK ADADAM CASING ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDON ABANDON ABANDON CEMENT JOB COMMENCE DRILLING OPNS ABANDON ABANDON CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (15). Ran 1" to 422' and spotted 135 sx ("C. circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 TITLE: Regulatory Compliance Technician DATE: 7-6-04 APPPROVED BY TITLE: DISTRICT SUPERVICES (GENERDAL MRAFIBILL OR 2000)	Pit or Below-grade Tank Application (For p	oit or below-grade tank closures, a form C-144 must be atta	ched)
12. Check Appropriate Box to Indicate Nature of Notice, Report of Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS PLUG AND ABANDON ABANDON ABANDON ABANDON ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND ABANDONMENT OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 TITLE: Regulatory Compliance Technician DATE: 7-6-04 APPPROVED BY TITLE: The District superposed Apple of the part of the pa	Pit Location: ULSectTwp	RngPit typeDepth to Groundwate	rDistance from nearest fresh water well
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE:	Distance from nearest surface water	Below-grade Tank Location ULSectT	wpRng;
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE:	feet from theline and	feet from theline	450730-
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE:			A
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE:	12 Check A	nnronriate Roy to Indicate Nature of Notic	e Report or Other Data
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTEMAR CASING COMMENCE DRILLING OPNS. PLUG AND ABANDON COMMENT CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded 21:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TTILE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) A. TTILE: Regulatory Compliance Technician DATE: 7-6-04			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLE: DISTRICT Superpyis Cap (SEAUSPALL ARACHEM)			
ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Surface and Intermediate Casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLES: SUSTRICT SUPERVISOR/GENERAL MRATIBAL AD 2 2000.	NOTICE OF INT	ENTION TO: SU	BSEQUENT REPORT OF:
PULL OR ALTER CASING	NOTICE OF INT	ENTION TO: SU PLUG AND ABANDON REMEDIAL WO	BSEQUENT REPORT OF:
OTHER: Surface and Intermediate Casing X	NOTICE OF INT	ENTION TO: SU PLUG AND ABANDON REMEDIAL WO	BSEQUENT REPORT OF: ORK ALTERING CASING Hobbs ORILLING OPNS. PLUG AND
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) TITLE: DISTRICT SUPPRVIS OR /GENERAL ADATIBLE OR 2002.	NOTICE OF INT	ENTION TO: PLUG AND ABANDON CHANGE PLANS COMMENCE D	BSEQUENT REPORT OF: ORK ALTERING CASING Hobbs PLUG AND ABANDONMENT
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) TITLE: DISTRICT SUPPRVIS OR /GENERAL ADATIBLE OR 2002.	NOTICE OF INT	ENTION TO: PLUG AND ABANDON REMEDIAL WO CHANGE PLANS COMMENCE D MULTIPLE CASING TEST	BSEQUENT REPORT OF: ORK ALTEMAG CASING HODDS PRILLING OPNS PLUG AND ABANDONMENT AND
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed at closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan . SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) TITLE: DISTRICT SUPERVISOR (GENTERAL MARCHELL) and APPPROVED BY	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	ENTION TO: PLUG AND ABANDON REMEDIAL WO CHANGE PLANS COMMENCE D MULTIPLE CASING TEST CEMENT JOB	BSEQUENT REPORT OF: ORK ALTEHING CASING Hobbs PRILLING OPNS ABANDONMENT AND
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed at closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan . SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) TITLE: DISTRICT SUPERVISOR (GENTERAL MARCHELL) and APPPROVED BY	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	ENTION TO: PLUG AND ABANDON REMEDIAL WO CHANGE PLANS COMMENCE D MULTIPLE CASING TEST CEMENT JOB	BSEQUENT REPORT OF: ORK ALTEHING CASING Hobbs PRILLING OPNS ABANDONMENT AND
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed at closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan . SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) TITLE: DISTRICT SUPERVISOR (GENTERAL MARCHELL) and APPPROVED BY	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	ENTION TO: PLUG AND ABANDON REMEDIAL WO CHANGE PLANS COMMENCE D MULTIPLE CASING TEST CEMENT JOB	BSEQUENT REPORT OF: ORK ALTEHING CASING Hobbs PRILLING OPNS ABANDONMENT AND
6-21-04 MIRT and spudded @ 12:30 p.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48# casing @ 433'. Cemented w/220 sx Premium Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed at closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan. SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLED: DISTRICT SLIPERVIS OR /CENTERAL MARKEDIAL AND APPROVED BY	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	ENTION TO: PLUG AND ABANDON REMEDIAL WO CHANGE PLANS COMMENCE D MULTIPLE CASING TEST CEMENT JOB OTHER:	BSEQUENT REPORT OF: ORK ALTEMING CASING Hobbs ORILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X
Plus w/additives and tailed in w/200 sx. Cement circulated. WOC 21 hrs, 15 min. Reduced hole to 12-1/4" and resumed drilling. 6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan. SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 TITLE: DISTRICT SUPERVISOR/GENIERAL MARATEMED O 2004	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complete	PLUG AND ABANDON	BSEQUENT REPORT OF: ORK ALTERING CASING Hobbs ORILLING OPNS PLUC AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date
6-28-04 TD 12-1/4" hole to 4250' @ 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'. Cemented w/1180 sx Halliburton Lite Premium Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed by closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan. SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLED: DISTRICT SUPERVISOR/GENERAL MARKETIME OF 2001	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work	PLUG AND ABANDON	BSEQUENT REPORT OF: ORK ALTERING CASING Hobbs ORILLING OPNS PLUC AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date
Plus w/additives and tailed in w/200 sx. Estimated TOC @ 400' (TS). Ran 1" to 422' and spotted 135 sx "C". Circulated 25 sx to pit. (Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLE: DISTRICT SUPERVISOR/GENERAL MARKED III and DATE in the pitch of the pitch	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30	PLUG AND ABANDON	BSEQUENT REPORT OF: ORK ALTEMING CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND X Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium
(Notified Sylvia Dickey w/NMOCD of TS and 1" cement job.) WOC 37 hrs, 30 min. Reduced hole to 8-3/4" and resumed drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE: TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLE: DISTRICT SUPERVISOR/CENTRAL WARTEN! O 2004	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30	PLUG AND ABANDON	BSEQUENT REPORT OF: ORK ALTEMING CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND X Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @	PLUG AND ABANDON CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: Pted operations. (Clearly state all pertinent details, k). SEE RULE 1103. For Multiple Completions: Pp.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 ix. Cement circulated. WOC 21 hrs, 15 min. Reduction 7:15 a.m. Set 9-5/8" 36# and 40# casing @ 4250'	BSEQUENT REPORT OF: ALTEMING CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium
TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLE: Regulatory Compliance Technician DATE: 7-6-04 TITLE: Regulatory Compliance Technician DATE: 7-6-04 Title Calstrict Supervisory Compliance Technician DATE: 7-6-04	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 s	PLUG AND ABANDON CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 ix. Cement circulated. WOC 21 hrs, 15 min. Reduction Testing and 40# casing @ 4250' ix. Estimated TOC @ 400' (TS). Ran 1" to 422' at 15 min. Randow 10 min. Reduction 10 min. Red	BSEQUENT REPORT OF: ALTEMIS CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit.
TITLE: Regulatory Compliance Technician DATE: 7-6-04 Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITLE: Regulatory Compliance Technician DATE: 7-6-04 Title: Regulatory Compliance Technician DATE: 7-6-04 Title: Regulatory Compliance Technician DATE: 7-6-04	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 s	PLUG AND ABANDON CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 ix. Cement circulated. WOC 21 hrs, 15 min. Reduction Testing and 40# casing @ 4250' ix. Estimated TOC @ 400' (TS). Ran 1" to 422' at 15 min. Randow 10 min. Reduction 10 min. Red	BSEQUENT REPORT OF: ALTEMIS CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit.
Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITIES: DISTRICT SUPERVISOR/CENTRAL WARRENT OF A COMMENT OF THE PARTY OF THE PART	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 bx. Cement circulated. WOC 21 hrs, 15 min. Reductions. Testimated TOC @ 400' (TS). Ran 1" to 422' at 15 and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.)	BSEQUENT REPORT OF: ALTEMIS CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below-
Type or print name: Stormi Davis E-mail address: Telephone No. 505-748-1471 (This space for State use) APPPROVED BY TITIES: DISTRICT SUPERVISOR/CENTRAL WARRENT OF A COMMENT OF THE PARTY OF THE PART	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 bx. Cement circulated. WOC 21 hrs, 15 min. Reductions. Testimated TOC @ 400' (TS). Ran 1" to 422' at 15 and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.) WOC 37 hrs, 30 min. Reductions and 1" cement job.)	BSEQUENT REPORT OF: ALTEMIS CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below-
(This space for State use) APPPROVED BY TITUDE DISTRICT SUPERVISOR (CENTRAL MARKETS)	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250' @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of I hereby certify that the information al grade tank has been/will be constructed by c	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 cx. Cement circulated. WOC 21 hrs, 15 min. Reductions. The completion of th	ALTERING CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below— or an (attached) alternative OCD-approved plan
APPROVED BY WILLIAM TITLE DISTRICT SUPERVISOR OF CENTERAL WARDEN OF COMMENTAL WARREND OF COMMENTS OF C	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250' @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of I hereby certify that the information al grade tank has been/will be constructed by c	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 cx. Cement circulated. WOC 21 hrs, 15 min. Reductions. The completion of th	ALTERING CASING Hobbs PRILLING OPNS PLUG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below— or an (attached) alternative OCD-approved plan
APPPROVED BY William TITION DISTRICT SUPERVISOR (CENTERAL MARCHELL OF COMMENTAL MARCHELL OF COMENTAL MARCHELL OF COMMENTAL MARCHELL	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250' @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of I hereby certify that the information al grade tank has been/will be constructed by c SIGNATURE:	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 ex. Cement circulated. WOC 21 hrs, 15 min. Reductions. Tits a.m. Set 9-5/8" 36# and 40# casing @ 4250' ex. Estimated TOC @ 400' (TS). Ran 1" to 422' a control of TS and 1" cement job.) WOC 37 hrs, 30 min. Reductions and the complete to the best of my knowledged according to NMOCD guidelines. a general permit are compliant.	BSEQUENT REPORT OF: ALTEMOS CASING Hobbs PRILLING OPNS PLOG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below— or an (attached) alternative OCD-approved plan — nece Technician DATE: 7-6-04
	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 starting any proposed work or recompletion. 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 starting any proposed work or recompletion. 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 starting any proposed work or recompletion. I hereby certify that the information at grade tank has been/will be constructed by constructed by the starting any proposed work or recompletion. Type or print name: Stormi Davis	TENTION TO: PLUG AND ABANDON	BSEQUENT REPORT OF: ALTEMOS CASING Hobbs PRILLING OPNS PLOG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/1180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below— or an (attached) alternative OCD-approved plan — nee Technician DATE: 7-6-04
	NOTICE OF INT PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed wor or recompletion. 6-21-04 MIRT and spudded @ 12:30 Plus w/additives and tailed in w/200 s 6-28-04 TD 12-1/4" hole to 4250" @ Plus w/additives and tailed in w/200 s (Notified Sylvia Dickey w/NMOCD of I hereby certify that the information at grade tank has been/will be constructed by c SIGNATURE: Type or print name: Stormi Davis (This space for State use)	PLUG AND ABANDON COMMENCE DE CHANGE PLANS COMMENCE DE CASING TEST CEMENT JOB OTHER: P.m. Drilled 17-1/2" hole to 433'. Set 13-3/8" 48 by. Cement circulated. WOC 21 hrs, 15 min. Reductions. Estimated TOC @ 400' (TS). Ran 1" to 422' as of TS and 1" cement job.) WOC 37 hrs, 30 min. Reductions true and complete to the best of my knowled losed according to NMOCD guidelines. a general permit and address: TITLE: Regulatory Compliance.	BSEQUENT REPORT OF: ALTEMOS CASING Hobbs PRILLING OPNS PLOG AND ABANDONMENT AND Surface and Intermediate Casing X and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion # casing @ 433'. Cemented w/220 sx Premium aced hole to 12-1/4" and resumed drilling. Cemented w/180 sx Halliburton Lite Premium and spotted 135 sx "C". Circulated 25 sx to pit. educed hole to 8-3/4" and resumed drilling. dge and belief. I further certify that any pit or below— or an (attached) alternative OCD-approved plan — nce Technician DATE: 7-6-04 Telephone No. 505-748-1471