

EC

OPER. OGRID NO. .6137  
PROPERTY NO. 34144  
POOL CODE ✓  
EFF. DATE 7/21/04  
API NO. 30-025-36778

FORM APPROVED  
OMB No. 1004-0136  
Expires November 30, 2000

APPLIC.

1a. Type of Work: ☒ DRILL

1b. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

2. Name of Operator  
DEVON ENERGY CORPORATION

Contact: LINDA GUTHRIE  
E-Mail: linda.guthrie@devn.com

3a. Address  
1500 MID-AMERICA TOWER 20 N. BROADWAY  
OKLAHOMA CITY, OK 73102

3b. Phone No. (include area code)  
Ph: 405.228.8209  
Fx: 405.552.1319

4. Location of Well (Report location clearly and in accordance with any State requirements.)

At surface SESE 660FSL 660FEL  
At proposed prod. zone SESE 990FSL 1080FEL

**SUBJECT TO LIKE APPROVAL BY STATE**

14. Distance in miles and direction from nearest town or post office\*  
APPROX 20 MILES WEST OF JAL, NM

15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)

16. No. of Acres in Lease

18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.

19. Proposed Depth  
14800 MD

21. Elevations (Show whether DF, KB, RT, GL, etc.)  
3408 GL

22. Approximate date work will start  
07/03/2004

5. Lease Serial No.  
NMNM13641

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.  
MAD DOG 15 FED COM 1

9. API Well No.

10. Field and Pool, or Exploratory  
WILDCAT

11. Sec., T., R., M., or Blk. and Survey or Area

Sec 15 T23S R34E Mer NMP  
SME: BLM

12. County or Parish  
LEA

13. State  
NM

17. Spacing Unit dedicated to this well  
320.00

20. BLM/BIA Bond No. on file

23. Estimated duration  
100 DAYS

24. Attachments

**Capitan Controlled Water Basin**

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature  
(Electronic Submission)

Name (Printed/Typed)  
LINDA GUTHRIE

Date  
06/03/2004

Title  
OPERATIONS ASSOCIATE

Approved by (Signature)

Name (Printed/Typed)

Date

Title  
FIELD MANAGER

Office  
CARLSBAD FIELD OFFICE

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

**APPROVAL FOR 1 YEAR**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #31125 verified by the BLM Well Information System  
For DEVON ENERGY CORPORATION, sent to the Hobbs  
Committed to AFMSS for processing by LINDA ASKWIG on 06/04/2004 (041A0189AE)

**DECLARED WATER BASIN  
CEMENT BEHIND THE 20"  
CASING MUST BE CIRCULATED**

**APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS  
ATTACHED**

**\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\***

**Additional Operator Remarks:**

Devon Energy proposes to drill to approximately 14,800 feet to test the Devonian for commercial quantities of gas. If deemed non-commercial, the wellbore will be plugged and abandoned as per Federal regulations. Programs to adhere to onshore oil and gas regulations are outlined in the following exhibits and attachments.

Approximately 919' of new access road will need to be constructed.

DISTRICT I  
1825 N. French Dr., Hobbs, NM 88240

DISTRICT II  
811 South First, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Ed., Artesia, NM 87410

DISTRICT IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-102  
Revised March 17, 1999

Submit to Appropriate District Office  
State Lease - 4 Copies  
Fee Lease - 3 Copies

OIL CONSERVATION DIVISION

2040 South Pacheco  
Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number <b>30-025-36778</b>	Pool Code <b>✓</b>	Pool Name <b>Wildcat; Devonian</b>
Property Code	Property Name <b>MAD DOG "15" FEDERAL COM</b>	Well Number <b>1</b>
OCRID No. <b>6137</b>	Operator Name <b>DEVON ENERGY PRODUCTION COMPANY LP</b>	Elevation <b>3408'</b>

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	15	23 S	34 E		660	SOUTH	660	EAST	LEA

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	15	23S	34E		990	South	1080	East	Lea

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
320			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p><b>OPERATOR CERTIFICATION</b></p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Linda Guthrie</i> Signature</p> <p><b>Linda Guthrie</b> Printed Name</p> <p><b>Regulatory Specialist</b> Title</p> <p><b>May 26, 2004</b> Date</p>
	<p><b>SURVEYOR CERTIFICATION</b></p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p><b>MARCH 15, 2004</b></p> <p>Date Surveyed</p> <p><i>GARY L JONES</i> Signature &amp; Seal of Professional Surveyor</p> <p><b>7977</b> Certification No.</p> <p><b>7977</b> Professional Surveyor</p> <p><b>BASIN SURVEYS</b></p>
	<p>Lat.: N32°17'57.0" Long.: W103°27'05.6"</p>

## **DRILLING PROGRAM**

Devon Energy Production Company, LP  
**MAD DOG 15 FED COM #1**  
660' FSL & 660' FEL, Section 15 T23S, R34E  
BHL: 990' FSL & 1080' FEL, Section 15-T23S-R34E  
Lea County, New Mexico

1. **Geologic Name of Surface Formation**

Alluvium

2. **Estimated Tops of Important Geologic Markers**

Rustler	900'
Delaware	4975'
Bone Spring	8350'
Wolfcamp	11100'
Strawn	11575'
Atoka	11775'
Morrow	12700'
Devonian	14525'
Total Depth	14800'

3. **Estimated Depths of Anticipated Fresh Water, Oil or Gas**

The estimated depths at which water, oil and gas will be encountered are as follows.

Water	None expected in area
Oil	Bone Spring @8350'
Gas	Upper Morrow @12700'
	Devonian @14,525'

4. **Casing Program**

Hole Size	Interval	OD Csg	Weight	Collar	Grade
26	0 - 925'	20"	94#	Btrs	H40
17.5	0-3500'	13 3/8"	68#	Btrs	J55
	3500'-5100'				HCK55
12 1/4"	0 -8000'	9 5/8"	43.5#	LT&C	HCP110
	8000'-11700'		47#		
8 1/2"	11300'-14525'	7 5/8" liner	39#	ST-L	HCL-80
6.5"	14525'-14800'	Open Hole			

5. CASING CEMENTING & SETTING DEPTH:

20"	Surface	Run 20" 94# H40 Btrs casing. Cement with 1027 sx 35:65:6 Poz Class C followed by 300 sx Class C. Cement to surface.
13 3/8"	Intermediate	Run 13 3/8" 68# J55 Btrs casing.. Cement Stage I w/ 600 sx 50:50 Poz:Class C followed by 500 sx 60:40 Poz Class C. Cement Stage II w/ 1800 sx 50:50 Poz:Class C followed by 250 sx 60:40 Poz:Class C. Cement back to 20" casing. <i>TO SURFACE.</i>
9 5/8"	Production Interm.	9 5/8" 43.5# & 47# HCP110 LT&C casing. Cement with 900 sx Class H. Cement 500' above the top hydrocarbon bearing interval.
7 5/8"	Production Liner	Run 7 5/8" 39# HCL-80 ST-L liner. Cement with 325 sx Class H. Cement to top of liner.

Note: Cement volumes may vary based on hole conditions and caliper information.

6. **PRESSURE CONTROL EQUIPMENT:** Exhibit I Prior to intermediate, the blowout preventor equipment will consist of a 2M system. A 2000 psi WP pipe ram and/or a 2000 psi (Hydril) preventor. After Tding intermediate, a Blow-out Preventer (5,000/10,000 PSI working pressure) consisting of double ram type preventer with bag type preventor will be used. Units will be hydraulically operated. Choke Manifold and Closing Unit. Blind rams on top, pipe rams on bottom to correspond with size of drill pipe in use. BOP will be tested as well as choke manifold. BOP will be worked at least once each day while drilling & blind ram will be worked on trips when no drill pipe is in hole. Full opening stabbing valve and upper Kelly cock will be utilized. Anticipated BHP 6300 PSI and 200° BHT.

7. PROPOSED MUD CIRCULATION SYSTEM:

DEPTH	MUD. WT.	MUD VISC.	FLUID LOSS	TYPE MUD
0' – 925'	8.4 – 8.8	29-36	NC	Fresh water spud mud use paper for seepage.
925' – 5100'	8.5 – 10	29-32	NC	Brine water, use ground paper for seepage control and lime for ph
5100' – 11,700'	8.4 – 9	29-34	N/C	Cut Brine use paper for seepage control
11,700' – 14,525'	9-12.5	34-38	10cc for drilling Morrow	Cut Brine. Mud up at 12,000'
14,525' – 14,800'	8.4	28-30	N/C	Fresh Water

Sufficient mud materials to maintain mud properties, meet lost circulation and weight increase requirement will be kept at well site at all times. In order to run casing and log well viscosity may have to be raised and water loss may have to be lowered.

8. Auxiliary Well Control and Monitoring Equipment

- A. A kelly cock will be in the drill string at all times.
- B. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.
- C. Hydrogen Sulfide detection equipment (Compliance Package) will be in operation when drilling out the 13 3/8" casing shoe until the well is TD'd.

9. Logging, Testing and Coring Program

- A. Drill stem tests may be run on potential pay interval.
- B. The open hole electrical logging program will be as follows.
  - 1) TD to intermediate casing; Induction/ Gamma Ray/ Neutron/ Density Log.
  - 2) TD to surface: Neutron with Gamma Ray.
- C. No coring program is planned.
- D. Additional testing may be initiated during drilling of the open hole section below 14,525'. Specific intervals will be targeted based on log evaluation, geological sample shows and drill stem tests.

11. Abnormal Pressures, Temperatures and Potential Hazards

Abnormally high pressured zones with a bottom hole pressure of approximately 7500 psi could possibly be encountered while drilling the Pennsylvanian interval. Sufficient barite will be on location to enable the weighting up to the estimated 11.5 ppg to control any high-pressure zone encountered. Along with the above mentioned primary control, a Blow Out Preventor System as outlined in Exhibit B will be utilized should the need arise to shut the well in prior to running and cementing the drilling liner. The estimated bottom hole temperature is 200°F. Hydrogen Sulfide has been reported at this depth in this area. No major lost circulation zones have been reported in the offsetting wells.

12. Anticipated Starting Date and Duration of Operations

Road and location preparation will not be undertaken until approval has been received from the BLM. If approved, this well will be drilled as part of a development project. The anticipated spud date for the project is in August 1, 2004. The drilling operation should require approximately 70 days. If the well is deemed productive, completion operations will require, at minimum, an additional 30 days of testing to ascertain whether permanent production facilities will be constructed.

## **SURFACE USE AND OPERATING PLAN**

Devon Energy Production Company, LP  
**MAD DOG 15 FED COM #1**  
660' FSL & 660' FEL, Section 15 T23S, R34E  
BHL: 990' FSL & 1080' FEL, Section 15-T23S-R34E  
Lea County, New Mexico

### **1. Existing Roads**

- A. The well site and elevation plat for the proposed well are reflected on Exhibit #2. This well was staked by Basin Surveys in Hobbs, NM.
- B. All roads into the location are depicted in Exhibit #3. New construction from the existing road will be used to access the location. New construction will conform to the specifications outlined in Item #2 below.
- C. Directions to location: From the junction of Delaware Basin Road and Co. Rd E-21, Go south on E-21 for 1.8 mile past Antelope Plant to proposed lease road.

### **2. Proposed Access Road**

Exhibit #3 shows the existing lease road. Access to this location will require the construction of about 919' of proposed access road. All new construction will adhere to the following.

- A. The maximum width of the road will be 15'. It will be crowned and made of 6" of rolled and compacted caliche. Water will be deflected, as necessary, to avoid accumulation and prevent surface erosion.
- B. Surface material will be native caliche. This material will be obtained from a BLM approved pit nearest in proximity to the location. The average grade will be approximately 1%.
- C. No cattle guards, grates or fence cuts will be required. No turnouts are planned.

### **3. Location of Existing and/or Proposed Facilities**

- A. In the event the well is found productive, a tank battery would be constructed and the necessary production equipment will be installed at the well site.
  - 1) If necessary, the well will be operated by means of an electric prime mover. Electric power poles will be set along side of the access road.
  - 2) The tank battery, all connections and all lines will adhere to API standards.



**RIO BLANCO 33 FEDERAL #2**  
**SURFACE USE AND OPERATING PLAN**  
**PAGE 2**

B. If the well is productive, rehabilitation plans are as follows.

- 1) The reserve pit will be closed pursuant to OCD rules and guidelines and reclaimed as per BLM specifications.
- 2) The original topsoil from the well site will be returned to the location. The drill site will then be contoured to the original natural state.

4. Methods of Handling Water Disposal

- A. Drill cuttings will be disposed into the reserve pit.
- B. Drilling fluids will be contained in steel mud tanks. The reserve pit will contain excess drilling fluid or fluid from the well during drilling, cementing and completion operations. The reserve pit will be an earthen pit roughly 200' x 150' x 8' in size.
- C. The reserve pit will be fenced on three sides throughout drilling operations and will be totally isolated upon removal of the rotary rig. The pit will be lined using a 20 mil liner to minimize loss of drilling fluids and saturation of the ground with brine water used during drilling.
- D. Water produced from the well during completion operations will be disposed into a steel tank or reserve pit, if volumes prove excessive. After placing the well on production through the production facilities, all water will be collected in tanks. Produced oil will be separated into steel stock tanks until sold.
- E. A portable chemical toilet will be available on the location for human waste during the drilling operations.
- F. Garbage, trash and waste paper produced during drilling operations will be collected in a contained trailer and disposed at an approved landfill. All waste material will be contained to prevent scattering by the wind. All water, fluids, salt or other chemicals will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be generated by this operation.
- G. All waste material will be removed within 30 days after the well is either completed or abandoned. The reserve pit will be completely fenced until it has it is ready to be closed. It will be closed pursuant to OCD rules and guidelines and reclaimed as per BLM specifications. Only the portion of the drilling pad used by the production equipment (pumping unit and tank battery) will remain in use. If the well is deemed non-commercial only a dry hole marker will remain.

5. Well Site Layout

**RIO BLANCO 33 FEDERAL #2**  
**SURFACE USE AND OPERATING PLAN**  
**PAGE 3**

- A. The drilling pad is shown on Exhibit #5. The pad, pits and general location of the rig equipment are displayed. Top soil will be stored adjacent to the pad until reclamation efforts are undertaken. Only modest cuts will be necessary to build the pad, which will be covered with 6" of compacted caliche.
- B. No permanent living facilities are planned, but temporary trailers for the tool pusher, drilling foreman and mud logger may be on location throughout drilling operations.

10. Plans for Restoration of Surface

- A. After concluding the drilling and/or completion operations, if the well is found non-commercial, the road will be reclaimed as directed by the BLM.
- B. The pit will be closed pursuant to OCD rules and guidelines and reclaimed as per BLM specifications. The original top soil will be returned to the pad and contoured as closely as possible to the original topography.
- C. The location and road will be rehabilitated as recommended by the BLM.
- D. The reserve pit will be fenced on three sides throughout drilling operations. After the rotary rig is removed, the reserve pit will be fenced on the fourth side to preclude endangering wildlife. The fencing will be in place until the pit is reclaimed.

11. Surface Ownership

The well site is owned by the Bureau of Land Management.

The surface location will be restored as directed by the BLM.

**RIO BLANCO 33 FEDERAL #2**  
**SURFACE USE AND OPERATING PLAN**  
**PAGE 4**

12. Other Information

- A. The wellsite and access route are located in a relatively flat area.
- B. The top soil at the wellsite and access route is sandy.
- C. The vegetation cover at the wellsite is moderately sparse, with prairie grasses, some mesquite bushes, and shinnery oak.
- D. No wildlife was observed but it is likely that deer, rabbits, coyotes and rodents traverse the area.
- E. A Cultural Resources Examination will be completed by Southern New Mexico Archaeological Services, Inc. and forwarded to the BLM office in Carlsbad, New Mexico.

13. Lessee's and Operator's Representative

The Devon Energy Production Company, L.P. representatives responsible for ensuring compliance of the surface use plan are listed below.

Bill Greenlees  
Operations Engineer Advisor

Don Mayberry  
Superintendent

Devon Energy Production Company, L.P.  
20 North Broadway, Suite 1500  
Oklahoma City, OK 73102-8260

Devon Energy Production Company, L.P.  
Post Office Box 250  
Artesia, NM 88211-0250

(405) 552-8194 (office)  
(405) 203-7778 (Cellular)

(505) 748-3371 (office)  
(505) 746-4945 (home)

Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access road; that I am familiar with the conditions that presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Devon Energy Production Company, L.P. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

Signed: \_\_\_\_\_

Bill Greenlees

Operations Engineer Advisor

Date: May 26, 2004

**RIO BLANCO 33 FEDERAL #2**  
**SURFACE USE AND OPERATING PLAN**  
**PAGE 4**

**12. Other Information**

- A. The wellsite and access route are located in a relatively flat area.
- B. The top soil at the wellsite and access route is sandy.
- C. The vegetation cover at the wellsite is moderately sparse, with prairie grasses, some mesquite bushes, and shinnery oak.
- D. No wildlife was observed but it is likely that deer, rabbits, coyotes and rodents traverse the area.
- E. A Cultural Resources Examination will be completed by Southern New Mexico Archaeological Services, Inc. and forwarded to the BLM office in Carlsbad, New Mexico.

**13. Lessee's and Operator's Representative**

The Devon Energy Production Company, L.P. representatives responsible for ensuring compliance of the surface use plan are listed below.

Bill Greenlees  
Operations Engineer Advisor

Don Mayberry  
Superintendent

Devon Energy Production Company, L.P.  
20 North Broadway, Suite 1500  
Oklahoma City, OK 73102-8260

Devon Energy Production Company, L.P.  
Post Office Box 250  
Artesia, NM 88211-0250

(405) 552-8194 (office)  
(405) 203-7778 (Cellular)

(505) 748-3371 (office)  
(505) 746-4945 (home)

**Certification**

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access road; that I am familiar with the conditions that presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Devon Energy Production Company, L.P. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.


Signed: \_\_\_\_\_  
Bill Greenlees  
Operations Engineer Advisor

Date: May 26, 2004

**Attachment to Exhibit #1**  
**NOTES REGARDING BLOWOUT PREVENTERS**  
**Devon Energy Production Company, LP**  
**MAD DOG 15 FED COM #1**  
**660' FSL & 660' FEL, Section 15 T23S, R34E**  
**BHL: 990' FSL & 1080' FEL, Section 15-T23S-R34E**  
**Lea County, New Mexico**

1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOP bore.
2. Wear ring will be properly installed in head.
3. Blowout preventer and all associated fittings will be in operable condition to withstand a minimum 5000 psi working pressure.
4. All fittings will be flanged.
5. A full bore safety valve tested to a minimum 5000 psi WP with proper thread connections will be available on the rotary rig floor at all times.
6. All choke lines will be anchored to prevent movement.
7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
8. Will maintain a kelly cock attached to the kelly.
9. Hand wheels and wrenches will be properly installed and tested for safe operation.
10. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.

SECTION 26, TOWNSHIP 20 SOUTH, RANGE 27 EAST, N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.



**Directions to Location:**

FROM THE JUNCTION OF DELAWARE BASIN ROAD AND  
CO. RD. E-21, GO SOUTH ON E-21 FOR 1.8 MILE  
PAST ANTELOPE PLANT TO PROPOSED LEASE ROAD.

**BASIN SURVEYS** P.O. BOX 1786-HOBBS, NEW MEXICO

W.O. Number: 4044

Drawn By: K. GOAD

Date: 03-16-2004

Disk: KJG CD#4 - 4044A.DWG


**DEVON ENERGY PROD. CO., L.P.**

REF: MAD DOG "15" FED. COM No. 1 / Well Pad Topo

THE MAD DOG "15" FED. COM No. 1 LOCATED 660' FROM  
THE SOUTH LINE AND 660' FROM THE EAST LINE OF  
SECTION 15, TOWNSHIP 23 SOUTH, RANGE 34 EAST,  
N.M.P.M., LEA COUNTY, NEW MEXICO.

**Survey Date:** 03-15-2004

Sheet 1 of 1 Sheets



**MAD DOG "15" FEDERAL COM #1**  
 Located at 660' FSL and 660' FEL  
 Section 15, Township 23 South, Range 34 East,  
 N.M.P.M., Lea County, New Mexico.



focused on excellence  
in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (505) 393-7316 - Office  
 (505) 392-3074 - Fax  
[basinsurveys.com](http://basinsurveys.com)


W.O. Number: 4044AA - KJG #1

Survey Date: 03-15-2004

Scale: 1" = 2000'

Date: 03-16-2004

**DEVON ENERGY  
 PRODUCTION  
 COMPANY LP.**



MAD DOG "15" FEDERAL COM #1  
 Located at 660' FSL and 660' FEL  
 Section 15, Township 23 South, Range 34 East,  
 N.M.P.M., Lea County, New Mexico.

**basin**  
**surveys**  
 focused on excellence  
 in the oilfield

P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (505) 393-7318 - Office  
 (505) 392-3074 - Fax  
 basin-surveys.com

W.O. Number: 4044AA - KJG #1

Survey Date: 03-15-2004

Scale: 1" = 2 miles

Date: 03-16-2004

**DEVON ENERGY**  
**PRODUCTION**  
**COMPANY LP.**






# PROPOSED 10-M BOPE AND CHOKE ARRANGEMENT


EXHIBIT B (A)

Lee County, New Mexico



**MINIMUM CHOKE MANIFOLD**  
3,000, 5,000 and 10,000 PSI Working Pressure

3 MWP - 5 MWP - 10 MWP



MINIMUM REQUIREMENTS										
No.		3,000 MWP			5,000 MWP			10,000 MWP		
		I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING
1	Line from drilling spool		3"	3,000		3"	5,000		3"	10,000
2	Cross 3"x3"x3"x2"			3,000			5,000			
	Cross 3"x3"x3"x3"									10,000
3	Valves (1) Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
4	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	1-13/16"		3,000	1-13/16"		5,000	1-13/16"		10,000
4a	Valves (1)	2-1/16"		3,000	2-1/16"		5,000	3-1/8"		10,000
5	Pressure Gauge			3,000			5,000			10,000
6	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
7	Adjustable Choke (3)	2"		3,000	2"		5,000	2"		10,000
8	Adjustable Choke	1"		3,000	1"		5,000	2"		10,000
9	Line		3"	3,000		3"	5,000		3"	10,000
10	Line		2"	3,000		2"	5,000		3"	10,000
11	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
12	Lines		3"	1,000		3"	1,000		3"	2,000
13	Lines		3"	1,000		3"	1,000		3"	2,000
14	Remote reading compound standpipe pressure gauge			3,000			5,000			10,000
15	Gas Separator		2"x5"			2"x5"			2"x5"	
16	Line		4"	1,000		4"	1,000		4"	2,000
17	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000

(1) Only one required in Class 3M.

(2) Gate valves only shall be used for Class 10M.

(3) Remote operated hydraulic chokes required on 5,000 psi and 10,000 psi for drilling.

**EQUIPMENT SPECIFICATIONS AND INSTALLATION INSTRUCTIONS**

- All connections in choke manifold shall be welded, studded, flanged or Cameron clamp of comparable rating.
- All flanges shall be API 6B or 6BX and ring gaskets shall be API RX or BX. Use only BX for 10 MWP.
- All lines shall be securely anchored.
- Chokes shall be equipped with tungsten carbide seats and needles, and replacements shall be available.
- Choke manifold pressure and standpipe pressure gauges shall be available at the choke manifold to assist in regulating chokes. As an alternate with automatic chokes, a choke manifold pressure gauge shall be located on the rig floor in conjunction with the standpipe pressure gauge.
- Line from drilling spool to choke manifold should be as straight as possible. Lines downstream from chokes shall make turns by large bends or 90° bends using bull plugged tees.
- Discharge lines from chokes, choke bypass and from top of gas separator should vent as far as practical from the well.

**UNITED STATES DEPARTMENT OF THE INTERIOR**  
**Bureau of Land Management**  
**Roswell Field Office**  
**2909 West Second Street**  
**Roswell, New Mexico 88201-1287**

**Statement Accepting Responsibility for Operations**

Operator Name: **Devon Energy Production Company, LP**  
Street or Box: **20 North Broadway, Suite 1500**  
City, State: **Oklahoma City, Oklahoma**  
Zip Code: **73102-8260**

The undersigned accepts all applicable terms, conditions, stipulations and restrictions concerning operations conducted on the leased land or portion thereof, as described below.

Lease No.: **NMNM13641**  
Legal Description of Land: **400 acres 15-23S-R34E**  
Formation(s): **Devonian**  
Bond Coverage: **Nationwide**  
BLM Bond File No.: **CO-1104**

Authorized Signature:

  
\_\_\_\_\_  
**Bill Greenlees**

Title: **Operations Engineering Advisor**

Date: **05/26/04**

## SPECIAL DRILLING STIPULATIONS

### THE FOLLOWING DATA IS REQUIRED ON THE WELL SIGN

Operator's Name Devon Energy Corp. Well Name & No. Mad Dog 15 Federal Com. #1  
Location 660 F S L & 660 F E L Sec. 15, T. 23 S, R. 34 E.  
Lease No. NM-13641 County Lea State New Mexico

The Special stipulations check marked below are applicable to the above described well and approval of this application to drill is conditioned upon compliance with such stipulations in addition to the General Requirements. The permittee should be familiar with the General Requirements, a copy of which is available from a Bureau of Land Management office. EACH PERMITTEE HAS THE RIGHT OF ADMINISTRATIVE APPEAL TO THESE STIPULATIONS PURSUANT TO TITLE 43 CRF 3165.3 AND 3165.4.

This permit is valid for a period of one year from the date of approval or until lease expiration or termination whichever is shorter.

#### I. SPECIAL ENVIRONMENT REQUIREMENTS

- ( ) Lesser Prairie Chicken (stips attached) ( ) Flood plain (stips attached)  
( ) San Simon Swale (stips attached) ( ) Other

#### II. ON LEASE - SURFACE REQUIREMENTS PRIOR TO DRILLING

( X ) The BLM will monitor construction of this drill site. Notify the ( X ) Carlsbad Field Office at (505) 234-5972 ( ) Hobbs Office (505) 393-3612, at least 3 working days prior to commencing construction.

( X ) Roads and the drill pad for this well must be surfaced with 6 inches of compacted caliche upon completion of well and it is determined to be a producer.

( X ) All topsoil and vegetation encountered during the construction of the drill site area will be stockpiled and made available for resurfacing of the disturbed area after completion of the drilling operation. Topsoil on the subject location is approximately 6 inches in depth. Approximately \_\_\_\_\_ cubic yards of topsoil material will be stockpiled for reclamation.

( X ) Other. V-Door North Construct a berm 2 feet in height around the east and north sides of the location.

#### III. WELL COMPLETION REQUIREMENTS

( ) A Communitization Agreement covering the acreage dedicated to the well must be filed for approval with the BLM. The effective date of the agreement must be prior to any sales.

( x ) Surface Restoration: If the well is a producer, the reserve pit(s) will be backfilled when dry, and cut-and-fill slopes will be reduced to a slope of 3:1 or less. All areas of the pad not necessary for production must be re-contoured to resemble the original contours of the surrounding terrain, and topsoil must be re-distributed and re-seeded with a drill equipped with a depth indicator (set at depth of 1/2 inch) with the following seed mixture, in pounds of Pure Live Seed (PLS), per acre.

( X ) A. Seed Mixture 1 (Loamy Sites)  
Side Oats Grama (*Bouteloua curtipendula*) 5.0  
Sand Dropseed (*Sporobolus cryptandrus*) 1.0

( ) B. Seed Mixture 2 (Sandy Sites)  
Sand Dropseed (*Sporobolus cryptandrus*) 1.0  
Sand Lovegrass (*Eragrostis trichodes*) 1.0  
Plains Bristlegrass (*Setaria magrostachya*) 2.0

( ) C. Seed Mixture 3 (Shallow Sites)  
Side oats Grama (*Boute curtipendula*) 1.0

( ) D. Seed Mixture 4 (Gypsum Sites)  
Alkali Sacaton (*Sporobollud airoides*) 1.0  
Four-Wing Saltbush (*Atriplex canescens*) 5.0

( ) OTHER SEE ATTACHED SEED MIXTURE

Seeding should be done either late in the fall (September 15 - November 15, before freeze up, or early as possible the following spring to take advantage of available ground moisture.

( ) Other.

## RESERVE PIT CONSTRUCTION STANDARDS

The reserve pit shall be constructed entirely in cut material and lined with 6 mil plastic. Mineral material extracted from within the boundary of the APD during construction of the well pad and reserve pits and be used for the construction of this well pad and its immediate access road only, as long as that portion of the access road it is use on remains on-lease. Removal of any additional material from this location for construction or improvement of other well pads and other access or lease roads must first be purchased from BLM.

Reclamation: Reclamation of this type of deep pit will consist of pushing the pit walls into the pit when sufficiently dry to support track equipment. The pit liner is NOT TO BE RUPTURED to facilitate drying; a ten month period after completion of the well is allowed for drying of the pit contents.

The pit area must be contoured to the natural terrain with all contaminated drilling mud buried with at least 3 feet of clean soil. The reclaimed area will then be seeded as specified in this permit.

## OPTIONAL PIT CONSTRUCTION STANDARDS

The reserve pit may be constructed in predominantly fill material if:

- (1) Lined as specified above and
- (2) A temporary or emergency pit may be constructed immediately adjacent to the reserve pit as long as the pit remains within the APD boundary. Mineral material removed from this pit may be used for the construction of this well pad only and its immediate access road, as long as that portion of the access road the material is used on remains on-lease. Removal of any material from the APD boundary for use on other well locations or roads must first be purchased from BLM.

Reclamation of the reserve pit consists of bulldozing all reserve pit contents and contaminants into the borrow pit and covering with a minimum of 3 feet of clean soil material. The entire area must be recontoured, all trash removed, and reseeded as specified in this permit.

## CULTURAL

Whether or not an archaeological survey has been completed and notwithstanding that operations are being conducted as approved, the lessee/operator/grantee shall notify the BLM immediately if previously unidentified cultural resources are observed during surface disturbing operations. From the time of the observation, the lessee/operator/grantee shall avoid operations that will result in disturbance to these cultural resources until directed to processed by BLM.

## TRASH PIT STIPS

All trash, junk, and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

## CONDITIONS OF APPROVAL - DRILLING (CONTINUED)

Operator's Name: Devon Energy Production Company LP Well No. 1 - Mad Dog 15 Federal Com  
Location: SH: 660' FSL & 660' FEL BH: 990' FSL & 1080' FEL sec. 15, T. 23 S., R. 34 E.  
Lease: NM-13641

.....

3. After setting the 13-3/8 inch intermediate casing string and before drilling into the Wolfcamp formation, the BOPE shall be tested as described in Onshore Order No. 2. Any equipment failing to test satisfactorily shall be repaired or replaced.

A. The BLM office shall be notified at (505) 393-3612 in sufficient time for a representative to witness the tests.

B. The tests shall be done by an independent service company.

C. The results of the test shall be reported to the BLM Hobbs Office at 414 West Taylor, Hobbs, New Mexico 88240.

D. Testing fluid must be water or an appropriate clear liquid suitable for sub-freezing temperatures. Use of drilling mud for testing is not permitted since it can mask small leaks.

E. Testing must be done in a safe workman like manner. Hard line connections shall be required.

### IV. DRILLING MUD:

1. Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented. Monitoring equipment shall consist of the following:

A. Recording pit level indicator to indicate volume gains and losses.

B. Flow-sensor on the flow-line to warn of abnormal mud returns from the well.

## CONDITIONS OF APPROVAL - DRILLING

Operator's Name: Devon Energy Production Company LP Well No. 1 - Mad Dog 15 Federal Com  
Location: SH: 660' FSL & 660' FEL BH: 990' FSL & 1080' FEL sec. 15, T. 23 S., R. 34 E.  
Lease: NM-13641

.....

### I. DRILLING OPERATIONS REQUIREMENTS:

1. The Bureau of Land Management (BLM) is to be notified at (505) 393-3612 in sufficient time for a representative to witness:

A. Spudding

B. Cementing casing: 20 inch 13-3/8 inch 9-5/8 inch 7-5/8 inch liner (JL)

C. BOP tests

2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.

3. Include the API No. assigned to well by NMOCD on the subsequent report of setting the first casing string.

4. A Communitization Agreement covering the acreage dedicated to this well must be filed for approval with the BLM. The effective date of the agreement shall be prior to any sales.

### II. CASING:

1. 20 inch surface casing should be set at approximately 925 feet (25 feet into the Rustler at approximately 900 feet), below usable water and circulate cement to the surface. If cement does not circulate to the surface this BLM office shall be notified and a temperature survey or cement bond log shall be run to verify the top of the cement. Remedial cementing shall be completed prior to drilling out that string.

2. Minimum required fill of cement behind the 13-3/8 inch intermediate casing is sufficient to tie back 200 feet into the 20 inch surface casing set at approximately 925 feet. If cement does not circulate to the surface, a temperature survey or cement bond log shall be run to verify the top of the cement. Remedial cementing may be required prior to drilling out that string. *circulate to surface.* (JL)

3. Minimum required fill of cement behind the 9-5/8 inch production casing is sufficient to tie back to approximately 7850 feet (500 feet above the top of the Bone Spring at approximately 8350 feet.)

4. Minimum required fill of cement behind the 7-5/8 inch production liner is sufficient to tie back 200 feet into the 7 inch production casing set at approximately 11700 feet. *reach top of liner.* (JL)

### III. PRESSURE CONTROL:

1. Before drilling below the 20 inch surface casing, the blowout preventer assembly shall consist of a minimum of One Annular Preventer or Two Ram-Type Preventers and a Kelly Cock/Stabbing Valve. Before drilling below the 13-3/8 inch intermediate casing, the blowout preventer assembly shall consist of a minimum of One Annular Preventer, Two Ram-Type Preventers, and a Kelly Cock/Stabbing Valve.

2. Before drilling below the 20 inch surface casing, minimum working pressure of the blowout preventer and related equipment (BOPE) shall be 2000 psi. Before drilling below the 13-3/8 inch intermediate casing, minimum working pressure of the BOPE shall be 5000 psi. Before drilling below the 9-5/8 inch production casing, minimum working pressure of the BOPE shall be 10000 psi.



BLM Serial Number: NM-13641  
Company Reference: Devon Energy Corp.  
Well No. & Name: Mad Dog 15 Federal Com. #1

STANDARD STIPULATIONS FOR PERMANENT RESOURCE ROADS  
CARLSBAD FIELD OFFICE

A copy of the grant and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder/grantee/permittee shall hereafter be identified as the holder in these stipulations. The Authorized Officer is the person who approves the Application for Permit to Drill (APD) and/or Right-of-Way (ROW).

GENERAL REQUIREMENTS

- A. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- B. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, *et. seq.*) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.
- C. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, *et. seq.* or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, *et. seq.*) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

D. If, during any phase of the construction, operation, maintenance, or termination of the road, any oil or other pollutant should be discharged, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting there from, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

E. The holder shall minimize disturbance to existing fences and other improvements on public domain surface. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times.

The holder will make a documented good-faith effort to contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence.

F. The Holder shall ensure that the entire right-of-way, including the driving surface, ditching and drainage control structures, road verges and any construction sites or zones, will be kept free of the following plant species: Malta starthistle, African rue, Scotch thistle and salt cedar.

Holder agrees to comply with the following stipulations:

1. ROAD WIDTH AND GRADE

The road will have a driving surface of 14 feet (all roads shall have a minimum driving surface of 12 feet, unless local conditions dictate a different width). The maximum grade is 10 percent unless the box below is checked. Maximum width of surface disturbance from construction will be 30 feet.

☐ Those segments of road where grade is in excess of 10% for more than 300 feet shall be designed by a professional engineer.

2. CROWNING AND DITCHING

Crowning with materials on site and ditching on one side of the road on the uphill side will be required. The road cross-section will conform to the cross section diagrams in Figure 1. If conditions dictate, ditching may be required for both sides of the road; if local conditions permit, a flat-bladed road may be considered (if these conditions exist, check the appropriate box below). The crown shall have a grade of approximately 2% (i.e., 1" crown on a 12' wide road).

☒ Ditching will be required on both sides of the roadway as shown on the attached map or as staked in the field.

☐ Flat-blading is authorized on segment(s) delineated on the attached map.

### 3. DRAINAGE

Drainage control shall be ensured over the entire road through the use of borrow ditches, outsloping, insloping, natural rolling topography, lead-off (turnout) ditches, culverts, and/or drainage dips.

A. All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval for lead-off ditches shall be determined according to the following table, but may be amended depending upon existing soil types and centerline road slope (in %):

#### SPACING INTERVAL FOR TURNOUT DITCHES

Percent slope	Spacing interval
0% - 4%	400' - 150'
4% - 6%	250' - 125'
6% - 8%	200' - 100'
8% - 10%	150' - 75'

A typical lead-off ditch has a minimum depth of 1 foot below and a berm 6 inches above natural ground level. The berm will be on the down-slope side of the lead-off ditch. The ditch end will tie into vegetation whenever possible.

For this road the spacing interval for lead-off ditches shall be at

☒ 400 foot intervals.

☐ \_\_\_\_\_ foot intervals.

☐ locations staked in the field as per spacing intervals above.

☐ locations delineated on the attached map.

B. Culvert pipes shall be used for cross drains where drainage dips or low water crossings are not feasible. The minimum culvert diameter must be 18 inches. Any culvert pipe installed shall be of sufficient diameter to pass the anticipated flow of water. Culvert location and required diameter are shown on the attached map (Further details can be obtained from the Roswell District Office or the appropriate Resource Area Office).


C. On road slopes exceeding 2%, drainage dips shall drain water into an adjacent lead-off ditch. Drainage dip location and spacing shall be determined by the formula:

$$\text{spacing interval} = \frac{400'}{\text{road slope in \%}} + 100'$$

Example: 4% slope: spacing interval =  $\frac{400}{4} + 100 = 200$  feet

#### 4. TURNOUTS

Unless otherwise approved by the Authorized Officer, vehicle turnouts will be required. Turnouts will be located at 2000-foot intervals, or the turnouts will be intervisible, whichever is less. Turnouts will conform to the following diagram:



STANDARD TURNOUT - PLAN VIEW

#### 5. SURFACING

Surfacing of the road or those portions identified on the attached map may, at the direction of the Authorized Officer, be required, if necessary, to maintain traffic within the right-of-way with caliche, gravel, or other surfacing material which shall be approved by the Authorized Officer. When surfacing is required, surfacing materials will be compacted to a minimum thickness of six inches with caliche material. The width of surfacing shall be no less than the driving surface. Prior to using any mineral materials from an existing or proposed Federal source, authorization must be obtained from the Authorized Officer.

A sales contract for the removal of mineral materials (caliche, sand, gravel, fill dirt, etc.) from an authorized pit, site, or on location must be obtained from the BLM prior to using any such mineral material from public lands. Contact the BLM solid minerals staff for the various options to purchase mineral material.

#### 6. CATTLEGUARDS

Where used, all cattleguard grids and foundation designs and construction shall meet the American Association of State Highway and Transportation Officials (AASHTO) Load Rating H-20, although AASHTO U-80 rated grids shall be required where heavy loads (exceeding H-20 loading), are anticipated (See BLM standard drawings for cattleguards). Cattleguard grid length shall not be less than 8 feet and width of not less than 14 feet. A wire gate (16-foot minimum width) will be provided on one side of the cattleguard unless requested otherwise by the surface user.

7. MAINTENANCE

The holder shall maintain the road in a safe, usable condition. A maintenance program shall include, but not be limited to blading, ditching, culvert installation, culvert cleaning, drainage installation, cattleguard maintenance, and surfacing.

8. PUBLIC ACCESS

Public access along this road will not be restricted by the holder without specific written approval being granted by the Authorized Officer. Gates or cattleguards on public lands will not be locked or closed to public use unless closure is specifically determined to be necessary and is authorized in writing by the Authorized Officer.

9. CULTURAL RESOURCES

Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the authorized officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the authorized officer after consulting with the holder.

10. SPECIAL STIPULATIONS:

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Avenue, Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy Minerals and Natural Resources

Form C-144  
March 12, 2004

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.  
For downstream facilities, submit to Santa Fe office

**Pit or Below-Grade Tank Registration or Closure**

Is pit or below-grade tank covered by a "general plan"? Yes ☐ No ☒

Type of action: Registration of a pit or below-grade tank ☒ Closure of a pit or below-grade tank ☐

Operator: Devon Energy Production Company, LP Telephone: (405) 228-8209 e-mail address: linda.guthrie@devon.com  
Address: 20 N Broadway, Suite 1500 Oklahoma City, OK 73102-8260  
Facility or well name: MAD DOG 15 FED COM 1 API #: 30-025-36778 U/L or Qtr/Qtr P Sec 15 T 23S R 34E  
County: Lea Latitude \_\_\_\_\_ Longitude \_\_\_\_\_ NAD: 1927 ☐ 1983 ☐ Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

**Pit**

Type: Drilling ☒ Production ☐ Disposal ☐

Workover ☐ Emergency ☐

Lined ☒ Unlined ☐

Liner type: Synthetic ☒ Thickness 12 mil Clay ☐ Volume \_\_\_\_\_ bbl

**Below-grade tank**

Volume: \_\_\_\_\_ bbl Type of fluid: \_\_\_\_\_

Construction material: \_\_\_\_\_

Double-walled, with leak detection? Yes ☐ If not, explain why not. \_\_\_\_\_

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)

Less than 50 feet

(20 points)

50 feet or more, but less than 100 feet

(10 points)

100 feet or more

(0 points)

Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)

Yes

(20 points)

No

(0 points)

Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)

Less than 200 feet

(20 points)

200 feet or more, but less than 1000 feet

(10 points)

1000 feet or more

(0 points)

**Ranking Score (Total Points)**

**If this is a pit closure:** (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location:

onsite ☐ offsite ☐ If offsite, name of facility \_\_\_\_\_. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☐ Yes ☐ If yes, show depth below ground surface \_\_\_\_\_ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐, or an (attached) alternative OCD-approved plan ☐.

Date: 05/26/04

Printed Name/Title Linda Guthrie Regulatory Specialist

Signature Linda Guthrie

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval:

Date: 7/21/04

Printed Name/Title \_\_\_\_\_

Signature Paul J. Harty

36728



**Devon Energy Corporation**  
**20 North Broadway**  
**Oklahoma City, Oklahoma 73102-8260**


# **Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan**

**For**

**Mad Dog 15 Federal Com # 1**



**660' FSL & 660' FEL,  
Sec-15, T-23S R-34E**

**Lea County NM**



## Mad Dog 15 Federal Com # 1

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitor.



Assumed 100 ppm ROE = 3000' (Radius of Exposure)  
100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated North on lease road. Crews should then block entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. There are no homes or buildings in or near the ROE.



## Emergency Procedures

In the case of a release of gas containing H<sub>2</sub>S, the first responder(s) must isolate the area and prevent entry by other persons into the 100 ppm ROE. Additionally the first responder(s) must evacuate any public places encompassed by the 100 ppm ROE. First responder(s) must take care not to injure themselves during this operation. Company and/or local officials must be contacted to aid in this operation. Evacuation of the public should be beyond the 100 ppm ROE.

All responders must have training in the detection of H<sub>2</sub>S, measures for protection against the gas, equipment used for protection and emergency response. Additionally, responders must be equipped with H<sub>2</sub>S monitors and air packs in order to control the release. Use the "buddy system" to ensure no injuries during the response.

## Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

## Characteristics of H<sub>2</sub>S and SO<sub>2</sub>

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H <sub>2</sub> S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO <sub>2</sub>	2.21 Air = 1	2 ppm	N/A	1000 ppm

## Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

## Devon Energy Corp. Company Call List

<b>Artesia (505)</b>	<b>Cellular</b>	<b>Office</b>	<b>Home</b>
Foreman – BJ Cathey.....	390-5893 .....	748-0176 .....	887-6026
Asst. Foreman – Bobby Jones.....	748-7447 .....	748-0176 .....	746-3194
Cecil Thurmond .....	748-7180 .....	748-0171 .....	887-1479
David Purdy .....	(432)631-2969.....	(432)495-7279 ....	(432)683-0735
Engineer – Tom Pepper .....	(405) 203-2242.....	(405) 552-4513 ...	(405) 728-8641

### Agency Call List

#### Lea County (505)

##### **Hobbs**

State Police .....	392-5588
City Police .....	397-9265
Sheriff's Office .....	393-2515
Ambulance.....	911
Fire Department .....	397-9308
LEPC (Local Emergency Planning Committee).....	393-2870
NMOCD .....	393-6161
US Bureau of Land Management .....	393-3612

##### **Lovington**

State Police.....	392-5588
City Police.....	396-2811
Sheriff's Office .....	396-3611
Ambulance .....	911
Fire Department. ....	396-2356
LEPC (Local Emergency Planning Committee) .....	396-2884
NMOCD.....	393-6161

US Bureau of Land Management 393-3612

New Mexico Emergency Response Commission (Santa Fe) (505)476-9600  
24 HR .....(505) 827-9126  
National Emergency Response Center (Washington, DC) ...(800) 424-8802

##### **Other**

Boots & Coots IWC .....1-800-256-9688 or (281) 931-8884  
Cudd Pressure Control.....(915) 699-0139 or (915) 563-3356  
Halliburton .....(505) 746-2757  
B. J. Services.....(505) 746-3569

Flight For Life -4000 24th St, Lubbock, TX .....(806) 743-9911  
Aerocare -Rr 3 Box 49f, Lubbock, TX .....(806) 747-8923  
Med Flight Air Amb 2301 Yale Blvd SE #D3, Albuq, NM .....(505) 842-4433  
S B Air Med Svc 2505 Clark Carr Loop SE, Albuq, NM ....(505) 842-4949

Prepared in conjunction with  
Wade Rohloff of;

