

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-36756
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator MAR Oil and Gas Corp.		6. State Oil & Gas Lease No. 25104
3. Address of Operator P.O. Box 5155 Santa Fe NM 87502		7. Lease Name or Unit Agreement Name: Eumont Hardy Unit
4. Well Location 1325 FNL, 1328 FWL Lot No 6 Section 5 Township 21S Range 37E NMPM County LEA		8. Well No. 104
10. Elevation (Show whether DR, RKB, RT, GR, etc.) GL 3449		9. Pool name Eumont Yates-Seven Rivers Queen

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

July 20, 2004 @ 8:45 am spudded well, drilled 12 1/4" hole to 551', ran new 8 5/8" X 24# J55 casing to 550' cemented with 125 sxs Halliburton Lite Premium cement with .25 flocele/sk followed by 150 sxs tail cement, circulated 25 sxs cmt to surface WOC, NU BOP, pressure test BOP 2000 psig, drill 7 7/8" hole from 550' to TD 3902', log well, ran new 5 1/2" X 15.50 J55 casing to 3902', lead cement with 650 sxs Halliburton Lite Premium plus cement, tail cement with 375 sxs premium 50-50 poz mix, plug down 7/29/04 11:28am

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Duane C Winkler

TITLE : VP Operations

DATE : July 31, 2004

Type or print name Duane C Winkler

Telephone No. 505-989-1977

(This space for State use)

APPROVED BY

Chris Williams

TITLE

Dist. Sup.

Conditions of approval, if any:

